

Development of a Multi-Client Chat System Using Threads

Submitted to : Polash Roy

Team Members: Sara Faria Sundra (58)

Asuma Bhuiyan (85)

Course: Networking Lab 3

Department of Computer Science and Engineering, University of Dhaka

Submission Date: 18th September 2025

1 Overview

Network programming allows programs to communicate over a network by creating end-points called sockets. These sockets are used to send and receive data between two nodes, commonly known as a client and a server.

Implementing threads in a server program permits handling multiple clients at once. Each client operates independently in its own thread, which prevents blocking and improves responsiveness.

This technique is crucial in chat applications, where multiple users need to exchange messages concurrently without delays.

2 Lab Goals

1. Learn the basics of network socket programming in Java.
2. Implement a threaded server that can serve several clients at the same time.
3. Build a working chat program demonstrating bidirectional communication.

3 System Design

1. Initialize a server program to listen on a defined port for incoming connections.
2. Allocate a dedicated thread for every connected client to handle its messages.
3. Maintain a thread-safe collection of all active clients for message delivery.
4. Develop a client application capable of sending messages to and receiving messages from the server.
5. Use a separate listener thread on the client side to continuously receive messages from the server.

4 Source Code

4.1 Server Implementation

```
1 import java.io.*;
2 import java.net.*;
3 import java.util.concurrent.ConcurrentHashMap;
4 import java.util.Map;
5
6 public class MessageServer {
7
8     private static Map<Integer, PrintWriter> connectedClients =
9         new ConcurrentHashMap<>();
10
11     public static void main(String[] args) throws IOException {
12         int listenPort = 12345;
13         System.out.println("Server started on port " + listenPort
14             );
15         System.out.println("Enter 'exit' to terminate the server.
16             ");
17
18         new Thread(new ConsoleHandler()).start();
19
20         ServerSocket serverSock = new ServerSocket(listenPort);
21         while (true) {
22             Socket clientSock = serverSock.accept();
23             new Thread(new ClientProcessor(clientSock)).start();
24         }
25     }
26
27     private static class ClientProcessor implements Runnable {
28         private Socket socket;
29         private int portNumber;
30         private PrintWriter writer;
31
32         public ClientProcessor(Socket sock) {
33             this.socket = sock;
34             this.portNumber = sock.getPort();
35         }
36
37         public void run() {
38             try {
39                 BufferedReader reader = new BufferedReader(
40                     new InputStreamReader(socket.
41                         getInputStream())
42                 );
43                 this.writer = new PrintWriter(socket.
44                     getOutputStream(), true);
45
46                 connectedClients.put(portNumber, writer);
47                 System.out.println("Connected: " + portNumber);
```

```

43         writer.println("Connected successfully. Your port
44             : " + portNumber);
45
46         String line;
47         while ((line = reader.readLine()) != null) {
48             if (line.equalsIgnoreCase("exit")) break;
49             System.out.println("Client " + portNumber + "
50                 : " + line);
51             writer.println("Server ack: " + line);
52         }
53     } catch (IOException e) {
54         System.out.println("Error with client " +
55             portNumber);
56     } finally {
57         connectedClients.remove(portNumber);
58         System.out.println("Disconnected: " + portNumber)
59             ;
60         try { socket.close(); } catch (IOException e) {}
61     }
62 }
63
64 private static class ConsoleHandler implements Runnable {
65     public void run() {
66         try (BufferedReader input = new BufferedReader(new
67             InputStreamReader(System.in))) {
68             String command;
69             while ((command = input.readLine()) != null) {
70                 if (command.equalsIgnoreCase("exit")) {
71                     System.out.println("Shutting down server
72                         ...");
73                     for (PrintWriter w : connectedClients.
74                         values()) {
75                         w.println("Server is stopping.");
76                     }
77                     System.exit(0);
78                 }
79
80                 String[] tokens = command.split(":", 2);
81                 if (tokens.length == 2) {
82                     try {
83                         int target = Integer.parseInt(tokens
84                             [0].trim());
85                         String msg = tokens[1].trim();
86                         PrintWriter client = connectedClients
87                             .get(target);
88                         if (client != null) {
89                             client.println("Server message: "
90                                 + msg);

```

```

83         System.out.println("Sent to " +
84                               target);
85     } else {
86         System.out.println("Client not
87                               found: " + target);
88     }
89     } catch (NumberFormatException e) {
90         System.out.println("Invalid port
91                               format.");
92     }
93     } else {
94         System.out.println("Format: port: message
95                               ");
96     }
97 }
98 }
99 }

```

Listing 1: MessageServer.java

4.2 Client Implementation

```

1  import java.io.*;
2  import java.net.*;
3
4  public class MessageClient {
5
6      public static void main(String[] args) {
7          String serverHost = "127.0.0.1";
8          int serverPort = 12345;
9
10         try {
11             Socket conn = new Socket(serverHost, serverPort);
12             System.out.println("Connected to server.");
13             System.out.println("Type 'exit' to leave.");
14
15             new Thread(new ServerReceiver(conn)).start();
16
17             PrintWriter out = new PrintWriter(conn.
18                 getOutputStream(), true);
19             BufferedReader userInput = new BufferedReader(new
20                 InputStreamReader(System.in));
21
22             String msg;
23             while (true) {
24                 msg = userInput.readLine();
25                 out.println(msg);

```

```

24         if (msg.equalsIgnoreCase("exit")) break;
25     }
26
27     conn.close();
28
29     } catch (IOException e) {
30         System.out.println("Cannot connect: " + e.getMessage
31             ());
32     }
33
34     System.out.println("Disconnected from server.");
35 }
36
37 private static class ServerReceiver implements Runnable {
38     private Socket sock;
39
40     public ServerReceiver(Socket socket) {
41         this.sock = socket;
42     }
43
44     public void run() {
45         try {
46             BufferedReader in = new BufferedReader(
47                 new InputStreamReader(sock.getInputStream
48                     ());
49             String serverMsg;
50             while ((serverMsg = in.readLine()) != null) {
51                 System.out.println("[Server] " + serverMsg);
52             } catch (IOException e) {
53                 System.out.println("Lost connection to server.");
54             }
55         }
56     }
57 }

```

Listing 2: MessageClient.java

5 Observations

- Server displays client connections and messages.
- Clients send messages and receive responses without blocking.

6 Conclusion

Traditional socket programs allow only one client at a time, causing delays. Threaded servers enable concurrent communication, improve efficiency, and allow multiple clients

```

// ChatServer.java
import java.io.*;
import java.net.*;
import java.util.*;

public class ChatServer {
    public static void main(String[] args) {
        try {
            ServerSocket serverSocket = new ServerSocket(12390);
            while (true) {
                Socket clientSocket = serverSocket.accept();
                new Thread(new ChatServerHandler(clientSocket)).start();
            }
        } catch (IOException e) {
            e.printStackTrace();
        }
    }
}

// ChatClient.java
import java.io.*;
import java.net.*;

public class ChatClient {
    public static void main(String[] args) {
        try {
            Socket clientSocket = new Socket("localhost", 12390);
            BufferedReader reader = new BufferedReader(new InputStreamReader(clientSocket.getInputStream()));
            PrintWriter writer = new PrintWriter(clientSocket.getOutputStream(), true);
            while (true) {
                String message = reader.readLine();
                if (message != null) {
                    System.out.println("Received: " + message);
                    if (message.equals("exit")) {
                        break;
                    }
                }
            }
        } catch (IOException e) {
            e.printStackTrace();
        }
    }
}

```

Output logs:

```

Starting server on port 12390
Type 'exit' to stop the server.
Send message to a client using format: port: message
Client connected on port: 35962
From 35962: client 1
Client connected on port: 57782
Client disconnected: 57782
Client connected on port: 47232
From 47232: client 2
47232: for client 2
Sent to 47232

[Server]: You are connected. Your port is 35962
[Server]: Server received: client 1

[Server]: You are connected. Your port is 47232
[Server]: Server received: client 2
[Server]: Message from server: for client 2

```

Figure 1: Active clients and server logs

```

// ChatServer.java
import java.io.*;
import java.net.*;
import java.util.*;

public class ChatServer {
    public static void main(String[] args) {
        try {
            ServerSocket serverSocket = new ServerSocket(12390);
            while (true) {
                Socket clientSocket = serverSocket.accept();
                new Thread(new ChatServerHandler(clientSocket)).start();
            }
        } catch (IOException e) {
            e.printStackTrace();
        }
    }
}

// ChatClient.java
import java.io.*;
import java.net.*;

public class ChatClient {
    public static void main(String[] args) {
        try {
            Socket clientSocket = new Socket("localhost", 12390);
            BufferedReader reader = new BufferedReader(new InputStreamReader(clientSocket.getInputStream()));
            PrintWriter writer = new PrintWriter(clientSocket.getOutputStream(), true);
            while (true) {
                String message = reader.readLine();
                if (message != null) {
                    System.out.println("Received: " + message);
                    if (message.equals("exit")) {
                        break;
                    }
                }
            }
        } catch (IOException e) {
            e.printStackTrace();
        }
    }
}

```

Output logs:

```

Starting server on port 12390
Type 'exit' to stop the server.
Send message to a client using format: port: message
Client connected on port: 35962
From 35962: client 1
Client connected on port: 57782
Client disconnected: 57782
Client connected on port: 47232
From 47232: client 2
47232: for client 2
Sent to 47232

[Server]: You are connected. Your port is 35962
[Server]: Server received: client 1

[Server]: You are connected. Your port is 47232
[Server]: Server received: client 2
[Server]: Message from server: for client 2

```

Figure 2: Client sending and receiving messages

to interact seamlessly.

Key Takeaways:

- Learn network socket operations in Java.
- Manage multi-threaded servers with shared data safely.
- Achieve real-time client-server message exchange.

Challenges:

- Safely accessing shared resources from multiple threads.
- Closing client sockets correctly.
- Handling unexpected disconnections smoothly.