

PRODUCT LEAFLET






Analog smoke detector with isolator 4401I



FEATURES

- State of the art detector for highest safety
- Built-in short circuit isolator
- Supports auto-addressing
- Nuisance alarms reduced by up to 46% by using Advance mode:
 - Variable sensitivity and time delay based on smoke changes just before and after fire alarm level has been reached
 - A learning function will ensure that the most suitable fire alarm algorithm is always used
- High-tech mesh net prevents dust and insects to enter the detection chamber
- Installation date and automatic service signal

DATA

-  - 10 to +50 °C
-  < 95%
-  Ø102x34 mm
-  75 g
-  Red LED
- 
 - Grey
 - White
 - Black

GENERAL

- Tested and approved according to EN54-7 and EN54-17
- VdS Approval: G220004
- CPR: 0786-CPR-21673

RELATED PRODUCTS

- 4412F - Analog base
- 4479 - Sounder base

PRODUCT LEAFLET





Analog base 4412F



FEATURES

- 3-terminal base for isolator detector
- Connector for shield
- Connector for extra cable pair (e.g. 24 V)
- Fast connectors for quickest installation available
- Cable entry from top or side
- Recess for label holder

DATA

-  - 10 to +50 °C
-  < 95%
-  Ø102 x 23.3 mm
-  59 g

GENERAL

- CE
- Compliant with EN54-5 and EN54-7.

RELATED PRODUCTS

- 4400I - Multi detector with isolator
- 3390 - Label holder
- 3391 - Labels for Label holder 3390