

# SF2568: Homework 2

Michael Hanke

January 25, 2018

1. The broadcast operation is a one-to-all collective communication operation where one of the processes sends the same message to all other processes.
  - (a) Assume our simple communication model for point-to-point communication. A straightforward implementation would require  $P - 1$  communication steps. Design an algorithm for the broadcast operation using only point-to-point communications which requires only  $O(\log P)$  communication steps. Hint: Recursive doubling (2)
  - (b) Do a (time-)performance analysis for your algorithm. (2)
  - (c) How can the scatter operation be implemented using  $O(\log P)$  communication steps? (2)
2. Consider a matrix  $A$  distributed on a  $P \times P$  process mesh. An algorithm has been given in the lecture for evaluating the matrix-vector product  $y = Ax$ . While  $x$  is column distributed,  $y$  is row distributed. In order to carry out a further multiplication  $Ay$ , the vector  $y$  must be transposed.
  - (a) Design an algorithm for this transposition. You may use the results from problem 1. (1)
  - (b) Make a performance analysis. (1)
  - (c) An extra credit will be given for a good (!) solution in the case that  $A$  is distributed in a  $P \times Q$  process mesh with  $P \neq Q$ .
3. We consider the problem of solving the 1-dimensional differential equation

$$\begin{aligned} u'' + r(x)u &= f(x), \quad 0 < x < 1 \\ u(0) &= 0, \quad u(1) = 0 \end{aligned}$$

Assume that  $r(x) \leq 0$  for all  $x \in (0, 1)$ . The equation can be discretized as follows: For a given  $N > 0$  let  $h = 1/(N + 1)$  and  $x_n = nh$ ,  $0 \leq n \leq N + 1$ . Then the discrete system reads

$$\frac{1}{h^2}(u_{n-1} - 2u_n + u_{n+1}) + r(x_n)u_n = f(x_n), \quad n = 1, \dots, N$$

where  $u_n \approx u(x_n)$  and  $u_0 = u_{N+1} = 0$ . One possibility for solving this linear system of equation is Jacobi iteration. Let  $u_n^{[0]}$  be a given guess of the solution. The sequence  $u^{[k]}$  given by

$$u_n^{[k+1]} = (u_{n-1}^{[k]} + u_{n+1}^{[k]} - h^2 f(x_n)) / (2.0 - h^2 r(x_n))$$

converges (slowly!) towards the exact solution.

Your task is to write a program which implements this algorithm using MPI. Test it out on a parallel computer. As a result, hand in a matlab plot of the solution and the error of a nontrivial problem of your choice, that is,  $r(x)$  should be a nonconstant function. Additionally, hand in the source code of your program.(4)  
Use  $N = 1000$ . Since the speed of convergence is very slow, around 1000000 steps may be necessary.

Hints:

- Your starting point may be the skeleton `poisson1D.skel.c` to be found in <http://www.math.kth.se/na/SF2568/parpro-18/poisson1D.skel.c>. A Fortran version is also available (`poisson1D.skel.f`).
- Implement red/black communication for the transfer of the overlap between adjacent processors.
- In order to avoid the gathering of the complete array at the master processor, let each processor print out its own part of the discrete solution.
- Do not forget to switch on optimization during compilation!
- In order to be able to plot the error of your numerical approximation you must know the exact solution. This can be done as follows: Fix an “exact” solution  $u$  of your choice. Then, for your selected  $r$ , insert  $u$  into the equation and compute the corresponding right-hand side  $f$  by  $f := u'' - ru$ .

A paper copy of your report shall be handed in at the Student Office, Teknikringen 8D.