



Web Security – IE2062

Topic: Bug Bounty Report 2

Y2S2.WE.CS

Name: S.D.W.Gunaratne

(IT23241978)

Table of Content

1) How I started?

2) Introduction

2.1 Domain

1.2 Severity

3) Vulnerability

3.1 Vulnerability title

3.2 Vulnerability description

3.3 Affected components

3.4 Impact assessment




3.5 Steps to reproduce

3.6 Proof of concept


3.7 Proposed mitigation or fix

How I started?

1. Once I search from Bug crowd, I saw the SoundCloud bug bounty program.

Title	Type	Scope rating	Min rewards	Max rewards	Compensation	Industry	More actions
 SoundCloud SoundCloud is the world's largest ope...	 Bug Bounty	⊕⊕⊕⊕	\$200	\$4,500		 Entertainment	...

2. Then, I discovered full main domain allowed for scope, so that I choose <https://soundcloud.com>.



to find the vulnerability.


Targets ⊕⊕⊕⊕ 4 out of 4


Bugcrowd calculates scope ratings based on the depth and breadth of in-scope targets.

In-scope targets ✓ In scope

P1 \$4100 – \$4500 P2 \$1500 – \$1750 P3 \$600 – \$850 P4 \$200 – \$250


The below mentioned targets are in-scope. We serve different webpages and API endpoints (api-*.soundcloud.com) on our subdomains. All these sub-domains are in scope, if not explicitly listed in the out of scope section.

 SoundCloud Android app Java Mobile Application Testing Kotlin

 soundcloud.com Scala ReactJS Website Testing +1

Support

3. I use several methods/tools to do penetration testing.
4. First, I used Nmap. It helps me to find what are the open ports, Identify the web technologies such as web servers.





5. Secondly, I used Subfider tool to find hidden or forgotten web asserts. Because hidden web assert can have poor security, unpatched vulnerabilities.

```
SD7 [Running] - Oracle VirtualBox
File Machine View Input Devices Help
1 2 3 4
File Actions Edit View Help
root@kali2025: ~ x root@kali2025: ~ x root@kali2025: ~ x
</html>
[WRN] Could not run source dnsdumpster: unexpected status code 403 received from https://dnsdumpster.com/
[alienvault] mail.billing.soundcloud.com
[alienvault] invite.soundcloud.com
[alienvault] discord.soundcloud.com
[alienvault] ptr8588.reporting.soundcloud.com
[alienvault] sonos.integrate.soundcloud.com
[alienvault] postman.soundcloud.com
[alienvault] developer.soundcloud.com
[alienvault] ingest.soundcloud.com
[alienvault] dwt.soundcloud.com
[alienvault] api-partners.soundcloud.com
[alienvault] invalid.soundcloud.com
[alienvault] get.soundcloud.com
[alienvault] lurl.soundcloud.com
[alienvault] onelink.soundcloud.com
[alienvault] api-widget.soundcloud.com
[alienvault] repost.soundcloud.com
[alienvault] status.soundcloud.com
[alienvault] mastering.soundcloud.com
[alienvault] velvetcake.soundcloud.com
[alienvault] artists.soundcloud.com
[alienvault] promoted.soundcloud.com
[alienvault] no9pldds1lmn3.soundcloud.com
[alienvault] pages.soundcloud.com
[alienvault] web-errors.soundcloud.com
[alienvault] visuals-queue.soundcloud.com
[alienvault] getstarted.soundcloud.com
[alienvault] merch.soundcloud.com
[alienvault] nba2kbeatsthesearch.soundcloud.com
[alienvault] eventgateway.soundcloud.com
[alienvault] checkout-android.soundcloud.com
[alienvault] links.billing.soundcloud.com
[alienvault] links.messages.soundcloud.com
[alienvault] community.soundcloud.com
[alienvault] api.soundcloud.com
[alienvault] careers.soundcloud.com
[alienvault] store.soundcloud.com
[alienvault] visuals.soundcloud.com
[alienvault] gql-api.soundcloud.com
[alienvault] player.soundcloud.com
[alienvault] api-auth.soundcloud.com
[alienvault] developers.soundcloud.com
[alienvault] cast.soundcloud.com
[alienvault] checkout.soundcloud.com
[alienvault] insights-ui.soundcloud.com
[alienvault] graph.soundcloud.com
[alienvault] api-mobi.soundcloud.com
[alienvault] api-mobile-staging.soundcloud.com
[alienvault] feeds.soundcloud.com
```

6. Thirdly, I used Wafwoof tool to find website is protected by a WAF (web application firewall). Because if WAF is active, so pen tester do their test without blocked, and they can do their testing with bypass WAF.

3) Vulnerability

3.1 Vulnerability title	Cross-Domain Misconfiguration CWE-264 OWASP_2021_A01
3.2 Vulnerability description	<p>Alert description:</p> <p>Web browser data loading may be possible, due to a Cross Origin Resource Sharing (CORS) misconfiguration on the web server.</p> <p>Extra information:</p> <p>The CORS misconfiguration on the web server permits cross-domain read requests from arbitrary third-party domains, using unauthenticated APIs on this domain.</p> <p>Web browser implementations do not permit arbitrary third parties to read the response from authenticated APIs, however. This reduces the risk somewhat.</p> <p>This misconfiguration could be used by an attacker to access data that is available in an unauthenticated manner, but which uses some other form of security, such as IP address whitelisting.</p> <p><i>Basic idea: a website's settings are messed up, letting other websites see data they shouldn't, even if the data was supposed to be somewhat protected.</i></p>
3.3 Affected components	Component: Web server/API Header: Access-Control-Allow-Origin: *

	<p>Issue Type: Cross-Origin Resource Sharing (CORS) Misconfiguration</p> <p>Location: Response headers from unauthenticated API endpoints</p>  <pre> HTTP/1.1 200 OK Content-Type: application/xml; charset=utf-8 Connection: keep-alive server: am/2 status: 200 OK cache-control: max-age=0, private, must-revalidate access-control-allow-origin: * referrer-policy: strict-origin-when-cross-origin access-control-expose-headers: Date </pre> <p>(Picture shows, http response header with CORS misconfigurations)</p>
<p>3.4 Impact assessment</p>	 <pre> HTTP/1.1 200 OK Content-Type: application/json; charset=utf-8 Connection: keep-alive server: am/2 status: 200 OK cache-control: max-age=0, private, must-revalidate access-control-allow-origin: * referrer-policy: strict-origin-when-cross-origin access-control-expose-headers: Date x-permitted-cross-domain-policies: none x-xss-protection: 1; mode=block x-request-id: 67F9E5363EB14D041CF4CC </pre> <p>Above picture represent, server responds.</p> <p>This allows any domain to make cross-origin read requests to unauthenticated API endpoints. While most browsers restrict cross-origin reads on authenticated endpoints, this misconfiguration:</p>

	<ul style="list-style-type: none"> • Allows attackers to fetch public data from another origin • May expose data meant for internal or trusted usage only • Weakens the Same-Origin Policy (SOP) enforcement • Can be combined with other vulnerabilities for advanced attacks
3.5 Steps to reproduce	<ul style="list-style-type: none"> • Visit the site: https://soundcloud.com • Open the developer tools in browser • Go Network • Find the header • Confirm: “ Access-Control-Allow-Origin: * “ • Go to console and run this: <pre>fetch("https://soundcloud.com") .then(res => res.text()) .then(data => console.log(data));</pre> • If data can see, that means API is accessible cross-origin.
3.6 Proof of concept	As a result, API data from the target domain is shown on another domain, proving the misconfiguration.
3.7 Proposed mitigation or fix	<p>Ensure that sensitive data is not available in an unauthenticated manner (using IP address whitelisting, for instance).</p> <p>Configure the "Access-Control-Allow-Origin" HTTP header to a more restrictive set of domains, or remove all CORS headers entirely, to allow the web browser to enforce the Same Origin Policy (SOP) in a more restrictive manner.</p>