Use Case Specification: UC-02

- **ID / Code:** UC-02
- **Use Case Name:** Configure Personal Preferences
- **Description:** Allows a user to configure their personal display and accessibility preferences (e.g., language, theme, font size, contrast, default filters), without affecting the global behaviour of the system.
- **Primary Actor:** Base User (inherited by Administrator and Super-Administrator)
- **Scope:** Subscription Management & Invoicing System
- **Level:** User Goal
- **Stakeholders & Interests:**
  - *Base User:* Wants to adapt the interface to their needs and accessibility requirements (UR-1.3, NFR-1.7).
  - *Super-Administrator:* Wants to guarantee that personal preferences never alter system-wide configuration, which only they can change (UR-1.3, NFR-2.7).
- **Preconditions:** The user is authenticated (UC-01).
- **Postconditions:** The user's preferences are stored and applied to their own sessions.
- **Success Guarantee:** The new preferences are saved in the user's profile and applied immediately to the interface.
- **Minimal Guarantee:** Global system configuration remains unchanged under any scenario; if saving fails, the previous preferences remain in force.
- **Trigger:** The user selects "Preferences" in their profile menu.
- **Main Success Scenario:**

1. **User:** Requests to configure personal preferences.
2. **System:** Displays the current preference values (language, theme, contrast, font size, default views, default filters, and notification display options).
3. **User:** Modifies one or more preferences and saves the changes.
4. **System:** Validates the selected values.
5. **System:** Stores the preferences in the user's profile, separately from the global configuration (NFR-2.7).
6. **System:** Applies the new preferences to the interface and shows a confirmation message.

- **Extensions:**
  - 3a. User cancels the operation:
    - 3a1. System discards the changes and keeps the previous preferences.
  - 3b. User accidentally closes the form or reloads the page before saving (NFR-1.5):
    - 3b1. System restores the last saved preferences; unsaved changes are discarded without data loss to the profile.
  - 4a. Invalid or unsupported value:
    - 4a1. System indicates which option is not valid and keeps the rest of the form data.
    - 4a2. The flow resumes at step 3.