

MTLN0=04



Page No : B-1 of 2  
IS : 2062

CM/L-0057534  
MTL-II/OR-2

STEEL AUTHORITY OF INDIA LIMITED  
BHILAI STEEL PLANT  
RESEARCH & CONTROL LAB (MECHANICAL TESTING LAB)  
TEST CERTIFICATE FOR HOT ROLLED MEDIUM AND HIGH TENSILE STRUCTURAL  
STEEL



Sold-to-Party: BM BSO HYDERABAD  
TARAMANDAL OFFICE COMPLEX  
HYDERABAD LOCAL 500004  
Ship-to-Party: WHM HYDERABAD, Medak.  
Process of Manufacture of Steel : Basic Oxygen Converter > Continuous Cast > Fully Killed Steel > SIAIK  
Specification : IS 2062 E 350 BR : 2011 RA 2021

We certify that the material described below fully conforms to IS 2062 : 2011 RA 2021. Chemical composition and Mechanical properties of the product, as tested in accordance with the scheme of testing and inspection contained in the BIS certification mark Number CM/L 0057534 are as indicated against each Order No.

TEST RESULTS

(Please refer to IS 2062 : 2011 RA 2021 for details of specification requirements)

| SECTION (NOMINAL SIZE)                  |       |        |           | Plate No | / Pc. No. | Heat No | MECHANICAL PROPERTIES |         |         |         |         |         |                                      |       |         |                | Bend Test | M Dia    |      |
|-----------------------------------------|-------|--------|-----------|----------|-----------|---------|-----------------------|---------|---------|---------|---------|---------|--------------------------------------|-------|---------|----------------|-----------|----------|------|
| THICK                                   | WIDTH | LENGTH | mm        |          |           |         | mm                    | mm      | YS      | UTS     | %E      | %E2     | CHARPY V NOTCH (L) Impact Values (J) | Iavg  | °C      |                |           |          |      |
|                                         |       |        |           |          |           |         |                       |         |         |         |         |         |                                      |       |         |                |           |          |      |
| 16                                      | 2500  | 12000  | 3448534/6 | 406768   | 406       | 527     | 23                    | --      | 80      | 82      | 88      | 83      | RT                                   | OK    | 2.0 T   |                |           |          |      |
| 16                                      | 2500  | 12000  | 3450647/1 | 407258   | 391       | 523     | 24                    | --      | 132     | 126     | 130     | 129     | RT                                   | OK    | 2.0 T   |                |           |          |      |
| 16                                      | 2500  | 12000  | 3450647/2 | 407258   | --        | --      | --                    | --      | --      | --      | --      | --      | --                                   | --    | 2.0 T   |                |           |          |      |
| 16                                      | 2500  | 12000  | 3450648/1 | 407258   | --        | --      | --                    | --      | --      | --      | --      | --      | --                                   | --    | --      |                |           |          |      |
| 16                                      | 2500  | 12000  | 3450648/2 | 407258   | --        | --      | --                    | --      | --      | --      | --      | --      | --                                   | --    | --      |                |           |          |      |
| 16                                      | 2500  | 12000  | 3450795/2 | 407271   | 414       | 568     | 24                    | --      | 118     | 100     | 102     | 107     | RT                                   | OK    | 2.0 T   |                |           |          |      |
| 16                                      | 2500  | 12000  | 3450796/1 | 407271   | 408       | 533     | 25                    | --      | --      | --      | --      | --      | OK                                   | 2.0 T | --      |                |           |          |      |
| 16                                      | 2500  | 12000  | 3450806/2 | 407271   | --        | --      | --                    | --      | --      | --      | --      | --      | --                                   | --    | --      |                |           |          |      |
| CHEMICAL COMPOSITION (LADLE ANALYSIS)   |       |        |           |          |           |         |                       |         |         |         |         |         |                                      |       |         |                |           |          |      |
| Heat                                    |       | No     | C         | S        | P         | Mn      | Si                    | Al      | Cu      | Cr      | Ni      | Mo      | Nb                                   | V     | Ti      | N <sup>2</sup> | B         | CE       |      |
| 406768                                  | 0.16  | 0.028  | 0.027     | 1.20     | 0.29      | 0.019   | < 0.02                | < 0.015 | < 0.015 | < 0.015 | < 0.015 | < 0.015 | < 0.010                              | 0.037 | < 0.010 | < 0.005        | 60        | < 0.0005 | 0.36 |
| 407258                                  | 0.16  | 0.013  | 0.019     | 1.45     | 0.26      | 0.032   | < 0.02                | < 0.015 | < 0.015 | < 0.015 | < 0.015 | < 0.015 | < 0.010                              | 0.037 | < 0.010 | < 0.005        | 60        | < 0.0005 | 0.41 |
| 407271                                  | 0.18  | 0.026  | 0.027     | 1.48     | 0.28      | 0.026   | < 0.02                | < 0.015 | < 0.015 | < 0.015 | < 0.015 | < 0.015 | < 0.010                              | 0.051 | < 0.010 | < 0.005        | 64        | < 0.0005 | 0.44 |
| Total Pieces Page / Sales Order : 8 / 8 |       |        |           |          |           |         |                       |         |         |         |         |         |                                      |       |         |                |           |          |      |
| Total Pieces Page / TC : 19             |       |        |           |          |           |         |                       |         |         |         |         |         |                                      |       |         |                |           |          |      |

Total Pieces Page / Sales Order : 8 / 8

Total Pieces / TC

: 19

The Material supplied conforms to the standard rolling and weight tolerances.,  
CE calculated by formula: [C + Mn/6 + (Cr + Mo + V)/5 + (Ni + Cu)/15],  
RT - Room temperature as defined in the specification,



J-126

Signature Not Verified

Digitally signed by S. SAJJU  
Date: 2025.11.10 14:48:33 IST  
Reason: Authorized Signatory RCL, BSP

Authorized Signatory

Research & Control Laboratory, Bhilai Steel Plant

Authorised Signatory  
SAIL/ CMO/ BSO