

Matlab Package: Envelope

May 14, 2012

Contents

I	tools	5
1	bootstrapse	5
2	bootstrapse_OLS	8
3	modelselectaic	10
4	modelselectbic	12
5	modelselectlrt	14
6	prediction	16
7	testcoefficient	19
II	env	22
8	aic_env	22
9	bic_env	24
10	bstrp_env	26
11	dF4env	28
12	env	29
13	F4env	33
14	lrt_env	34
15	predict_env	36

16 testcoefficient_env	39
III henv	41
17 aic_henv	41
18 bic_henv	43
19 bstrp_henv	45
20 dF4henv	47
21 F4henv	48
22 henv	49
23 lrt_henv	53
24 predict_henv	55
25 testcoefficient_henv	58
IV ienv	60
26 aic_ienv	60
27 bic_ienv	62
28 bstrp_ienv	64
29 dF4ienv	66
30 F4ienv	67
31 ienv	68
32 lrt_ienv	72
33 predict_ienv	74
34 testcoefficient_ienv	77
V penv	79
35 aic_penv	79

36	bic_penv	81
37	bstrp_penv	83
38	lrt_penv	85
39	penv	87
40	predict_penv	91
41	testcoefficient_penv	94
VI senv		96
42	aic_senv	96
43	bic_senv	98
44	bstrp_senv	100
45	dF4senv	102
46	F4senv	103
47	objfun	104
48	predict_senv	105
49	senv	108
50	testcoefficient_senv	112
VII xenv		114
51	aic_xenv	114
52	bic_xenv	116
53	bstrp_xenv	118
54	dF4xenv	120
55	F4xenv	121
56	lrt_xenv	122
57	predict_xenv	124

58 testcoefficient_xenv	126
59 xenv	128

Part I

tools

1 bootstrapse

Perform bootstrap to estimate actual standard errors for models in the envelope family.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
bootse = bootstrapse(X, Y, u, B, modelType)
bootse = bootstrapse(X, Y, u, B, modelType, Opts)
```

Input

X: Predictors. The predictors can be univariate or multivariate, discrete or continuous.

For model type for method 'env', 'henv', 'ienv', 'senv', and 'xenv'. X is an n by p matrix, p is the number of predictors.

For model type 'penv', X is A list containing the value of X1 and X2.

- X.X1 (only for 'penv'): Predictors of main interest. An n by p1 matrix, n is the number of observations, and p1 is the number of main predictors. The predictors can be univariate or multivariate, discrete or continuous.
- X.X2 (only for 'penv'): Covariates, or predictors not of main interest. An n by p2 matrix, p2 is the number of covariates.

Y: Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.

u: Dimension of the envelope subspace. The legitimate range of u depends on the model specified.

B: Number of bootstrap samples. A positive integer.

modelType: A string characters indicting the model, choices can be 'env', 'henv', 'ienv', 'penv', 'senv' and 'xenv'.

Opts: A list containing the optional input parameter, to control the iterations in sg_min. If one or several (even all) fields are not defined, the default settings are used.

- Opts.maxIter: Maximum number of iterations. Default value: 300.
- Opts.ftol: Tolerance parameter for F. Default value: 1e-10.
- Opts.gradtol: Tolerance parameter for dF. Default value: 1e-7.
- Opts.verbose: Flag for print out the number of bootstrap samples, logical 0 or 1. Default value: 0.

Output

bootse: For 'env', 'henv', 'ienv', 'senv' and 'xenv', an r by p matrix containing the standard errors for elements in β computed by bootstrap. For 'penv', an r by p1 matrix containing the standard errors for β_1 computed by bootstrap.

Description

This function computes the bootstrap standard errors for the regression coefficients or for partial envelope model, the main regression coefficients in the specified model by bootstrapping the residuals.

Example

```
load wheatprotein.txt
X = wheatprotein(:, 8);
Y = wheatprotein(:, 1:6);
alpha = 0.01;
u = lrt_env(X, Y, alpha);
B = 100;
modelType = 'env';
bootse = bootstrapse(X, Y, u, B, modelType)
```

bootse =

```
0.2896
0.4352
0.3189
0.5735
0.2543
0.5840
```

```

load fiberpaper.dat
Y = fiberpaper(:, 1 : 4);
Xtemp = fiberpaper(:, 5 : 7);
X.X1 = Xtemp(:, 3);
X.X2 = Xtemp(:, 1 : 2);
alpha = 0.01;
u = lrt_penv(X, Y, alpha);
B = 100;
modelType = 'penv';
bootse = bootstrapse(X, Y, u, B, modelType)

```

```
bootse =
```

```

0.0027
0.0012
0.0020
0.0009

```

2 bootstrapse_OLS

Compute bootstrap standard error for ordinary least squares.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
bootse = bootstrapse_OLS(X, Y, B)
```

Input

X: Predictors, an n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.

Y: Multivariate responses, an n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.

B: Number of bootstrap samples. A positive integer.

Opts: A list containing the optional input parameter. If not defined, the default setting is used.

- Opts.verbose: Flag for print out the number of bootstrap samples, logical 0 or 1. Default value: 0.

Output

bootse: The standard error for elements in β computed by bootstrap. An r by p matrix.

Description

This function computes the bootstrap standard errors for the regression coefficients in ordinary least squares by bootstrapping the residuals.

Example

```
load wheatprotein.txt
X = wheatprotein(:, 8);
Y = wheatprotein(:, 1 : 6);
bootse = bootstrapse_OLS(X, Y, 200)

bootse =

    10.2168
     8.3940
     9.0503
     9.9677
    14.5822
     5.5874
```

3 modelselectaic

Select the dimension for the envelope family using Akaike information criteria.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
u = modelselectaic(X, Y, modelType)
u = modelselectaic(X, Y, modelType, Opts)
```

Input

X: Predictors. The predictors can be univariate or multivariate, discrete or continuous.

For model type for method 'env', 'henv', 'ienv', 'senv', and 'xenv'. X is an n by p matrix, p is the number of predictors.

For model type 'penv', X is A list containing the value of X1 and X2.

- X.X1 (only for 'penv'): Predictors of main interest. An n by p1 matrix, n is the number of observations, and p1 is the number of main predictors. The predictors can be univariate or multivariate, discrete or continuous.
- X.X2 (only for 'penv'): Covariates, or predictors not of main interest. An n by p2 matrix, p2 is the number of covariates.

Y: Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.

modelType: A string characters indicting the model, choices can be 'env', 'henv', 'ienv', 'penv', 'senv' and 'xenv'.

Opts: A list containing the optional input parameter, to control the iterations in sg_min. If one or several (even all) fields are not defined, the default settings are used.

- Opts.maxIter: Maximum number of iterations. Default value: 300.
- Opts.ftol: Tolerance parameter for F. Default value: 1e-10.

- Opts.gradtol: Tolerance parameter for dF. Default value: 1e-7.
- Opts.verbose: Flag for print out dimension selection process, logical 0 or 1. Default value: 0.

Output

u: Dimension of the envelope. An integer between 0 and r.

Description

This function implements the Akaike information criteria (AIC) to select the dimension of the envelope subspace for method 'env', 'henv', 'ienv', 'penv', 'senv', and 'xenv'.

Example

```
load wheatprotein.txt
X = wheatprotein(:, 8);
Y = wheatprotein(:, 1 : 6);
modelType = 'env';
u = modelselectaic(X, Y, modelType)
```

u =

1

```
load fiberpaper.dat
Y = fiberpaper(:, 1 : 4);
Xtemp = fiberpaper(:, 5 : 7);
X.X1 = Xtemp(:, 3);
X.X2 = Xtemp(:, 1 : 2);
modelType = 'penv';
u = modelselectaic(X, Y, modelType)
```

u =

3

4 modelselectbic

Select the dimension for the envelope family using Bayesian information criteria.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
u = modelselectbic(X, Y, modelType)
u = modelselectbic(X, Y, modelType, Opts)
```

Input

X: Predictors. The predictors can be univariate or multivariate, discrete or continuous.

For model type for method 'env', 'henv', 'ienv', 'senv', and 'xenv'. X is an n by p matrix, p is the number of predictors.

For model type 'penv', X is A list containing the value of X1 and X2.

- X.X1 (only for 'penv'): Predictors of main interest. An n by p1 matrix, n is the number of observations, and p1 is the number of main predictors. The predictors can be univariate or multivariate, discrete or continuous.
- X.X2 (only for 'penv'): Covariates, or predictors not of main interest. An n by p2 matrix, p2 is the number of covariates.

Y: Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.

modelType: A string characters indicting the model, choices can be 'env', 'henv', 'ienv', 'penv', 'senv' and 'xenv'.

Opts: A list containing the optional input parameter, to control the iterations in sg_min. If one or several (even all) fields are not defined, the default settings are used.

- Opts.maxIter: Maximum number of iterations. Default value: 300.
- Opts.ftol: Tolerance parameter for F. Default value: 1e-10.

- Opts.gradtol: Tolerance parameter for dF. Default value: 1e-7.
- Opts.verbose: Flag for print out dimension selection process, logical 0 or 1. Default value: 0.

Output

u: Dimension of the envelope. An integer between 0 and r.

Description

This function implements the Bayesian information criteria (BIC) to select the dimension of the envelope subspace for method 'env', 'henv', 'ienv', 'penv', 'seenv', and 'xenv'.

Example

```
load wheatprotein.txt
X = wheatprotein(:, 8);
Y = wheatprotein(:, 1 : 6);
modelType = 'env';
u = modelselectbic(X, Y, modelType)
```

u =

1

```
load fiberpaper.dat
Y = fiberpaper(:, 1 : 4);
Xtemp = fiberpaper(:, 5 : 7);
X.X1 = Xtemp(:, 3);
X.X2 = Xtemp(:, 1 : 2);
modelType = 'penv';
u = modelselectbic(X, Y, modelType)
```

u =

1

5 modelselectlrt

Select the dimension for the envelope family using likelihood ratio testing procedure.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
u = modelselectlrt(X, Y, alpha, modelType)
u = modelselectlrt(X, Y, alpha, modelType, Opts)
```

Input

X: Predictors. The predictors can be univariate or multivariate, discrete or continuous.

For model type for method 'env', 'henv', 'ienv', and 'xenv'. X is an n by p matrix, p is the number of predictors.

For model type 'penv', X is A list containing the value of X1 and X2.

- X.X1 (only for 'penv'): Predictors of main interest. An n by p1 matrix, n is the number of observations, and p1 is the number of main predictors. The predictors can be univariate or multivariate, discrete or continuous.
- X.X2 (only for 'penv'): Covariates, or predictors not of main interest. An n by p2 matrix, p2 is the number of covariates.

Y: Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.

alpha: Significance level for testing. A real number between 0 and 1, often taken at 0.05 or 0.01.

modelType: A string characters indicting the model, choices can be 'env', 'henv', 'ienv', 'penv' and 'xenv'.

Opts: A list containing the optional input parameter, to control the iterations in sg.min. If one or several (even all) fields are not defined, the default settings are used.

- Opts.maxIter: Maximum number of iterations. Default value: 300.
- Opts.ftol: Tolerance parameter for F. Default value: 1e-10.
- Opts.gradtol: Tolerance parameter for dF. Default value: 1e-7.
- Opts.verbose: Flag for print out dimension selection process, logical 0 or 1. Default value: 0.

Output

u: Dimension of the envelope. An integer between 0 and r.

Description

This function implements the likelihood ratio testing procedure to select the dimension of the envelope subspace for method 'env', 'henv', 'ienv', 'penv', and 'xenv'. The likelihood ratio testing procedure does not support 'senv', because the scaled envelope models are not nested with the standard model.

Example

```
load wheatprotein.txt
X = wheatprotein(:, 8);
Y = wheatprotein(:, 1 : 6);
alpha = 0.01;
modelType = 'env';
u = modelselectlrt(X, Y, alpha, modelType)
```

u =

1

```
load fiberpaper.dat
Y = fiberpaper(:, 1 : 4);
Xtemp = fiberpaper(:, 5 : 7);
X.X1 = Xtemp(:, 3);
X.X2 = Xtemp(:, 1 : 2);
alpha = 0.01;
modelType = 'penv';
u = modelselectlrt(X, Y, alpha, modelType)
```

u =

1

6 prediction

Perform estimation or prediction for models in the envelope family.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
PredictOutput = prediction(ModelOutput, Xnew, infType, modelType)
```

Input

ModelOutput: A list containing the model outputs from fitting the models.

Xnew: The value of X with which to estimate or predict Y.

For 'env', 'henv', 'ienv', 'senv' and 'xenv', it is a p by 1 vector.

For 'penv', it is a list containing the value of X1 and X2.

- * Xnew.X1 (only for 'penv'): A p1 by 1 vector containing the value of X1.
- * Xnew.X2 (only for 'penv'): A p2 by 1 vector containing the value of X2.

infType: A string of characters indicting the inference type, the choices can be 'estimation' or 'prediction'.

modelType: A string characters indicting the model, choices can be 'env', 'henv', 'ienv', 'penv', 'senv' and 'xenv'.

Output

PredictOutput: A list containing the results of the inference.

- PredictOutput.value: The fitted value or the prediction value evaluated at Xnew. An r by 1 vector.
- PredictOutput.covMatrix: The covariance matrix of PredictOutput.value. An r by r matrix.
- PredictOutput.SE: The standard error of elements in PredictOutput.value. An r by 1 vector.

Description

This function evaluates the user-specified model, could be 'env', 'henv', 'ienv', 'penv', 'senv' or 'xenv', at new value Xnew. It can perform estimation: find the fitted value when $X = X_{\text{new}}$, or prediction: predict Y when $X = X_{\text{new}}$. The covariance matrix and the standard errors are also provided.

Example

```
load wheatprotein.txt
X = wheatprotein(:, 8);
Y = wheatprotein(:, 1:6);
modelType = 'env';
u = modelselectbic(X, Y, modelType);
ModelOutput = env(X, Y, u);
Xnew = X(2, :)';
PredictOutput = predict_env(ModelOutput, Xnew, 'estimation')
[PredictOutput.value, Y(2, :)] % Compare the fitted value with
the observed value
```

PredictOutput =

```
value: [6x1 double]
covMatrix: [6x6 double]
SE: [6x1 double]
```

ans =

```
474.7135  458.0000
127.4740  112.0000
251.2044  236.0000
380.8280  368.0000
380.9473  383.0000
-6.3287  -15.0000
```

```
load fiberpaper.dat
Y = fiberpaper(:, 1 : 4);
Xtemp = fiberpaper(:, 5 : 7);
X.X1 = Xtemp(:, 3);
X.X2 = Xtemp(:, 1 : 2);
modelType = 'penv';
```

```

u = modelselectbic(X, Y, modelType);
ModelOutput = penv(X, Y, u);
Xnew.X1 = X.X1(1, :)';
Xnew.X2 = X.X2(1, :)';
PredictOutput = predict_penv(ModelOutput, Xnew, 'estimation')
PredictOutput.SE

```

```

PredictOutput =

```

```

    value: [4x1 double]
 covMatrix: [4x4 double]
        SE: [4x1 double]

```

```

ans =

```

```

1.4680
0.4234
0.7145
0.3161

```

7 testcoefficient

This function tests the null hypothesis $L * \beta * R = A$ versus the alternative hypothesis $L * \beta * R \neq A$, where β is estimated under the model in the envelope family.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
TestOutput = testcoefficient(ModelOutput, modelType)
TestOutput = testcoefficient(ModelOutput, modelType, TestInput)
```

Input

ModelOutput: A list containing the model outputs from fitting the models.

modelType: A string characters indicting the model, choices can be 'env', 'henv', 'ienv', 'penv', 'senv' and 'xenv'.

TestInput: A list that specifies the null hypothesis, including L, R, and A. If not provided by the user, default values will be used.

- TestInput.L: The matrix multiplied to β on the left. According to different model, it has different size requirement. Default value will be set if the user does not specify.
- TestInput.R: The matrix multiplied to β on the right. According to different model, it has different size requirement. Default value will be set if the user does not specify.
- TestInput.A: The matrix on the right hand side of the equation. Default value will be set if the user does not specify.

Output

TestOutput: A list containing test statistics, degrees of freedom for the reference chi-squared distribution, and the p-value. At the same time, a table is printed out.

- TestOutput.chisqStatistic: The test statistics. A real number.
- TestOutput.df: The degrees of freedom of the reference chi-squared distribution. A positive integer.
- TestOutput.pValue: p-value of the test. A real number in [0, 1].

Description

This function tests for hypothesis $H_0 : L\beta R = A$, versus $H_\alpha : L\beta R \neq A$. The β is estimated by a model in the envelope model. If the user does not specify the values for L, R and A, then the test is equivalent to the standard F test on if $\beta = 0$ (for 'env', 'ienv', 'penv', 'senv' and 'xenv'), or if the group main effects are all zeros (for 'henv'). The test statistics used is $\text{vec}(L\beta R - A) \hat{\Sigma}^{-1} \text{vec}(L\beta R - A)^T$, and the reference distribution is chi-squared distribution with degrees of freedom the same as the length of $\text{vec}(A)$.

Example

```
load wheatprotein.txt
X = wheatprotein(:, 8);
Y = wheatprotein(:, 1:6);
alpha = 0.01;
u = lrt_env(X, Y, alpha);
ModelOutput = env(X, Y, u);
modelType = 'env';
TestOutout = testcoefficient(ModelOutput, modelType);
```

Test Hypothesis	Chisq Statistic	DF	P-value
L * beta * R = A	116.230	6	0.0000

```
load fiberpaper.dat
Y = fiberpaper(:, 1 : 4);
Xtemp = fiberpaper(:, 5 : 7);
X.X1 = Xtemp(:, 3);
X.X2 = Xtemp(:, 1 : 2);
alpha = 0.01;
u = lrt_penv(X, Y, alpha);
ModelOutput = penv(X, Y, u);
r = size(Y, 2);
p1 = size(X.X1, 2);
TestInput.L = rand(2, r);
TestInput.R = rand(p1, 1);
TestInput.A = zeros(2, 1);
TestOutout = testcoefficient_penv(ModelOutput, TestInput);
```

Test Hypothesis	Chisq Statistic	DF	P-value
L * beta * R = A	12.598	2	0.0018

Part II

env

8 aic_env

Select the dimension of the envelope subspace using Akaike information criterion.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
u = aic_env(X, Y)
u = aic_env(X, Y, Opts)
```

Input

X: Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.

Y: Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- `Opts.maxIter`: Maximum number of iterations. Default value: 300.
- `Opts.ftol`: Tolerance parameter for F. Default value: $1e-10$.
- `Opts.gradtol`: Tolerance parameter for dF. Default value: $1e-7$.
- `Opts.verbose`: Flag for print out dimension selection process, logical 0 or 1. Default value: 0.

Output

u: Dimension of the envelope. An integer between 0 and r .

Description

This function implements the Akaike information criteria (AIC) to select the dimension of the envelope subspace.

Example

```
load wheatprotein.txt
X = wheatprotein(:, 8);
Y = wheatprotein(:, 1:6);
u = aic_env(X, Y)
```

u =

1

9 bic_env

Select the dimension of the envelope subspace using Bayesian information criterion.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
u = bic_env(X, Y)
u = bic_env(X, Y, Opts)
```

Input

X: Predictors. An n by p matrix, p is the number of predictors and n is the number of observations. The predictors can be univariate or multivariate, discrete or continuous.

Y: Multivariate responses. An n by r matrix, r is the number of responses. The responses must be continuous variables.

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- `Opts.maxIter`: Maximum number of iterations. Default value: 300.
- `Opts.ftol`: Tolerance parameter for F. Default value: $1e-10$.
- `Opts.gradtol`: Tolerance parameter for dF. Default value: $1e-7$.
- `Opts.verbose`: Flag for print out dimension selection process, logical 0 or 1. Default value: 0.

Output

u: Dimension of the envelope. An integer between 0 and r .

Description

This function implements the Bayesian information criteria (BIC) to select the dimension of the envelope subspace.

Example

```
load wheatprotein.txt
X = wheatprotein(:, 8);
Y = wheatprotein(:, 1:6);
u = bic_env(X, Y)
```

u =

1

10 bstrp_env

Compute bootstrap standard error for the envelope model.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
bootse = bstrp_env(X, Y, u, B)
bootse = bstrp_env(X, Y, u, B, Opts)
```

Input

X: Predictors, an n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.

Y: Multivariate responses, an n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.

u: Dimension of the envelope subspace. A positive integer between 0 and r .

B: Number of bootstrap samples. A positive integer.

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- `Opts.maxIter`: Maximum number of iterations. Default value: 300.
- `Opts.ftol`: Tolerance parameter for F. Default value: $1e-10$.
- `Opts.gradtol`: Tolerance parameter for dF. Default value: $1e-7$.
- `Opts.verbose`: Flag for print out the number of bootstrap samples, logical 0 or 1. Default value: 0.

Output

bootse: The standard error for elements in β computed by bootstrap. An r by p matrix.

Description

This function computes the bootstrap standard errors for the regression coefficients in the envelope model by bootstrapping the residuals.

Example

```
load wheatprotein.txt
X = wheatprotein(:, 8);
Y = wheatprotein(:, 1:6);
alpha = 0.01;
u = lrt_env(X, Y, alpha)

u =

    1

B = 100;
bootse = bstrp_env(X, Y, u, B)

bootse =

    0.2893
    0.4260
    0.3523
    0.5628
    0.1675
    0.6192
```

11 dF4env

The first derivative of the objective function for computing the envelope subspace.

Contents

- Syntax
- Input
- Output
- Description

Syntax

```
df = dF4env(R, DataParameter)
```

Input

R: An r by u semi orthogonal matrix, $0 < u \leq r$.

DataParameter: A structure that contains the statistics calculated from the data.

Output

df: An r by u matrix containing the value of the derivative function evaluated at R .

Description

The objective function is derived in Section 4.3 in Cook et al. (2010) by using maximum likelihood estimation. This function is the derivative of the objective function.

12 env

Fit the envelope model.

Contents

- Syntax
- Input
- Output
- Description
- References
- Example

Syntax

```
ModelOutput = env(X, Y, u)
ModelOutput = env(X, Y, u, Opts)
```

Input

X: Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.

Y: Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables, and r should be strictly greater than p .

u: Dimension of the envelope. An integer between 0 and r .

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- `Opts.maxIter`: Maximum number of iterations. Default value: 300.
- `Opts.ftol`: Tolerance parameter for F. Default value: $1e-10$.
- `Opts.gradtol`: Tolerance parameter for dF. Default value: $1e-7$.
- `Opts.verbose`: Flag for print out Grassmann manifold optimization process, logical 0 or 1. Default value: 0.

Output

ModelOutput: A list that contains the maximum likelihood estimators and some statistics.

- `ModelOutput.beta`: The envelope estimator of the regression coefficients β . An r by p matrix.

- `ModelOutput.Sigma`: The envelope estimator of the error covariance matrix. An r by r matrix.
- `ModelOutput.Gamma`: The orthogonal basis of the envelope subspace. An r by u semi-orthogonal matrix.
- `ModelOutput.Gamma0`: The orthogonal basis of the complement of the envelope subspace. An r by $r-u$ semi-orthogonal matrix.
- `ModelOutput.eta`: The coordinates of β with respect to `Gamma`. An u by p matrix.
- `ModelOutput.Omega`: The coordinates of `Sigma` with respect to `Gamma`. An u by u matrix.
- `ModelOutput.Omega0`: The coordinates of `Sigma` with respect to `Gamma0`. An $r-u$ by $r-u$ matrix.
- `ModelOutput.alpha`: The estimated intercept in the envelope model. An r by 1 vector.
- `ModelOutput.l`: The maximized log likelihood function. A real number.
- `ModelOutput.covMatrix`: The asymptotic covariance of $\text{vec}(\beta)$. An rp by rp matrix. The covariance matrix returned are asymptotic. For the actual standard errors, multiply by $1/n$.
- `ModelOutput.asyEnv`: The asymptotic standard error for elements in β under the envelope model. An r by p matrix. The standard errors returned are asymptotic, for actual standard errors, multiply by $1/\sqrt{n}$.
- `ModelOutput.ratio`: The asymptotic standard error ratio of the standard multivariate linear regression estimator over the envelope estimator, for each element in β . An r by p matrix.
- `ModelOutput.np`: The number of parameters in the envelope model. A positive integer.
- `ModelOutput.n`: The number of observations in the data. A positive integer.

Description

This function fits the envelope model to the responses and predictors, using the maximum likelihood estimation. When the dimension of the envelope is between 1 and $r-1$, we implemented the algorithm in Cook et al. (2010). When the dimension is r , then the envelope model degenerates to the standard multivariate linear regression. When the dimension is 0, it means that X and Y are uncorrelated, and the fitting is different.

References

1. The codes is implemented based on the algorithm in Section 4.3 of Cook et al (2010).
2. The Grassmann manifold optimization step calls the package `sg_min` 2.4.1 by Ross Lippert (<http://web.mit.edu/~ripper/www.sgmin.html>).

Example

The following codes will reconstruct the results in the wheat protein data example in Cook et al. (2010).

```
load wheatprotein.txt
X = wheatprotein(:, 8);
Y = wheatprotein(:, 1:6);
alpha = 0.01;
u = lrt_env(X, Y, alpha)

u =

    1

ModelOutput = env(X, Y, u)

ModelOutput =

    beta: [6x1 double]
    Sigma: [6x6 double]
    Gamma: [6x1 double]
    Gamma0: [6x5 double]
    eta: 8.5647
    Omega: 7.8762
    Omega0: [5x5 double]
    alpha: [6x1 double]
    l: -850.7592
    covMatrix: [6x6 double]
    asyEnv: [6x1 double]
    ratio: [6x1 double]
    np: 28
    n: 50

ModelOutput.Omega

ans =

    7.8762
```

```
eig(ModelOutput.Omega0)
```

```
ans =
```

```
1.0e+03 *
```

```
6.5166
```

```
0.2083
```

```
0.0201
```

```
0.0004
```

```
0.0003
```

```
ModelOutput.ratio
```

```
ans =
```

```
28.0945
```

```
18.4326
```

```
23.6384
```

```
16.3211
```

```
65.8245
```

```
6.4668
```


13 F4env

Objective function for computing the envelope subspace.

Contents

- Syntax
- Input
- Output
- Description

Syntax

```
f = F4env(R, DataParameter)
```

Input

R: An r by u semi orthogonal matrix, $0 < u \leq r$.

DataParameter: A structure that contains the statistics calculated from the data.

Output

f: A scalar containing the value of the objective function evaluated at **R**.

Description

The objective function is derived in Section 4.3 of Cook et al. (2010) using maximum likelihood estimation. The columns of the semi-orthogonal matrix that minimizes this function span the estimated envelope subspace.

14 lrt_env

Select the dimension of the envelope subspace using likelihood ratio testing.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
u = lrt_env(X, Y, alpha)
u = lrt_env(X, Y, alpha, Opts)
```

Input

X: Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.

Y: Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.

alpha: Significance level for testing. A real number between 0 and 1, often taken at 0.05 or 0.01.

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- `Opts.maxIter`: Maximum number of iterations. Default value: 300.
- `Opts.ftol`: Tolerance parameter for F. Default value: $1e-10$.
- `Opts.gradtol`: Tolerance parameter for dF. Default value: $1e-7$.
- `Opts.verbose`: Flag for print out dimension selection process, logical 0 or 1. Default value: 0.

Output

u: Dimension of the envelope. An integer between 0 and r .

Description

This function implements the likelihood ratio testing procedure to select the dimension of the envelope subspace, with pre-specified significance level α .

Example

```
load wheatprotein.txt
X = wheatprotein(:, 8);
Y = wheatprotein(:, 1:6);
alpha = 0.01;
u = lrt_env(X, Y, alpha)
```

u =

1

15 predict_env

Perform estimation or prediction under the envelope model.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
PredictOutput = predict_env(ModelOutput, Xnew, infType)
```

Input

ModelOutput: A list containing the maximum likelihood estimators and other statistics inherited from env.

Xnew: The value of X with which to estimate or predict Y. A p by 1 vector.

infType: A string of characters indicting the inference type, the choices can be 'estimation' or 'prediction'.

Output

PredictOutput: A list containing the results of the inference.

- PredictOutput.value: The fitted value or the prediction value evaluated at Xnew. An r by 1 vector.
- PredictOutput.covMatrix: The covariance matrix of PredictOutput.value. An r by r matrix.
- PredictOutput.SE: The standard error of elements in PredictOutput.value. An r by 1 vector.

Description

This function evaluates the envelope model at new value Xnew. It can perform estimation: find the fitted value when $X = X_{\text{new}}$, or prediction: predict Y when $X = X_{\text{new}}$. The covariance matrix and the standard errors are also provided.

Example

```
load wheatprotein.txt
X = wheatprotein(:, 8);
Y = wheatprotein(:, 1:6);
alpha = 0.01;
u = lrt_env(X, Y, alpha);
ModelOutput = env(X, Y, u);
Xnew = X(2, :)';
PredictOutput = predict_env(ModelOutput, Xnew, 'estimation')
[PredictOutput.value, Y(1, :)] % Compare the fitted value with the data
PredictOutput.SE
```

```
PredictOutput =
```

```
value: [6x1 double]
covMatrix: [6x6 double]
SE: [6x1 double]
```

```
ans =
```

```
474.7135 468.0000
127.4740 123.0000
251.2044 246.0000
380.8280 374.0000
380.9473 386.0000
-6.3287 -11.0000
```

```
ans =
```

```
4.8892
4.0227
4.3237
4.7470
6.8186
2.6948
```

```
PredictOutput = predict_env(ModelOutput, Xnew, 'prediction')
PredictOutput.SE
```

```
PredictOutput =
```

```
      value: [6x1 double]  
      covMatrix: [6x6 double]  
      SE: [6x1 double]
```

```
ans =
```

```
474.7135  
127.4740  
251.2044  
380.8280  
380.9473  
-6.3287
```

```
ans =
```

```
34.9161  
28.7280  
30.8775  
33.9006  
48.6945  
19.2448
```

16 testcoefficient_env

This function tests the null hypothesis $L * \beta * R = A$ versus the alternative hypothesis $L * \beta * R \neq A$, where β is estimated under the envelope model.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
TestOutput = testcoefficient_env(ModelOutput)
TestOutput = testcoefficient_env(ModelOutput, TestInput)
```

Input

ModelOutput: A list containing the maximum likelihood estimators and other statistics inherited from env.

TestInput: A list that specifies the null hypothesis, including L, R, and A. If not provided by the user, default values will be used.

- TestInput.L: The matrix multiplied to β on the left. It is a d1 by r matrix, while d1 is less than or equal to r. Default value: identity matrix I_r .
- TestInput.R: The matrix multiplied to β on the right. It is a p by d2 matrix, while d2 is less than or equal to p. Default value: identity matrix I_p .
- TestInput.A: The matrix on the right hand side of the equation. It is a d1 by d2 matrix. Default value: d1 by d2 zero matrix.

Output

TestOutput: A list containing test statistics, degrees of freedom for the reference chi-squared distribution, and the p-value. At the same time, a table is printed out.

- TestOutput.chisqStatistic: The test statistics. A real number.
- TestOutput.df: The degrees of freedom of the reference chi-squared distribution. A positive integer.
- TestOutput.pValue: p-value of the test. A real number in $[0, 1]$.

Description

This function tests for hypothesis $H_0 : L\beta R = A$, versus $H_\alpha : L\beta R \neq A$. The β is estimated by the envelope model. If the user does not specify the values for L, R and A, then the test is equivalent to the standard F test on if $\beta = 0$. The test statistics used is $\text{vec}(L\beta R - A) \hat{\Sigma}^{-1} \text{vec}(L\beta R - A)^T$, and the reference distribution is chi-squared distribution with degrees of freedom $d1 * d2$.

Example

```
load wheatprotein.txt
X = wheatprotein(:, 8);
Y = wheatprotein(:, 1:6);
alpha = 0.01;
u = lrt_env(X, Y, alpha);
ModelOutput = env(X, Y, u);
TestOutout = testcoefficient_env(ModelOutput);
```

Test Hypothesis	Chisq Statistic	DF	P-value
L * beta * R = A	116.230	6	0.0000

```
r = size(Y, 2);
p = size(X, 2);
TestInput.L = rand(2, r);
TestInput.R = rand(p, 1);
TestInput.A = zeros(2, 1);
TestOutout = testcoefficient_senv(ModelOutput, TestInput);
```

Test Hypothesis	Chisq Statistic	DF	P-value
L * beta * R = A	61.344	2	0.0000

Part III

henv

17 aic_henv

Select the dimension of the envelope subspace using Akaike information criterion for the heteroscedastic envelope model.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
u = aic_henv(X, Y)
u = aic_henv(X, Y, Opts)
```

Input

X: Group indicators. A matrix with n rows. X can only have p unique rows, where p is the number of groups. For example, if there are two groups, X can only have 2 different kinds of rows, such as $(0, 1)$ and $(1, 0)$, or $(1, 0, 10)$ and $(0, 5, 6)$. The number of columns is not restricted, as long as X only has p unique rows.

Y: Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables, and r should be greater than p .

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- `Opts.maxIter`: Maximum number of iterations. Default value: 300.
- `Opts.ftol`: Tolerance parameter for F . Default value: $1e-10$.
- `Opts.gradtol`: Tolerance parameter for dF . Default value: $1e-7$.
- `Opts.verbose`: Flag for print out dimension selection process, logical 0 or 1. Default value: 0.

Output

u: Dimension of the envelope. An integer between 0 and r .

Description

This function implements the Akaike information criteria (AIC) to select the dimension of the envelope subspace for the heteroscedastic envelope model.

Example

```
load waterstrider.mat
u = aic_henv(X, Y)
```

u =

6

18 bic_henv

Select the dimension of the envelope subspace using Bayesian information criterion for the heteroscedastic envelope model.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
u = bic_henv(X, Y)
u = bic_henv(X, Y, Opts)
```

Input

X: Group indicators. A matrix with n rows. X can only have p unique rows, where p is the number of groups. For example, if there are two groups, X can only have 2 different kinds of rows, such as $(0, 1)$ and $(1, 0)$, or $(1, 0, 10)$ and $(0, 5, 6)$. The number of columns is not restricted, as long as X only has p unique rows.

Y: Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables, and r should be greater than p .

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- `Opts.maxIter`: Maximum number of iterations. Default value: 300.
- `Opts.ftol`: Tolerance parameter for F . Default value: $1e-10$.
- `Opts.gradtol`: Tolerance parameter for dF . Default value: $1e-7$.
- `Opts.verbose`: Flag for print out dimension selection process, logical 0 or 1. Default value: 0.

Output

u: Dimension of the envelope. An integer between 0 and r .

Description

This function implements the Bayesian information criteria (BIC) to select the dimension of the envelope subspace for the heteroscedastic envelope model.

Example

```
load waterstrider.mat
u = bic_henv(X, Y)
```

u =

4

19 bstrp_henv

Compute bootstrap standard error for the heteroscedastic envelope model.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
bootse = bstrp_henv(X, Y, u, B)
bootse = bstrp_henv(X, Y, u, B, Opts)
```

Input

X: Group indicators. A matrix with n rows. X can only have p unique rows, where p is the number of groups. For example, if there are two groups, X can only have 2 different kinds of rows, such as $(0, 1)$ and $(1, 0)$, or $(1, 0, 10)$ and $(0, 5, 6)$. The number of columns is not restricted, as long as X only has p unique rows.

Y: Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables, and r should be greater than p .

u: Dimension of the envelope subspace. A positive integer between 0 and r .

B: Number of bootstrap samples. A positive integer.

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- `Opts.maxIter`: Maximum number of iterations. Default value: 300.
- `Opts.ftol`: Tolerance parameter for F . Default value: $1e-10$.
- `Opts.gradtol`: Tolerance parameter for dF . Default value: $1e-7$.
- `Opts.verbose`: Flag for print out the number of bootstrap samples, logical 0 or 1. Default value: 0.

Output

bootse: The standard error for elements in β computed by bootstrap. An r by p matrix.

Description

This function computes the bootstrap standard errors for the regression coefficients in the heteroscedastic envelope model by bootstrapping the residuals.

Example

```
load waterstrider.mat

u = lrt_henv(X, Y, 0.01)

u =

     6

B = 100;
bootse = bstrp_henv(X, Y, u, B)

bootse =

    0.0305    0.0466    0.0647
    0.0309    0.0485    0.0682
    0.0305    0.0432    0.0638
    0.0205    0.0289    0.0425
    0.0385    0.0553    0.0799
    0.0295    0.0427    0.0618
    0.0389    0.0567    0.0819
    0.0321    0.0463    0.0665
```

20 dF4henv

The first derivative of the objective function for computing the envelope subspace in the heteroscedastic envelope model.

Contents

- Syntax
- Input
- Output
- Description

Syntax

```
df = dF4henv(R, DataParameter)
```

Input

R: An r by u semi orthogonal matrix, $0 < u \leq r$.

DataParameter: A structure that contains the statistics calculated from the data.

Output

df: An r by u matrix containing the value of the derivative function evaluated at R .

Description

The objective function is derived in Section 2.2 in Su and Cook (2012) by using maximum likelihood estimation. This function is the derivative of the objective function.

21 F4henv

Objective function for computing the envelope subspace in heteroscedastic envelope model.

Contents

- Syntax
- Input
- Output
- Description

Syntax

```
f = F4henv(R, DataParameter)
```

Input

R: An r by u semi orthogonal matrix, $0 < u \leq r$.

DataParameter: A structure that contains the statistics calculated from the data.

Output

f: A scalar containing the value of the objective function evaluated at R .

Description

The objective function is derived in Section 2.2 of Su and Cook (2012) using maximum likelihood estimation. The columns of the semi-orthogonal matrix that minimizes this function span the estimated envelope subspace in the heteroscedastic envelope model.

22 henv

Fit the heteroscedastic envelope model.

Contents

- Syntax
- Input
- Output
- Description
- References
- Example

Syntax

```
ModelOutput = henv(X, Y, u)
ModelOutput = henv(X, Y, u, Opts)
```

Input

X: Group indicators. A matrix with n rows. X can only have p unique rows, where p is the number of groups. For example, if there are two groups, X can only have 2 different kinds of rows, such as $(0, 1)$ and $(1, 0)$, or $(1, 0, 10)$ and $(0, 5, 6)$. The number of columns is not restricted, as long as X only has p unique rows.

Y: Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables, and r should be greater than p .

u: Dimension of the envelope. An integer between 0 and r .

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- `Opts.maxIter`: Maximum number of iterations. Default value: 300.
- `Opts.ftol`: Tolerance parameter for F . Default value: $1e-10$.
- `Opts.gradtol`: Tolerance parameter for dF . Default value: $1e-7$.
- `Opts.verbose`: Flag for print out Grassmann manifold optimization process, logical 0 or 1. Default value: 0.

Output

ModelOutput: A list that contains the maximum likelihood estimators and some statistics.

- **ModelOutput.mu:** The heteroscedastic envelope estimator of the grand mean. A r by 1 vector.
- **ModelOutput.mug:** The heteroscedastic envelope estimator of the group mean. A r by p matrix, the i th column of the matrix contains the mean for the i th group.
- **ModelOutput.Yfit:** A n by r matrix, the i th row gives the group mean of the group that the i th observation belongs to. As X is just a group indicator, and is not ordinal, **ModelOutput.mug** alone does not tell which group corresponds to which group mean.
- **ModelOutput.Gamma:** The orthogonal basis of the envelope subspace. An r by u semi-orthogonal matrix.
- **ModelOutput.Gamma0:** The orthogonal basis of the complement of the envelope subspace. An r by $r-u$ semi-orthogonal matrix.
- **ModelOutput.beta:** The heteroscedastic envelope estimator of the group main effect. An r by p matrix, the i th column of the matrix contains the main effect for the i th group.
- **ModelOutput.groupInd:** A matrix containing the unique values of group indicators. The matrix has p rows. The group mean of the i th row is stored in the i th column of **ModelOutput.mug**.
- **ModelOutput.Sigma:** The heteroscedastic envelope estimator of the error covariance matrix. A three dimensional matrix with dimension r , r and p , **ModelOutput.Sigma**(:, :, i) contains the estimated covariance matrix for the i th group.
- **ModelOutput.eta:** The coordinates of β with respect to **Gamma**. An u by p matrix, the i th column contains the coordinates of the main effect of the i th group with respect to **Gamma**.
- **ModelOutput.Omega:** The coordinates of **Sigma** with respect to **Gamma**. An u by u by p matrix, **ModelOutput.Omega**(:, :, i) contains the coordinates of the covariance matrix of the i th group with respect to **Gamma**.
- **ModelOutput.Omega0:** The coordinates of **Sigma** with respect to **Gamma0**. An $r - u$ by $r - u$ matrix.
- **ModelOutput.l:** The maximized log likelihood function. A real number.
- **ModelOutput.np:** The number of parameters in the heteroscedastic envelope model. A positive integer.
- **ModelOutput.covMatrix:** The asymptotic covariance of $(\mu', \text{vec}(\beta'))'$. An $r(p + 1)$ by $r(p + 1)$ matrix. The covariance matrix returned are asymptotic. For the actual standard errors, multiply by $1 / n$.
- **ModelOutput.asyHenv:** The asymptotic standard errors for elements in β under the heteroscedastic envelope model. An r by p matrix. The standard errors returned are asymptotic, for actual standard errors, multiply by $1 / \sqrt{n}$.

- `ModelOutput.ratio`: The asymptotic standard error ratio of the standard multivariate linear regression estimator over the heteroscedastic envelope estimator. An r by p matrix, the (i, j) th element in `ModelOutput.ratio` is the elementwise standard error ratio for the i th element in the j th group mean effect.
- `ModelOutput.ng`: The number of observations in each group. A p by 1 vector.

Description

This function fits the heteroscedastic envelope model to the responses and predictors, using the maximum likelihood estimation. When the dimension of the envelope is between 1 and $r-1$, we implemented the algorithm in Su and Cook (2012). When the dimension is r , then the envelope model degenerates to the standard multivariate linear model for comparing group means. When the dimension is 0, it means there is not any group effect, and the fitting is different.

References

1. The codes is implemented based on the algorithm in Section 2.2 of Su and Cook (2012).
2. The Grassmann manifold optimization step calls the package `sg_min` 2.4.1 by Ross Lippert (<http://web.mit.edu/~ripper/www.sgmin.html>).

Example

The following codes produce the results of the water strider example in Su and Cook (2011).

```
load waterstrider.mat
u = lrt_henv(X, Y, 0.01)

u =

6

ModelOutput = henv(X, Y, u)
ModelOutput.ratio
```

```
ModelOutput =
```

```
      mu: [8x1 double]
      mug: [8x3 double]
      Yfit: [90x8 double]
      Gamma: [8x6 double]
      Gamma0: [8x2 double]
      beta: [8x3 double]
      groupInd: [3x2 double]
      Sigma: [8x8x3 double]
      eta: [6x3 double]
      Omega: [6x6x3 double]
      Omega0: [2x2 double]
      np: 98
      l: 1.0051e+03
      covMatrix: [32x32 double]
      asyHenv: [8x3 double]
      ratio: [8x3 double]
      ng: [3x1 double]
```

```
ans =
```

```
6.5439    11.2830    6.4954
4.6325     5.3226    4.7242
4.4456     5.0741    4.4198
4.7338     6.2469    5.1937
8.0377    12.5386    9.4823
9.5067    11.5974   11.3444
11.8632   15.6080   12.5611
6.9792    11.1559   10.1002
```

23 lrt_henv

Select the dimension of the envelope subspace using likelihood ratio testing for the heteroscedastic envelope model.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
u = lrt_henv(X, Y, alpha)
u = lrt_henv(X, Y, alpha, Opts)
```

Input

X: Group indicators. A matrix with n rows. X can only have p unique rows, where p is the number of groups. For example, if there are two groups, X can only have 2 different kinds of rows, such as (0, 1) and (1, 0), or (1, 0, 10) and (0, 5, 6). The number of columns is not restricted, as long as X only has p unique rows.

Y: Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables, and r should be greater than p .

alpha: Significance level for testing. A real number between 0 and 1, often taken at 0.05 or 0.01.

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- `Opts.maxIter`: Maximum number of iterations. Default value: 300.
- `Opts.ftol`: Tolerance parameter for F. Default value: $1e-10$.
- `Opts.gradtol`: Tolerance parameter for dF. Default value: $1e-7$.
- `Opts.verbose`: Flag for print out dimension selection process, logical 0 or 1. Default value: 0.

Output

u: Dimension of the envelope. An integer between 0 and r .

Description

This function implements the likelihood ratio testing procedure to select the dimension of the envelope subspace in heteroscedastic envelope model, with pre-specified significance level α .

Example

```
load waterstrider.mat  
u = lrt_henv(X, Y, 0.01)
```

u =

6

24 predict_henv

Perform estimation or prediction under the heteroscedastic envelope model.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
PredictOutput = predict_henv(ModelOutput, Xnew, infType)
```

Input

ModelOutput: A list containing the maximum likelihood estimators and other statistics inherited from henv.

Xnew: A group indicator. It must be a column vector, whose transpose is the same as one of the group indicators from the original data.

infType: A string of characters indicating the inference type, the choices can be 'estimation' or 'prediction'.

Output

PredictOutput: A list containing the results of the inference.

- PredictOutput.value: The fitted value or the prediction value evaluated at Xnew. An r by 1 vector.
- PredictOutput.covMatrix: The covariance matrix of PredictOutput.value. An r by r matrix.
- PredictOutput.SE: The standard error of elements in PredictOutput.value. An r by 1 vector.

Description

This function evaluates the inner envelope model at new value Xnew. It can perform estimation: find the group mean for the group indicated by Xnew, or prediction: predict Y for the group indicated by Xnew. The covariance matrix and the standard errors are also provided.

Example

```
load waterstrider.mat
u = lrt_henv(X, Y, 0.01);
ModelOutput = henv(X, Y, u);
ModelOutput.groupInd
ModelOutput.mug
Xnew = X(1, :)'

ans =

    -1    -1
     0     1
     1     0

ans =

    -1.1417    -1.1267    -1.0845
    -1.4063    -1.4067    -1.3132
    -1.3314    -1.3336    -1.2152
    -0.3113    -0.1839    -0.1736
     0.4003     0.3847     0.3072
     0.4107     0.3753     0.3735
     0.3467     0.3271     0.3179
    -0.1954    -0.2100    -0.3488

Xnew =

     1
     0

PredictOutput = predict_henv(ModelOutput, Xnew, 'estimation')
PredictOutput.value %This is the 3rd group mean
PredictOutput.SE

PredictOutput =

    value: [8x1 double]
   covMatrix: [8x8 double]
         SE: [8x1 double]
```



```
ans =
```

```
-1.0845  
-1.3132  
-1.2152  
-0.1736  
0.3072  
0.3735  
0.3179  
-0.3488
```

```
ans =
```

```
0.0682  
0.0695  
0.0651  
0.0436  
0.0832  
0.0636  
0.0847  
0.0698
```

```
PredictOutput = predict_henv(ModelOutput, Xnew, 'prediction')  
PredictOutput$SE
```

```
PredictOutput =
```

```
value: [8x1 double]  
covMatrix: [8x8 double]  
SE: [8x1 double]
```

```
ans =
```

```
0.3720  
0.3812  
0.3581  
0.2398  
0.4612  
0.3519  
0.4710  
0.3854
```

25 testcoefficient_henv

This function tests the null hypothesis $L * \beta * R = A$ versus the alternative hypothesis $L * \beta * R \neq A$, where β is estimated under the heteroscedastic envelope model.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
TestOutput = testcoefficient_henv(ModelOutput)
TestOutput = testcoefficient_henv(ModelOutput, TestInput)
```

Input

ModelOutput: A list containing the maximum likelihood estimators and other statistics inherited from henv.

TestInput: A list that specifies the null hypothesis, including L, R, and A. If not provided by the user, default values will be used.

- TestInput.L: The matrix multiplied to β on the left. It is a $d1$ by r matrix, while $d1$ is less than or equal to $r - 1$. Default value: identity matrix I_r .
- TestInput.R: The matrix multiplied to β on the right. It is a p by $d2$ matrix, while $d2$ is less than or equal to p . Default value: identity matrix $(I_{p-1}, 0_{(p-1) \times 1})^T$. This is because the columns of β sum to 0. Then we cannot use I_p as default.
- TestInput.A: The matrix on the right hand side of the equation. It is a $d1$ by $d2$ matrix. Default value: $d1$ by $d2$ zero matrix.

Output

TestOutput: A list containing test statistics, degrees of freedom for the reference chi-squared distribution, and the p-value. At the same time, a table is printed out.

- TestOutput.chisqStatistic: The test statistics. A real number.
- TestOutput.df: The degrees of freedom of the reference chi-squared distribution. A positive integer.
- TestOutput.pValue: p-value of the test. A real number in $[0, 1]$.

Description

This function tests for hypothesis $H_0 : L\beta R = A$, versus $H_\alpha : L\beta R \neq A$. The β is estimated by the heteroscedastic envelope model. If the user does not specify the values for L, R and A, then the test is equivalent to the standard F test on if all the main group effects are 0. The test statistics used is $\text{vec}(L\beta R - A) \hat{\Sigma}^{-1} \text{vec}(L\beta R - A)^T$, and the reference distribution is chi-squared distribution with degrees of freedom $d1 * d2$.

Example

```
load waterstrider.mat
u = lrt_henv(X, Y, 0.01);
ModelOutput = henv(X, Y, u);
TestOutout = testcoefficient_henv(ModelOutput);
```

Test Hypothesis	Chisq Statistic	DF	P-value
L * beta * R = A	226.256	16	0.0000

```
r = size(Y, 2);
p = size(ModelOutput.beta, 2);
TestInput.L = rand(2, r);
TestInput.R = rand(p, 1);
TestInput.A = zeros(2, 1);
TestOutout = testcoefficient_henv(ModelOutput, TestInput);
```

Test Hypothesis	Chisq Statistic	DF	P-value
L * beta * R = A	23.429	2	0.0000

Part IV

ienv

26 aic_ienv

Select the dimension of the inner envelope subspace using Akaike information criterion.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
u = aic_ienv(X, Y)
u = aic_ienv(X, Y, Opts)
```

Input

X: Predictors. An n by p matrix, p is the number of predictors and n is the number of observations. The predictors can be univariate or multivariate, discrete or continuous.

Y: Multivariate responses. An n by r matrix, r is the number of responses. The responses must be continuous variables.

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- `Opts.maxIter`: Maximum number of iterations. Default value: 300.
- `Opts.ftol`: Tolerance parameter for F. Default value: $1e-10$.
- `Opts.gradtol`: Tolerance parameter for dF. Default value: $1e-7$.
- `Opts.verbose`: Flag for print out dimension selection process, logical 0 or 1. Default value: 0.

Output

u: Dimension of the inner envelope. An integer between 0 and p or equal to r .

Description

This function implements the Akaike information criteria (AIC) to select the dimension of the inner envelope subspace.

Example

```
load irisf.mat  
u = aic_ienv(X, Y)
```

```
u =
```

```
1
```

27 bic_ienv

Select the dimension of the inner envelope subspace using Bayesian information criterion.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
u = bic_ienv(X, Y)
u = bic_ienv(X, Y, Opts)
```

Input

X: Predictors. An n by p matrix, p is the number of predictors and n is the number of observations. The predictors can be univariate or multivariate, discrete or continuous.

Y: Multivariate responses. An n by r matrix, r is the number of responses. The responses must be continuous variables.

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- `Opts.maxIter`: Maximum number of iterations. Default value: 300.
- `Opts.ftol`: Tolerance parameter for F. Default value: $1e-10$.
- `Opts.gradtol`: Tolerance parameter for dF. Default value: $1e-7$.
- `Opts.verbose`: Flag for print out dimension selection process, logical 0 or 1. Default value: 0.

Output

u: Dimension of the inner envelope. An integer between 0 and p or equal to r .

Description

This function implements the Bayesian information criteria (BIC) to select the dimension of the inner envelope subspace.

Example

```
load irisf.mat
u = bic_ienv(X, Y)
```

u =

1

28 bstrp_ienv

Compute bootstrap standard error for the inner envelope model.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
bootse = bstrp_ienv(X, Y, u, B)
bootse = bstrp_ienv(X, Y, u, B, Opts)
```

Input

X: Predictors, an n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.

Y: Multivariate responses, an n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.

u: Dimension of the inner envelope. An integer between 0 and p or equal to r .

B: Number of bootstrap samples. A positive integer.

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- `Opts.maxIter`: Maximum number of iterations. Default value: 300.
- `Opts.ftol`: Tolerance parameter for F. Default value: $1e-10$.
- `Opts.gradtol`: Tolerance parameter for dF. Default value: $1e-7$.
- `Opts.verbose`: Flag for print out the number of bootstrap samples, logical 0 or 1. Default value: 0.

Output

bootse: The standard error for elements in β computed by bootstrap. An r by p matrix.

Description

This function computes the bootstrap standard errors for the regression coefficients in the inner envelope model by bootstrapping the residuals.

Example

```
load irisf.mat

u = bic_ienv(X, Y)

u =

    1

B = 100;
bootse = bstrp_ienv(X, Y, u, B)

bootse =

    13.4695    4.9601
     7.4709    2.7315
    14.9316    5.2913
     8.7597    3.0853
```

29 dF4ienv

First derivative of the objective function for computing the inner envelope subspace.

Contents

- Syntax
- Input
- Output
- Description

Syntax

```
df = dF4ienv(R, DataParameter)
```

Input

R: An r by u semi-orthogonal matrix, $0 < u \leq p$.

DataParameter: A structure that contains the statistics calculated from the data.

Output

df: The first derivative of the objective function for computing the inner envelope subspace. An r by u matrix.

Description

This first derivative of F4ienv obtained by matrix calculus calculations.

30 F4ienv

Objective function for computing the inner envelope subspace.

Contents

- Syntax
- Input
- Output
- Description

Syntax

```
f = F4ienv(R, DataParameter)
```

Input

R: An r by u semi orthogonal matrix, $0 < u \leq p$.

DataParameter: A structure that contains the statistics calculated from the data.

Output

f: A scalar containing the value of the objective function evaluated at **R**.

Description

The objective function is derived in Section 3.3 in Su and Cook (2012) by using maximum likelihood estimation. The columns of the semi-orthogonal matrix that minimizes this function span the estimated inner envelope subspace.

31 ienv

Fit the inner envelope model.

Contents

- Syntax
- Input
- Output
- Description
- References
- Example

Syntax

```
ModelOutput = ienv(X, Y, u)
ModelOutput = ienv(X, Y, u, Opts)
```

Input

X: Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.

Y: Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables, and r should be strictly greater than p .

u: Dimension of the inner envelope. An integer between 0 and p or equal to r .

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- `Opts.maxIter`: Maximum number of iterations. Default value: 300.
- `Opts.ftol`: Tolerance parameter for F. Default value: $1e-10$.
- `Opts.gradtol`: Tolerance parameter for dF. Default value: $1e-7$.
- `Opts.verbose`: Flag for print out Grassmann manifold optimization process, logical 0 or 1. Default value: 0.

Output

ModelOutput: A list that contains the maximum likelihood estimators and some statistics.

- `ModelOutput.beta`: The envelope estimator of the regression coefficients β . An r by p matrix.
- `ModelOutput.Sigma`: The envelope estimator of the error covariance matrix. An r by r matrix.
- `ModelOutput.Gamma1`: The orthogonal basis of the inner envelope subspace. An r by u semi-orthogonal matrix.
- `ModelOutput.Gamma0`: The orthogonal basis of the complement of the inner envelope subspace. An r by $r-u$ semi-orthogonal matrix.
- `ModelOutput.eta1`: The transpose of the coordinates of β with respect to `Gamma1`. An p by u matrix.
- `ModelOutput.B`: An $(r - u)$ by $(p - u)$ semi-orthogonal matrix, so that $(\text{Gamma0}, \text{Gamma0} * B)$ spans β .
- `ModelOutput.eta2`: The transpose of the coordinates of β with respect to `Gamma0`. An p by $(p-u)$ matrix.
- `ModelOutput.Omega1`: The coordinates of `Sigma` with respect to `Gamma1`. An u by u matrix.
- `ModelOutput.Omega0`: The coordinates of `Sigma` with respect to `Gamma0`. An $r - u$ by $r - u$ matrix.
- `ModelOutput.alpha`: The estimated intercept in the inner envelope model. An r by 1 vector.
- `ModelOutput.l`: The maximized log likelihood function. A real number.
- `ModelOutput.covMatrix`: The asymptotic covariance of $\text{vec}(\beta)$. An rp by rp matrix. The covariance matrix returned are asymptotic. For the actual standard errors, multiply by $1/n$.
- `ModelOutput.asyIenv`: Asymptotic standard error for elements in β under the inner envelope model. An r by p matrix. The standard errors returned are asymptotic, for actual standard errors, multiply by $1 / \sqrt{n}$.
- `ModelOutput.ratio`: The asymptotic standard error ratio of the standard multivariate linear regression estimator over the inner envelope estimator, for each element in β . An r by p matrix.
- `ModelOutput.np`: The number of parameters in the inner envelope model. A positive integer.
- `ModelOutput.n`: The number of observations in the data. A positive integer.

Description

This function fits the inner envelope model to the responses and predictors, using the maximum likelihood estimation. When the dimension of the envelope is between 1 and $p-1$, we implemented the algorithm in Su and Cook (2012). When the dimension is p , then the inner envelope model degenerates to the standard multivariate linear regression. When the dimension is 0, it means that X and Y are uncorrelated, and the fitting is different.

References

1. The codes is implemented based on the algorithm in Su and Cook (2012).
2. The Grassmann manifold optimization step calls the package `sg_min` 2.4.1 by Ross Lippert (<http://web.mit.edu/~ripper/www.sgmin.html>).

Example

The following codes gives the results of the Fisher's iris data example in Su and Cook (2012).

```
load irisf.mat

d = bic_ienv(X, Y)

d =

1

ModelOutput = ienv(X, Y, d)
1 - 1 ./ ModelOutput.ratio

ModelOutput =

    beta: [4x2 double]
    Sigma: [4x4 double]
    Gamma1: [4x1 double]
    Gamma0: [4x3 double]
    B: [3x1 double]
    eta1: [2x1 double]
    eta2: [2x1 double]
    Omega1: 8.3751
    Omega0: [3x3 double]
    alpha: [4x1 double]
    np: 16
    l: -1.4805e+03
    covMatrix: [8x8 double]
    asyIenv: [4x2 double]
    ratio: [4x2 double]
    n: 150

ans =
```

0.0049	0.2122
0.0020	0.0806
0.0033	0.1404
0.0004	0.0138

32 lrt_ienv

Select the dimension of the inner envelope subspace using likelihood ratio testing.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
u = lrt_ienv(X, Y, alpha)
u = lrt_ienv(X, Y, alpha, Opts)
```

Input

X: Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.

Y: Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.

alpha: Significance level for testing. A real number between 0 and 1, often taken at 0.05 or 0.01.

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- `Opts.maxIter`: Maximum number of iterations. Default value: 300.
- `Opts.ftol`: Tolerance parameter for F. Default value: $1e-10$.
- `Opts.gradtol`: Tolerance parameter for dF. Default value: $1e-7$.
- `Opts.verbose`: Flag for print out dimension selection process, logical 0 or 1. Default value: 0.

Output

u: Dimension of the inner envelope. An integer between 0 and p or equal to r .

Description

This function implements the likelihood ratio testing procedure to select the dimension of the inner envelope subspace, with pre-specified significance level α .

Example

```
load irisf.mat

alpha = 0.01;
u = lrt_ienv(X, Y, alpha)

u =

     1
```

33 predict_ienv

Perform estimation or prediction under the inner envelope model.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
PredictOutput = predict_ienv(ModelOutput, Xnew, infType)
```

Input

ModelOutput: A list containing the maximum likelihood estimators and other statistics inherited from ienv.

Xnew: The value of X with which to estimate or predict Y. A p by 1 vector.

infType: A string of characters indicting the inference type, the choices can be 'estimation' or 'prediction'.

Output

PredictOutput: A list containing the results of the inference.

- PredictOutput.value: The fitted value or the prediction value evaluated at Xnew. An r by 1 vector.
- PredictOutput.covMatrix: The covariance matrix of PredictOutput.value. An r by r matrix.
- PredictOutput.SE: The standard error of elements in PredictOutput.value. An r by 1 vector.

Description

This function evaluates the inner envelope model at new value Xnew. It can perform estimation: find the fitted value when $X = X_{\text{new}}$, or prediction: predict Y when $X = X_{\text{new}}$. The covariance matrix and the standard errors are also provided.

Example

```
load irisf.mat
d = bic_ienv(X, Y);
ModelOutput = ienv(X, Y, d);
Xnew = X(1, :)';
PredictOutput = predict_ienv(ModelOutput, Xnew, 'estimation')
[PredictOutput.value, Y(1, :)] % Compare the fitted value with the data
PredictOutput.SE
```

```
PredictOutput =
```

```
value: [4x1 double]
covMatrix: [4x4 double]
SE: [4x1 double]
```

```
ans =
```

```
49.9458    51.0000
34.2592    35.0000
14.5771    14.0000
2.4513     2.0000
```

```
ans =
```

```
1.0978
0.7146
0.9265
0.4357
```

```
PredictOutput = predict_ienv(ModelOutput, Xnew, 'prediction')
PredictOutput.SE
```

```
PredictOutput =
```

```
value: [4x1 double]
covMatrix: [4x4 double]
SE: [4x1 double]
```

```
ans =
```

```
5.2197
```

3.3897
4.3996
2.0642

34 testcoefficient_ienv

This function tests the null hypothesis $L * \beta * R = A$ versus the alternative hypothesis $L * \beta * R \neq A$, where β is estimated under the inner envelope model.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
TestOutput = testcoefficient_ienv(ModelOutput)
TestOutput = testcoefficient_ienv(ModelOutput, TestInput)
```

Input

ModelOutput: A list containing the maximum likelihood estimators and other statistics inherited from ienv.

TestInput: A list that specifies the null hypothesis, including L, R, and A. If not provided by the user, default values will be used.

- TestInput.L: The matrix multiplied to β on the left. It is a d1 by r matrix, while d1 is less than or equal to r. Default value: identity matrix I_r .
- TestInput.R: The matrix multiplied to β on the right. It is a p by d2 matrix, while d2 is less than or equal to p. Default value: identity matrix I_p .
- TestInput.A: The matrix on the right hand side of the equation. It is a d1 by d2 matrix. Default value: d1 by d2 zero matrix.

Output

TestOutput: A list containing test statistics, degrees of freedom for the reference chi-squared distribution, and the p-value. At the same time, a table is printed out.

- TestOutput.chisqStatistic: The test statistics. A real number.
- TestOutput.df: The degrees of freedom of the reference chi-squared distribution. A positive integer.
- TestOutput.pValue: p-value of the test. A real number in $[0, 1]$.

Description

This function tests for hypothesis $H_0 : L\beta R = A$, versus $H_\alpha : L\beta R \neq A$. The β is estimated by the inner envelope model. If the user does not specify the values for L, R and A, then the test is equivalent to the standard F test on if $\beta = 0$. The test statistics used is $\text{vec}(L\beta R - A) \hat{\Sigma}^{-1} \text{vec}(L\beta R - A)^T$, and the reference distribution is chi-squared distribution with degrees of freedom $d1 * d2$.

Example

```
load irisf.mat
d = bic_ienv(X,Y);
ModelOutput = ienv(X,Y,d);
TestOutout = testcoefficient_ienv(ModelOutput);
```

Test Hypothesis	Chisq Statistic	DF	P-value
L * beta * R = A	4642.913	8	0.0000

```
TestInput.L = rand(2, 4);
TestInput.R = rand(2, 1);
TestInput.A = zeros(2, 1);
TestOutout = testcoefficient_ienv(ModelOutput, TestInput);
```

Test Hypothesis	Chisq Statistic	DF	P-value
L * beta * R = A	1834.229	2	0.0000

Part V

penv

35 aic_penv

Select the dimension of the partial envelope subspace using Akaike information criterion.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
u = aic_penv(X, Y)
u = aic_penv(X, Y, Opts)
```

Input

X: A list containing the value of X1 and X2.

- X.X1: Predictors of main interest. An n by p1 matrix, n is the number of observations, and p1 is the number of main predictors. The predictors can be univariate or multivariate, discrete or continuous.
- X.X2: Covariates, or predictors not of main interest. An n by p2 matrix, p2 is the number of covariates.

Y: Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.

Opts: A list containing the optional input parameter, to control the iterations in sg_min. If one or several (even all) fields are not defined, the default settings are used.

- Opts.maxIter: Maximum number of iterations. Default value: 300.
- Opts.ftol: Tolerance parameter for F. Default value: 1e-10.
- Opts.gradtol: Tolerance parameter for dF. Default value: 1e-7.
- Opts.verbose: Flag for print out dimension selection process, logical 0 or 1. Default value: 0.

Output

u: Dimension of the envelope. An integer between 0 and r.

Description

This function implements the Akaike information criteria (AIC) to select the dimension of the partial envelope subspace.

Example

```
load fiberpaper.dat
Y = fiberpaper(:, 1 : 4);
Xtemp = fiberpaper(:, 5 : 7);
X.X1 = Xtemp(:, 3);
X.X2 = Xtemp(:, 1 : 2);
u = aic_penv(X, Y)
```

u =

3

36 bic_penv

Select the dimension of the partial envelope subspace using Bayesian information criterion.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
u = bic_penv(X, Y)
u = bic_penv(X, Y, Opts)
```

Input

X: A list containing the value of X1 and X2.

- X.X1: Predictors of main interest. An n by p1 matrix, n is the number of observations, and p1 is the number of main predictors. The predictors can be univariate or multivariate, discrete or continuous.
- X.X2: Covariates, or predictors not of main interest. An n by p2 matrix, p2 is the number of covariates.

Y: Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.

Opts: A list containing the optional input parameter, to control the iterations in sg_min. If one or several (even all) fields are not defined, the default settings are used.

- Opts.maxIter: Maximum number of iterations. Default value: 300.
- Opts.ftol: Tolerance parameter for F. Default value: 1e-10.
- Opts.gradtol: Tolerance parameter for dF. Default value: 1e-7.
- Opts.verbose: Flag for print out dimension selection process, logical 0 or 1. Default value: 0.

Output

u: Dimension of the envelope. An integer between 0 and r.

Description

This function implements the Bayesian information criteria (BIC) to select the dimension of the partial envelope subspace.

Example

```
load fiberpaper.dat
Y = fiberpaper(:, 1 : 4);
Xtemp = fiberpaper(:, 5 : 7);
X.X1 = Xtemp(:, 3);
X.X2 = Xtemp(:, 1 : 2);
u = bic_penv(X, Y)
```

u =

1

37 bstrp_penv

Compute bootstrap standard error for the partial envelope model.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
bootse = bstrp_penv(X, Y, u, B)
bootse = bstrp_penv(X, Y, u, B, Opts)
```

Input

X: A list containing the value of X1 and X2.

- X.X1: Predictors of main interest. An n by p1 matrix, n is the number of observations, and p1 is the number of main predictors. The predictors can be univariate or multivariate, discrete or continuous.
- X.X2: Covariates, or predictors not of main interest. An n by p2 matrix, p2 is the number of covariates.

Y: Multivariate responses, an n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.

u: Dimension of the partial envelope subspace. A positive integer between 0 and r.

B: Number of bootstrap samples. A positive integer.

Opts: A list containing the optional input parameter, to control the iterations in sg_min. If one or several (even all) fields are not defined, the default settings are used.

- Opts.maxIter: Maximum number of iterations. Default value: 300.
- Opts.ftol: Tolerance parameter for F. Default value: 1e-10.
- Opts.gradtol: Tolerance parameter for dF. Default value: 1e-7.
- Opts.verbose: Flag for print out the number of bootstrap samples, logical 0 or 1. Default value: 0.

Output

bootse: The standard error for elements in β_1 computed by bootstrap. An r by p_1 matrix.

Description

This function computes the bootstrap standard errors for the regression coefficients in the partial envelope model by bootstrapping the residuals.

Example

```
load fiberpaper.dat
Y = fiberpaper(:, 1 : 4);
Xtemp = fiberpaper(:, 5 : 7);
X.X1 = Xtemp(:, 3);
X.X2 = Xtemp(:, 1 : 2);
alpha = 0.01;
u = lrt_penv(X, Y, alpha)
```

u =

```
1
```

```
B = 100;
bootse = bstrp_penv(X, Y, u, B)
```

bootse =

```
0.0074
0.0021
0.0043
0.0019
```

38 lrt_penv

Select the dimension of the partial envelope subspace using likelihood ratio testing.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
u = lrt_penv(X, Y, alpha)
u = lrt_penv(X, Y, alpha, Opts)
```

Input

X: A list containing the value of X1 and X2.

- X.X1: Predictors of main interest. An n by p1 matrix, n is the number of observations, and p1 is the number of main predictors. The predictors can be univariate or multivariate, discrete or continuous.
- X.X2: Covariates, or predictors not of main interest. An n by p2 matrix, p2 is the number of covariates.

Y: Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.

alpha: Significance level for testing. A real number between 0 and 1, often taken at 0.05 or 0.01.

Opts: A list containing the optional input parameter, to control the iterations in sg_min. If one or several (even all) fields are not defined, the default settings are used.

- Opts.maxIter: Maximum number of iterations. Default value: 300.
- Opts.ftol: Tolerance parameter for F. Default value: 1e-10.
- Opts.gradtol: Tolerance parameter for dF. Default value: 1e-7.
- Opts.verbose: Flag for print out dimension selection process, logical 0 or 1. Default value: 0.

Output

u: Dimension of the partial envelope subspace. An integer between 0 and r .

Description

This function implements the likelihood ratio testing procedure to select the dimension of the partial envelope subspace, with pre-specified significance level α .

Example

```
load fiberpaper.dat
Y = fiberpaper(:, 1 : 4);
Xtemp = fiberpaper(:, 5 : 7);
X.X1 = Xtemp(:, 3);
X.X2 = Xtemp(:, 1 : 2);
alpha = 0.01;
u = lrt_penv(X, Y, alpha)
```

u =

1

39 `penv`

Fit the partial envelope model.

Contents

- Syntax
- Input
- Output
- Description
- References
- Example

Syntax

```
ModelOutput = penv(X, Y, u)
ModelOutput = penv(X, Y, u, Opts)
```

Input

X: A list containing the value of X1 and X2.

- X.X1: Predictors of main interest. An n by p1 matrix, n is the number of observations, and p1 is the number of main predictors. The predictors can be univariate or multivariate, discrete or continuous.
- X.X2: Covariates, or predictors not of main interest. An n by p2 matrix, p2 is the number of covariates.

Y: Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables, and r should be strictly greater than p1.

u: Dimension of the partial envelope. An integer between 0 and r.

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- Opts.maxIter: Maximum number of iterations. Default value: 300.
- Opts.ftol: Tolerance parameter for F. Default value: 1e-10.
- Opts.gradtol: Tolerance parameter for dF. Default value: 1e-7.
- Opts.verbose: Flag for print out Grassmann manifold optimization process, logical 0 or 1. Default value: 0.

Output

ModelOutput: A list that contains the maximum likelihood estimators and some statistics.

- **ModelOutput.beta1:** The partial envelope estimator of β_1 , which is the regression coefficients for X1. An r by p1 matrix.
- **ModelOutput.beta2:** The partial envelope estimator of β_2 , which is the regression coefficients for X2. An r by p2 matrix.
- **ModelOutput.Sigma:** The partial envelope estimator of the error covariance matrix. An r by r matrix.
- **ModelOutput.Gamma:** The orthogonal basis of the partial envelope subspace. An r by u semi-orthogonal matrix.
- **ModelOutput.Gamma0:** The orthogonal basis of the complement of the partial envelope subspace. An r by r - u semi-orthogonal matrix.
- **ModelOutput.eta:** The coordinates of β_1 with respect to Gamma. An u by p1 matrix.
- **ModelOutput.Omega:** The coordinates of Sigma with respect to Gamma. An u by u matrix.
- **ModelOutput.Omega0:** The coordinates of Sigma with respect to Gamma0. An r - u by r - u matrix.
- **ModelOutput.alpha:** The estimated intercept in the partial envelope model. An r by 1 vector.
- **ModelOutput.l:** The maximized log likelihood function. A real number.
- **ModelOutput.covMatrix:** The asymptotic covariance of $(\text{vec}(\beta_2)', \text{vec}(\beta_1)')'$. An rp by rp matrix. The covariance matrix returned are asymptotic. For the actual standard errors, multiply by 1/n.
- **ModelOutput.asyPenv:** Asymptotic standard error for elements in β_1 under the partial envelope model. An r by p1 matrix. The standard errors returned are asymptotic, for actual standard errors, multiply by 1/sqrt(n).
- **ModelOutput.ratio:** The asymptotic standard error ratio of the standard multivariate linear regression estimator over the partial envelope estimator, for each element in β_1 . An r by p1 matrix.
- **ModelOutput.np:** The number of parameters in the envelope model. A positive integer.
- **ModelOutput.n:** The number of observations in the data. A positive integer.

Description

This function fits the partial envelope model to the responses Y and predictors X1 and X2, using the maximum likelihood estimation. When the dimension of the envelope is between 1 and r - 1, we implemented the algorithm in Su and Cook (2011). When the dimension is r, then the partial envelope model degenerates to the standard multivariate linear regression with Y as the responses and both X1 and X2 as predictors. When the dimension is 0, X1 and Y are

uncorrelated, and the fitting is the standard multivariate linear regression with Y as the responses and X_2 as the predictors.

References

1. The codes is implemented based on the algorithm in Section 3.2 of Su and Cook (2012).
2. The Grassmann manifold optimization step calls the package `sg_min` 2.4.1 by Ross Lippert (<http://web.mit.edu/~ripper/www.sgmin.html>).

Example

The following codes reconstruct the results of the paper and fiber example in Su and Cook (2012).

```
load fiberpaper.dat
Y = fiberpaper(:, 1 : 4);
Xtemp = fiberpaper(:, 5 : 7);
X.X1 = Xtemp(:, 3);
X.X2 = Xtemp(:, 1 : 2);
alpha = 0.01;
u = lrt_penv(X, Y, alpha)

u =

1

ModelOutput = penv(X, Y, u)
ModelOutput.Omega
eig(ModelOutput.Omega0)
ModelOutput.ratio

ModelOutput =

    beta1: [4x1 double]
    beta2: [4x2 double]
    alpha: [4x1 double]
    Gamma: [4x1 double]
        eta: 0.0047
    Omega: 0.0149
    Omega0: [3x3 double]
    Sigma: [4x4 double]
         l: -35.6323
```

```
np: 23
covMatrix: [12x12 double]
asyPenv: [4x1 double]
ratio: [4x1 double]
n: 62
```

```
ans =
```

```
0.0149
```

```
ans =
```

```
4.9819
0.0999
0.0050
```

```
ans =
```

```
66.0742
6.9326
10.5048
9.6279
```

40 `predict_penv`

Perform estimation or prediction under the partial envelope model.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
PredictOutput = predict_penv(ModelOutput, Xnew, infType)
```

Input

ModelOutput: A list containing the maximum likelihood estimators and other statistics inherited from `penv`.

Xnew: A list containing the value of X1 and X2 with which to estimate or predict Y.

- * **Xnew.X1:** A p1 by 1 vector containing the value of X1.
- * **Xnew.X2:** A p2 by 1 vector containing the value of X2.

infType: A string of characters indicting the inference type, the choices can be 'estimation' or 'prediction'.

Output

PredictOutput: A list containing the results of the inference.

- **PredictOutput.value:** The fitted value or the prediction value evaluated at Xnew. An r by 1 vector.
- **PredictOutput.covMatrix:** The covariance matrix of PredictOutput.value. An r by r matrix.
- **PredictOutput.SE:** The standard error of elements in PredictOutput.value. An r by 1 vector.

Description

This function evaluates the envelope model at new value X_{new} . It can perform estimation: find the fitted value when $X = X_{\text{new}}$, or prediction: predict Y when $X = X_{\text{new}}$. The covariance matrix and the standard errors are also provided.

Example

```
load fiberpaper.dat
Y = fiberpaper(:, 1 : 4);
Xtemp = fiberpaper(:, 5 : 7);
X.X1 = Xtemp(:, 3);
X.X2 = Xtemp(:, 1 : 2);
alpha = 0.01;
u = lrt_penv(X, Y, alpha);
ModelOutput = penv(X, Y, u);
Xnew.X1 = X.X1(1, :)';
Xnew.X2 = X.X2(1, :)';
PredictOutput = predict_penv(ModelOutput, Xnew, 'estimation')
[PredictOutput.value, Y(1, :)] % Compare the fitted value with the data
PredictOutput.SE
```

PredictOutput =

```
value: [4x1 double]
covMatrix: [4x4 double]
SE: [4x1 double]
```

ans =

```
21.1169    21.3120
 7.1173     7.0390
 5.3637     5.3260
 0.8737     0.9320
```

ans =

```
1.4680
0.4234
0.7145
0.3161
```

```

PredictOutput = predict_penv(ModelOutput, Xnew, 'prediction')
PredictOutput.SE

PredictOutput =

      value: [4x1 double]
 covMatrix: [4x4 double]
        SE: [4x1 double]

ans =

2.4277
0.6982
1.1802
0.5220

```

41 testcoefficient_penv

This function tests the null hypothesis $L * \beta * R = A$ versus the alternative hypothesis $L * \beta * R \neq A$, where β is estimated under the envelope model.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
TestOutput = testcoefficient_penv(ModelOutput)
TestOutput = testcoefficient_penv(ModelOutput, TestInput)
```

Input

ModelOutput: A list containing the maximum likelihood estimators and other statistics inherited from `penv`.

TestInput: A list that specifies the null hypothesis, including L , R , and A . If not provided by the user, default values will be used.

- TestInput.L: The matrix multiplied to β on the left. It is a d_1 by r matrix, while d_1 is less than or equal to r . Default value: identity matrix I_r .
- TestInput.R: The matrix multiplied to β on the right. It is a p_1 by d_2 matrix, while d_2 is less than or equal to p_1 . Default value: identity matrix I_{p_1} .
- TestInput.A: The matrix on the right hand side of the equation. It is a d_1 by d_2 matrix. Default value: d_1 by d_2 zero matrix.

Output

TestOutput: A list containing test statistics, degrees of freedom for the reference chi-squared distribution, and the p-value. At the same time, a table is printed out.

- TestOutput.chisqStatistic: The test statistics. A real number.
- TestOutput.df: The degrees of freedom of the reference chi-squared distribution. A positive integer.
- TestOutput.pValue: p-value of the test. A real number in $[0, 1]$.

Description

This function tests for hypothesis $H_0 : L\beta R = A$, versus $H_\alpha : L\beta R \neq A$. The β is estimated by the partial envelope model. If the user does not specify the values for L, R and A, then the test is equivalent to the standard F test on if $\beta = 0$. The test statistics used is $\text{vec}(L\beta R - A) \hat{\Sigma}^{-1} \text{vec}(L\beta R - A)^T$, and the reference distribution is chi-squared distribution with degrees of freedom $d1 * d2$.

Example

```
load fiberpaper.dat
Y = fiberpaper(:, 1 : 4);
Xtemp = fiberpaper(:, 5 : 7);
X.X1 = Xtemp(:, 3);
X.X2 = Xtemp(:, 1 : 2);
alpha = 0.01;
u = lrt_penv(X, Y, alpha);
ModelOutput = penv(X, Y, u);
TestOutout = testcoefficient_penv(ModelOutput);
```

Test Hypothesis	Chisq Statistic	DF	P-value
L * beta * R = A	12.604	4	0.0134

```
r = size(Y, 2);
p1 = size(X.X1, 2);
TestInput.L = rand(2, r);
TestInput.R = rand(p1, 1);
TestInput.A = zeros(2, 1);
TestOutout = testcoefficient_penv(ModelOutput, TestInput);
```

Test Hypothesis	Chisq Statistic	DF	P-value
L * beta * R = A	11.452	2	0.0033

Part VI

seiv

42 aic_seiv

Select the dimension of the scaled envelope subspace using Akaike information criterion.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
u = aic_seiv(X, Y)
u = aic_seiv(X, Y, Opts)
```

Input

X: Predictors. An n by p matrix, p is the number of predictors and n is the number of observations. The predictors can be univariate or multivariate, discrete or continuous.

Y: Multivariate responses. An n by r matrix, r is the number of responses. The responses must be continuous variables.

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- `Opts.maxIter`: Maximum number of iterations. Default value: 300.
- `Opts.ftol`: Tolerance parameter for F. Default value: $1e-10$.
- `Opts.gradtol`: Tolerance parameter for dF. Default value: $1e-7$.
- `Opts.verbose`: Flag for print out dimension selection process, logical 0 or 1. Default value: 0.

Output

u: Dimension of the inner envelope. An integer between 0 and r .

Description

This function implements the Akaike information criteria (AIC) to select the dimension of the scaled envelope subspace.

Example

```
load('sales.txt')
Y = sales(:, 4 : 7);
X = sales(:, 1 : 3);
u = aic_senv(X, Y)
```

u =

4

43 `bic_senv`

Select the dimension of the scaled envelope subspace using Bayesian information criterion.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
u = bic_senv(X, Y)
u = bic_senv(X, Y, Opts)
```

Input

X: Predictors. An n by p matrix, p is the number of predictors and n is the number of observations. The predictors can be univariate or multivariate, discrete or continuous.

Y: Multivariate responses. An n by r matrix, r is the number of responses. The responses must be continuous variables.

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- `Opts.maxIter`: Maximum number of iterations. Default value: 300.
- `Opts.ftol`: Tolerance parameter for F. Default value: $1e-10$.
- `Opts.gradtol`: Tolerance parameter for dF. Default value: $1e-7$.
- `Opts.verbose`: Flag for print out dimension selection process, logical 0 or 1. Default value: 0.

Output

u: Dimension of the inner envelope. An integer between 0 and r .

Description

This function implements the Bayesian information criteria (BIC) to select the dimension of the scaled envelope subspace.

Example

```
load('sales.txt')
Y = sales(:, 4 : 7);
X = sales(:, 1 : 3);
u = bic_senv(X, Y)
```

u =

2

44 bstrp_senv

Compute bootstrap standard error for the scaled envelope model.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
bootse = bstrp_senv(X, Y, u, B)
bootse = bstrp_senv(X, Y, u, B, Opts)
```

Input

X: Predictors, an n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.

Y: Multivariate responses, an n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.

u: Dimension of the envelope subspace. A positive integer between 0 and r .

B: Number of bootstrap samples. A positive integer.

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- `Opts.maxIter`: Maximum number of iterations. Default value: 300.
- `Opts.ftol`: Tolerance parameter for F. Default value: $1e-10$.
- `Opts.gradtol`: Tolerance parameter for dF. Default value: $1e-7$.
- `Opts.verbose`: Flag for print out the number of bootstrap samples, logical 0 or 1. Default value: 0.

Output

bootse: The standard error for elements in β computed by bootstrap. An r by p matrix.

Description

This function computes the bootstrap standard errors for the regression coefficients in the scaled envelope model by bootstrapping the residuals.

Example

```
load('sales.txt')
Y = sales(:, 4 : 7);
X = sales(:, 1 : 3);

u = bic_senv(X, Y)

u =

    2

B = 20;
bootse = bstrp_senv(X, Y, u, B)

bootse =

    0.0539    0.0472    0.0554
    0.0675    0.0912    0.1178
    0.0567    0.0781    0.0791
    0.0986    0.0944    0.1283
```

45 dF4senv

First derivative of the objective function for computing the envelope subspace in the scaled envelope model.

Contents

- Syntax
- Input
- Output
- Description

Syntax

```
df = dF4senv(R, DataParameter)
```

Input

R: An r by u semi-orthogonal matrix, $0 < u \leq r$.

DataParameter: A structure that contains the statistics calculated from the data.

Output

df: The first derivative of the objective function for computing the envelope subspace. An r by u matrix.

Description

This first derivative of F4senv obtained by matrix calculus calculations.

46 F4senv

Objective function for computing the envelope subspace in scaled envelope model.

Contents

- Syntax
- Input
- Output
- Description

Syntax

```
f = F4senv(R, DataParameter)
```

Input

R: An r by u semi orthogonal matrix, $0 < u \leq r$.

DataParameter: A structure that contains the statistics calculated from the data.

Output

f: A scalar containing the value of the objective function evaluated at R .

Description

The objective function is derived in Section 4.1 in Cook and Su (2012) using maximum likelihood estimation. The columns of the semi-orthogonal matrix that minimizes this function span the estimated envelope subspace.

47 objfun

Objective function for computing the scales in the scaled envelope model.

Contents

- Syntax
- Input
- Output
- Description

Syntax

```
f = objfun(d, Gamma, DataParameter)
```

Input

d: An $r - 1$ dimensional column vector containing the scales for the 2nd to the r th responses. All the entries in d are positive.

Gamma: A r by u semi-orthogonal matrix that spans the envelope subspace or the estimated envelope subspace.

DataParameter: A structure that contains the statistics calculated from the data.

Output

f: A scalar containing the value of the objective function evaluated at d .

Description

The objective function is derived in Section 4.1 of Su and Cook (2012) using maximum likelihood estimation.

48 `predict_senv`

Perform estimation or prediction under the scaled envelope model.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
PredictOutput = predict_senv(ModelOutput, Xnew, infType)
```

Input

ModelOutput: A list containing the maximum likelihood estimators and other statistics inherited from `senv`.

Xnew: The value of X with which to estimate or predict Y . A p by 1 vector.

infType: A string of characters indicting the inference type, the choices can be 'estimation' or 'prediction'.

Output

PredictOutput: A list containing the results of the inference.

- `PredictOutput.value`: The fitted value or the prediction value evaluated at X_{new} . An r by 1 vector.
- `PredictOutput.covMatrix`: The covariance matrix of `PredictOutput.value`. An r by r matrix.
- `PredictOutput.SE`: The standard error of elements in `PredictOutput.value`. An r by 1 vector.

Description

This function evaluates the scaled envelope model at new value X_{new} . It can perform estimation: find the fitted value when $X = X_{\text{new}}$, or prediction: predict Y when $X = X_{\text{new}}$. The covariance matrix and the standard errors are also provided.

Example

```
load('sales.txt')
Y = sales(:, 4 : 7);
X = sales(:, 1 : 3);
u = bic_senv(X, Y);
ModelOutput = senv(X, Y, u);
Xnew = X(1, :)';
PredictOutput = predict_senv(ModelOutput, Xnew, 'estimation')
[PredictOutput.value, Y(1, :)] % Compare the fitted value with the data
PredictOutput.SE
```

```
PredictOutput =
```

```
      value: [4x1 double]
covMatrix: [4x4 double]
      SE: [4x1 double]
```

```
ans =
```

```
      8.9109      9.0000
     11.5096     12.0000
      9.6063      9.0000
     19.5119     20.0000
```

```
ans =
```

```
      7.7627
      5.8952
      4.2205
      8.0134
```

```
PredictOutput = predict_senv(ModelOutput, Xnew, 'prediction')
PredictOutput.SE
```

```
PredictOutput =
```

```
      value: [4x1 double]
covMatrix: [4x4 double]
      SE: [4x1 double]
```

ans =

8.3024
6.3052
4.4254
8.5956

49 `senv`

Fit the scaled envelope model.

Contents

- Syntax
- Input
- Output
- Description
- References
- Example

Syntax

```
ModelOutput = senv(X, Y, u)
ModelOutput = senv(X, Y, u, Opts)
```

Input

X: Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.

Y: Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables, and r should be strictly greater than p .

u: Dimension of the envelope. An integer between 0 and r .

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- `Opts.maxIter`: Maximum number of iterations. Default value: 300.
- `Opts.ftol`: Tolerance parameter for F. Default value: $1e-10$.
- `Opts.gradtol`: Tolerance parameter for dF. Default value: $1e-7$.
- `Opts.verbose`: Flag for print out number of iterations, logical 0 or 1. Default value: 0.

Output

ModelOutput: A list that contains the maximum likelihood estimators and some statistics.

- `ModelOutput.beta`: The scaled envelope estimator of the regression coefficients β . An r by p matrix.

- `ModelOutput.Sigma`: The scaled envelope estimator of the error covariance matrix. An r by r matrix.
- `ModelOutput.Lambda`: The matrix of estimated scales. An r by r diagonal matrix with the first diagonal element equal to 1 and other diagonal elements being positive.
- `ModelOutput.Gamma`: The orthogonal basis of the envelope subspace. An r by u semi-orthogonal matrix.
- `ModelOutput.Gamma0`: The orthogonal basis of the complement of the envelope subspace. An r by $r - u$ semi-orthogonal matrix.
- `ModelOutput.eta`: The coordinates of β with respect to `Gamma`. An u by p matrix.
- `ModelOutput.Omega`: The coordinates of `Sigma` with respect to `Gamma`. An u by u matrix.
- `ModelOutput.Omega0`: The coordinates of `Sigma` with respect to `Gamma0`. An $r - u$ by $r - u$ matrix.
- `ModelOutput.alpha`: The estimated intercept in the scaled envelope model. An r by 1 vector.
- `ModelOutput.l`: The maximized log likelihood function. A real number.
- `ModelOutput.covMatrix`: The asymptotic covariance of $\text{vec}(\beta)$. An rp by rp matrix. The covariance matrix returned are asymptotic. For the actual standard errors, multiply by $1 / n$.
- `ModelOutput.asySenv`: Asymptotic standard error for elements in β under the scaled envelope model. An r by p matrix. The standard errors returned are asymptotic, for actual standard errors, multiply by $1 / \sqrt{n}$.
- `ModelOutput.ratio`: The asymptotic standard error ratio of the standard multivariate linear regression estimator over the scaled envelope estimator, for each element in β . An r by p matrix.
- `ModelOutput.np`: The number of parameters in the scaled envelope model. A positive integer.
- `ModelOutput.n`: The number of observations in the data. A positive integer.

Description

This function fits the scaled envelope model to the responses and predictors, using the maximum likelihood estimation. When the dimension of the envelope is between 1 and $r - 1$, we implemented the algorithm in Cook and Su (2012). When the dimension is r , then the scaled envelope model degenerates to the standard multivariate linear regression. When the dimension is 0, it means that X and Y are uncorrelated, and the fitting is different.

References

1. The codes is implemented based on the algorithm in Section 4.1 of Cook and Su (2012).

2. The Grassmann manifold optimization step calls the package `sg_min` 2.4.1 by Ross Lippert (<http://web.mit.edu/~ripper/www.sgmin.html>).

Example

The following codes produce the results of the test and performance example in Cook and Su (2012).

```
load('sales.txt')
Y = sales(:, 4 : 7);
X = sales(:, 1 : 3);
u = bic_senv(X, Y)

u =

    2

ModelOutput = senv(X, Y, u)
ModelOutput.Lambda
1 - 1 ./ ModelOutput.ratio

ModelOutput =

    beta: [4x3 double]
    Sigma: [4x4 double]
    Lambda: [4x4 double]
    Gamma: [4x2 double]
    Gamma0: [4x2 double]
    eta: [2x3 double]
    Omega: [2x2 double]
    Omega0: [2x2 double]
    alpha: [4x1 double]
    np: 23
    l: -386.1900
    covMatrix: [12x12 double]
    asySenv: [4x3 double]
    ratio: [4x3 double]
    n: 50

ans =

    1.0000         0         0         0
```

0	0.9729	0	0
0	0	0.8067	0
0	0	0	1.7016

ans =

0.7020	0.5218	0.6517
0.6137	0.3219	0.5614
0.4439	0.1858	0.3924
0.5375	0.4639	0.5228

50 testcoefficient_senv

This function tests the null hypothesis $L * \beta * R = A$ versus the alternative hypothesis $L * \beta * R \neq A$, where β is estimated under the scaled envelope model.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
TestOutput = testcoefficient_senv(ModelOutput)
TestOutput = testcoefficient_senv(ModelOutput, TestInput)
```

Input

ModelOutput: A list containing the maximum likelihood estimators and other statistics inherited from `senv`.

TestInput: A list that specifies the null hypothesis, including L , R , and A . If not provided by the user, default values will be used.

- TestInput.L: The matrix multiplied to β on the left. It is a $d1$ by r matrix, while $d1$ is less than or equal to r . Default value: identity matrix I_r .
- TestInput.R: The matrix multiplied to β on the right. It is a p by $d2$ matrix, while $d2$ is less than or equal to p . Default value: identity matrix I_p .
- TestInput.A: The matrix on the right hand side of the equation. It is a $d1$ by $d2$ matrix. Default value: $d1$ by $d2$ zero matrix.

Output

TestOutput: A list containing test statistics, degrees of freedom for the reference chi-squared distribution, and the p-value. At the same time, a table is printed out.

- TestOutput.chisqStatistic: The test statistics. A real number.
- TestOutput.df: The degrees of freedom of the reference chi-squared distribution. A positive integer.
- TestOutput.pValue: p-value of the test. A real number in $[0, 1]$.

Description

This function tests for hypothesis $H_0 : L\beta R = A$, versus $H_\alpha : L\beta R \neq A$. The β is estimated by the scaled envelope model. If the user does not specify the values for L, R and A, then the test is equivalent to the standard F test on if $\beta = 0$. The test statistics used is $\text{vec}(L\beta R - A) \hat{\Sigma}^{-1} \text{vec}(L\beta R - A)^T$, and the reference distribution is chi-squared distribution with degrees of freedom $d1 * d2$.

Example

```
load('sales.txt')
Y = sales(:,4:7);
X = sales(:,1:3);
u = bic_senv(X,Y)
ModelOutput = senv(X,Y,u);
TestOutout = testcoefficient_senv(ModelOutput);
```

Test Hypothesis	Chisq Statistic	DF	P-value
L * beta * R = A	4827.816	12	0.0000

```
r = size(Y, 2);
p = size(X, 2);
TestInput.L = rand(2, r);
TestInput.R = rand(p, 1);
TestInput.A = zeros(2, 1);
TestOutout = testcoefficient_senv(ModelOutput, TestInput);
```

Test Hypothesis	Chisq Statistic	DF	P-value
L * beta * R = A	1025.948	2	0.0000

Part VII

xenv

51 aic_xenv

Use Akaike information criterion to select the dimension of the envelope subspace for the reduction on X .

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
u = aic_xenv(X, Y)
u = aic_xenv(X, Y, Opts)
```

Input

X: Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.

Y: Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- `Opts.maxIter`: Maximum number of iterations. Default value: 300.
- `Opts.ftol`: Tolerance parameter for F . Default value: $1e-10$.
- `Opts.gradtol`: Tolerance parameter for dF . Default value: $1e-7$.
- `Opts.verbose`: Flag for print out dimension selection process, logical 0 or 1. Default value: 0.

Output

u: Dimension of the envelope. An integer between 0 and p .

Description

This function implements the Akaike information criteria (AIC) to select the dimension of the envelope subspace for the reduction on X.

Example

```
load wheatprotein.txt
X = wheatprotein(:, 1 : 6);
Y = wheatprotein(:, 7);
u = aic_xenv(X, Y)
```

u =

4

52 bic_xenv

Use Bayesian information criterion to select the dimension of the envelope subspace for the reduction on X.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
u = bic_xenv(X, Y)
u = bic_xenv(X, Y, Opts)
```

Input

X: Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.

Y: Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.

Opts: A list containing the optional input parameter, to control the iterations in sg_min. If one or several (even all) fields are not defined, the default settings are used.

- Opts.maxIter: Maximum number of iterations. Default value: 300.
- Opts.ftol: Tolerance parameter for F. Default value: 1e-10.
- Opts.gradtol: Tolerance parameter for dF. Default value: 1e-7.
- Opts.verbose: Flag for print out dimension selection process, logical 0 or 1. Default value: 0.

Output

u: Dimension of the envelope. An integer between 0 and p.

Description

This function implements the Bayesian information criteria (BIC) to select the dimension of the envelope subspace for the reduction on X.

Example

```
load wheatprotein.txt
X = wheatprotein(:, 1 : 6);
Y = wheatprotein(:, 7);
u = bic_xenv(X, Y)
```

u =

4

53 bstrp_xenv

Compute bootstrap standard error of the envelope model for the reduction on X .

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
bootse = bstrp_xenv(X, Y, u, B)
bootse = bstrp_xenv(X, Y, u, B, Opts)
```

Input

X: Predictors, an n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.

Y: Multivariate responses, an n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.

u: Dimension of the envelope subspace. A positive integer between 0 and p .

B: Number of bootstrap samples. A positive integer.

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- `Opts.maxIter`: Maximum number of iterations. Default value: 300.
- `Opts.ftol`: Tolerance parameter for F. Default value: $1e-10$.
- `Opts.gradtol`: Tolerance parameter for dF. Default value: $1e-7$.
- `Opts.verbose`: Flag for print out the number of bootstrap samples, logical 0 or 1. Default value: 0.

Output

bootse: The standard error for elements in β computed by bootstrap. An p by r matrix.

Description

This function computes the bootstrap standard errors for the regression coefficients in the envelope model by bootstrapping the residuals. The envelope model here is for the reduction on X.

Example

```
load wheatprotein.txt
X = wheatprotein(:, 1 : 6);
Y = wheatprotein(:, 7);
alpha = 0.01;
u = lrt_xenv(X, Y, alpha)

u =

    4

B = 100;
bootse = bstrp_xenv(X, Y, u, B)

bootse =

    0.0222
    0.0387
    0.0413
    0.0167
    0.0022
    0.0087
```

54 dF4xenv

The first derivative of the objective function for computing the envelope subspace for the reduction on X .

Contents

- Syntax
- Input
- Output
- Description

Syntax

```
df = dF4xenv(R, DataParameter)
```

Input

R: A p by u semi orthogonal matrix, $0 < u \leq p$.

DataParameter: A structure that contains the statistics calculated from the data.

Output

df: An p by u matrix containing the value of the derivative function evaluated at R .

Description

The objective function is derived in Section 4.5.1 of Cook et al. (2012) by using maximum likelihood estimation. This function is the derivative of the objective function.

55 F4xenv

Objective function for computing the envelope subspace for the reduction on X.

Contents

- Syntax
- Input
- Output
- Description

Syntax

```
f = F4xenv(R, DataParameter)
```

Input

R: A p by u semi orthogonal matrix, $0 < u \leq p$.

DataParameter: A structure that contains the statistics calculated from the data.

Output

f: A scalar containing the value of the objective function evaluated at R.

Description

The objective function is derived in Section 4.5.1 of Cook et al. (2012) using maximum likelihood estimation. The columns of the semi-orthogonal matrix that minimizes this function span the estimated envelope subspace.

56 lrt_xenv

Use likelihood ratio testing to select the dimension of the envelope subspace for the reduction on X .

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
u = lrt_xenv(X, Y, alpha)
u = lrt_xenv(X, Y, alpha, Opts)
```

Input

X: Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.

Y: Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables.

alpha: Significance level for testing. A real number between 0 and 1, often taken at 0.05 or 0.01.

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- `Opts.maxIter`: Maximum number of iterations. Default value: 300.
- `Opts.ftol`: Tolerance parameter for F. Default value: $1e-10$.
- `Opts.gradtol`: Tolerance parameter for dF. Default value: $1e-7$.
- `Opts.verbose`: Flag for print out dimension selection process, logical 0 or 1. Default value: 0.

Output

u: Dimension of the envelope. An integer between 0 and p .

Description

This function implements the likelihood ratio testing procedure to select the dimension of the envelope subspace for the reduction on X , with pre-specified significance level α .

Example

```
load wheatprotein.txt
X = wheatprotein(:, 1 : 6);
Y = wheatprotein(:, 7);
alpha = 0.01;
u = lrt_xenv(X, Y, alpha)
```

u =

4

57 `predict_xenv`

Perform estimation or prediction under the envelope model for the reduction on X.

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
PredictOutput = predict_xenv(ModelOutput, Xnew, infType)
```

Input

ModelOutput: A list containing the maximum likelihood estimators and other statistics inherited from `xenv`.

Xnew: The value of X with which to estimate or predict Y. A p by 1 vector.

infType: A string of characters indicting the inference type, the choices can be 'estimation' or 'prediction'.

Output

PredictOutput: A list containing the results of the inference.

- `PredictOutput.value`: The fitted value or the prediction value evaluated at Xnew. An r by 1 vector.
- `PredictOutput.covMatrix`: The covariance matrix of `PredictOutput.value`. An r by r matrix.
- `PredictOutput.SE`: The standard error of elements in `PredictOutput.value`. An r by 1 vector.

Description

This function evaluates the envelope model for the reduction on X at new value Xnew. It can perform estimation: find the fitted value when $X = X_{\text{new}}$, or prediction: predict Y when $X = X_{\text{new}}$. The covariance matrix and the standard errors are also provided.

Example

```
load wheatprotein.txt
X = wheatprotein(:, 1 : 6);
Y = wheatprotein(:, 7);
u = bic_xenv(X, Y)
ModelOutput = xenv(X, Y, u);
Xnew = X(1, :)';
PredictOutput = predict_xenv(ModelOutput, Xnew, 'estimation')
[PredictOutput.value, Y(1, :)] % Compare the fitted value with the data
PredictOutput.SE

PredictOutput =

    value: 9.1751
covMatrix: 16.8439
    SE: 4.1041

ans =

    9.1751    9.2300

ans =

    4.1041

    PredictOutput = predict_xenv(ModelOutput, Xnew, 'prediction')
    PredictOutput.SE

PredictOutput =

    value: 9.1751
covMatrix: 16.8760
    SE: 4.1080

ans =

    4.1080
```

58 testcoefficient_xenv

This function tests the null hypothesis $L * \beta * R = A$ versus the alternative hypothesis $L * \beta * R \neq A$, where β is estimated under the envelope model for the reduction on X .

Contents

- Syntax
- Input
- Output
- Description
- Example

Syntax

```
TestOutput = testcoefficient_xenv(ModelOutput)
TestOutput = testcoefficient_xenv(ModelOutput, TestInput)
```

Input

ModelOutput: A list containing the maximum likelihood estimators and other statistics inherited from `xenv`.

TestInput: A list that specifies the null hypothesis, including L , R , and A . If not provided by the user, default values will be used.

- TestInput.L: The matrix multiplied to β on the left. It is a $d1$ by p matrix, while $d1$ is less than or equal to p . Default value: identity matrix I_p .
- TestInput.R: The matrix multiplied to β on the right. It is a r by $d2$ matrix, while $d2$ is less than or equal to r . Default value: identity matrix I_r .
- TestInput.A: The matrix on the right hand side of the equation. It is a $d1$ by $d2$ matrix. Default value: $d1$ by $d2$ zero matrix.

Output

TestOutput: A list containing test statistics, degrees of freedom for the reference chi-squared distribution, and the p-value. At the same time, a table is printed out.

- TestOutput.chisqStatistic: The test statistics. A real number.
- TestOutput.df: The degrees of freedom of the reference chi-squared distribution. A positive integer.
- TestOutput.pValue: p-value of the test. A real number in $[0, 1]$.

Description

This function tests for hypothesis $H_0 : L\beta R = A$, versus $H_\alpha : L\beta R \neq A$. The β is estimated by the envelope model for the reduction on X. If the user does not specify the values for L, R and A, then the test is equivalent to the standard F test on if $\beta = 0$. The test statistics used is $\text{vec}(L\beta R - A) \hat{\Sigma}^{-1} \text{vec}(L\beta R - A)^T$, and the reference distribution is chi-squared distribution with degrees of freedom $d1 * d2$.

Example

```
load wheatprotein.txt
X=wheatprotein(:, 1 : 6);
Y=wheatprotein(:, 7);
u = bic_xenv(X, Y);
ModelOutput=xenv(X, Y, u);
TestOutout = testcoefficient_xenv(ModelOutput);
```

Test Hypothesis	Chisq Statistic	DF	P-value
L * beta * R = A	3233.053	6	0.0000

```
r = size(Y, 2);
p = size(X, 2);
TestInput.L = rand(2, p);
TestInput.R = rand(r, 1);
TestInput.A = zeros(2, 1);
TestOutout = testcoefficient_xenv(ModelOutput, TestInput);
```

Test Hypothesis	Chisq Statistic	DF	P-value
L * beta * R = A	33.578	2	0.0000

59 xenv

Fit the envelope model for the reduction on X .

Contents

- Syntax
- Input
- Output
- Description
- References
- Example

Syntax

```
ModelOutput = xenv(X, Y, u)
ModelOutput = xenv(X, Y, u, Opts)
```

Input

X: Predictors. An n by p matrix, p is the number of predictors. The predictors can be univariate or multivariate, discrete or continuous.

Y: Multivariate responses. An n by r matrix, r is the number of responses and n is number of observations. The responses must be continuous variables, and r should be strictly greater than p .

u: Dimension of the envelope. An integer between 0 and p .

Opts: A list containing the optional input parameter, to control the iterations in `sg_min`. If one or several (even all) fields are not defined, the default settings are used.

- `Opts.maxIter`: Maximum number of iterations. Default value: 300.
- `Opts.ftol`: Tolerance parameter for F . Default value: $1e-10$.
- `Opts.gradtol`: Tolerance parameter for dF . Default value: $1e-7$.
- `Opts.verbose`: Flag for print out Grassmann manifold optimization process, logical 0 or 1. Default value: 0.

Output

ModelOutput: A list that contains the maximum likelihood estimators and some statistics.

- `ModelOutput.beta`: The envelope estimator of the regression coefficients β . An p by r matrix.

- `ModelOutput.SigX`: The envelope estimator of the covariance matrix of X , Σ_X . A p by p matrix.
- `ModelOutput.Gamma`: The orthogonal basis of the envelope subspace. An p by u semi-orthogonal matrix.
- `ModelOutput.Gamma0`: The orthogonal basis of the complement of the envelope subspace. An p by $p-u$ semi-orthogonal matrix.
- `ModelOutput.eta`: The coordinates of β with respect to `Gamma`. An u by r matrix.
- `ModelOutput.Omega`: The coordinates of Σ_X with respect to `Gamma`. An u by u matrix.
- `ModelOutput.Omega0`: The coordinates of Σ_X with respect to `Gamma0`. An $p - u$ by $p - u$ matrix.
- `ModelOutput.mu`: The estimated intercept. An r by 1 vector.
- `ModelOutput.sigYcX`: The estimated conditional covariance matrix of Y given X . An r by r matrix.
- `ModelOutput.l`: The maximized log likelihood function. A real number.
- `ModelOutput.covMatrix`: The asymptotic covariance of $\text{vec}(\beta)$. An pr by pr matrix. The covariance matrix returned are asymptotic. For the actual standard errors, multiply by $1 / n$.
- `ModelOutput.asyXenv`: Asymptotic standard error for elements in β under the envelope model. An r by p matrix. The standard errors returned are asymptotic, for actual standard errors, multiply by $1 / \sqrt{n}$.
- `ModelOutput.ratio`: The asymptotic standard error ratio of the standard multivariate linear regression estimator over the envelope estimator, for each element in β . An p by r matrix.
- `ModelOutput.np`: The number of parameters in the envelope model. A positive integer.
- `ModelOutput.n`: The number of observations in the data. A positive integer.

Description

This function fits the envelope model to the responses and predictors, using the maximum likelihood estimation. When the dimension of the envelope is between 1 and $r - 1$, we implemented the algorithm in Cook et al. (2012). When the dimension is r , then the envelope model degenerates to the standard multivariate linear regression. When the dimension is 0, it means that X and Y are uncorrelated, and the fitting is different.

References

1. The codes is implemented based on the algorithm in Section 4.5.1 of Cook et al (2012).
2. The Grassmann manifold optimization step calls the package `sg_min` 2.4.1 by Ross Lippert (<http://web.mit.edu/~ripper/www.sgmin.html>).

Example

```
load wheatprotein.txt
X = wheatprotein(:, 1 : 6);
Y = wheatprotein(:, 7);

p = size(X, 2);
ModelOutput = xenv(X, Y, p);

% When u = p, the envelope model reduces to the ordinary least squares
% regression

temp = fit_OLS(X, Y);
temp.SigmaOLS
ModelOutput.sigYcX
temp.betaOLS'
ModelOutput.beta

ans =

    0.0321

ans =

    0.0321

ans =

   -0.0416
   -0.0490
    0.3368
   -0.1981
    0.0020
   -0.0480

ans =

   -0.0416
   -0.0490
    0.3368
   -0.1981
    0.0020
   -0.0480
```

```

u = bic_xenv(X, Y);
ModelOutput = xenv(X, Y, u)

ModelOutput =

    beta: [6x1 double]
    SigX: [6x6 double]
    Gamma: [6x4 double]
    Gamma0: [6x2 double]
    eta: [4x1 double]
    Omega: [4x4 double]
    Omega0: [2x2 double]
    mu: 24.8863
    sigYcX: 0.0321
    l: -6.7737e+05
    covMatrix: [6x6 double]
    asyXenv: [6x1 double]
    ratio: [6x1 double]
    np: 27
    n: 50

% To compare with the results obtained by Partial Least Squares, use the
% plsregress command
[XL, YL, XS, YS, BETA, PCTVAR, MSE, stats] = plsregress(X, Y, u);
ModelOutput.beta
BETA(2 : end, :)

ans =

-0.0443
-0.0481
 0.3377
-0.1963
 0.0019
-0.0487

ans =

-0.0199
 0.1373

```

0.1309
-0.1827
0.0056
-0.0708