

# Foodie Web Documentation

## 1. Introduction

Foodie is a revolutionary food delivery app designed to bring a variety of delicious cuisines from multiple restaurants straight to your doorstep. Built with Laravel & Flutter. Foodie offers a seamless and intuitive user experience, making it easier than ever to discover, order, and enjoy your favorite meals from local eateries.

### Key Features:

1. **Wide Selection of Restaurants:** Explore a vast array of restaurants, from local favorites to popular chains, all available at your fingertips.
2. **User-Friendly Interface:** Enjoy a sleek and intuitive design that makes browsing menus, placing orders, and tracking deliveries effortless.
3. **Real-Time Order Tracking:** Stay updated with real-time tracking of your order from preparation to delivery, ensuring you know exactly when your food will arrive.
4. **Customizable Orders:** Personalize your meals with special instructions and dietary preferences to suit your taste and dietary needs.
5. **Secure Payment Options:** Choose from multiple secure payment methods, including credit/debit cards, digital wallets, and cash on delivery.
6. **Exclusive Deals and Discounts:** Take advantage of exclusive offers, promotions, and discounts available only through the Foodie app.
7. **Easy Reordering:** Quickly reorder your favorite meals with just a few taps, thanks to a user-friendly reorder feature.
8. **Ratings and Reviews:** Make informed decisions with access to detailed ratings and reviews from other Foodie users.
9. **24/7 Customer Support:** Receive dedicated support anytime you need assistance, ensuring a smooth and satisfying food delivery experience.
10. **Multi-Platform Accessibility:** Enjoy Foodie on both Android and iOS devices, with a consistent and optimized performance across platforms.

### Why Choose Foodie?

Foodie stands out as a top-tier food delivery app by combining an extensive restaurant selection with a user-centric design, reliable delivery service, and secure payment options. Whether you're craving a gourmet meal, a quick bite, or something in between, Foodie makes it easy to satisfy your hunger with convenience and style.

## 2. Server Requirement

PHP Version (8.0 or above)

SSL Certificate


Google Map API Key

Google Firebase Account with Upgraded (Blaze) Plan


## 3. Create Firebase Project

**3.1 :** Go to firebase console through this link: <https://firebase.google.com/>


**3.2 :** Click on “Go to console” in the top right corner.



**3.3 :** Click on “Add project”, it will redirect you to the new project creation page. Enter your project name and click on “Continue”, again click on “Continue” after that select “Default Account for firebase” and then click on “Create Project”.



**3.4 : After successfully creating a new project, you will be directed to the overview page. From there, simply navigate to the icons link to proceed further.**



**Upon redirection, you'll land on the 'Add Firebase to your web app' page. Here, input your app's nickname and proceed by clicking 'Register app'. Afterward, scroll down to find detailed information as outlined below.**


```
// Import the functions you need from the SDKs you need
import { initializeApp } from "firebase/app";
import { getAnalytics } from "firebase/analytics";
// TODO: Add SDKs for Firebase products that you want to use
// https://firebase.google.com/docs/web/setup#available-libraries

// Your web app's Firebase configuration
// For Firebase JS SDK v7.20.0 and later, measurementId is optional
const firebaseConfig = {
  apiKey: "AIzaSyA8vTnUWzYtGfXqZgKjHlMnOpQrStUvWxYz",
  authDomain: "my-app-1234567890.firebaseapp.com",
  projectId: "my-app-1234567890",
  storageBucket: "my-app-1234567890.appspot.com",
  messagingSenderId: "12345678901234567890123456789012",
  appId: "1:12345678901234567890123456789012:web:12345678901234567890123456789012",
  measurementId: "G-XXXXXXXXXX"
};

// Initialize Firebase
const app = initializeApp(firebaseConfig);
const analytics = getAnalytics(app);
```


**All of these details will be incorporated into both the app and admin panel documentation for comprehensive reference and seamless integration.**

**3.5 : Next, navigate to 'Firestore Database' in the left sidebar. Select your project name from the drop-down menu, and then proceed by clicking on 'Create database'.**




**3.6 : Choose your preferred option and click on the 'Next' button. Subsequently, proceed by clicking on "Enable"**

**3.7 : Following that, locate "Realtime Database" in the left sidebar. Select your project name from the drop-down menu, and proceed by clicking on "Create Database"**




**3.8 : Choose your preferred option and proceed by clicking the "Next" button, then click on "Enable" to activate the selected feature.**

**3.9 : Firstore Database Rules Update.**



## Step 10: Upgrade your firebase plan.



See Video: [How to setup & configure Firebase Project?](#)

## 4. Firestore Database Collection Import Export

To perform Firebase Collection Import Export, follow these straightforward steps:

4.1 : To set up NPM on your computer, download Node.js from the following link: <https://nodejs.org/en/download/> Node.js Download Page.

4.2 : Unzip the source code file named "Firebase Import Export Collections.zip"

4.3 : If you haven't already created a Firebase project, set it up now.

4.4 : Configure the **credentials.json** file, which you can obtain from your Firebase Project settings. Then navigate to the Service account, then select Node.js. Generate a new private key and wait until the key is created. It will automatically download and replace the current credentials.json file.

**4.5** Navigate to the extracted **Firestore Import Export Collections** zip file path and then press and hold the Ctrl+Shift buttons. While holding them, right-click the mouse button, and select "Open PowerShell window here" from the context menu. This will open a PowerShell window where you can run the import/export command.

**4.6 :** Execute the following commands to perform import/export operations for collections:

To import all collections, execute the following command:

```
npx -p node-firestore-import-export firestore-import -a  
credentials.json -b collections.json
```

To export all collections, execute the following command:

```
npx -p node-firestore-import-export firestore-export -a  
credentials.json -b collections.json
```

Once the export command is executed, the collections.json file will be downloaded.

**Please Note:** Prior to executing the above command, ensure that you have correctly updated your Firebase credentials in the credentials.json file.

See video: [How to Import Export Collections in Firebase?](#)

## 5. Order Tracking & Delivery Dispatching

**5.1 :** The customer initiates a new order

**5.2 :** The store approves/rejects the new order

**5.3 :** If the store accepts the order, it is assigned to a nearby available driver.

**5.4 : The driver can choose to either accept or decline the order. If the driver accepts the order, they are assigned to pick up and deliver the items.**

**5.5 : The driver arrives at the store to collect the order. Once picked up, the driver updates the order status in the app for the customer. After delivery, the driver can mark the order as completed in the driver app.**

**5.6 : If the driver rejects the order, the dispatch process restarts to find another available driver nearby.**

**5.7 : Customers can track the delivery status of all their orders on their delivery app. The app utilizes Flutter code to handle most order updates. However, the backend system, which manages access to all available nearby drivers and stores, facilitates the delivery process.**

## **6. Deploy Firebase Cloud Functions**

All the necessary Firebase Functions have been initially coded by us, you just need to deploy these functions to your own Firebase account. This means that you need to upload the source code inside the Firebase Functions folder to your account. If a Firebase account has been created, find a Firebase project, and 2 apps (iOS and Android)

### **6.1 : Setting up Node.js and the Firebase CLI**

For comprehensive guidance, refer to the official Firebase documentation on getting started: "Write, test, and deploy your first functions" in Cloud Functions for Firebase.

You'll need Node.js and the Firebase CLI to write functions and deploy them to Cloud Functions.

To set up NPM on your computer, download Node.js from the following link: [Node.js download](#). Once Node.js is installed, proceed to install the Firebase CLI.

Use the following command to install the CLI via npm:



```
npm install -g firebase-tools
```

If you've already set up the Firebase tools, you can simply run the following command:

```
npm install
```

These steps will ensure you're ready to start writing and deploying functions with Firebase. If you encounter any issues, consult the [Firebase documentation](#) for troubleshooting assistance.

## 6.2 : Initialize your project

To initialize the project, authenticate the Firebase tool by running the following command. You'll be prompted to log in to your account via your web browser:

```
firebase login
```

## 6.3 : Implementing Cloud Functions

Since we're providing the complete source code for your Firebase Cloud Functions:

Extract the zip file [Order Tracking Firebase Function folder.zip](#).

Fill in the necessary credentials in the following files located within the zip:

1. [.firebaserc](#) (Add your Firestore Project ID)
2. [index.js](#) (Add your Firestore database URL)
3. [serviceAccountKey.json](#) (Add your Firebase service account credentials)

With these steps, you've successfully set up the required credentials.

## 6.4 : Deploy Firebase Functions

Simply run the following command in the [Order Tracking Firebase Function > functions](#) directory.

```
firebase deploy --only functions
```

Now you can go to your Firebase Console and check, as the functions have been deployed. It is possible to see the logs for each function, understand the output, and know when it gets called.

See Video: [How to deploy cloud functions in firebase?](#)

## 7. Demo User Authentication Import

7.1 : Get files from the source zip

7.2 : Get serviceAccountKey.json from firebase configuration

7.3 : `npm install`

7.4 : Run command `node import-user.js`

You can see the process of importing users in the firestore.  
(Note: Do not close the terminal during the running process)

```
starting update for user with email: testnp048@foodie.com
old user found: UserRecord {
  uid: 'w9SLq120tzvokJ0v8WAJkFS04N04',
  email: 'testnp048@foodie.com',
  emailVerified: false,
  displayName: undefined,
  photoURL: undefined,
  phoneNumber: undefined,
  disabled: false,
  metadata: UserMetadata {
    creationTime: 'Mon, 10 Jan 2022 09:21:25 GMT',
    lastSignInTime: null,
    lastRefreshTime: null
  },
  providerData: [],
  passwordHash: undefined,
  passwordSalt: undefined,
  tokensValidAfterTime: 'Mon, 10 Jan 2022 09:21:25 GMT',
  tenantId: undefined
}
old user deleted.
New user data ready: {
  disabled: false,
  displayName: undefined,
  email: 'testnp048@foodie.com',
  emailVerified: false,
  phoneNumber: undefined,
  photoURL: undefined,
  uid: 'w9SLq120tzvokJ0v8WAJkFS04N04'
}
New user created: UserRecord {
  uid: 'w9SLq120tzvokJ0v8WAJkFS04N04',
  email: 'testnp048@foodie.com',
  emailVerified: false,
  displayName: undefined,
  photoURL: undefined,
  phoneNumber: undefined,
  disabled: false,
  metadata: UserMetadata {
    creationTime: 'Mon, 10 Jan 2022 09:21:25 GMT',
    lastSignInTime: null,
    lastRefreshTime: null
  },
  providerData: [],
  passwordHash: undefined,
  passwordSalt: undefined,
  tokensValidAfterTime: 'Mon, 10 Jan 2022 09:21:25 GMT',
  tenantId: undefined
}
```

## 8. Firestore Database Indexing

To perform Firebase indexing, follow these straightforward steps:

8.1 : To set up NPM on your computer, download Node.js from the following link:  
<https://nodejs.org/en/download/>

8.2 : Unzip the source code file named "Firebase Indexing.zip" here.

8.3 : Navigate to the extracted directory of "Firebase Indexing" zip file. Press and hold the ctrl+shift buttons, then right-click the mouse button. From the context menu, select "Open PowerShell window here" to launch Windows PowerShell and execute import/export commands.

8.4 : Execute the command `firebase login` to log in to Firebase, if you haven't already done so.

8.5 : Execute the command `firebase init`

8.6 : Proceed with Y and press the enter button.

8.7 : Choose the Option > Firestore: Configure security rules and index files for Firestore.

**Please Note: Choose the arrow down key to navigate and select options, and press the space button to confirm your selection.**

8.8 : Choose the Option > Use an existing project

8.9 : Choose your project

8.10 : Press Enter > ? What file should be used for Firestore Rules? firestore.rules

8.11 : Press Enter > ? What file should be used for Firestore indexes?  
(firestore.indexes.json)

8.12: Now, the `firestore.indexes.json` file will be downloaded. Open this file and copy all the code from `firestore_indexes.json` file, then paste it into `firestore.indexes.json` file.

**8.13: Now execute the command** `firebase deploy --only firestore:indexes` **to import indexing in firestore.**


**See video:** [How to Import Firestore Database Indexing in Firebase?](#)

## 9. Admin Panel Setup

Ensure that your server meets the requirements outlined in the documentation's Server Requirement section. Upon downloading the code, upload the admin zip file to your server and extract it. The admin panel can be installed on either a domain or a subdomain.

### 9.1 Create Database

**9.1.1 : Create a new database from your server's MYSQL database.**



**9.1.2 : Create New Database**

# MySQL® Databases

Manage large amounts of information over the web easily. MySQL databases are necessary to run many web-based applications like shopping carts. For more information, read the [documentation](#).

## Create New Database

New Database:

democom\_

Create Database

### 9.1.3 : Create a new database user

## MySQL Users

### Add New User

Username

democom\_

Password

Password (Again)

Strength ⓘ

Very Weak (0/100)

Password Generator

Create User

### 9.1.4 : Connect the database to the newly created database user.

## Add User To Database

User

sisappde\_foodordering

Database

sisappde\_foodordering

Add

### 9.1.5 : Grant all privileges to your user by selecting "All PRIVILEGES" and then clicking on "Make Changes"

ALL PRIVILEGES	
<input type="checkbox"/> ALTER	<input type="checkbox"/> ALTER ROUTINE
<input type="checkbox"/> CREATE	<input type="checkbox"/> CREATE ROUTINE
<input type="checkbox"/> CREATE TEMPORARY TABLES	<input type="checkbox"/> CREATE VIEW
<input type="checkbox"/> DELETE	<input type="checkbox"/> DROP
<input type="checkbox"/> EVENT	<input type="checkbox"/> EXECUTE
<input type="checkbox"/> INDEX	<input type="checkbox"/> INSERT
<input type="checkbox"/> LOCK TABLES	<input type="checkbox"/> REFERENCES
<input type="checkbox"/> SELECT	<input type="checkbox"/> SHOW VIEW
<input type="checkbox"/> TRIGGER	<input type="checkbox"/> UPDATE

Make Changes Reset

## 9.2 Configure Admin Panel

**9.2.1 :** Once you've downloaded the code, upload the admin zip file to your server and extract it. The admin panel can be installed on either a domain or subdomain.

**9.2.2 :** Next, you'll need to configure the following settings in your `.env` file: Database host, Database name, Database username, Database password, and your Firebase project credentials.

```
FIREBASE_APIKEY=
FIREBASE_AUTH_DOMAIN=
FIREBASE_DATABASE_URL=
FIREBASE_PROJECT_ID=
FIREBASE_STORAGE_BUCKET=
FIREBASE_MESSAGING_SENDER_ID=
FIREBASE_APP_ID=
FIREBASE_MEASUREMENT_ID=
FIREBASE_KEY=
```

To obtain Firebase credentials, navigate to Project Settings > General > Web apps, then select your web app.

```
// TODO: Add SDKs for Firebase products that you want to use
// https://firebase.google.com/docs/web/setup#available-libraries

// Your web app's Firebase configuration
// For Firebase JS SDK v7.20.0 and later, measurementId is optional
const firebaseConfig = {
  apiKey: "XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX",
  authDomain: "XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX",
  databaseURL: "XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX",
  projectId: "XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX",
  storageBucket: "XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX",
  messagingSenderId: "XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX",
  appId: "XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX",
  measurementId: "XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX"
};

// Initialize Firebase
const app = initializeApp(firebaseConfig);
const analytics = getAnalytics(app);
```

Please Note: Please ensure to update your mail SMTP credentials in the .env file of your admin panel. Failure to do so will result in the mail functionality not working. Refer to the following snapshot for guidance.

```
MAIL_MAILER=smtp
MAIL_HOST=mail.domain.com
MAIL_PORT=465
MAIL_USERNAME=username@domain.com
MAIL_PASSWORD=password
MAIL_ENCRYPTION=ssl
MAIL_FROM_ADDRESS=username@domain.com
MAIL_FROM_NAME="${APP_NAME}"
```

**9.2.3 :** Import the provided **foodie\_admin\_database.sql** file to initialize the database.

**9.2.4 :** Now the admin panel is ready to run.

**9.2.5: Important:** To work firebase push notification feature functions correctly, please upload your Firebase credentials file in the Admin Panel by navigating to **Settings > Global Settings > Notifications Settings**.

**NOTIFICATIONS SETTING**

**Sender ID**  
  
Instructions: Navigate to your Firebase Project Settings > Cloud Messaging. Under Firebase Cloud Messaging API, you will find the Sender ID.

**Upload Credentials File (JSON Format)**  

**Choose File** No file chosen

  
Instructions: Navigate to your Firebase Project Settings > Cloud Messaging, scroll down to Web Configuration, and click on the 'Generate key pair' button. A JSON file will be downloaded.

**9.2.6:** Enable withdrawal method option to allow payment method as a withdrawal method for restaurant/driver payouts by navigating to **Settings > Payment Methods**.

#### WITHDRAWAL SETTINGS

✓ Enable Stripe

Enable this option to allow Stripe as a payment method for restaurant/driver withdrawals.

### 9.2.7: Please set up your preferred delivery zone by navigating to Zone menu

Zone List + Zone Create

Show 10 entries

Search:

<input type="checkbox"/> All	Zone Name	Status	Actions
<input type="checkbox"/>	Ahmedabad	<input checked="" type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>
<input type="checkbox"/>	Bhuj	<input checked="" type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>
<input type="checkbox"/>	Gandhinagar	<input checked="" type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>
<input type="checkbox"/>	Hyderabad	<input checked="" type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>
<input type="checkbox"/>	Rajkot	<input checked="" type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>
<input type="checkbox"/>	Surat	<input checked="" type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>
<input type="checkbox"/>	Vadodara	<input checked="" type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>
<input type="checkbox"/>	Worldwide	<input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>

Showing 1 to 8 of 8 entries

Previous

1

Next

## 10. Website Panel Setup

10.1 : Once you've downloaded the code, upload the web panel zip file to your server and extract it. You can install the web panel on your main domain.

10.2 : Now you'll need to configure the `.env` file with your Database host, Database name, Database username, Database password, and your Firebase project credentials.

10.3 : Import the provided `foodie_website_database.sql` file to import the database.

10.4 : Now the website panel is ready to run.



## 11. Restaurant Panel Setup

11.1 : Once you've downloaded the code, upload the restaurant panel zip file to your server and extract it. You can install the web panel on your main domain or subdomain.

11.2 : Now you'll need to configure the `.env` file with your Database host, Database name, Database username, Database password, and your Firebase project credentials.

11.3 : Import the provided `foodie_restaurant_database.sql` file to import the database.

11.4 : Now the restaurant panel is ready to run.

**Thank You**

© 2021-2024 Foodie. All Rights Reserved.