

```
In [2]: import matplotlib.pyplot as plt
from sklearn import datasets
from sklearn.cluster import KMeans
import pandas as pd
import numpy as np

# import some data to play with
iris = datasets.load_iris()
X = pd.DataFrame(iris.data)
X.columns = ['Sepal_Length', 'Sepal_Width', 'Petal_Length', 'Petal_Width']
y = pd.DataFrame(iris.target)
y.columns = ['Targets']

# Build the K Means Model
model = KMeans(n_clusters=3)
model.fit(X)

# model.labels_ : Gives cluster no for which samples belongs to
# # Visualise the clustering results
plt.figure(figsize=(14,14))
colormap = np.array(['red', 'lime', 'black'])
# Plot the Original Classifications using Petal features
plt.subplot(2, 2, 1)
plt.scatter(X.Petal_Length, X.Petal_Width, c=colormap[y.Targets], s=40)
plt.title('Real Clusters')
plt.xlabel('Petal Length')
plt.ylabel('Petal Width')

# Plot the Models Classifications
plt.subplot(2, 2, 2)
plt.scatter(X.Petal_Length, X.Petal_Width, c=colormap[model.labels_], s=40)
plt.title('K-Means Clustering')
plt.xlabel('Petal Length')
plt.ylabel('Petal Width')

# General EM for GMM
from sklearn import preprocessing
# transform your data such that its distribution will have a
# mean value 0 and standard deviation of 1.
```



```


scaler = preprocessing.StandardScaler()
scaler.fit(X)
xsa = scaler.transform(X)
xs = pd.DataFrame(xsa, columns = X.columns)
from sklearn.mixture import GaussianMixture
gmm = GaussianMixture(n_components=3)
gmm.fit(xs)
gmm_y = gmm.predict(xs)
plt.subplot(2, 2, 3)
plt.scatter(X.Petal_Length, X.Petal_Width, c=colormap[gmm_y], s=40)
plt.title('GMM Clustering')
plt.xlabel('Petal Length')
plt.ylabel('Petal Width')
print('Observation: The GMM using EM algorithm based clustering matched the true labels more closely than the Kmeans

```

Matplotlib is building the font cache; this may take a moment.

Observation: The GMM using EM algorithm based clustering matched the true labels more closely than the Kmeans.





In []: