

Air Combination

Air Filter + Mist Separator + Regulator

AC20C-B to AC40C-B



How to Order

AC **30** C - **03** **DE** - - - B

- Option/Semi-standard: Select one each for a to j.
 - Option/Attachment/Semi-standard symbol: When more than one specification is required, indicate in alphanumeric order.
- Example) AC30C·F03DE1·SV-16NR-B

		Symbol	Description	Body size					
				20	25	30	40		
2	Pipe thread type	Nil	Rc	●	●	●	●		
		N ^{Note 1)}	NPT	●	●	●	●		
		F ^{Note 2)}	G	●	●	●	●		
		+							
3	Port size	01	1/8	●	—	—	—		
		02	1/4	●	●	●	●		
		03	3/8	—	●	●	●		
		04	1/2	—	—	●	●		
		06	3/4	—	—	—	●		
		+							
4	Option ^{Note 3)}	a	Float type auto drain	Nil	Without auto drain	●	●	●	●
			C ^{Note 4)}	N.C. (Normally closed) Drain port is closed when pressure is not applied.	●	●	●	●	
			D ^{Note 5)}	N.O. (Normally open) Drain port is open when pressure is not applied.	—	—	—	—	
		b	Pressure gauge ^{Note 6)}	Nil	Without pressure gauge	●	●	●	●
			E	Square embedded type pressure gauge (with limit indicator)	●	●	●	●	
			G	Round type pressure gauge (with limit indicator)	●	●	●	●	
	M		Round type pressure gauge (with color zone)	●	●	●	●		
	c	Digital pressure switch	E1	Output: NPN output/Electrical entry: Wiring bottom entry	●	●	●	●	
		E2	Output: NPN output/Electrical entry: Wiring top entry	●	●	●	●		
		E3	Output: PNP output/Electrical entry: Wiring bottom entry	●	●	●	●		
		E4	Output: PNP output/Electrical entry: Wiring top entry	●	●	●	●		
	5	Attachment	c	Pressure switch	Nil	Without attachment	●	●	●
S ^{Note 7)}				Mounting position: AF+AFM+S+AR	●	●	●	●	
T-spacer			T	Mounting position: AF+AFM+T+AR	—	—	—	—	
d			Pressure relief 3 port valve	Nil	Without attachment	●	●	●	●
			V	Mounting position: AF+AFM+AR+V	●	●	●	●	
V1 ^{Note 8)}			Mounting position: V+AF+AFM+AR+CK	—	—	—	—		
6	7	e	Set pressure ^{Note 9)}	Nil	0.05 to 0.85 MPa setting	●	●	●	●
			1	0.02 to 0.2 MPa setting	—	—	—	—	
	f	Bowl ^{Note 10)}	Nil	Polycarbonate bowl	●	●	●	●	
			2	Metal bowl	●	●	●	●	
			6	Nylon bowl	●	●	●	●	
			8	Metal bowl with level gauge	—	—	—	—	
			C	With bowl guard	—	—	—	—	
			6C	Nylon bowl with bowl guard	●	—	—	—	
			+						
	g	Air filter	Nil	With drain cock	●	●	●	●	
Mist separator drain port ^{Note 13)}		J ^{Note 14)}	Drain guide 1/8	—	—	—	—		
W ^{Note 15)}		Drain guide 1/4	—	—	●	●			
			Drain cock with barb fitting: For ø6 x ø4 nylon tube	—	—	—	—		
h	Exhaust mechanism	Nil	Relieving type	●	●	●	●		
		N	Non-relieving type	—	—	—	—		

Air Combination **AC20C-B to AC40C-B** Series



AC20C-B

AC40C-B

</

Note 1) Pressure gauge connection threads are not available for F.R.L. unit with a square embedded type pressure gauge or with a digital pressure switch.

Note 2) -5 to 50°C for the products with the digital pressure switch

Note 3) Conditions: Mist separator inlet pressure: 0.7 MPa; The rated flow varies depending on the inlet pressure

Keep the air flow within the rated flow to prevent an outflow of lubricant to the outlet side

Note 4) When the compressor oil mist discharge concentration is 30 mg/m³ (ANR)

Note 5) Bowl seal and other O-rings are slightly lubricated.

