

EXERCISE 18

Structure of 'restaurants' collection:

```

{
  "address": {
    "building": "1007",
    "coord": [ -73.856077, 40.848447 ],
    "street": "Morris Park Ave",
    "zipcode": "10462"
  },
  "borough": "Bronx",
  "cuisine": "Bakery",
  "grades": [
    { "date": { "$date": "1393804800000" }, "grade": "A", "score": 2 },
    { "date": { "$date": "1378857600000" }, "grade": "A", "score": 6 },
    { "date": { "$date": "1358985600000" }, "grade": "A", "score": 10 },
    { "date": { "$date": "1322006400000" }, "grade": "A", "score": 9 },
    { "date": { "$date": "1299715200000" }, "grade": "B", "score": 14 }
  ],
  "name": "Morris Park Bake Shop",
  "restaurant_id": "30075445"
}

```

1. Write a MongoDB query to find the restaurant Id, name, borough and cuisine for those restaurants which prepared dish except 'American' and 'Chinees' or

restaurant's name begins with letter 'Wil'.

*db.restaurants.find({\$or: [{name: {\$regex: /^wil/i}}, {cuisine: {\$nin: ["American", "Chinees"]}}], {restaurant\_id: 1, name: 1, borough: 1, cuisine: 1}});*

2. Write a MongoDB query to find the restaurant Id, name, and grades for those restaurants which achieved a grade of "A" and scored 11 on an ISODate "2014-08-11T00:00:00Z" among many of survey dates..

*db.restaurants.find({\$elemMatch: {grade: "A", score: 11, date: ISO DATE: ISO DATE ("2014-08-11T00:00:00Z")}});*

3. Write a MongoDB query to find the restaurant Id, name and grades for those restaurants where the 2nd element of grades array contains a grade of "A" and

score 9 on an ISODate "2014-08-11T00:00:00Z". *db.restaurants.find({grades: 1, grade: "A", grades: 1, score: "9", grades: 1, ISO date: ("2014-08-11T00:00:00Z")}, {restaurant\_id: 1, name: 1});*

4. Write a MongoDB query to find the restaurant Id, name, address and geographical location for those restaurants where 2nd element of coord array contains a value

*db.restaurants.find({address.coord: 1: (\$gt: 40, \$lte: 52)}, {restaurant\_id: 1, name: 1, address: 1});*

which is more than 42 and upto 52..

5. Write a MongoDB query to arrange the name of the restaurants in ascending order along with all the columns.

```
db.restaurants.find().sort({name:1});
```

6. Write a MongoDB query to arrange the name of the restaurants in descending order along with all the columns.

```
db.restaurants.find().sort({name:-1});
```

7. Write a MongoDB query to arranged the name of the cuisine in ascending order and for that same cuisine borough should be in descending order.

```
db.restaurants.find().sort({cuisine:1, borough:-1});
```

8. Write a MongoDB query to know whether all the addresses contains the street or not.

```
db.restaurants.find({"address.street":{$exists:true}});
```

9. Write a MongoDB query which will select all documents in the restaurants collection where the coord field value is Double.

```
db.restaurants.find({"address.coord":{"type":"double"}});
```

10. Write a MongoDB query which will select the restaurant Id, name and grades for those restaurants which returns 0 as a remainder after dividing the score by 7.

```
db.restaurants.find({"grades.score":{"mod":7}}, {"_id":1, "name":1, "grades":1});
```

11. Write a MongoDB query to find the restaurant name, borough, longitude and attitude and cuisine for those restaurants which contains 'mon' as three letters somewhere in its name.

```
db.restaurants.find({"name":{"regex":"/mon/i"}}, {"name":1, "borough":1, "address.coord":1, "cuisine":1});
```

12. Write a MongoDB query to find the restaurant name, borough, longitude and latitude and cuisine for those restaurants which contain 'Mad' as first three letters of its name.

```
db.restaurants.find({"name":{"regex":"/Mad/i"}}, {"name":1, "borough":1, "address.coord":1, "latitude":1, "cuisine":1});
```



13. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5.

```
db.restaurants.find({"grades.score": {$lt: 5}});
```

14. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan.

```
db.restaurant.find({"borough": "Manhattan", "grades.score": {$lt: 5}});
```

15. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan or Brooklyn.

```
db.restaurants.find({"borough": {$in: ["Manhattan", "Brooklyn"]}, "grades.score": {$lt: 5}});
```

16. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan or Brooklyn, and their cuisine is not American.

```
db.restaurants.find({"borough": {$in: ["Manhattan", "Brooklyn"]}, "cuisine": {$nin: ["American"]}, {"grades.score": {$lt: 5}});
```

17. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan or Brooklyn, and their cuisine is not American or Chinese.

```
db.restaurants.find({"borough": {$in: ["Manhattan", "Brooklyn"]}, "cuisine": {$nin: ["American", "Chinese"]}, {"grades.score": {$lt: 5}});
```

18. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6.

```
db.restaurants.find({"grades.score": {$all: [2, 6]}});
```

19. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan.

```
db.restaurants.find({"borough": {"in": ["Manhattan"]}, {"grades.score": {$all: [2, 6]}});
```

20. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan or Brooklyn.

```
db.restaurants.find({"borough": {"in": ["Manhattan", "Brooklyn"]}, {"grades.score": {$all: [2, 6]}});
```



21. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan or Brooklyn, and their cuisine is not American.

*db.restaurants.find({'borough': {'\$in': ['Manhattan', 'Brooklyn']}, 'grades.score': {'\$all': [2, 6]}});*

22. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan or Brooklyn, and their cuisine is not American or Chinese.

*db.restaurant.find({'borough': {'\$in': ['Manhattan', 'Brooklyn']}, 'cuisine': {'\$ne': 'American'}});*

23. Write a MongoDB query to find the restaurants that have a grade with a score of 2 or a grade with a score of 6.

*db.restaurant.find({'grades.score': {'\$in': [2, 6]}});*

Sample document of 'movies' collection

```
{
  _id: ObjectId("573a1390f29313caabcd42e8"),
  plot: 'A group of bandits stage a brazen train hold-up, only to find a determined posse hot on their heels.',
  genres: [ 'Short', 'Western' ],
  runtime: 11,
  cast: [
    'A.C. Abadie',
    "Gilbert M. 'Broncho Billy' Anderson",
    'George Barnes',
    'Justus D. Barnes'
  ],
  poster: 'https://m.media-
amazon.com/images/M/MV5BMTU3NjE5NzYtYTtyNS00MDVmLWlwYjgtMmYwYWwixZDYyNzU2XkEyXkFqcG
deQXVyNzQzNzQxNzI@_V1_SY1000_SX677_AL_.jpg',
  title: 'The Great Train Robbery',
  fullplot: "Among the earliest existing films in American cinema - notable as the first film that presented a
narrative story to tell - it depicts a group of cowboy outlaws who hold up a train and rob the passengers.
They are then pursued by a Sheriff's posse. Several scenes have color included - all hand tinted."
```

```

languages: [ 'English' ],
released: ISODate("1903-12-01T00:00:00.000Z"),
directors: [ 'Edwin S. Porter' ],
rated: 'TV-G',
awards: { wins: 1, nominations: 0, text: '1 win.' },
lastupdated: '2015-08-13 00:27:59.177000000',
year: 1903,
imdb: { rating: 7.4, votes: 9847, id: 439 },
countries: [ 'USA' ],
type: 'movie',
tomatoes: {
viewer: { rating: 3.7, numReviews: 2559, meter: 75 },
fresh: 6,
critic: { rating: 7.6, numReviews: 6, meter: 100 },
rotten: 0,
lastUpdated: ISODate("2015-08-08T19:16:10.000Z")
}

```

1. Find all movies with full information from the 'movies' collection that released in the year 1893.

```
db.movies.find({year: 1893})
```

2. Find all movies with full information from the 'movies' collection that have a runtime greater than 120 minutes.

```
db.movies.find({runtime: { $gt: 120 }})
```

3. Find all movies with full information from the 'movies' collection that have "Short" genre.

```
db.movies.find({genres: "short"})
```



4. Retrieve all movies from the 'movies' collection that were directed by "William K.L. Dickson" and include complete information for each movie.

```
db.movies.find({directors: "William"})
```

5. Retrieve all movies from the 'movies' collection that were released in the USA and include complete information for each movie.

```
db.movies.find({countries: "USA"})
```

6. Retrieve all movies from the 'movies' collection that have complete information and are rated as "UNRATED".

```
db.movies.find({rated: "UNRATED"})
```

7. Retrieve all movies from the 'movies' collection that have complete information and have received more than 1000 votes on IMDb.

```
db.movies.find({imdbvotes: {$gt: 1000}})
```

8. Retrieve all movies from the 'movies' collection that have complete information and have an IMDb rating higher than 7.

```
db.movies.find({imdbrating: {$gt: 7}})
```

9. Retrieve all movies from the 'movies' collection that have complete information and have a viewer rating higher than 4 on Tomatoes.

```
db.movies.find({"tomatoes.viewer.rating": {$gt: 4}})
```

10. Retrieve all movies from the 'movies' collection that have received an award.

```
db.movies.find({awards-wins: {$gt: 0}})
```

11. Find all movies with title, languages, released, directors, writers, awards, year, genres, runtime, cast, countries from the 'movies' collection in MongoDB that have at least one nomination.

```
db.movies.find({awards-nominations: {$gt: 0}})
```

12. Find all movies with title, languages, released, directors, writers, awards, year, genres, runtime, cast, countries from the 'movies' collection in MongoDB with cast

```
db.movies.find({cast: "Charles Kayser"})
```

including "Charles Kayser".

13. Retrieve all movies with title, languages, released, directors, writers, countries from the 'movies' collection in MongoDB that released on May 9, 1893.

```
db.movies.find({released: 80, date: {"1893-05-09T00:00:00Z": 1}})
```

14. Retrieve all movies with title, languages, released, directors, writers, countries from the 'movies' collection in MongoDB that have a word "scene" in the title.

```
db.movies.find({'title': /scene/i})
```

<u>Evaluation Procedure</u>	<u>Marks awarded</u>
<u>Practice Evaluation (5)</u>	5
<u>Viva(5)</u>	5
<u>Total (10)</u>	10
<u>Faculty Signature</u>	