


Полудницын романов практика номер 16



PC/PT PC0

2960-24TT Switch0

2960-24TT Switch1

Physical
Config
CLI
Attributes

IOS Command Line Interface

```

Version ID                : V02
CLEI Code Number         : C05310088A
Hardware Board Revision Number : 0x01

Switch Ports Model        SW Version  SW Image
-----
*   1 26    WS-C2960-24TT-L  15.0(2)SE4  C2960-LANBASEK9-M

Cisco IOS Software, C2960 Software (C2960-LANBASEK9-M), Version 15.0(2)SE4, RELEASE SOFTWARE (fc1)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2013 by Cisco Systems, Inc.
Compiled Wed 26-Jun-13 02:49 by nguyen

Press RETURN to get started!

%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up
%LINK-5-CHANGED: Interface FastEthernet0/2, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/2, changed state to up


Switch>en
Switch#conf t
Enter configuration commands, one per line. End with CTRL/Z.
Switch(config)#hostname law
law(config)#int vlan1
law(config-if)#no sh

law(config-if)#
%LINK-5-CHANGED: Interface Vlan1, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed state to up

law(config-if)#ip address 192.168.0.2 255.255.255.0
law(config-if)#exit
law(config)#

```

Copy
Paste



☐ Top

Physical Config Desktop Programming Attributes

Command Prompt

```
Cisco Packet Tracer PC Command Line 1.0
C:\>ping 192.168.0.2

Pinging 192.168.0.2 with 32 bytes of data:

Request timed out.
Reply from 192.168.0.2: bytes=32 time<1ms TTL=255
Reply from 192.168.0.2: bytes=32 time<1ms TTL=255
Reply from 192.168.0.2: bytes=32 time<1ms TTL=255

Ping statistics for 192.168.0.2:
    Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>ping 192.168.0.3

Pinging 192.168.0.3 with 32 bytes of data:

Request timed out.
Reply from 192.168.0.3: bytes=32 time=3ms TTL=255
Reply from 192.168.0.3: bytes=32 time<1ms TTL=255
Reply from 192.168.0.3: bytes=32 time<1ms TTL=255

Ping statistics for 192.168.0.3:
    Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 3ms, Average = 1ms

C:\>telnet 192.168.0.3
Trying 192.168.0.3 ...Open

User Access Verification

Password:
lsw>en
Password:
lsw#
```

☐ Top