OUTPRO.INDIA

Corporate Digital Presence Platform

COMPLETE TECHNICAL DOCUMENTATION

Document Version	v1.1.0
Release Date	April 2026
Status	Production
Classification	Confidential
Prepared by	Outpro.India Technical Team

© Outpro.India. All rights reserved.

Table of Contents

1. System Architecture
2. Tech Stack
3. Installation Guide
4. User Manual
5. Admin Guide
6. Maintenance Plan
7. Backup Strategy
8. Troubleshooting
Appendix A — API Endpoint Reference
Appendix B — Environment Variable Reference

© Outpro.India. All rights reserved.

1. System Architecture

Outpro.India is a Jamstack-style platform combining static site generation, serverless API routes, and a containerised REST API to deliver a corporate digital presence system with an integrated admin panel.

1.1 High-Level Architecture

The platform is composed of three independent, deployable tiers that communicate through well-defined HTTP APIs and webhooks.

Tier	Technology	Responsibility
Frontend	Next.js 14 · Vercel	Public website, admin panel, SSG/ISR pages
Backend	Node.js · Express · AWS ECS Fargate	REST API, business logic, auth, CRM integration
Database	MongoDB Atlas	Leads, sessions, audit log, media metadata, portfolio, testimonials
CDN / WAF	Cloudflare Pro	Global delivery, WAF, DDoS protection, rate limits
Storage	Supabase Storage	Media assets with ClamAV virus scanning pipeline
Email	Resend API	Transactional email: lead confirmation, admin alerts
CRM	HubSpot / Zoho	Lead sync with exponential-backoff retry

> *Note: Database change: This project has migrated from PostgreSQL (Supabase) to MongoDB Atlas. All data models, queries, and connection logic now use the MongoDB Node.js driver / Mongoose ODM. The data tier section and environment variable reference reflect this change.*

1.2 Request Flow

Every public request follows this path from browser to data store:

- Browser sends HTTPS request to outpro.india or api.outpro.india.
- Cloudflare WAF evaluates the request: checks against OWASP ruleset, rate limits, and bot signatures. Blocked requests are rejected here.
- Cache HIT: Cloudflare serves the cached SSG page directly from the nearest PoP. No origin request is made.
- Cache MISS: Cloudflare forwards to Vercel (frontend) or the AWS Application Load Balancer (backend API).
- Vercel serves Next.js pages: SSG pages served from Vercel's edge cache. API routes execute as Vercel serverless functions.
- AWS ALB distributes requests across 2–6 ECS Fargate tasks running the Node.js/Express application.
- Express validates the JWT, checks role permissions, validates the request body (Zod), and executes business logic.
- The application reads/writes to MongoDB Atlas, calls Supabase Storage, or calls external services (Resend, HubSpot).
- The response is serialised into the standard JSON envelope and returned through ALB → Cloudflare → browser.

1.3 Security Layers

© Outpro.India. All rights reserved.

Layer	Control	Technology
0 – Network	WAF, DDoS, bot management	Cloudflare Pro
1 – Transport	TLS 1.3 end-to-end, HSTS preload	ACM + ALB + Cloudflare
2 – Application	CSP headers, XSS sanitisation (DOMPurify), CSRF	Helmet.js + Next.js headers
3 – Authentication	JWT HS256 + HttpOnly cookie + per-JTI revocation	jsonwebtoken + Secrets Manager
4 – MFA	TOTP (Google Authenticator compatible)	speakeasy
5 – Authorisation	Role-based (super_admin / editor / viewer)	Custom Express middleware
6 – API	Rate limiting, reCAPTCHA v3, Zod validation	Upstash Redis + Google
7 – Data	MongoDB Atlas encryption at rest (AES-256)	Atlas + KMS
8 – Supply chain	Dependency audit, container scanning	pnpm audit + Trivy + CodeQL

© Outpro.India. All rights reserved.

2. Tech Stack

2.1 Frontend

Package	Version	Purpose
Next.js	14.2.x	App Router, SSG, ISR, API routes, image optimisation
React	18.3.x	Component model, Suspense, server components
TypeScript	5.4.x	Type safety across the entire codebase
Tailwind CSS	3.4.x	Utility-first styling with custom design tokens
Framer Motion	11.x	Animations: hero, counters, page transitions, carousels
TanStack Query	5.x	Server state management, caching, optimistic updates
Zustand	4.x	Client state: auth, toasts, UI flags
React Hook Form	7.x	Form state, validation integration
Zod	3.x	Runtime schema validation (mirrors backend rules)
Embla Carousel	8.x	Touch-friendly testimonial carousel
DnD Kit	6.x/8.x	Drag-and-drop testimonial reorder in admin
Lucide React	0.395.x	Icon library
jose	5.x	JWT verification in Next.js Edge middleware

2.2 Backend

Package	Version	Purpose
Node.js	20 LTS	Runtime
Express	4.18.x	HTTP framework, middleware pipeline
MongoDB Node.js driver / Mongoose	latest	MongoDB Atlas client with connection pooling and ODM
bcrypt	5.1.x	Password hashing (cost factor 12)
jsonwebtoken	9.x	JWT signing and verification
speakeasy	2.x	TOTP MFA secret generation and verification
Zod	3.x	Server-side input validation (all 14 schemas)
Helmet	7.x	HTTP security headers
Winston	3.x	Structured JSON logging with daily rotation
Multer	1.4.x	Multipart file upload handling
file-type	19.x	Magic-byte MIME validation (not extension)
DOMPurify + jsdom	3.x/24.x	HTML sanitisation to prevent XSS

© Outpro.India. All rights reserved.

Package	Version	Purpose
Resend	3.x	Transactional email delivery
Axios	1.7.x	HTTP client for external API calls (HubSpot, reCAPTCHA)
node-cron	3.x	Scheduled jobs: session cleanup, audit log purge

2.3 Infrastructure

Service	Tier	Monthly Cost (USD)
Vercel	Pro (1 seat)	~$20
AWS ECS Fargate	2 tasks × 0.5 vCPU × 1 GB	~$18
AWS ALB	1× ap-south-1	~$18
AWS NAT Gateways	3× AZ (HA)	~$100
MongoDB Atlas	M10 cluster (ap-south-1)	~$57
Supabase Storage	Pro tier (media only)	~$10
Cloudflare	Pro	~$20
AWS Secrets Manager	1 secret	~$0.40
AWS CloudWatch	Logs + metrics	~$5
AWS S3 (backups)	~5 GB	~$0.75
Total estimate		~$249 / month

© Outpro.India. All rights reserved.

3. Installation Guide

3.1 Prerequisites

Requirement	Minimum Version	Notes
Node.js	20.0.0	Use nvm to manage versions: nvm use 20
pnpm	9.0.0	Install: npm install -g pnpm@9
Docker	24.0	Required for local Redis. MongoDB can be Atlas free tier or Docker.
Docker Compose	2.20	Bundled with Docker Desktop
Git	2.40	
AWS CLI	2.15	For deployment only; optional for local dev
Terraform	1.7.0	For infrastructure provisioning only

3.2 Local Development Setup

Step 1: Clone the repository

```
git clone https://github.com/outpro-india/outpro-platform.git
cd outpro-platform
```

Step 2: Start local services (Redis)

```
docker compose up redis -d
```

This starts Redis 7 on port 6379. MongoDB can be served from a free Atlas cluster or a local Docker container.

```
# Optional: start MongoDB locally
docker compose up mongo -d   # starts on port 27017
```

Step 3: Configure environment variables

```
cp outpro-backend/.env.example outpro-backend/.env.local
```

Edit the file and set at minimum the following values for local development:

Variable	Where	How to obtain
MONGODB_URI	backend	mongodb+srv://user:pass@cluster.mongodb.net/outpro or mongodb://localhost:27017/outpro
JWT_SECRET	backend	openssl rand -hex 64
REVALIDATION_SECRET	backend + frontend	openssl rand -hex 32

© Outpro.India. All rights reserved.

Variable	Where	How to obtain
RECAPTCHA_SECRET_KEY	backend	Google reCAPTCHA Admin Console
NEXT_PUBLIC_RECAPTCHA_SITE_KEY	frontend	Google reCAPTCHA Admin Console
RESEND_API_KEY	backend	resend.com → API Keys
SUPABASE_URL	backend	Supabase Project Settings → API (storage only)
SUPABASE_SERVICE_ROLE_KEY	backend	Supabase Project Settings → API

Step 4: Start the backend API

```
cd outpro-backend && pnpm install --frozen-lockfile
pnpm dev   # runs on http://localhost:5000
```

Verify with:

```
curl http://localhost:5000/api/v1/health
```

> *Note: There are no SQL migrations to run. MongoDB collections and indexes are created automatically on first connection via Mongoose schema definitions.*

Step 5: Seed development data (optional)

A seed script is available if required. Run from the backend directory:

```
pnpm run seed
```

> *Note: Warning: The seed script checks NODE_ENV and will refuse to run in production. Default admin credentials: arjun@outpro.india / Outpro@Dev2026!*

Step 6: Start the frontend

```
cd ../   # repo root
pnpm install --frozen-lockfile
pnpm dev   # runs on http://localhost:3000
```

3.3 Production Deployment

One-time infrastructure setup

- Bootstrap Terraform state: bash devops/scripts/bootstrap-tfstate.sh
- Configure all GitHub Actions secrets (see README.md → First-Time Setup).
- Provision infrastructure: cd devops/terraform && terraform init && terraform apply
- Set real secret values in AWS Secrets Manager.
- Ensure MongoDB Atlas M10 cluster is provisioned in ap-south-1 with network peering or VPC private endpoint to ECS.

Subsequent deployments

All subsequent deployments are fully automated via GitHub Actions:

© Outpro.India. All rights reserved.

- Push to main branch → backend-deploy.yml builds, scans, and deploys to ECS production.
- Push to main branch → frontend-deploy.yml deploys to Vercel production.
- Terraform changes → terraform.yml runs plan on PR, apply on merge.

© Outpro.India. All rights reserved.

4. User Manual

This chapter covers the public-facing website. For admin panel instructions, see Chapter 5.

4.1 Navigating the Website

Page	URL	Content
Home	/	Hero, statistics, services preview, portfolio highlights, testimonials
About	/about	Company story, team, values, awards and recognition
Services	/services	Overview of all six service areas with deliverables and pricing
Portfolio	/portfolio	Filterable project gallery with category filter and pagination
Testimonials	/testimonials	Client reviews with video testimonials and rating breakdown
Contact	/contact	Contact form, office information, Google Maps location

4.2 Submitting a Contact Form

- Navigate to https://www.outpro.india/contact
- Enter your Full Name (required, 2–120 characters).
- Enter your Business Email (required, valid email address).
- Optionally enter Company Name, Phone Number (E.164 format: +919876543210), Service Interest, and Budget Range.
- Enter your Message (required, 10–2000 characters).
- Click Send Message. The form is protected by Google reCAPTCHA v3 (automatic, no checkbox required).
- On success, a confirmation email is sent to the address provided.

> *Note: Submissions are rate-limited to 100 per minute per IP address. If you receive a rate limit error, wait 60 seconds and try again.*

4.3 Browsing the Portfolio

- Click a category pill (All, Web Dev, Branding, Mobile, UI/UX, Marketing, SEO) to filter the grid.
- Click any project card to open the full case study page.
- Use pagination controls to navigate through multiple pages (9 projects per page).

4.4 Viewing Testimonials

- Use the filter bar to show: All reviews, Featured only, Video testimonials only, or 5-star reviews only.
- For video testimonials, click the play button to open the video in a modal player.
- The star rating breakdown chart at the top shows the distribution of all ratings.

© Outpro.India. All rights reserved.

5. Admin Guide

5.1 Roles and Permissions

Capability	super_admin	editor	viewer
View dashboard KPIs	✓	✓	✓
View leads	✓	✓	✓ (read only)
Update lead status	✓	✓	✗
Delete leads	✓	✗	✗
Create / update portfolio projects	✓	✓	✗
Delete portfolio projects	✓	✗	✗
Create / update testimonials	✓	✓	✗
Delete testimonials	✓	✗	✗
Reorder testimonials (drag-drop)	✓	✓	✗
Upload media assets	✓	✓	✗
Delete media assets	✓	✗	✗
Manage admin users	✓	✗	✗
View audit log (full IP)	✓	✗	✗
View audit log (redacted IP)	✓	✓	✓

5.2 Logging In

- Navigate to https://www.outpro.india/login
- Enter your admin email address and password.
- If MFA is enabled: enter the 6-digit code from your authenticator app.
- Click Sign in.

> *⚠ Warning: Warning: After 5 consecutive failed login attempts, your account is temporarily locked with exponential backoff (up to 60 minutes). Contact a super_admin to unlock your account earlier.*

5.3 Dashboard

The Dashboard is the first page shown after login. It provides a real-time overview of platform activity.

- Period selector: Switch between 7-day, 30-day, and 90-day views using the buttons in the top-right.
- KPI cards: New leads, Conversion rate, Average testimonial rating, Portfolio view count.
- Recent leads table: Shows the 5 most recent contact form submissions.
- Recent activity feed: Shows the 10 most recent admin actions from the audit log.

5.4 Managing Leads

© Outpro.India. All rights reserved.

Lead status workflow

Status	Meaning	When to use
new	Recently submitted, unread	Default on submission
read	Opened by an admin	Automatically set on first open
replied	A response has been sent to the prospect	After sending a reply email
converted	The lead became a paying client	After contract signed

5.5 Managing Portfolio Projects

- Go to Admin → Portfolio → click New Project.
- Fill in: Slug (URL-safe, e.g. brandhouse-rebrand), Title, Client Name, Category.
- Optionally add: Description, Cover Image (from media library), Project URL, Completed Date.
- Toggle Is Featured to highlight the project on the home page.
- Toggle Is Published to make the project visible on the public portfolio page.

> *⚠ Warning: Warning: Slugs must be lowercase kebab-case (letters, numbers, and hyphens only). A slug cannot be changed after publication without breaking existing links.*

5.6 Managing Testimonials

- Drag and drop testimonial rows to change display order. Click Save Order to commit changes.
- The displayOrder field controls the sequence in the public carousel and the Testimonials page grid.
- Marking a testimonial as Featured ensures it appears on the home page carousel.
- Video URLs must be from YouTube or Vimeo. Other URLs are rejected.

5.7 Media Library

Allowed type	Max size	After upload
JPEG, PNG, WebP, GIF	10 MB	Queued for virus scan
SVG	10 MB	Queued for virus scan
PDF	10 MB	Queued for virus scan
MP4, MOV	50 MB	Queued for virus scan

Scan statuses: Scanning, Clean (public URL available), Infected (quarantined), Error (retry).

5.8 Enabling MFA on Your Account

- Go to Admin → Settings → Two-factor authentication → Set up MFA.
- Scan the QR code with Google Authenticator, Authy, or any TOTP-compatible app.
- Enter the 6-digit code from your authenticator app and click Verify & Enable.

© Outpro.India. All rights reserved.

6. Maintenance Plan

6.1 Routine Maintenance Schedule

Frequency	Task	Owner	Effort
Daily (automated)	MongoDB Atlas automated backup	Atlas managed	0 min
Daily (automated)	Expired session cleanup (adminSessions collection)	ECS cron 02:00 UTC	0 min
Daily	Review CloudWatch alarm emails	DevOps	10 min
Weekly	Review dependency updates (Dependabot PRs)	Engineering	30 min
Weekly	Audit log review for anomalous actions	DevOps / Admin	15 min
Monthly (automated)	Audit log purge (entries > 2 years)	ECS cron 03:00 UTC	0 min
Monthly	Review CloudWatch cost and usage report	DevOps	20 min
Monthly	Run pnpm audit --audit-level=critical on both repos	Engineering	30 min
Quarterly	Rotate JWT_SECRET and REVALIDATION_SECRET	DevOps	30 min
Quarterly	Review admin user access (remove leavers)	super_admin	15 min
Quarterly	Restore test: restore from Atlas snapshot to staging	DevOps	60 min
Annually	Full disaster recovery drill	DevOps	4 hours

6.2 MongoDB Atlas Maintenance

MongoDB Atlas M10 cluster manages the following automatically:

- Continuous backups with point-in-time recovery (PITR) up to the last 7 days.
- Automatic minor version patching and replica set management.
- Oplog-based change streams for real-time monitoring.

Manual tasks:

- Monitor collection growth in contactLeads and auditLog monthly.
- Review slow query logs (Atlas Performance Advisor) quarterly.
- Verify indexes are being used via Atlas Query Profiler after any schema changes.

© Outpro.India. All rights reserved.

7. Backup Strategy

7.1 What Is Backed Up

Data	Method	Frequency	Retention	Storage
MongoDB (Atlas)	Automatic (Atlas managed PITR)	Continuous / Daily	7 days PITR	Atlas infrastructure
MongoDB (mongodump)	Manual via backup-database.sh	Daily 02:00 UTC	365 days	S3 ap-south-1 + DR
Media assets	Supabase Storage (managed)	Continuous	Until manually deleted	Supabase Storage
Application code	Git (GitHub)	Per commit	Indefinite	GitHub
Infrastructure state	Terraform (S3 backend, versioned)	Per apply	Indefinite	S3 ap-south-1
API logs (CloudWatch)	CloudWatch Logs	Continuous	30 days	CloudWatch
Audit log (exported)	Weekly export to S3	Weekly	2 years (Glacier IR)	S3
Container images	ECR	Per push	10 tagged versions	ECR ap-south-1

7.2 Backup Process — Database

The automated daily backup is executed by devops/scripts/backup-database.sh:

- The script retrieves MONGODB_URI from AWS Secrets Manager.
- mongodump is executed with --gzip --archive to produce a compressed binary dump.
- The dump file is uploaded to S3 with --sse aws:kms encryption.
- The script verifies the uploaded object size is > 1 KB. Failure triggers an alert.
- S3 cross-region replication automatically copies the object to the us-east-1 DR bucket.

7.3 Restore Procedure

```
# List available backups
aws s3 ls s3://outpro-production-backups/db/ --recursive

# Download
TIMESTAMP='20260413_020001'
aws s3 cp s3://outpro-production-backups/db/${TIMESTAMP}/database.gz /tmp/restore.gz

# Restore
mongorestore --uri "$MONGODB_URI" --gzip --archive=/tmp/restore.gz --drop
```

> *✗ Important: Important: Always test the restore on a staging database first. The --drop flag will drop and recreate all collections, overwriting any existing data in the target database.*

© Outpro.India. All rights reserved.

7.4 Recovery Objectives

Scenario	RPO (max data loss)	RTO (restore time)	Procedure
Data corruption	Up to 24 hours	30–120 minutes	Restore from mongodump or use Atlas PITR
Accidental data deletion	Up to 24 hours	30–60 minutes	Restore from previous mongodump snapshot
ECS service failure	0 (stateless)	< 5 minutes	ECS auto-replaces failed tasks
AWS region outage	Up to 24 hours	2–4 hours	Restore from DR bucket in us-east-1
Vercel deployment failure	0 (atomic)	< 1 minute	Vercel one-click rollback

© Outpro.India. All rights reserved.

8. Troubleshooting

8.1 Frontend Issues

Symptom	Likely cause	Resolution
Contact form shows reCAPTCHA error	NEXT_PUBLIC_RECAPTCHA_SITE_KEY missing	Verify env var in Vercel Dashboard → Settings → Environment Variables
Portfolio grid shows no projects	Backend API unreachable or CORS mismatch	Check NEXT_PUBLIC_API_URL; verify ALLOWED_ORIGINS includes the Vercel domain
Admin login redirects to /login	JWT_SECRET mismatch	Ensure the same JWT_SECRET is set in Vercel env vars and AWS Secrets Manager
Images not loading	NEXT_PUBLIC_SUPABASE_URL missing or media not yet clean-scanned	Verify env var; check scan status in admin panel
Stale content after update	ISR not triggered or REVALIDATION_SECRET mismatch	Manually trigger: curl -X POST .../api/revalidate -H 'Authorization: Bearer YOUR_SECRET'
Page returns 500 in production	Build-time env var missing	Check Vercel deployment logs → Functions tab

8.2 Backend / API Issues

Symptom	Likely cause	Resolution
All API requests return 503	ECS tasks not running	Check ECS service in AWS Console
API returns 401 on all requests	JWT_SECRET mismatch	Rotate secrets with devops/scripts/rotate-secrets.sh
POST /contact returns 403 CAPTCHA_FAILED	RECAPTCHA_SECRET_KEY wrong or score < 0.5	Verify secret key in Secrets Manager; check Google reCAPTCHA admin
Email notifications not delivered	RESEND_API_KEY expired or domain not verified	Check Resend dashboard; verify domain DNS (SPF, DKIM)
CRM sync fails silently	HUBSPOT_API_KEY expired	Rotate the HubSpot private app token; update in Secrets Manager; force ECS redeploy
MongoDB connection timeout	MONGODB_URI wrong or Atlas IP whitelist missing	Verify URI in Secrets Manager; add ECS NAT Gateway IPs to Atlas network access list
Media upload returns 413	File exceeds size limit	Limit: 10 MB images, 50 MB videos
Health check returns degraded	MongoDB unreachable	Check Atlas cluster status at cloud.mongodb.com; verify MONGODB_URI is correct

8.3 Infrastructure Issues

© Outpro.India. All rights reserved.

Symptom	Likely cause	Resolution
ECS tasks keep restarting	Application crash (bad env var)	View logs: aws logs tail /ecs/outpro-production-api --follow
ECS deployment stuck IN_PROGRESS	New tasks failing health check	Check CloudWatch logs; ECS circuit breaker will auto-rollback after threshold
ALB 5xx alarm firing	Application errors or OOM kills	Check CloudWatch ECS memory metric; increase api_memory in Terraform if hitting 100%
Terraform apply fails with state lock	Previous apply crashed	Run: terraform force-unlock LOCK_ID
S3 backup upload failing	ECS task role missing s3:PutObject	Verify aws_iam_role_policy.ecs_task_s3 is applied; check CloudTrail

8.4 Viewing Logs

```
# Live API log streaming
aws logs tail /ecs/outpro-production-api --follow
```

```
# Filter for ERROR-level messages only
aws logs tail /ecs/outpro-production-api --follow --filter-pattern "[timestamp,
level=ERROR, ...]"
```

8.5 Emergency Procedures

Emergency	Immediate action	Command / location
API completely down	Roll back to previous ECS task definition	bash devops/scripts/rollback.sh production
Suspected credential compromise	Rotate all secrets immediately	bash devops/scripts/rotate-secrets.sh production
DDoS attack	Enable Cloudflare Under Attack mode	Cloudflare Dashboard → Security → Settings
Data breach suspected	Scale ECS service to 0 tasks (isolate)	aws ecs update-service --cluster ... --desired-count 0
Accidental data deletion	Restore from latest mongodump backup	See Section 7.3 Restore Procedure
Production deploy broken	Rollback Vercel deployment	Vercel Dashboard → Deployments → Previous deploy → Promote to Production

© Outpro.India. All rights reserved.

Appendix A — API Endpoint Reference

Base URL: https://api.outpro.india/api/v1 — All responses use the standard envelope: { success, data, meta } or { success, error }.

#	Method	Endpoint	Auth	Description
1	POST	/auth/login	Public	Admin login + optional TOTP verification
2	POST	/auth/logout	JWT	Logout and revoke session (JTI blacklisted in MongoDB)
3	GET	/auth/me	JWT	Get authenticated user profile
4	PATCH	/auth/password	JWT	Change password (revokes all other sessions)
5	POST	/auth/mfa/setup	JWT	Generate MFA QR code
6	POST	/auth/mfa/verify	JWT	Enable MFA on account
7	POST	/contact	Public + reCAPTCHA	Submit contact form
8	GET	/contact/leads	JWT	List leads (paginated)
9	GET	/contact/leads/stats	JWT	Lead statistics
10	GET	/contact/leads/:id	JWT	Get single lead
11	PATCH	/contact/leads/:id	JWT editor+	Update lead status
12	DELETE	/contact/leads/:id	JWT super_admin	Delete lead
13	GET	/portfolio	Public	List portfolio projects
14	GET	/portfolio/categories	Public	Category project counts
15	GET	/portfolio/:slug	Public	Get project by slug
16	POST	/portfolio	JWT editor+	Create project
17	PATCH	/portfolio/:id	JWT editor+	Update project
18	DELETE	/portfolio/:id	JWT super_admin	Delete project
19	POST	/portfolio/revalidate	Webhook secret	Trigger Next.js ISR
20	GET	/testimonials	Public	List testimonials
21	GET	/testimonials/stats	JWT	Testimonial statistics
22	GET	/testimonials/:id	Public	Get testimonial
23	POST	/testimonials	JWT editor+	Create testimonial
24	PATCH	/testimonials/reorder	JWT editor+	Batch reorder carousel
25	PATCH	/testimonials/:id	JWT editor+	Update testimonial
26	DELETE	/testimonials/:id	JWT super_admin	Delete testimonial
27	GET	/admin/dashboard	JWT	KPI dashboard (7d/30d/90d)

© Outpro.India. All rights reserved.

#	Method	Endpoint	Auth	Description
28	GET	/admin/users	JWT super_admin	List admin users
29	POST	/admin/users	JWT super_admin	Create admin user
30	PATCH	/admin/users/:id	JWT super_admin	Update admin user
31	DELETE	/admin/users/:id	JWT super_admin	Delete admin user
32	GET	/admin/audit-log	JWT	View audit trail
33	POST	/admin/media	JWT editor+	Upload media asset
34	GET	/admin/media	JWT	List media assets
35	DELETE	/admin/media/:id	JWT super_admin	Delete media asset
36	GET	/health	Public	Uptime health probe (checks MongoDB connection)

Appendix B — Environment Variable Reference

Variable	Service	Required	Description
MONGODB_URI	Backend	✓	MongoDB Atlas connection string — mongodb+srv://user:pass@cluster.mongodb.net/outpro
JWT_SECRET	Backend + Frontend	✓	Min 64 chars — generate: openssl rand -hex 64
JWT_EXPIRY	Backend	✓	Token lifetime (default: 8h)
SESSION_MAX_AGE_SECONDS	Backend	✓	Cookie max-age in seconds (default: 28800 = 8h)
REVALIDATION_SECRET	Backend + Frontend	✓	Min 32 chars — ISR webhook secret
RECAPTCHA_SECRET_KEY	Backend	✓	Server-side reCAPTCHA v3 secret
NEXT_PUBLIC_RECAPTCHA_SITE_KEY	Frontend	✓	Client-side reCAPTCHA v3 key
RESEND_API_KEY	Backend	✓	Transactional email API key
EMAIL_FROM	Backend	✓	Sender address (default: noreply@outpro.india)
EMAIL_ADMIN_NOTIFY	Backend	✓	Lead notification recipient
SUPABASE_URL	Backend	✓	Supabase project URL (storage only)
SUPABASE_SERVICE_ROLE_KEY	Backend	✓	Supabase service role key (bypasses RLS)
NEXT_PUBLIC_API_URL	Frontend	✓	Backend API base URL
HUBSPOT_API_KEY	Backend	✗	CRM sync — skipped if absent
UPSTASH_REDIS_REST_URL	Backend	✗	Rate limiting — falls back to in-memory
UPSTASH_REDIS_REST_TOKEN	Backend	✗	Upstash Redis auth token
BCRYPT_ROUNDS	Backend	✗	Password hash cost factor (default: 12)
LOG_LEVEL	Backend	✗	error / warn / info / debug (default: info)

© Outpro.India. All rights reserved.

Variable	Service	Required	Description
ALLOWED_ORIGINS	Backend	✗	Comma-separated CORS origins (default: http://localhost:3000)
DB_POOL_MIN	Backend	✗	MongoDB connection pool min size (default: 2)
DB_POOL_MAX	Backend	✗	MongoDB connection pool max size (default: 10)
RATE_LIMIT_AUTH_PER_MIN	Backend	✗	Auth endpoint rate limit (default: 10)
RATE_LIMIT_PUBLIC_PER_MIN	Backend	✗	Public endpoint rate limit (default: 100)

v1.1.0 · April 2026 · © Outpro.India. All rights reserved.