

Rajalakshmi Engineering College

Name: Sanjai E

Email: 241801242@rajalakshmi.edu.in

Roll no: 241801242

Phone: 9363574090

Branch: REC

Department: I AI & DS FD

Batch: 2028

Degree: B.E - AI & DS

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 1

Attempt : 1

Total Mark : 10

Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Your task is to create a program to manage a playlist of items. Each item is represented as a character, and you need to implement the following operations on the playlist.

Here are the main functionalities of the program:

Insert Item: The program should allow users to add items to the front and end of the playlist. Items are represented as characters. Display Playlist: The program should display the playlist containing the items that were added.

To implement this program, a doubly linked list data structure should be used, where each node contains an item character.

Input Format

The input consists of a sequence of space-separated characters, representing the items to be inserted into the doubly linked list.

The input is terminated by entering - (hyphen).

Output Format

The first line of output prints "Forward Playlist: " followed by the linked list after inserting the items at the end.

The second line prints "Backward Playlist: " followed by the linked list after inserting the items at the front.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: a b c -

Output: Forward Playlist: a b c

Backward Playlist: c b a

Answer

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {  
    char item;  
    struct Node* next;  
    struct Node* prev;  
};
```

```
// You are using GCC
```

```
void insertAtEnd(struct Node** head, char item) {  
    struct Node* newNode=(struct Node*)malloc(sizeof(struct Node));  
    if(newNode==NULL){  
        return;  
    }  
    newNode->item=item;  
    newNode->next=NULL;  
    if(*head==NULL){  
        newNode->prev=NULL;
```

```

        *head=newNode;
    }else{
        struct Node*temp=*head;
        while(temp->next!=NULL){
            temp=temp->next;
        }
        temp->next=newNode;
        newNode->prev=temp;
    }
}

void displayForward(struct Node* head) {
    if(head==NULL){
        printf("Forward Playlist: \n");
        return;
    }
    struct Node*temp=head;
    while(temp!=NULL){
        printf("%c ",temp->item);
        temp=temp->next;
    }
    printf("\n");
}

void displayBackward(struct Node* tail) {
    if(tail==NULL){
        printf("Backward Playlist: \n");
        return;
    }
    struct Node*temp=tail;
    while(temp!=NULL){
        printf("%c ",temp->item);
        temp=temp->prev;
    }
    printf("\n");
}

void freePlaylist(struct Node* head) {
    struct Node*temp=head;
    while(temp!=NULL){
        struct Node*next=temp->next;
        free(temp);
        temp=next;
    }
}

```

```

    }
}
int main() {
    struct Node* playlist = NULL;
    char item;

    while (1) {
        scanf("%c", &item);
        if (item == '-') {
            break;
        }
        insertAtEnd(&playlist, item);
    }

    struct Node* tail = playlist;
    while (tail->next != NULL) {
        tail = tail->next;
    }

    printf("Forward Playlist: ");
    displayForward(playlist);

    printf("Backward Playlist: ");
    displayBackward(tail);

    freePlaylist(playlist);

    return 0;
}

```

Status : Correct

Marks : 10/10