```
In [2]:
import csv
num attribute=5
a=[]
with open('project1.csv', 'r') as csvfile:
    reader=csv.reader(csvfile)
    for row in reader:
        a.append(row)
        print(row)
print("\n The total number of training instances are : ",len(a))
num attribute = len(a[0])-1
print("\n The initial hypothesis is : ")
hypothesis = ['0']*num attribute
print(hypothesis)
for j in range(0, num attribute):
   hypothesis[j]=a[0][j]
print("\n Find-S: Finding maximally specific Hypothesis\n")
for i in range(0,len(a)):
   if a[i][num_attribute] == 'Yes':
        for j in range(0, num attribute):
             if a[i][j]!=hypothesis[j]:
                 hypothesis[j]='?'
             else:
                hypothesis[j]=a[i][j]
    print("\n For training Example No: {0} the hypothesis is".format(i), hypothesis)
print("\n The Maximally specific hypothesis for the training instance is ")
print(hypothesis)
['Vivo', '6000MAH', 'MTHP70', '4GB', '64GB', 'Yes']
['Vivo', '6000MAH', 'MTHP80', '4GB', '64GB', 'Yes']
['Redmi', '4000MAH', 'SD636', '6GB', '64GB', 'No']
['Vivo', '6000MAH', 'MTH780', '6GB', '128GB', 'Yes']
['Redmi', '4000MAH', 'SD636', '6GB', '64GB', 'No']
The total number of training instances are : 5
The initial hypothesis is :
['0', '0', '0', '0', '0']
 Find-S: Finding maximally specific Hypothesis
 For training Example No:0 the hypothesis is ['Vivo', '6000MAH', 'MTHP70', '4GB', '64GB']
 For training Example No:1 the hypothesis is ['Vivo', '6000MAH', '?', '4GB', '64GB']
 For training Example No:2 the hypothesis is ['Vivo', '6000MAH', '?', '4GB', '64GB']
 For training Example No:3 the hypothesis is ['Vivo', '6000MAH', '?', '?']
 For training Example No:4 the hypothesis is ['Vivo', '6000MAH', '?', '?', '?']
The Maximally specific hypothesis for the training instance is
['Vivo', '6000MAH', '?', '?', '?']
In [ ]:
```



