In [3]:

```
import pandas as pd
from sklearn.model_selection import train_test_split
from sklearn.feature_extraction.text import CountVectorizer
from sklearn.naive_bayes import MultinomialNB
from sklearn import metrics

msg=pd.read_csv('naivetext (1).csv',names=['message','label'])

print('The dimensions of the dataset',msg.shape)

msg['labelnum']=msg.label.map({'pos':1,'neg':0})
X=msg.message
y=msg.labelnum


xtrain,xtest,ytrain,ytest=train_test_split(X,y)
print ('\n the total number of Training Data :',ytrain.shape)
print ('\n the total number of Test Data :',ytest.shape)



cv = CountVectorizer()
xtrain_dtm = cv.fit_transform(xtrain)
xtest_dtm=cv.transform(xtest)
print('\n The words or Tokens in the text documents \n')
print(cv.get_feature_names())
df=pd.DataFrame(xtrain_dtm.toarray(),columns=cv.get_feature_names())


clf = MultinomialNB().fit(xtrain_dtm,ytrain)
predicted = clf.predict(xtest_dtm)


print('\n Accuracy of the classifier is',metrics.accuracy_score(ytest,p
redicted))
print('\n Confusion matrix')
```

```
print(metrics.confusion_matrix(ytest,predicted))
print('\n The value of Precision', metrics.precision_score(ytest,predicted))
print('\n The value of Recall', metrics.recall_score(ytest,predicted))
```

```
The dimensions of the dataset (18, 2)

 the total number of Training Data : (13,)

 the total number of Test Data : (5,)

 The words or Tokens in the text documents

['about', 'am', 'amazing', 'an', 'and', 'awesome', 'bad', 'beers', 'best', 'boss', 'can', 'deal', 'do', 'enemy', 'feel', 'good', 'he', 'horrible', 'is', 'juice', 'like', 'locality', 'my', 'not', 'of', 'place', 'restaurant', 'sick', 'stay', 'stuff', 'sworn', 'taste', 'that', 'the', 'these', 'this', 'tired', 'to', 'very', 'view', 'what', 'with', 'work']

 Accuracy of the classifier is 0.6

 Confusion matrix
[[1 0]
 [2 2]]

 The value of Precision 1.0

 The value of Recall 0.5
```

In [ ]:

In [ ]: