16/10/2026

Datatypes : A data type specifies the type of data that a vare -able can store in python.

Ex : a = 10 → Integer (int)

name = "sanjana" → String (str)

Single valued datatype

1. Integer (int) : Integer is a data type used to store whole numbers without decimal points.

```
Ex: a = 10
    b = -25
    Print (a)
    print ( type (a))
```

2. Float (float) : Float is a data type used to store decimal numbers.

```
Ex:  a = 10.5
     print (a)
     print ( type (a))
```

3. String (str) : String is a data type used to store a sequence of characters enclosed in single or double quotation marks.

```
Ex: name = "Sanjana"
    Print (name)
    print (type (name))
```

4. Boolean (bool) : Boolean is a data type that represents only two values : True or false.

```
Ex : a = True
     b = False
     print (type (a))
```

5. Complex (complex) : Complex is a datatype used to store numbers containing a real part & an imaginary part.

```
Ex : 3 + 4j
     print (a)
     print (type (a))
```

Multivalued datatype

1. List (list) : A list is used to store multiple items in a single variable. Lists are ordered & can be modified.

```
Ex : a = [10, 20, 30, 40]
     print (a)
     print (type (a))
```

2. Tuple (tuple) : A tuple is used to store multiple items in a single variable. Tuples are ordered & cannot be modified after creation.

```
Ex : a = (10, 20, 30)
     print (a)
     print (type (a))
```

3. Set (set) : A set is used to store unique items. It does not allow duplicate values.

```
Ex : a = {10, 20, 30, 40}
     print (a)
     print (type (a))
```

4. Dictionary (dict) : A dictionary stores data in key-value pairs.

```
Ex : student = {"name" : "sanjana", "age" : 22}
     print (student)
     print (type (student))
```

10. None (NoneType) : None represents the absence of a value.

Ex : a = None
print (a)
print (type (a)).