MAILDESK — EMAIL MANAGEMENT SYSTEM

Integrated OOPS and DBMS Project Report

Submitted by

_____ – _____

_____ – _____

_____ – _____

of

BACHELOR OF ENGINEERING

in

Department Name: _____

INSTITUTION: _____

(Institution / autonomous status, if applicable)

[INSTITUTION LOGO]

November 2026

BONAFIDE CERTIFICATE

This is to certify that the project report titled “MAILDESK — EMAIL MANAGEMENT SYSTEM” is the bonafide work of the students whose names and registration numbers are entered below. The work was completed as an academic project integrating Object Oriented Programming in Java and Database Management Systems.

The report describes the design, implementation, database structure, interface, and observed outputs of the submitted application. The student team has prepared the work for academic assessment and has identified the implemented functions and the known limitations of the project.

STUDENT DETAILS AND SIGNATURES

NAME OF STUDENT	REGISTER NUMBER	SIGNATURE
_____	_____	_____
_____	_____	_____
_____	_____	_____

INTERNAL FACULTY

Ms.DHANALAKSHMI K
Assistant professor
Object oriented programming in java
Artificial Intelligence and Data Science

Ms.DHANALAKSHMI K
Assistant professor
Database management systems
Artificial Intelligence and Data Science

Date of submission / practical examination: _____

INTERNAL EXAMINER	EXTERNAL EXAMINER
Signature: _____	Signature: _____
Date: _____	Date: _____

ABSTRACT

Maildesk is a Java desktop email-management system that brings common Gmail tasks into one focused workspace. A user can connect through Google OAuth, browse Inbox, Sent, and Gmail Spam, search the locally cached sender, recipient, subject, and body, read messages, and compose plain-text email. The Swing application uses an application service boundary so the interface, Gmail integration, local spam analysis, and persistence can be understood as separate parts.

The project's distinctive feature is an explainable second opinion for suspicious messages. A deterministic Java rule classifier assigns a score from visible signals such as blocked senders, suspicious phrases, many links, and urgent subject wording. The interface presents reasons with the score so the mailbox owner can review and correct the decision. A score is a rule score, not a probability. Gmail's own Spam label remains distinct from Maildesk's locally suspected messages. A saved user correction is retained per account.

For predictable demonstrations, the live connection and refresh retrieve up to six recent messages from each of Inbox, Sent, and Gmail Spam, deduplicate message IDs, and cap the local sample at 18 unique messages. The application stores accounts, messages, recipients, labels, spam results, feedback, and blocked senders in MySQL through JDBC. Composite account/message keys scope cached records to an account. OAuth tokens and database passwords remain in local configuration and are not stored in the message tables.

The separate demo launcher uses fictional in-memory messages. It does not connect to Gmail or MySQL, use the network, or deliver real email. The project uses Java 17 or newer, Swing, Maven, the Gmail REST API, Google OAuth, and MySQL 8. The report documents its flow, use cases, data model, modules, source-level implementation, screenshots, setup, and verification coverage. Attachments, rich text, scheduled synchronization, broad public OAuth distribution, and machine-learning classification are future work, not current features.

TABLE OF CONTENTS

CHAPTER	CONTENTS	PAGE NO.
1	INTRODUCTION: problem statement, project overview, purpose, scope	5–8
2	FUNCTIONALITIES PROVIDED	9
3	SYSTEM FLOW DIAGRAM: dataflow, use cases, ER model, architecture	10–14
4	MODULE DESCRIPTION: workspace, authorization, mailbox, messages, spam, demo	15–24
5	IMPLEMENTATION: Java contracts, Gmail, spam rules, JDBC, setup, verification	25–41
6	CONCLUSION	42
7	REFERENCES	43
A	COMPLETE JAVA, SQL, TEST, SCRIPT, AND BUILD SOURCE	44–119
B	APPLICATION OUTPUT AND SCREENSHOTS	120–124

Student names, register numbers, department, institution name and logo, and submission / practical-examination date are left for completion. Faculty details are shown on the bonafide certificate. No personal or institutional details from the supplied example have been copied into this report.

1 - INTRODUCTION

1.1 PROBLEM STATEMENT

Email users often move between separate mailbox views to find recent work, inspect a message, compose a reply, and check suspicious requests. A basic spam filter can hide a message or provide little explanation for its decision. When users cannot see the reason, they have less confidence in the result and may have difficulty correcting a false positive.

A student-scale email management application should combine the common tasks in a clear interface while keeping the user involved in security decisions. It also needs a reliable way to preserve a small mailbox cache in a relational database without turning the project into a full Gmail mirror.

Maildesk addresses this problem with a focused desktop workspace, a bounded recent-message sample, MySQL persistence, and an explainable local spam review. The user sees matched warning reasons and can mark a received message as spam or not spam. Gmail's own Spam folder and Maildesk's local suggestions remain separate views.

The difficulty is not simply that a mailbox contains many messages. The same mailbox combines routine notices, personal correspondence, receipts, work requests, and potentially deceptive messages. A user must locate relevant mail while deciding which content deserves caution. A useful student project should therefore demonstrate both ordinary message handling and a transparent review mechanism. It should also explain exactly which data is local, which action reaches Gmail, and how the user can correct a recommendation.

1 - INTRODUCTION

1.2 PROJECT OVERVIEW

Maildesk is a Java Swing desktop client connected to Gmail through Google's OAuth flow and Gmail REST API. Its main window presents a navigation rail, mailbox list, search controls, a message reader pane, and a compose form. JDBC connects its application cache to a local MySQL database.

The core service is exposed through an EmailService interface. GmailEmailService coordinates remote Gmail actions with the local store; DemoEmailService implements the same interface using fictional in-memory messages. Because both implementations share a contract, the interface can be demonstrated without credentials, network access, or a running database.

On live startup, the system requests six recent items from Inbox, Sent, and Spam, deduplicates IDs, then stores no more than 18 unique messages. Local spam analysis attaches a score and reasons to received messages. Search covers the cached sample. Compose sends plain-text email after validation. The database persists message data, Gmail labels, spam explanations, feedback, and blocked senders per account.

The application has two deliberate execution paths. The live path uses the user-authorized Gmail account and MySQL. The presentation path uses deterministic fictional content held only in memory. Both paths use the same EmailService interface, which keeps the UI behavior consistent while making the demo safe and independent of internet access. The report treats these paths separately wherever a screenshot or test could otherwise be mistaken for a live mailbox action.

1 - INTRODUCTION

1.3 PURPOSE AND OBJECTIVES

The purpose of Maildesk is to demonstrate an end-to-end Java and DBMS application that makes email work easier to understand. The system centralizes reading, searching, writing, and review while showing how an object-oriented service layer can connect a Swing interface to both an external API and a relational database.

Project objectives

- Connect a Gmail account by using Google OAuth in the system browser; do not collect the mailbox password.
- Show Inbox, Sent, Gmail Spam, and locally Suspected Spam in a consistent desktop interface.
- Search the cached sender, recipient, subject, and plain-text body.
- Validate a plain-text draft before requesting a Gmail send.
- Persist account-scoped messages, recipients, Gmail labels, spam reasons, and user corrections through JDBC.
- Explain why the local rule classifier suggested review and allow the user to correct it.
- Provide a fictional offline demonstration that is safe to show without connecting to a real account.

These objectives provide a practical basis for evaluating the result: authorization should be explicit; message retrieval should be bounded; data access should remain account-scoped; remote changes should follow a user action; and suspicious-message recommendations should show their reasons. The team can demonstrate each objective by tracing a user action through the Swing panel, service method, provider or database adapter, and visible result.

1 - INTRODUCTION

1.4 SCOPE

CURRENT PROJECT SCOPE	OUTSIDE THE CURRENT BUILD
Gmail Desktop OAuth; Inbox, Sent, Gmail Spam; recent-message cache; local search.	Hosted multi-user mail service or a complete replacement for Gmail.
Read, send plain-text, refresh, mark spam / not spam.	Attachments, rich-text editing, and scheduled synchronization.
MySQL persistence via JDBC and one active connected account.	Enterprise administration or public multi-account hosting.
Transparent deterministic spam rules and account-specific feedback.	Machine-learning classification or a probability-calibrated risk score.
Offline demo with fictional, in-memory mail.	Real delivery from demo mode or database persistence in demo mode.

The live application uses Google permissions configured for the Gmail API. Distribution to a broad public audience may require the applicable Google consent-screen and OAuth verification work. The Windows package contains the application runtime, but each live installation still requires local MySQL and a user-provided Desktop OAuth client.

Scope is also a statement of what the team can support reliably. A small recent-message cache keeps the report and classroom demonstration reproducible, while the offline mode avoids requiring a reviewer to grant account access. Features such as full mailbox synchronization, attachment scanning, multiple simultaneous accounts, and machine learning would require additional design, privacy analysis, quota handling, and user testing, so they are documented as future work.

2 - FUNCTIONALITIES PROVIDED

Maildesk offers a compact set of workflows that can be explained and demonstrated from one workspace. A live mailbox owner signs in through Google, then chooses one of the four mailbox views. The interface updates the list and reader pane without replacing the connected account.

FUNCTION	USER VALUE	BOUNDARY
Connect Gmail	Use Google sign-in and load recent mail.	Requires configured Desktop OAuth credentials and consent.
Inbox / Sent / Gmail Spam	Read common mailbox categories.	Gmail labels identify provider folders.
Suspected Spam	Review the local rule model’s suggestions.	Separate from Gmail’s Spam folder.
Search	Find a message in the cached sample.	Does not search every remote Gmail message.
Compose	Send a validated plain-text message.	No attachments or rich formatting.
Correct spam	Save the user’s decision and update Gmail.	Only explicit user actions change Gmail labels.
Offline demo	Explore fictional data without external setup.	No network, MySQL, or real mail delivery.

Refresh replaces the local recent snapshot; it does not delete Gmail messages. Failed reads do not become an empty successful result. A local correction is associated with the account and may override the later automatic rule result.

3 - SYSTEM FLOW DIAGRAM

3.1 OVERALL SYSTEM FLOW




Figure 1: System flow from account connection through user review

The flow starts when a user connects Gmail. Maildesk requests up to six recent messages from each supported provider label. IDs returned from more than one label are deduplicated before the 18-item cap is applied. The service evaluates received messages locally and writes the snapshot and analysis into MySQL.

The person then reads, searches, or composes. Gmail state changes occur only after a corresponding user action. A spam correction is also saved to local feedback. In offline demo mode, the connection step is simulated and the data path remains in memory.

Each boundary has a defined responsibility. OAuth establishes identity and permission; Gmail supplies provider messages and receives explicit user changes; the classifier adds a local review signal; the JDBC store persists a bounded cache and feedback; the UI presents the combined state. The demo mode replaces the live integrations with in-memory behavior while preserving the workflow. A failure at one boundary is surfaced as a failed action rather than being silently converted into successful empty data.

3 - SYSTEM FLOW DIAGRAM

3.2 DATAFLOW DIAGRAM




Figure 2: Data flow between the person, application, Gmail, classifier, and MySQL

The Swing interface accepts searches and explicit actions. The application service validates the selected mailbox or draft and routes requests to the Gmail gateway or the database store. Gmail returns message metadata and body text; the local classifier derives a score and explanation from the message fields and account-specific blocked-sender list.

The database stores a cache and the results needed for the local UI. OAuth tokens remain in a local protected token store rather than in the email tables. The demo implementation bypasses all external boxes and reads fictional fixtures from memory.

The data flow distinguishes message content from authorization credentials. Message metadata and plain-text content pass through the service into the local cache; OAuth tokens are kept in a separate local token directory. Search is limited to the loaded sample. The database does not act as a public server and is not exposed to other accounts. This separation helps explain why neither a message's Gmail password nor an OAuth secret is stored in the relational message rows.

3 - SYSTEM FLOW DIAGRAM

3.3 USE CASE DIAGRAM




Figure 3: Mailbox owner use cases and the presenter's demo entry

ACTOR	USE CASE	DESCRIPTION
Mailbox owner	Connect / disconnect	Authorize a Gmail account or end the local session.
Mailbox owner	Browse / search	Choose Inbox, Sent, Spam, or Suspected Spam; search the cache.
Mailbox owner	Read / compose	Open a cached message or compose a validated plain-text message.
Mailbox owner	Review / correct	Read rule reasons and mark a received message spam or not spam.
Presenter	Run demo	Explore fictional content without Gmail or database setup.

The primary actor is the mailbox owner because every live action is performed under that person's authorization. The presenter actor has a narrower role: start offline demo mode and show fictional output. Use cases that change Gmail—sending, marking spam, clearing spam, and marking read—are distinguished from local actions such as opening a view or searching the current sample. This makes the user's authorization and intent visible in the requirements.

3 - SYSTEM FLOW DIAGRAM

3.4 ENTITY RELATIONSHIP DIAGRAM




Figure 4: MySQL entities and account-scoped key relationships

The accounts table identifies each connected mailbox. Messages use the composite key (account_id, gmail_message_id). Recipient and label rows reference that key. Spam results are stored per message, while feedback and blocked-sender rows are associated with the account. This structure keeps repeated recipients and Gmail labels out of a single overloaded message column.

Foreign keys enforce parent-child relationships. The composite message key ensures lookups and writes are scoped to the active account. sql/schema.sql contains the full table definitions and constraints.

The schema resolves one-to-many relationships explicitly. One account owns many messages; one message can have several recipients and Gmail labels; one message can have a current spam analysis and a user feedback record. Composite keys and foreign keys provide referential integrity, while account IDs prevent a lookup from treating two users' identical Gmail message IDs as the same local row. The complete DDL is reproduced in Appendix A.

3 - SYSTEM FLOW DIAGRAM

3.5 SOFTWARE ARCHITECTURE




Figure 5: Swing, service, Gmail, OAuth, spam analysis, and persistence layers

The Swing UI depends on EmailService rather than on GmailApiClient or JdbcMailStore directly. GmailEmailService is the live implementation. DemoEmailService uses the same application boundary with fictional data. This separation allows interface behavior to be reviewed without granting real Gmail permissions.

The Gmail package owns OAuth and REST details. The storage package owns the MailStore contract and its JDBC implementation. SpamClassifier is a deterministic local component. Model classes carry immutable message and result values between these layers.

Dependency direction is chosen to keep the interface replaceable. The UI calls the service contract; GmailEmailService and DemoEmailService implement that contract. The live service coordinates GmailGateway and MailStore, while the spam component computes an explanation from domain data. This design limits provider-specific HTTP details to the Gmail package and SQL details to storage, reducing the chance that a screen handler contains persistence logic.

4 - MODULE DESCRIPTION

MODULE OVERVIEW

The project is divided into related modules so each function has a clear role. The interface module handles presentation and user actions. The service module coordinates business operations. Gmail, spam, and storage modules implement integrations behind stable boundaries.

MODULE	MAIN RESPONSIBILITY	KEY CLASSES
Welcome / account	Explain product and start OAuth.	MailAppPanel, GmailAuth
Mailbox workspace	Navigation, table, reader, search.	MainFrame, MailAppPanel, MailTableModel
Compose	Validate and submit plain-text draft.	ComposePanel
Gmail integration	Authorize, fetch, read, send, label.	GmailApiClient, GmailEmailService
Spam review	Calculate score and show reasons.	SpamClassifier, SpamResult
Database	Persist messages and feedback.	MailStore, JdbcMailStore
Offline demo	Simulate screen actions with fictional data.	DemoApp, DemoEmailService

The following pages explain each visible module and connect it to the implementation that supports it.

Each module has a visible or testable boundary. The welcome panel begins authorization, the workspace organizes messages, the compose panel validates user input, the service coordinates operations, and the repositories persist the local state. The same module map is used in the source listings in Appendix A, so a reviewer can move from this description to the complete class implementation without guessing where a responsibility lives.

4 - MODULE DESCRIPTION

4.1 WELCOME AND CONNECT SCREEN

The welcome page introduces the three product ideas: a clear inbox, a second look at suspicious messages, and user control over the decision. The production button begins Gmail authorization. The demo button opens the same mailbox workspace with fictional content.

The connected-account label and status message communicate whether Maildesk is ready. The page does not ask the user to type a Gmail password. In demo mode a banner explicitly states that sample messages are shown and nothing is sent to Gmail.

The welcome view is a decision point rather than a generic login screen. It introduces the product workflows before requesting an account connection. Its primary action is visually prominent, while the supporting copy explains that authorization occurs through Google in the system browser. This makes the credential boundary clear and prepares the user for the browser transition.

The production button requires a configured Desktop OAuth client and a Google account allowed by the consent-screen settings. The page does not collect or store a Gmail password. A returning user may have a locally saved OAuth token; the app then refreshes that token as permitted by Google and proceeds to load the bounded sample.

The output pages in Appendix B show this welcome screen from the offline demonstration build. They document the user interface and explanatory copy. They do not claim that every installation has a configured OAuth client or an active Gmail connection.

The welcome text sets expectations before account access begins. It identifies the core benefits and explains that Gmail authentication occurs in Google’s browser flow. Keeping the offline demo entry visible gives a reviewer a way to inspect the product without sharing credentials. The status line is part of the interaction: it communicates missing setup or a denied authorization in a form that points back to configuration steps.

4 - MODULE DESCRIPTION

4.2 GOOGLE AUTHORIZATION MODULE

Gmail access uses an OAuth Desktop client and the system browser. GmailAuth generates a random state and PKCE verifier, derives an S256 challenge, starts an HTTP callback bound to 127.0.0.1, and opens Google's authorization page. After Google returns a code to the local callback, the app exchanges the code and verifier for tokens.

A saved local token may be refreshed without collecting the user's password. The token store protects the local files and the repository ignores credentials and token directories. The Gmail scope used by the application is gmail.modify because reading messages and updating labels require those operations.

A Google project in testing mode must include the user as a test user. The app's local sign-in does not bypass Google consent settings or public-app verification requirements.

The authorization flow uses a random state value to bind the returned callback to the initiated request and PKCE to bind the code exchange to the local application. The callback listens only on loopback and uses an ephemeral port. The application checks the state before accepting a code, applies a timeout, exchanges the code through HTTPS, and closes the local server after completion. This design avoids asking the user to type or transmit a Gmail password to Maildesk.

4 - MODULE DESCRIPTION

4.3 MAILBOX NAVIGATION

The left navigation presents Inbox, Sent, Gmail Spam, and Suspected Spam. Selecting a mailbox changes the view title and retrieves messages through the shared service. The central table shows sender or recipient, subject, and time. The right pane is reserved for message contents and the spam review.

The table model presents an immutable view of the selected results. A single selected row is opened in the reader pane. Empty search results and empty folders have dedicated states so an empty list is not confused with a broken connection.

Mailbox navigation is coordinated with the active service implementation. The interface does not need to know whether the data is backed by Gmail or by demo fixtures. This shared contract keeps selection, search, and reading consistent in both modes. Selecting a provider mailbox changes the label query; selecting Suspected Spam instead filters locally analyzed results and saved corrections.

The bounded sample is reflected in the interface: the table displays messages currently loaded into Maildesk’s local cache. Search and filtering stay responsive because they operate on a small set. The application avoids wording that implies remote, account-wide search. If a needed message is outside the sample, the user can view it in Gmail or refresh Maildesk for the latest bounded selection.

Appendix B includes the inbox output with fictional senders and message content. The screenshot documents layout and navigation, not the presence of a real mailbox connection.

Navigation state is kept separate from the underlying messages. Selecting a folder changes the active mailbox and refreshes the visible list; selecting Suspected Spam filters by the locally computed suggestion. The reader selection is tied to a stable Gmail message ID rather than the table row number, so sorting or filtering does not accidentally open a different record. These details keep actions predictable as the visible list changes.

4 - MODULE DESCRIPTION

4.4 RECENT SAMPLE AND REFRESH

The live client intentionally works with a bounded sample rather than downloading the entire mailbox during first connection. GmailEmailService requests six recent messages for each of Inbox, Sent, and Spam. The Gmail API client deduplicates message IDs, and the service applies an overall limit of 18.

Refresh repeats the same bounded workflow. Replacing the local snapshot removes records from the local cache if they are absent from the latest sample, but it does not delete messages from Gmail. A refresh failure is reported as an error and the previous cache is preserved.

This boundary is useful for a small class demonstration: the count is easy to inspect, and the behavior does not imply a complete synchronization engine.

The per-label request limit and combined 18-message ceiling are both enforced deliberately. A message appearing under more than one Gmail label is deduplicated by its provider ID. The refresh operation replaces only Maildesk’s local snapshot and uses a database transaction so a partial update is not presented as complete. Gmail data is changed only by explicit message actions; snapshot replacement never deletes remote mail.

4 - MODULE DESCRIPTION

4.5 SEARCH AND MESSAGE READER

Search matches sender, recipients, subject, and body text in the local sample. It does not claim to search every message stored in Gmail. Results are sorted newest first. Selecting a message asks the service to load the latest body and, when necessary, update Gmail's unread status.

The reader pane displays the sender, recipient, subject, date, body, and spam reason card. Plain text is rendered as plain text so message content cannot be interpreted as Swing HTML. Long bodies can scroll vertically, keeping the end of a message reachable at common window widths.

Search normalizes the query and compares it with fields available on the locally cached message. Recipient matching considers the complete recipient collection. An empty query restores the selected mailbox view. Search text is filtered in the application layer and is never concatenated into an SQL statement.

Opening a row changes the reader state to the selected message. The implementation must handle missing or malformed body content without preventing the sender, subject, date, and labels from rendering. Subject and sender values remain plain text. When the selected message is unread, the service is responsible for synchronizing the read-state action with Gmail and updating the local model.

Appendix B presents a reader output. The combined list-and-reader design keeps message context visible, which makes it easier to inspect several candidates in sequence without losing the selected mailbox or search context.

The reader separates message identity and content: a row selection identifies a Gmail message, then the service retrieves or supplies its body and status. A missing body is treated as a normal message condition rather than a fatal UI error. Search applies to sender, recipients, subject, and cached body text, and communicates its local scope. Plain text is rendered as text, avoiding HTML interpretation of untrusted message content.

4 - MODULE DESCRIPTION

4.6 COMPOSE MODULE

The compose form collects one recipient address, a subject, and a plain-text body. Before handing the draft to the service, the form checks that the recipient is valid, the subject contains 1–200 characters on one line, and the body is non-empty and within the configured limit.

The production service validates again before sending. This protects the application boundary even if a different interface implementation is introduced later. The demo compose form keeps the same validation behavior but stores the result only in its local Sent view.

Attachments, rich-text formatting, draft synchronization, and multiple recipients are not part of this version.

Validation is repeated at the service boundary so that correctness does not depend on a particular Swing form. The MIME builder encodes a plain-text message using UTF-8 and submits it through Gmail's send operation. No message is sent until the user presses the send action and the service accepts the draft.

The UI enters a busy state while a send is pending, prevents duplicate submissions, and reports either success or a recoverable error. It does not automatically retry an ambiguous send failure because the first request may already have reached Gmail. The output in Appendix B shows the offline compose screen and its demo notice; it is not a delivered message.

The compose workflow is validated at both the UI and service layers. The user receives a specific field-level error before a network request is made. The MIME builder produces a plain-text message with UTF-8 content and submits it through the Gmail API in live mode. The interface avoids automatic retries after an ambiguous send result; this prevents a transient connection failure from creating duplicate delivery.

4 - MODULE DESCRIPTION

4.7 SUSPECTED SPAM MODULE

Suspected Spam is a local review queue generated from Maildesk's rules. It does not copy or rename Gmail's Spam label. The message detail shows the rule score and each reason that contributed to it. The user can choose Mark as spam or Not spam after reviewing the evidence.

The demonstration screenshot uses a fictional invoice message and a reserved .test domain. Its threatening wording, link mismatch, and sensitive-data request are written as sample signals for the interface demonstration; they are not evidence from a real account.

The classifier assigns a score from a documented set of deterministic signals: a blocked sender, suspicious phrases, multiple links, and urgency terms. Reasons are retained alongside the total so that the interface can explain the decision. The score is a rule score, not a calibrated probability, and it should not be interpreted as a guarantee of safety or fraud.

The Suspected Spam list and Gmail Spam folder remain separate. The first is Maildesk's local recommendation; the second is a provider label. A user correction is persisted independently from the generated score. The distinction matters because users may want to inspect an automatically flagged message without changing its Gmail label.

Appendix B includes a fictional review output that demonstrates the score, reason list, and correction controls. This screenshot illustrates a design workflow and does not represent a real phishing message or account.

The review model favors explainability over hidden automation. The score is assembled from readable conditions, each matched condition yields a reason, and the threshold is a decision rule rather than a probability estimate. The user may correct the suggestion, and that correction is kept separately from the classifier output. This allows the report to describe what the system recommended and what the user chose without conflating the two.

4 - MODULE DESCRIPTION

4.8 USER CORRECTION AND LABEL ACTIONS

A user correction has two effects in the live application: Maildesk asks Gmail to apply or remove the Spam label, and the local database saves the user's correction. A correction is associated with the connected account and message ID. On a later analysis, stored feedback takes precedence over the automatic classifier result.

USER ACTION	GMAIL EFFECT	LOCAL EFFECT
Mark as spam	Add SPAM and remove INBOX where applicable.	Save spam feedback and current labels.
Not spam	Remove SPAM and add INBOX where applicable.	Save not-spam feedback and current labels.
Open unread message	Remove UNREAD through Gmail.	Save latest message and read state.
Disconnect	End local authorization session.	Clear active account from the UI; does not delete Gmail or DB rows.

The application does not automatically replay a failed send or label change. This avoids accidental duplicate mail or repeated changes after a network error.

A label mutation is sent only after the corresponding control is activated by the user. The service updates Gmail and saves the resulting local feedback, while the UI reports errors if either operation cannot be confirmed. The correction applies to the current account and message ID. Keeping the feedback separate makes it possible to preserve user intent across a later recalculation of the automatic spam score.

4 - MODULE DESCRIPTION

4.9 STANDALONE DEMONSTRATION MODULE

The standalone demo is an offline presentation mode built against the same EmailService interface as the live client. DemoEmailService seeds fictional messages in memory, supports mailbox navigation, search, message reading, local demo send, and spam corrections.

DEMO ACTION	RESULT
Open demo mailbox	Shows fictional Inbox, Sent, Gmail Spam, and Suspected Spam.
Search	Filters the in-memory sample.
Compose / send	Creates a demo Sent item; no email is delivered.
Mark spam / not spam	Changes only local demo labels and correction state.
Restart application	Reloads the seed sample; demo changes are not persistent.

The banner is part of the safety and presentation design. It states that sample messages are used and no email is sent through Gmail. No account or internet connection is required to demonstrate the interface.

Demo fixtures use reserved example domains and invented subjects, dates, and bodies. They provide enough variation to show mailbox navigation, search, reading, compose, and spam explanation without exposing personal data. The demo service resets on application restart, which reinforces that it is a presentation fixture rather than a second persistent mailbox. Its banner remains visible so sample actions cannot be mistaken for Gmail delivery.

5 - IMPLEMENTATION

5.1 SOURCE ORGANIZATION

SOURCE AREA	RESPONSIBILITY
src/main/java/ems/ui	Swing frames, panels, table model, compose form, visual theme.
src/main/java/ems/service	EmailService contract and live Gmail service coordination.
src/main/java/ems/gmail	Google OAuth, token persistence, Gmail REST and MIME message helpers.
src/main/java/ems/storage	MailStore boundary, JDBC store, database schema setup.
src/main/java/ems/model	Account, mailbox, message, and spam-result domain objects.
src/main/java/com/emailapp/spam	Deterministic rule classifier and score weights.
src/demo/java	Offline demo app and fictional in-memory service.
src/test/java and sql/	Verification code and MySQL schema.

The shared application boundary avoids coupling the interface directly to JDBC or HTTP code. The project uses Maven and the Maven Wrapper to compile Java 17 source and produce an executable JAR. A Windows packaging script uses jpackage to create an app image with a bundled runtime.

The repository separates production Java, demo Java, test Java, database schema, and Windows scripts. Production code contains the actual service and UI; demo code supplies the offline fixture; tests verify behavior through local fixtures; SQL defines persistent structures; and scripts package or launch the application. Appendix A reproduces these source files so the project can be reviewed from the report itself.

5 - IMPLEMENTATION

5.2 SHARED SERVICE CONTRACT

The EmailService interface is the method-name contract shared by the Swing UI, the live Gmail integration, and the offline demo. The UI depends on these operations and does not need to know which implementation is active.

AppException carries a recoverable message suitable for a user notice. Database and provider details are translated into bounded, non-sensitive descriptions. The contract calls that can wait for network or storage work execute on a background worker rather than the Swing event thread.

The service contract is the collaboration point between UI and integrations. Method names and value types are stable across live and demo implementations. This prevents a screen from relying on Gmail-specific response objects and allows the demo to exercise the same user flow. Checked application exceptions keep failure handling explicit at the call site, while the interface avoids exposing SQL statements or HTTP request construction to the UI.

5 - IMPLEMENTATION

5.3 DOMAIN MODEL AND OBJECT-ORIENTED DESIGN

EmailMessage is an immutable snapshot. It holds an account ID, Gmail message ID, sender, recipient list, subject, plain-text body, received time, and provider label IDs. Lists and sets are copied when the model is created, so callers cannot mutate the stored collections through an earlier reference.

Account contains a local database identifier and an email address; OAuth credentials do not belong in this object. Mailbox is an enum with INBOX, SENT, SPAM, and SUSPECTED. SpamResult contains a rule score, suspected flag, and immutable explanation list.

The domain model expresses the concepts used throughout the project rather than leaking database row structures into every component. An Account identifies the active mailbox locally, EmailMessage describes one cached message, Mailbox names a navigable view, and SpamResult records an explainable analysis. Immutable collections prevent the UI or classifier from mutating message values after they have entered the service workflow.

5 - IMPLEMENTATION

5.4 SWING UI AND BACKGROUND WORKERS

Swing components must be changed on the event-dispatch thread. Network requests and JDBC operations can take time, so MailAppPanel uses SwingWorker. The busy flag prevents duplicate user actions while the operation is in flight. On completion, the UI displays the result or a safe error message.

The reader and compose forms use reusable Swing panels. MailTableModel presents the selected mailbox rows. UI checks exercise these screens headlessly through the same service boundary used by the live application.

SwingWorker separates the event-dispatch thread from network and JDBC work. The background phase performs the service call; the completion phase updates controls and model state on the UI thread. Busy-state handling prevents duplicate operations and provides visible progress. Error handling unwraps expected exceptions into user-facing messages while keeping technical details in the application’s diagnostic path.

5 - IMPLEMENTATION

5.5 GOOGLE OAUTH AUTHORIZATION CODE FLOW

GmailAuth implements Authorization Code with PKCE for a native desktop client. The app creates a random state and verifier, hashes the verifier with SHA-256, and binds a temporary callback listener to the IPv4 loopback address. The browser opens Google's authorization endpoint with the challenge and requested Gmail scope.

The callback validates state before accepting the authorization code. Maildesk then exchanges the code and verifier for tokens. A bounded timeout produces a clear sign-in error. The local callback server is always stopped in a finally block.

PKCE protects the native-client code exchange by requiring the verifier held by the application. State validation protects against an unrelated callback being accepted. The callback server binds to 127.0.0.1 rather than a public interface and is closed after one authorization attempt. Credentials and token files are local configuration, excluded from version control, and must be supplied by each user's Google project.

5 - IMPLEMENTATION

5.6 GMAIL REST AND MESSAGE OPERATIONS

GmailApiClient is the network adapter behind GmailGateway. It obtains an access token from the token provider and makes HTTP requests to the Gmail API. The service obtains the account profile after authorization, then retrieves message metadata and content through message IDs.

OPERATION	APPLICATION BEHAVIOR
Profile	Read the authorized account email address.
List messages	Request messages with the chosen Gmail labels and query.
Read message	Load sender, recipient, subject, plain-text body, timestamp, and labels.
Send	Build and submit a MIME message with one recipient and plain-text body.
Modify labels	Update unread or spam status only after an explicit user action.

The application never sends mail as part of automated tests. The user sees status text when an operation fails, and the UI does not mistake a local cache error for a successful remote operation.

The API adapter isolates URL construction, HTTP status handling, response parsing, and Gmail-specific payloads. Message IDs are listed first, then details are fetched and converted into domain objects. Sending constructs a MIME payload; label changes use explicit Gmail modify operations. Transient read failures may be retried within a bounded policy, while sends and label writes are not replayed automatically.

5 - IMPLEMENTATION

5.7 BOUNDED RECENT-MAIL IMPORT

The recent-message path queries three Gmail labels independently: INBOX, SENT, and SPAM. Each request is limited to a per-label count. A linked set deduplicates IDs that occur in multiple categories. The service applies an overall limit before replacing the local snapshot.

GmailEmailService calls fetchRecentMessages(accountId, 6) and limits the combined sample to 18. The schema uses the Gmail message ID as part of its primary key, so repeated refreshes update the same cached record rather than creating duplicates.

The phrase “sample” is deliberate: the application is not presented as a complete Gmail mirror or as a full synchronization engine.

The bounded refresh avoids a first-run full-mailbox scan and controls both provider requests and local storage size. The application reads Inbox, Sent, and Spam, deduplicates overlapping IDs, and stores at most 18 unique messages. This limit is stated to the user and in the report. It is a demonstration choice, not a Gmail API quota claim or a promise of complete mailbox synchronization.

5 - IMPLEMENTATION

5.8 EXPLAINABLE SPAM CLASSIFIER

SpamClassifier is a deterministic rule model. It begins at zero, adds points for matched evidence, and stores a reason for each contributing rule. A blocked sender adds 50 points; each matched suspicious phrase adds 20 up to three matches; five or more links add 15; and urgent subject wording adds 10. The review threshold is 50.

The score is not machine learning and is not a probability. The purpose of this module is an inspectable second opinion. Feedback stored by JdbcMailStore can override the later automatic suggestion for that account and message.

Rule weights are intentionally visible and deterministic. A blocked sender contributes the largest single signal; suspicious phrases accumulate only up to a fixed count; multiple links and urgency wording add smaller signals. The threshold controls queue membership. A rule score has no probabilistic calibration, so the application presents the matched reasons and leaves the final action to the mailbox owner.

5 - IMPLEMENTATION

5.9 DATABASE SCHEMA: ACCOUNTS AND MESSAGES

The accounts table has a generated account_id and a unique email_address. The messages table is keyed by account_id and gmail_message_id. Its columns store sender, subject, body text, received time, and read state.

The database uses utf8mb4. The project schema creates email_management when permitted and initializes its tables from sql/schema.sql. A dedicated database user should be used for the local application.

The account row is created or reused by normalized email address. A message is scoped by both account ID and Gmail ID, allowing repeated refreshes to update a row without collision across accounts. Text columns are sized for subjects and message bodies, timestamps retain sub-second precision, and explicit constraints enforce account ownership. Database encoding uses utf8mb4 so message text is not limited to basic ASCII.

5 - IMPLEMENTATION

5.10 NORMALIZED RECIPIENTS AND LABELS

Recipients and Gmail labels are stored as child records. This allows a message to have multiple recipients and labels without placing a delimiter-encoded list in a single database cell. The child rows reference the same composite key as the parent message.

The composite foreign key ensures a label or recipient cannot be attached to a message in another account. Cascading deletion removes these child rows when a locally cached parent message is removed.

Separate child tables support messages with multiple recipients and multiple labels. A composite foreign key points each child row to the exact parent message and account. This avoids comma-separated lists that are difficult to query or validate. Cascading deletion applies only to local cached children when a parent cache row is replaced or removed; it has no effect on the Gmail mailbox.

5 - IMPLEMENTATION

5.11 SPAM RESULTS, FEEDBACK, AND BLOCKED SENDERS

TABLE	IMPORTANT FIELDS	ROLE
spam_results	account_id, gmail_message_id, score, suspected_spam, reasons, analyzed_at	Stores the latest automatic explanation.
spam_feedback	account_id, gmail_message_id, user_marked_spam, corrected_at	Stores the user's saved correction.
blocked_senders	account_id, sender_email	Adds an account-specific classifier signal.

Spam results reference the message composite key. Feedback is scoped to the account and intentionally can survive replacement of the small message sample. Blocked senders use the account ID and normalized address as their key.

When the store analyzes a message, it loads the account's blocked senders and passes the matching state into SpamClassifier. The user's explicit feedback remains a separate record rather than being folded into the automatic score.

Automatic analysis, user correction, and blocked-sender preferences have different meanings and are stored separately. The spam result records the calculated score and explanation; feedback records the owner's later decision; a blocked sender supplies an account-specific classifier input. Keeping these concepts distinct prevents a user correction from being misrepresented as a classifier result.

5 - IMPLEMENTATION

5.12 JDBC PERSISTENCE AND TRANSACTIONS

JdbcMailStore implements the MailStore contract with prepared statements. Snapshot replacement and related record writes run in a transaction. The store upserts the message, replaces recipient and label rows, recalculates automatic spam reasons, and removes cached messages that are no longer in the current bounded snapshot.

The transaction groups the local cache update so a partial snapshot is not treated as complete. The code checks that every message belongs to the account ID passed to the store. SQL values are bound through PreparedStatement parameters rather than concatenated into user-facing query strings.

JdbcMailStore uses prepared statements for values and transaction boundaries for multi-table changes. It validates that message data belongs to the account ID being written, replaces related recipient and label rows consistently, and updates spam analysis alongside the snapshot. A failed database operation rolls back the transaction and is surfaced to the service rather than leaving a half-written sample.

5 - IMPLEMENTATION

5.13 CONFIGURATION AND DATA PROTECTION

AppConfig reads local settings and supports environment-variable overrides. The documented properties include the database URL, username, password, Gmail Desktop credentials path, and local token directory. Sensitive local config files are ignored by Git.

SETTING	EXAMPLE PROPERTY / VARIABLE	PURPOSE
Database URL	db.url / DB_URL	Select local MySQL database.
Database login	db.user, db.password / DB_USER, DB_PASSWORD	Authenticate the application to MySQL.
OAuth JSON	gmail.credentials / GMAIL_CREDENTIALS	Point to the Google Desktop OAuth file.
Token directory	gmail.tokenDir / GMAIL_TOKEN_DIR	Keep saved sign-in tokens outside source control.

The repository excludes OAuth credentials, token files, passwords, and private mail exports. Do not put these values in a report, source file, screenshot, issue, or shared GitHub commit. Use a dedicated local MySQL account with permission to access only the project database.

Configuration comes from a local properties file with supported environment-variable overrides. Database passwords, OAuth client JSON, access tokens, and message exports are excluded from Git. Users should use a dedicated local database account and should never place secrets in screenshots or report code listings. The application stores OAuth tokens separately from message data and does not persist a Gmail password.

5 - IMPLEMENTATION

5.14 ERROR HANDLING AND RESPONSIVENESS

The application surfaces errors in terms the user can act on. A missing credential path points to setup instructions. A database error points to db.url, db.user, and db.password. A provider rate limit tells the user to retry after a temporary delay. Sensitive provider payloads and password values are not included in ordinary status messages.

SwingWorker runs service operations away from the UI event thread. Controls are disabled while an operation is in flight to prevent duplicate sends, refreshes, or session changes. A failed message open clears stale details from the reader pane. A failed refresh keeps the previous signed-in state and cached sample.

Gmail read requests use bounded retry with backoff for transient responses. Sends and label changes are not automatically replayed after an error, because that could duplicate mail or repeat a mailbox change.

Errors are presented in terms that guide the next action: missing OAuth setup, denied Google access, unavailable MySQL, invalid input, or a temporary provider response. The interface retains the previous state when a refresh fails and clears stale reader content if opening a message fails. Controls are restored after background operations so a single error does not leave the application unresponsive.

5 - IMPLEMENTATION

5.15 BUILD AND WINDOWS PACKAGE

The Maven Wrapper builds the project using the JDK version declared in the project. The executable JAR uses ems.App as its production entry point. The demo has a separate launcher so the offline behavior is explicit.

The Windows packaging script creates a Windows x64 app image with jpackage and a bundled Java runtime, then prepares the shareable ZIP. Users should extract the complete ZIP before running Maildesk.exe. A live installation still needs MySQL and the user's Desktop OAuth JSON.

The packaged application does not include a private OAuth client file, local token cache, or database password.

The Maven Wrapper provides a reproducible build entry point, and the project's JDK target is recorded in its build configuration. The production launcher and demo launcher have distinct entry points. The Windows package bundles a runtime but excludes user OAuth credentials, token state, and database passwords. Setup therefore remains local to each user, and the archive must be extracted before launching.

5 - IMPLEMENTATION

5.16 VERIFICATION AND TEST PLAN

AREA	CHECKED BEHAVIOR
OAuth	Loopback callback, state validation, token parsing, timeout and error behavior.
Gmail HTTP	Request responses, parsing, MIME construction, label operations, retry boundaries.
Spam rules	Weights, explanations, threshold, and blocked-sender handling.
JDBC	Schema initialization, account isolation, transactional snapshot replacement, feedback.
Swing contract	Search, mailbox navigation, compose validation, failure state, busy controls.
MySQL	Separate opt-in local check using its own fixture account.

The repository's default verification uses local HTTP fixtures and an isolated test database. Automated tests do not send real email. A live account acceptance walkthrough is separate: configure OAuth and MySQL, connect a test account, refresh, compare the bounded sample, and inspect saved rows in MySQL Workbench.

A successful offline demo proves that the UI can be explored without external setup; it does not prove that real Gmail credentials or the local database are configured.

Verification is divided into unit-level rules, local HTTP fixtures, database-store behavior, and UI checks. Tests use controlled data and do not send mail to real recipients. A live acceptance walkthrough is a separate manual step that requires configured Google OAuth and MySQL. This distinction prevents test results from being mistaken for proof that every external account or database is already configured.

5 - IMPLEMENTATION

5.17 CURRENT LIMITATIONS AND FUTURE WORK

LIMIT TODAY	PROPOSED FOLLOW-UP
At most 18 recent unique messages are cached.	Add user-controlled pagination after measuring API quotas.
Plain-text composition only.	Add attachment preview, safe download, and richer drafts.
Deterministic rule scoring.	Evaluate tuning with a labeled, consented sample; report false positives.
One active account at a time.	Consider a carefully isolated multi-account workspace.
Manual refresh.	Explore scheduled sync and notifications with explicit controls.
Google app remains configured for testing in the student setup.	Complete applicable consent and OAuth verification before broad public use.

The project does not claim a trained AI model. Any future scoring change should preserve visible evidence, make uncertainty understandable, and keep the mailbox owner in the decision loop. Planned features should be tested with controlled data before being described as implemented.

The current design prioritizes a safe, bounded classroom demonstration. A future version should first measure API usage, improve pagination, and validate spam rules against an appropriately consented and labeled sample. Attachment scanning and richer composition require content-safety decisions. Multi-account support requires additional isolation and credential-lifecycle design. These proposals are not described as features already delivered.

6 - CONCLUSION

Maildesk combines Java Swing, object-oriented service boundaries, Gmail OAuth and REST access, MySQL, and JDBC in one email-management application. The workspace supports mailbox navigation, local search, message reading, validated plain-text composition, and explicit label actions.

The report's principal project contribution is an explainable second opinion for suspicious messages. The rule score is accompanied by reasons, and a person can correct the result. Gmail's own Spam label stays distinct from Maildesk's local review queue. The bounded 18-message sample makes the classroom demonstration predictable and manageable.

A separate offline demo provides fictional messages for presentation and interface review. The live path requires a correctly configured Desktop OAuth client and local MySQL server. The project clearly identifies limits such as attachments, rich text, scheduled synchronization, machine learning, and production OAuth approval as future work.

Through this project, the team can demonstrate how an object-oriented Java application communicates with an external provider, protects account boundaries in a relational schema, and reports user-visible reasons for a security-sensitive suggestion.

The completed work also establishes a practical base for future development. The current modules make it possible to add controlled pagination, improved message composition, or additional review signals without merging provider, database, and screen responsibilities into a single class. Any expansion should preserve the existing principle that mailbox owners can inspect and correct suspicious-message suggestions.

The implementation should be presented as a working academic desktop application with defined boundaries: the live Gmail path depends on local Google OAuth configuration and MySQL, while the screenshot and classroom demo path uses fictional in-memory data. This distinction is part of the project's correctness and is reflected throughout the report and its appendices.

7 - REFERENCES

1. Maildesk source repository, setup guide, architecture documentation, SQL schema, and Windows packaging notes. https://github.com/Sanjay-AI-ML/email-management-work

2. Google for Developers. Gmail API documentation. https://developers.google.com/workspace/gmail/api

3. Google Identity. OAuth 2.0 for native and desktop applications. https://developers.google.com/identity/protocols/oauth2/native-app

4. Google for Developers. Gmail API authorization scopes. https://developers.google.com/workspace/gmail/api/auth/scopes

5. Oracle. Java SE documentation. https://docs.oracle.com/en/java/

6. MySQL. MySQL 8.0 Reference Manual. https://dev.mysql.com/doc/refman/8.0/en/

7. Project source files: src/main/java/ems, src/main/java/com/emailapp/spam, src/demo/java, sql/schema.sql, docs/SETUP.md, and docs/ARCHITECTURE.md.

8. User-provided reference document: EMPLOYEE DETAILS AND PAYROLL MANAGEMENT SYSTEM (academic report structure used as the formatting model).

9. Oracle. Java Swing documentation. https://docs.oracle.com/javase/tutorial/uiswing/

10. Oracle. JDBC Basics. https://docs.oracle.com/javase/tutorial/jdbc/basics/

11. IETF. RFC 7636: Proof Key for Code Exchange by OAuth Public Clients. https://datatracker.ietf.org/doc/html/rfc7636

12. Google for Developers. Gmail API messages resource and users.messages methods. https://developers.google.com/workspace/gmail/api/reference/rest/v1/users.messages

13. MySQL. Connector/J Developer Guide. https://dev.mysql.com/doc/connector-j/en/

APPENDIX A — COMPLETE SOURCE CODE

This appendix reproduces the project's complete Java implementation, offline demonstration implementation, automated Java verification sources, MySQL schema, Windows helper scripts, and Maven build configuration. Source is reproduced as committed in the project, with monospace formatting added for readability. File headings are report labels and are not part of the source text.

The listing order follows the project's implementation structure: production classes first, followed by demo classes, test classes, database definition, launch and packaging scripts, and the Maven build file. Credentials, local OAuth tokens, and local database passwords are not included.

APPENDIX A.1 — PRODUCTION JAVA

src/main/java/com/emailapp/App.java

```
package com.emailapp;

/** Member 2's launcher remains an alias for the single production entry point. */
public final class App {
    private App() { }
    public static void main(String[] args) { ems.App.main(args); }
}
```

src/main/java/com/emailapp/database/BlockedSenderRepository.java

```
package com.emailapp.database;

import ems.storage.JdbcMailStore;
import java.sql.SQLException;

/** Account-scoped sender blocks used by the local classifier. */
public final class BlockedSenderRepository {
    private final JdbcMailStore store;
    public BlockedSenderRepository() { this(new JdbcMailStore()); }
    public BlockedSenderRepository(JdbcMailStore store) { this.store = store; }
    public boolean isBlocked(long accountId, String senderEmail) throws SQLException {
        return store.isSenderBlocked(accountId, senderEmail);
    }
    public void block(long accountId, String senderEmail) throws SQLException {
        store.setSenderBlocked(accountId, senderEmail, true);
    }
    public void unblock(long accountId, String senderEmail) throws SQLException {
        store.setSenderBlocked(accountId, senderEmail, false);
    }
}
```

src/main/java/com/emailapp/database/DatabaseConnection.java

```
package com.emailapp.database;

import java.sql.Connection;
import java.sql.DriverManager;
import java.sql.SQLException;

public final class DatabaseConnection {

    private DatabaseConnection() { }

    private static final String URL =
            System.getenv().getOrDefault(
                    "DB_URL",

"jdbc:mysql://localhost:3306/email_management?createDatabaseIfNotExist=true&connectionTimeZone=UTC&forceConnecti
onTimeZoneToSession=true&connectTimeout=5000&socketTimeout=15000"
            );

    private static final String USER =
```

```
            System.getenv().getOrDefault("DB_USER", "root");

    private static final String PASSWORD =
            System.getenv().getOrDefault("DB_PASSWORD", "");

    public static Connection getConnection()
            throws SQLException {

        return DriverManager.getConnection(URL, USER, PASSWORD);
    }
}
```

src/main/java/com/emailapp/database/MessageRepository.java

```
package com.emailapp.database;

import ems.model.EmailMessage;
import ems.storage.JdbcMailStore;
import java.sql.SQLException;
import java.util.List;
import java.util.Set;

/** Member 3 compatibility facade; use MailStore for application operations. */
public final class MessageRepository {
    private final JdbcMailStore store;
    public MessageRepository() { this(new JdbcMailStore()); }
    public MessageRepository(JdbcMailStore store) { this.store = store; }
    public void save(EmailMessage message) throws SQLException {
        store.saveMessages(message.getAccountId(), List.of(message));
    }
    /** Saving the full snapshot keeps recipients and labels consistent atomically. */
    public void saveRecipients(EmailMessage message) throws SQLException { save(message); }
    public void saveLabels(EmailMessage message) throws SQLException { save(message); }
    public List<EmailMessage> findByAccount(long accountId) throws SQLException { return
store.findAll(accountId); }
    public List<String> findRecipients(long accountId, String messageId) throws SQLException {
        return store.findMessage(accountId, messageId).map(EmailMessage::getRecipientEmails).orElse(List.of());
    }
    public Set<String> findLabels(long accountId, String messageId) throws SQLException {
        return store.findMessage(accountId, messageId).map(EmailMessage::getGmailLabelIds).orElse(Set.of());
    }
    public void updateReadStatus(long accountId, String messageId, boolean read) throws SQLException {
        store.updateReadStatus(accountId, messageId, read);
    }
}
```

src/main/java/com/emailapp/database/SpamFeedbackRepository.java

```
package com.emailapp.database;

import ems.storage.JdbcMailStore;
import java.sql.SQLException;

/** User corrections take precedence over automatic results across refreshes. */
public final class SpamFeedbackRepository {
    private final JdbcMailStore store;
    public SpamFeedbackRepository() { this(new JdbcMailStore()); }
    public SpamFeedbackRepository(JdbcMailStore store) { this.store = store; }
    public void saveFeedback(long accountId, String messageId, boolean spam) throws SQLException {
        store.saveFeedback(accountId, messageId, spam);
    }
}
```

src/main/java/com/emailapp/database/SpamRepository.java

```
package com.emailapp.database;

import ems.model.EmailMessage;
import ems.model.SpamResult;
import ems.storage.JdbcMailStore;
import java.sql.SQLException;

/** Compatibility facade for Member 3's original repository API. */
public final class SpamRepository {
    private final JdbcMailStore store;
    public SpamRepository() { this(new JdbcMailStore()); }
    public SpamRepository(JdbcMailStore store) { this.store = store; }
    public void save(EmailMessage message, SpamResult result) throws SQLException {
        store.saveSpamResult(message.getAccountId(), message.getGmailMessageId(), result);
    }
    public SpamResult findByMessage(long accountId, String messageId) throws SQLException {
        if (store.findMessage(accountId, messageId).isEmpty()) return null;
        return store.getSpamResult(accountId, messageId);
    }
```

```
}
```

src/main/java/com/emailapp/spam/SpamClassifier.java

```
package com.emailapp.spam;

import ems.model.EmailMessage;
import ems.model.SpamResult;
import java.util.ArrayList;
import java.util.List;
import java.util.Locale;
import java.util.regex.Pattern;

/** Explainable local rules, independent of Gmail's own SPAM classification. */
public final class SpamClassifier {
    private static final Pattern LINK = Pattern.compile("https?://\\S+", Pattern.CASE_INSENSITIVE);
    private static final List<String> PHRASES = List.of(
            "claim your prize", "verify your account", "you have won",
            "urgent action required", "click here to claim");

    public SpamResult analyze(EmailMessage message) {
        return analyze(message, false);
    }

    /** The store supplies account-specific block information within its transaction. */
    public SpamResult analyze(EmailMessage message, boolean blockedSender) {
        int score = 0;
        List<String> reasons = new ArrayList<>();
        String sender = message.getSenderEmail().trim().toLowerCase(Locale.ROOT);
        String subject = message.getSubject().toLowerCase(Locale.ROOT);
        String body = message.getBodyText().toLowerCase(Locale.ROOT);
        if (blockedSender) {
            score += SpamRules.BLOCKED_SENDER;
            reasons.add("Sender is blocked");
        }
        String content = subject + " " + body;
        int phraseMatches = 0;
        for (String phrase : PHRASES) {
            if (content.contains(phrase)) {
                score += SpamRules.SUSPICIOUS_PHRASE;
                reasons.add("Suspicious phrase: " + phrase);
                // Distinct signals accumulate; one phrase alone should not classify a message.
                if (++phraseMatches == 3) break;
            }
        }
        if (LINK.matcher(body).results().limit(5).count() >= 5) {
            score += SpamRules.MANY_LINKS;
            reasons.add("Message contains many links");
        }
        if (subject.contains("urgent") || subject.contains("act now")) {
            score += SpamRules.URGENT_SUBJECT;
            reasons.add("Urgent subject wording");
        }
        if (sender.isBlank()) reasons.add("Sender address is missing");
        return new SpamResult(score, score >= SpamRules.SPAM_THRESHOLD, reasons);
    }
}
```

src/main/java/com/emailapp/spam/SpamRules.java

```
package com.emailapp.spam;

public final class SpamRules {

    private SpamRules() {
        // Prevent object creation
    }

    public static final int BLOCKED_SENDER = 50;
    public static final int SUSPICIOUS_PHRASE = 20;
    public static final int MANY_LINKS = 15;
    public static final int URGENT_SUBJECT = 10;

    public static final int SPAM_THRESHOLD = 50;
}
```

src/main/java/ems/App.java

```
package ems;

import ems.config.AppConfig;
import ems.exception.AppException;
import ems.service.GmailEmailService;
```

```
import ems.storage.JdbcMailStore;
import ems.ui.MainFrame;
import ems.ui.UiTheme;
import java.nio.file.Files;
import java.sql.DriverManager;
import javax.swing.JOptionPane;
import javax.swing.SwingUtilities;

/** Production entry point. The demo has its own explicitly labelled launcher. */
public final class App {
    private App() { }

    public static void main(String[] args) {
        if (args.length > 0 && args[0].equals("--help")) {
            System.out.println("Maildesk - Java Gmail client\n"
                    + "Run: java -jar target/maildesk.jar\n"
                    + "Check setup: java -jar target/maildesk.jar --check-setup\n"
                    + "Configuration: config/app.properties (or DB_URL, DB_USER, DB_PASSWORD, GMAIL_CREDENTIALS,
GMAIL_TOKEN_DIR).\n"
                    + "See README.md for Google Desktop OAuth and MySQL setup.");
            return;
        }
        if (args.length > 1 || args.length == 1 && !args[0].equals("--check-setup")) {
            System.err.println("Unknown option. Use --help or --check-setup.");
            System.exit(2);
        }
        try {
            AppConfig config = AppConfig.load();
            JdbcMailStore store = new JdbcMailStore(() -> DriverManager.getConnection(
                    config.getDatabaseUrl(), config.getDatabaseUser(), config.getDatabasePassword()));
            if (args.length == 1) {
                boolean credentials = Files.isRegularFile(config.getGmailCredentialsPath());
                System.out.println("Google Desktop OAuth JSON: " + (credentials ? "found" : "missing - follow
README.md setup"));
                boolean database = false;
                try { store.initialize(); database = true; System.out.println("MySQL: connected; schema
ready."); }
                catch (java.sql.SQLException exception) {
                    System.out.println("MySQL: unavailable - check db.url, db.user and db.password in
config/app.properties.");
                }
                System.out.println("Live Gmail access also requires the user to authorize the app in their
browser.");
                if (!credentials || !database) System.exit(1);
                return;
            }
            GmailEmailService service = GmailEmailService.createDefault();
            SwingUtilities.invokeLater(() -> {
                UiTheme.install();
                new MainFrame(service).setVisible(true);
            });
        } catch (AppException | RuntimeException exception) {
            String message = exception instanceof AppException ? exception.getMessage()
                    : "Maildesk could not start. Check config/app.properties and use --check-setup.";
            System.err.println(message);
            if (args.length == 0 && !java.awt.GraphicsEnvironment.isHeadless()) {
                SwingUtilities.invokeLater(() -> JOptionPane.showMessageDialog(null, message,
                        "Maildesk setup", JOptionPane.ERROR_MESSAGE));
            }
            System.exit(1);
        }
    }
}
```

src/main/java/ems/config/AppConfig.java

```
package ems.config;

import ems.exception.AppException;
import java.io.IOException;
import java.io.Reader;
import java.nio.charset.StandardCharsets;
import java.nio.file.Files;
import java.nio.file.Path;
import java.util.Map;
import java.util.Properties;

/** Local-only configuration; environment values override an optional properties file. */
public final class AppConfig {
    private final Path home;
    private final Path configFile;
    private final Properties properties;
    private final Map<String, String> environment;

    private AppConfig(Path home, Path configFile, Properties properties, Map<String, String> environment) {
        this.home = home.toAbsolutePath().normalize();
        this.configFile = configFile.toAbsolutePath().normalize();
        this.properties = properties;
        this.environment = Map.copyOf(environment);
    }
```

```
    public static AppConfig load() throws AppException {
        return load(Path.of(System.getProperty("maildesk.home", ".")), System.getenv());
    }

    public static AppConfig load(Path home, Map<String, String> environment) throws AppException {
        Path normalized = home.toAbsolutePath().normalize();
        Path file = normalized.resolve("config/app.properties");
        Properties properties = new Properties();
        if (Files.exists(file)) {
            try (Reader reader = Files.newBufferedReader(file, StandardCharsets.UTF_8)) {
                properties.load(reader);
            } catch (IOException | IllegalArgumentException exception) {
                throw new AppException("Cannot read config/app.properties. Check the local file format and
permissions.", exception);
            }
        }
        return new AppConfig(normalized, file, properties, environment);
    }

    private String value(String environmentKey, String propertyKey, String fallback) {
        return environment.containsKey(environmentKey) ? environment.get(environmentKey)
                : properties.getProperty(propertyKey, fallback);
    }

    public String getDatabaseUrl() {
        return value("DB_URL", "db.url", "jdbc:mysql://localhost:3306/email_management"
                + "?createDatabaseIfNotExist=true&connectionTimeZone=UTC&forceConnectionTimeZoneToSession=true"
                + "&connectTimeout=5000&socketTimeout=15000").strip();
    }

    public String getDatabaseUser() { return value("DB_USER", "db.user", "root").strip(); }
    public String getDatabasePassword() { return value("DB_PASSWORD", "db.password", ""); }
    public Path getGmailCredentialsPath() {
        if (environment.containsKey("GMAIL_CREDENTIALS") || properties.containsKey("gmail.credentials")) {
            return localPath(value("GMAIL_CREDENTIALS", "gmail.credentials", "config/credentials.json"));
        }
        // Accept the filenames documented by Member 2, with the local config taking precedence.
        for (String candidate : new String[] {"config/credentials.json", "config/client_secret.json",
                "credentials.json", "client_secret.json", "client_secrets.json"}) {
            Path path = home.resolve(candidate);
            if (Files.isRegularFile(path)) return path;
        }
        return home.resolve("config/credentials.json");
    }
    public Path getTokenDirectory() {
        return localPath(value("GMAIL_TOKEN_DIR", "gmail.tokenDir", "config/tokens"));
    }
    public Path getConfigFile() { return configFile; }
    public Path getHome() { return home; }

    private Path localPath(String value) {
        Path path = Path.of(value.strip());
        return (path.isAbsolute() ? path : home.resolve(path)).normalize();
    }
}
```

src/main/java/ems/exception/AppException.java

```
package ems.exception;

/** A recoverable application failure whose message can be displayed to the user. */
public class AppException extends Exception {
    private static final long serialVersionUID = 1L;

    public AppException(String message) {
        super(message);
    }

    public AppException(String message, Throwable cause) {
        super(message, cause);
    }
}
```

src/main/java/ems/gmail/AccessTokenProvider.java

```
package ems.gmail;

import ems.exception.AppException;

/** Separates authorization from HTTP mailbox operations and permits local-server tests. */
public interface AccessTokenProvider {
    void authorize() throws AppException;
    String accessToken() throws AppException;
    String refreshAccessToken() throws AppException;
    void disconnect();
}
```

src/main/java/ems/gmail/GmailApiClient.java

```
package ems.gmail;

import com.google.gson.Gson;
import com.google.gson.JsonObject;
import com.google.gson.JsonParser;
import ems.exception.AppException;
import ems.model.EmailMessage;
import java.io.IOException;
import java.net.URI;
import java.net.URLEncoder;
import java.net.http.HttpClient;
import java.net.http.HttpRequest;
import java.net.http.HttpResponse;
import java.nio.charset.StandardCharsets;
import java.nio.file.Path;
import java.time.Duration;
import java.time.Instant;
import java.util.ArrayList;
import java.util.HashSet;
import java.util.LinkedHashSet;
import java.util.List;
import java.util.Set;

/** Gmail REST client using an OAuth desktop session and standards-compliant MIME messages. */
public final class GmailApiClient implements GmailGateway {
    private static final URI GOOGLE_API = URI.create("https://gmail.googleapis.com/gmail/v1/users/me/");
    private static final Gson JSON = new Gson();
    private final URI baseUri;
    private final HttpClient http;
    private final AccessTokenProvider tokens;
    private final RetryDelay retryDelay;

    public GmailApiClient(Path credentialsFile, Path tokenDirectory) {
        this(GOOGLE_API, HttpClient.newBuilder().connectTimeout(Duration.ofSeconds(20)).build(),
                new GmailAuth(credentialsFile, tokenDirectory));
    }

    /** The injected endpoint and token provider support deterministic local HTTP tests. */
    public GmailApiClient(URI baseUri, HttpClient http, AccessTokenProvider tokens) {
        this(baseUri, http, tokens, Thread::sleep);
    }

    GmailApiClient(URI baseUri, HttpClient http, AccessTokenProvider tokens, RetryDelay retryDelay) {
        if (!baseUri.toString().endsWith("/")) {
            throw new IllegalArgumentException("Gmail API base URI must end with '/'.");
        }
        this.baseUri = baseUri;
        this.http = http;
        this.tokens = tokens;
        this.retryDelay = retryDelay;
    }

    @Override public String connect() throws AppException {
        tokens.authorize();
        JsonObject profile = request("GET", "profile", null);
        return requiredString(profile, "emailAddress");
    }

    @Override public List<EmailMessage> fetchMessages(long accountId) throws AppException {
        Set<String> ids = new LinkedHashSet<>();
        Set<String> pageTokens = new HashSet<>();
        String pageToken = "";
        do {
            String path = "messages?maxResults=500&includeSpamTrash=true&q="
                    + encode("-in:trash -in:drafts");
            if (!pageToken.isEmpty()) path += "&pageToken=" + encode(pageToken);
            JsonObject page = request("GET", path, null);
            try {
                if (page.has("messages")) {
                    for (var value : page.getAsJsonArray("messages")) {
                        ids.add(requiredString(value.getAsJsonObject(), "id"));
                    }
                }
                pageToken = page.has("nextPageToken") ? requiredString(page, "nextPageToken") : "";
            } catch (RuntimeException malformedPage) {
                throw new AppException("Gmail returned an unreadable mailbox page. Please refresh again.",
malformedPage);
            }
            if (!pageToken.isEmpty() && !pageTokens.add(pageToken)) {
                throw new AppException("Gmail repeated a mailbox page. Please refresh again.");
            }
        } while (!pageToken.isEmpty());
        return readMessages(accountId, ids);
    }

    /** Bounded startup window; never presented as a complete mailbox snapshot. */
```

```
    @Override public List<EmailMessage> fetchRecentMessages(long accountId, int perMailbox) throws AppException
{
        int limit = Math.max(1, Math.min(perMailbox, 100));
        Set<String> ids = new LinkedHashSet<>();
        for (String label : List.of("INBOX", "SENT", "SPAM")) {
            JsonObject page = request("GET", "messages?maxResults=" + limit
                    + "&includeSpamTrash=true&labelIds=" + label + "&q=" + encode("-in:trash -in:drafts"),
null);
            try {
                if (page.has("messages")) {
                    int count = 0;
                    for (var item : page.getAsJsonArray("messages")) {
                        if (count++ >= limit) break;
                        ids.add(requiredString(item.getAsJsonObject(), "id"));
                    }
                }
            } catch (RuntimeException malformedPage) {
                throw new AppException("Gmail returned an unreadable recent-mail page. Click Refresh to try
again.", malformedPage);
            }
        }
        return readMessages(accountId, ids);
    }

    private List<EmailMessage> readMessages(long accountId, Set<String> ids) throws AppException {
        List<EmailMessage> result = new ArrayList<>();
        for (String id : ids) {
            try {
                result.add(getMessage(accountId, id));
            } catch (MessageUnavailableException deletedDuringSync) {
                // A message can disappear between the list and get calls.
            }
        }
        return result;
    }

    @Override public EmailMessage getMessage(long accountId, String id) throws AppException {
        JsonObject message = request("GET", "messages/" + messageId(id) + "?format=raw", null);
        Set<String> labels = new HashSet<>();
        try {
            if (message.has("labelIds")) {
                for (var label : message.getAsJsonArray("labelIds")) labels.add(label.getAsString());
            }
        } catch (RuntimeException malformedLabels) {
            throw new AppException("Gmail returned unreadable message labels. Please refresh again.",
malformedLabels);
        }
        String raw = requiredString(message, "raw");
        Instant received = null;
        if (message.has("internalDate")) {
            try { received = Instant.ofEpochMilli(message.get("internalDate").getAsLong()); }
            catch (RuntimeException invalidDate) {
                throw new AppException("Gmail returned an invalid message date.", invalidDate);
            }
        }
        return MimeMessages.parse(accountId, id, raw, received, labels);
    }

    @Override public String sendMessage(String senderEmail, String recipientEmail, String subject,
            String body) throws AppException {
        JsonObject message = new JsonObject();
        message.addProperty("raw", MimeMessages.compose(senderEmail, recipientEmail, subject, body));
        JsonObject response = request("POST", "messages/send", message);
        try {
            return requiredString(response, "id");
        } catch (AppException incompleteSendResponse) {
            throw new AppException("Gmail accepted the send request but returned no message ID. "
                    + "Check Sent before sending again.");
        }
    }

    @Override public void setRead(String id) throws AppException {
        modify(id, Set.of(), Set.of("UNREAD"));
    }

    @Override public void setSpam(String id, boolean spam) throws AppException {
        modify(id, spam ? Set.of("SPAM") : Set.of("INBOX"),
                spam ? Set.of("INBOX") : Set.of("SPAM"));
    }

    private void modify(String id, Set<String> add, Set<String> remove) throws AppException {
        JsonObject body = new JsonObject();
        body.add("addLabelIds", JSON.toJsonTree(add));
        body.add("removeLabelIds", JSON.toJsonTree(remove));
        request("POST", "messages/" + messageId(id) + "/modify", body);
    }

    @Override public void disconnect() { tokens.disconnect(); }

    private JsonObject request(String method, String path, JsonObject body) throws AppException {
        boolean sending = "POST".equals(method) && path.equals("messages/send");
        boolean refreshed = false;
        int retries = 0;
```

```
        while (true) {
            String token = tokens.accessToken();
            HttpRequest.Builder builder = HttpRequest.newBuilder(baseUri.resolve(path))
                    .timeout(Duration.ofSeconds(60))
                    .header("Authorization", "Bearer " + token)
                    .header("Accept", "application/json");
            if (body == null) builder.GET();
            else builder.header("Content-Type", "application/json; charset=UTF-8")
                    .method(method, HttpRequest.BodyPublishers.ofString(JSON.toJson(body)));
            try {
                HttpResponse<String> response = http.send(builder.build(),
                        HttpResponse.BodyHandlers.ofString(StandardCharsets.UTF_8));
                int status = response.statusCode();
                if (status == 401 && !refreshed) {
                    tokens.refreshAccessToken();
                    refreshed = true;
                    continue;
                }
                if (status < 200 || status >= 300) {
                    Set<String> reasons = errorReasons(response.body());
                    if (method.equals("GET") && retries < 6 && transientFailure(status, reasons)) {
                        retryDelay.pause(1000L << retries++);
                        continue;
                    }
                    if (sending && status >= 500) {
                        throw new AppException("Could not confirm delivery. Check Gmail Sent before retrying.");
                    }
                    throw apiFailure(status, reasons);
                }
                if (response.body().isBlank()) return new JsonObject();
                return JsonParser.parseString(response.body()).getAsJsonObject();
            } catch (IOException e) {
                throw new AppException(sending
                        ? "Could not confirm delivery. Check Gmail Sent before retrying."
                        : "Could not reach Gmail. Check your internet connection and try again.", e);
            } catch (InterruptedException e) {
                Thread.currentThread().interrupt();
                throw new AppException(sending
                        ? "Could not confirm delivery. Check Gmail Sent before retrying."
                        : "The Gmail operation was interrupted.", e);
            } catch (RuntimeException e) {
                throw new AppException(sending
                        ? "Could not confirm delivery. Check Gmail Sent before retrying."
                        : "Gmail returned an unreadable response. Please try again.", e);
            }
        }
    }

    private static boolean transientFailure(int status, Set<String> reasons) {
        return status == 429 || status == 500 || status == 502 || status == 503 || status == 504
                || status == 403 && (reasons.contains("rateLimitExceeded")
                || reasons.contains("userRateLimitExceeded"));
    }

    /** Read only machine error codes; never echo Google's response or account details. */
    private static Set<String> errorReasons(String body) {
        Set<String> result = new HashSet<>();
        try {
            JsonObject error = JsonParser.parseString(body).getAsJsonObject().getAsJsonObject("error");
            for (String field : List.of("errors", "details")) {
                if (error != null && error.has(field) && error.get(field).isJsonArray()) {
                    for (var item : error.getAsJsonArray(field)) {
                        if (item.isJsonObject() && item.getAsJsonObject().has("reason")) {
                            result.add(item.getAsJsonObject().get("reason").getAsString());
                        }
                    }
                }
            }
        } catch (RuntimeException ignored) { /* Fall back to a safe HTTP-status explanation. */ }
        return result;
    }

    private static AppException apiFailure(int status, Set<String> reasons) {
        if (status == 403) {
            if (reasons.contains("dailyLimitExceeded") || reasons.contains("quotaExceeded")) {
                return new AppException("The Google Cloud project's Gmail API quota is exhausted. "
                        + "Check Gmail API quotas in Google Cloud or wait for the quota to reset.");
            }
            if (transientFailure(status, reasons)) {
                return new AppException("Gmail temporarily limited requests. Your sign-in is still valid. "
                        + "Wait a moment, then click Refresh.");
            }
            if (reasons.contains("domainPolicy")) {
                return new AppException("Your Google Workspace administrator blocks Gmail access for this app. "
                        + "Ask your administrator to allow it.");
            }
            if (reasons.contains("insufficientPermissions") ||
reasons.contains("ACCESS_TOKEN_SCOPE_INSUFFICIENT")) {
                return new AppException("The Google sign-in did not grant the required Gmail permission. "
                        + "Disconnect, connect again, and allow Maildesk to manage Gmail.");
            }
        }
        return switch (status) {
            case 401 -> new AppException("Gmail authorization expired. Disconnect and connect again.");
            case 403 -> new AppException("Gmail denied access. Enable the Gmail API in your Google Cloud "
                    + "project, add your account as a test user, and grant Gmail permissions when connecting.");
```

```
            case 404 -> new MessageUnavailableException();
            case 429 -> new AppException("Gmail's request limit was reached. Wait a moment and refresh again.");
            default -> new AppException("Gmail could not complete the request (HTTP " + status + "). Please try
again.");
        };
    }

    @FunctionalInterface interface RetryDelay { void pause(long milliseconds) throws InterruptedException; }

    private static String messageId(String id) throws AppException {
        if (id == null || !id.matches("[A-Za-z0-9_-]+")) throw new AppException("Invalid Gmail message ID.");
        return id;
    }

    private static String encode(String value) {
        return URLEncoder.encode(value, StandardCharsets.UTF_8);
    }

    private static String requiredString(JsonObject object, String key) throws AppException {
        if (!object.has(key) || !object.get(key).isJsonPrimitive()
                || !object.get(key).getAsJsonPrimitive().isString()
                || object.get(key).getAsString().isBlank()) {
            throw new AppException("Gmail returned an incomplete response. Please refresh again.");
        }
        return object.get(key).getAsString();
    }

    private static final class MessageUnavailableException extends AppException {
        private static final long serialVersionUID = 1L;
        private MessageUnavailableException() { super("This message is no longer available in Gmail. Refresh the
mailbox."); }
    }
}
```

src/main/java/ems/gmail/GmailAuth.java

```
package ems.gmail;

import com.google.gson.JsonObject;
import com.google.gson.JsonParser;
import com.sun.net.httpserver.HttpExchange;
import com.sun.net.httpserver.HttpServer;
import ems.exception.AppException;
import java.awt.Desktop;
import java.io.IOException;
import java.net.InetSocketAddress;
import java.net.URI;
import java.net.URLDecoder;
import java.net.URLEncoder;
import java.net.http.HttpClient;
import java.net.http.HttpRequest;
import java.net.http.HttpResponse;
import java.nio.charset.StandardCharsets;
import java.nio.file.Files;
import java.nio.file.Path;
import java.security.MessageDigest;
import java.security.SecureRandom;
import java.time.Duration;
import java.time.Instant;
import java.util.Base64;
import java.util.LinkedHashMap;
import java.util.Map;
import java.util.concurrent.CompletableFuture;
import java.util.concurrent.ExecutionException;
import java.util.concurrent.TimeUnit;
import java.util.concurrent.TimeoutException;

/** OAuth Authorization Code + PKCE using the system browser and a loopback-only callback. */
public final class GmailAuth implements AccessTokenProvider {
    static final String SCOPE = "https://www.googleapis.com/auth/gmail.modify";
    private static final URI GOOGLE_AUTHORIZE = URI.create("https://accounts.google.com/o/oauth2/v2/auth");
    private static final URI GOOGLE_TOKEN = URI.create("https://oauth2.googleapis.com/token");
    private final Path credentialsFile;
    private final TokenStore store;
    private final HttpClient http;
    private final URI authorizeEndpoint;
    private final URI tokenEndpoint;
    private final BrowserOpener browser;
    private final Duration timeout;
    private String clientId;
    private String clientSecret;
    private String accessToken;
    private String refreshToken;
    private Instant expiresAt = Instant.EPOCH;
    private boolean ignoreSavedTokens;

    public GmailAuth(Path credentialsFile, Path tokenDirectory) {
        this(credentialsFile, tokenDirectory,
                HttpClient.newBuilder().connectTimeout(Duration.ofSeconds(20)).build(),
                GOOGLE_AUTHORIZE, GOOGLE_TOKEN, GmailAuth::openBrowser, Duration.ofMinutes(3));
```

```
    }

    GmailAuth(Path credentialsFile, Path tokenDirectory, HttpClient http,
            URI authorizeEndpoint, URI tokenEndpoint, BrowserOpener browser, Duration timeout) {
        this.credentialsFile = credentialsFile;
        this.store = new TokenStore(tokenDirectory);
        this.http = http;
        this.authorizeEndpoint = authorizeEndpoint;
        this.tokenEndpoint = tokenEndpoint;
        this.browser = browser;
        this.timeout = timeout;
    }

    @Override public synchronized void authorize() throws AppException {
        readCredentials();
        if (accessToken != null && !expiresAt.isBefore(Instant.now().plusSeconds(60))) return;
        if (!ignoreSavedTokens && accessToken == null) loadTokens();
        if (accessToken != null && !expiresAt.isBefore(Instant.now().plusSeconds(60))) return;
        if (refreshToken != null) {
            try {
                refreshAccessToken();
                return;
            } catch (AuthorizationExpired expired) {
                // Revoked/expired grants require a new explicit authorization in the browser.
            }
        }
        authorizeInBrowser();
    }

    @Override public synchronized String accessToken() throws AppException {
        if (accessToken == null) throw new AppException("Connect a Gmail account first.");
        if (expiresAt.isBefore(Instant.now().plusSeconds(60))) return refreshAccessToken();
        return accessToken;
    }

    @Override public synchronized String refreshAccessToken() throws AppException {
        if (refreshToken == null) {
            forgetTokens();
            throw new AuthorizationExpired();
        }
        Map<String, String> form = clientFields();
        form.put("grant_type", "refresh_token");
        form.put("refresh_token", refreshToken);
        applyTokens(exchangeToken(form));
        return accessToken;
    }

    @Override public synchronized void disconnect() { forgetTokens(); }

    private void readCredentials() throws AppException {
        if (!Files.isRegularFile(credentialsFile)) {
            throw new AppException("Gmail setup is required. Enable the Gmail API, create a Desktop app "
                    + "OAuth client in Google Cloud, and save its downloaded JSON as "
                    + credentialsFile.toAbsolutePath() + ". See README.md for setup steps.");
        }
        try {
            JsonObject root = JsonParser.parseString(Files.readString(credentialsFile,
                    StandardCharsets.UTF_8)).getAsJsonObject();
            if (!root.has("installed")) {
                throw new AppException("Use Google OAuth credentials for a Desktop app, not a Web
application.");
            }
            JsonObject installed = root.getAsJsonObject("installed");
            clientId = installed.get("client_id").getAsString();
            clientSecret = installed.has("client_secret") ? installed.get("client_secret").getAsString() : "";
            if (clientId.isBlank()) throw new IllegalArgumentException("Missing client ID");
        } catch (AppException e) {
            throw e;
        } catch (IOException | RuntimeException e) {
            throw new AppException("The Gmail credentials file could not be read. Download new Desktop app
credentials.", e);
        }
    }

    private void loadTokens() throws AppException {
        try {
            JsonObject data = store.load();
            if (data == null || !clientId.equals(string(data, "client_id"))) return;
            accessToken = string(data, "access_token");
            refreshToken = string(data, "refresh_token");
            expiresAt = data.has("expires_at") ? Instant.ofEpochMilli(data.get("expires_at").getAsLong())
                    : Instant.EPOCH;
        } catch (IOException | RuntimeException e) {
            throw new AppException("Could not read the protected Gmail sign-in cache. Check permissions on the
token directory.", e);
        }
    }

    private void authorizeInBrowser() throws AppException {
        HttpServer server = null;
        try {
            String state = randomToken();
            String verifier = randomToken();
```

```
            String challenge = Base64.getUrlEncoder().withoutPadding().encodeToString(
                    MessageDigest.getInstance("SHA-256").digest(verifier.getBytes(StandardCharsets.US_ASCII)));
            server = HttpServer.create(new InetSocketAddress("127.0.0.1", 0), 0);
            URI redirect = URI.create("http://127.0.0.1:" + server.getAddress().getPort() + "/oauth2callback");
            CompletableFuture<String> code = new CompletableFuture<>();
            server.createContext("/oauth2callback", exchange -> handleCallback(exchange, state, code));
            server.start();
            Map<String, String> form = new LinkedHashMap<>();
            form.put("client_id", clientId);
            form.put("redirect_uri", redirect.toString());
            form.put("response_type", "code");
            form.put("scope", SCOPE);
            form.put("access_type", "offline");
            form.put("prompt", "consent select_account");
            form.put("state", state);
            form.put("code_challenge", challenge);
            form.put("code_challenge_method", "S256");
            browser.open(URI.create(authorizeEndpoint + "?" + formEncode(form)));
            String authCode = code.get(timeout.toMillis(), TimeUnit.MILLISECONDS);
            Map<String, String> tokenForm = clientFields();
            tokenForm.put("grant_type", "authorization_code");
            tokenForm.put("code", authCode);
            tokenForm.put("redirect_uri", redirect.toString());
            tokenForm.put("code_verifier", verifier);
            applyTokens(exchangeToken(tokenForm));
        } catch (AppException e) {
            throw e;
        } catch (TimeoutException e) {
            throw new AppException("Google sign-in timed out. Click Connect Gmail and complete sign-in within
three minutes.", e);
        } catch (ExecutionException e) {
            if (e.getCause() instanceof AppException app) throw app;
            throw new AppException("Google sign-in could not be completed. Please try again.", e);
        } catch (InterruptedException e) {
            Thread.currentThread().interrupt();
            throw new AppException("Google sign-in was interrupted.", e);
        } catch (Exception e) {
            throw new AppException("Could not open Google sign-in. Check that a default web browser is available
"
                    + "and local loopback connections are allowed.", e);
        } finally {
            if (server != null) server.stop(0);
        }
    }

    private static void handleCallback(HttpExchange exchange, String state, CompletableFuture<String> result)
            throws IOException {
        int status = 400;
        String message = "Invalid sign-in response. Return to the application and try again.";
        String authorizationCode = null;
        AppException authorizationFailure = null;
        try {
            Map<String, String> query = parseQuery(exchange.getRequestURI().getRawQuery());
            String returnedState = query.getOrDefault("state", "");
            boolean valid = exchange.getRequestMethod().equals("GET")
                    && exchange.getRequestURI().getPath().equals("/oauth2callback")
                    && MessageDigest.isEqual(state.getBytes(StandardCharsets.UTF_8),
                            returnedState.getBytes(StandardCharsets.UTF_8));
            if (valid && query.containsKey("error")) {
                authorizationFailure = new AppException("Google sign-in was cancelled or access was denied.");
                message = "Sign-in was not completed. You can close this tab and return to the application.";
            } else if (valid && !query.getOrDefault("code", "").isBlank()) {
                status = 200;
                message = "Authorization received. You can close this tab and return to the application.";
                authorizationCode = query.get("code");
            }
        } catch (IllegalArgumentException malformedQuery) {
            // Reject malformed callbacks without revealing query data or cancelling a legitimate response.
        }
        byte[] page = ("<!doctype html><html><head><meta charset='utf-8'><title>Gmail connection</title>"
                + "</head><body><p>" + message + "</p></body></html>").getBytes(StandardCharsets.UTF_8);
        exchange.getResponseHeaders().set("Content-Type", "text/html; charset=UTF-8");
        exchange.getResponseHeaders().set("Cache-Control", "no-store");
        exchange.getResponseHeaders().set("Content-Security-Policy", "default-src 'none'");
        try {
            exchange.sendResponseHeaders(status, page.length);
            try (var output = exchange.getResponseBody()) { output.write(page); }
        } finally {
            // Complete only after the browser response is written; otherwise a fast denial
            // can stop the listener while it is still displaying the return-to-app page.
            if (authorizationCode != null) result.complete(authorizationCode);
            else if (authorizationFailure != null) result.completeExceptionally(authorizationFailure);
        }
    }

    private JsonObject exchangeToken(Map<String, String> form) throws AppException {
        HttpRequest request = HttpRequest.newBuilder(tokenEndpoint).timeout(Duration.ofSeconds(45))
                .header("Content-Type", "application/x-www-form-urlencoded")
                .POST(HttpRequest.BodyPublishers.ofString(formEncode(form))).build();
        try {
            HttpResponse<String> response = http.send(request,
                    HttpResponse.BodyHandlers.ofString(StandardCharsets.UTF_8));
            if (response.statusCode() < 200 || response.statusCode() >= 300) {
                if (response.body().contains("invalid_grant")) {
                    forgetTokens();
                    throw new AuthorizationExpired();
```

```
                }
                throw new AppException("Google could not authorize Gmail (HTTP " + response.statusCode()
                        + "). Check your OAuth client configuration and test-user access.");
            }
            return JsonParser.parseString(response.body()).getAsJsonObject();
        } catch (IOException e) {
            throw new AppException("Could not reach Google's sign-in server. Check your internet connection.",
e);
        } catch (InterruptedException e) {
            Thread.currentThread().interrupt();
            throw new AppException("Google sign-in was interrupted.", e);
        } catch (RuntimeException e) {
            throw new AppException("Google returned an unreadable sign-in response.", e);
        }
    }

    private void applyTokens(JsonObject data) throws AppException {
        try {
            String newToken = string(data, "access_token");
            if (newToken == null || newToken.isBlank()) throw new IllegalArgumentException("Missing token");
            if (data.has("scope") && !java.util.Arrays.asList(data.get("scope").getAsString().split(" "))
                    .contains(SCOPE)) {
                throw new AppException("Gmail permission was not granted. Connect again and allow Gmail
access.");
            }
            accessToken = newToken;
            String newRefresh = string(data, "refresh_token");
            if (newRefresh != null && !newRefresh.isBlank()) refreshToken = newRefresh;
            long expires = data.has("expires_in") ? data.get("expires_in").getAsLong() : 3600;
            expiresAt = Instant.now().plusSeconds(Math.max(1, expires));
            JsonObject cache = new JsonObject();
            cache.addProperty("client_id", clientId);
            cache.addProperty("access_token", accessToken);
            if (refreshToken != null) cache.addProperty("refresh_token", refreshToken);
            cache.addProperty("expires_at", expiresAt.toEpochMilli());
            store.save(cache);
            ignoreSavedTokens = false;
        } catch (AppException e) {
            throw e;
        } catch (IOException e) {
            throw new AppException("Gmail authorized, but the protected sign-in cache could not be saved. "
                    + "Check permissions on the token directory.", e);
        } catch (RuntimeException e) {
            throw new AppException("Google returned incomplete sign-in credentials. Connect again.", e);
        }
    }

    private Map<String, String> clientFields() {
        Map<String, String> form = new LinkedHashMap<>();
        form.put("client_id", clientId);
        if (clientSecret != null && !clientSecret.isBlank()) form.put("client_secret", clientSecret);
        return form;
    }

    private void forgetTokens() {
        accessToken = null;
        refreshToken = null;
        expiresAt = Instant.EPOCH;
        ignoreSavedTokens = true;
        try { store.clear(); } catch (IOException ignored) {
            // The current process will never reuse a cache after disconnect, even if deletion fails.
        }
    }

    static Map<String, String> parseQuery(String query) {
        Map<String, String> values = new LinkedHashMap<>();
        if (query == null || query.isEmpty()) return values;
        for (String pair : query.split("&")) {
            String[] parts = pair.split("=", 2);
            String key = URLDecoder.decode(parts[0], StandardCharsets.UTF_8);
            String value = URLDecoder.decode(parts.length == 2 ? parts[1] : "", StandardCharsets.UTF_8);
            if (values.putIfAbsent(key, value) != null) throw new IllegalArgumentException("Duplicate
parameter");
        }
        return values;
    }

    static String formEncode(Map<String, String> form) {
        return form.entrySet().stream().map(entry -> URLEncoder.encode(entry.getKey(), StandardCharsets.UTF_8)
                + "=" + URLEncoder.encode(entry.getValue(), StandardCharsets.UTF_8))
                .collect(java.util.stream.Collectors.joining("&"));
    }

    private static String string(JsonObject object, String key) {
        return object.has(key) && !object.get(key).isJsonNull() ? object.get(key).getAsString() : null;
    }

    private static String randomToken() {
        byte[] bytes = new byte[32];
        new SecureRandom().nextBytes(bytes);
        return Base64.getUrlEncoder().withoutPadding().encodeToString(bytes);
    }
```

```
    private static void openBrowser(URI uri) throws IOException {
        if (!Desktop.isDesktopSupported() || !Desktop.getDesktop().isSupported(Desktop.Action.BROWSE)) {
            throw new IOException("No default browser is available.");
        }
        Desktop.getDesktop().browse(uri);
    }

    @FunctionalInterface
    interface BrowserOpener { void open(URI uri) throws Exception; }

    private static final class AuthorizationExpired extends AppException {
        private static final long serialVersionUID = 1L;
        private AuthorizationExpired() { super("Gmail authorization expired or was revoked. Connect Gmail
again."); }
    }
}
```

src/main/java/ems/gmail/GmailGateway.java

```
package ems.gmail;

import ems.exception.AppException;
import ems.model.EmailMessage;
import java.util.List;

/** Remote Gmail operations. Implementations must not expose tokens in errors. */
public interface GmailGateway {
    String connect() throws AppException;
    List<EmailMessage> fetchMessages(long accountId) throws AppException;
    default List<EmailMessage> fetchRecentMessages(long accountId, int perMailbox) throws AppException {
        return fetchMessages(accountId);
    }
    EmailMessage getMessage(long accountId, String gmailMessageId) throws AppException;
    String sendMessage(String senderEmail, String recipientEmail, String subject, String body)
            throws AppException;
    void setRead(String gmailMessageId) throws AppException;
    void setSpam(String gmailMessageId, boolean spam) throws AppException;
    void disconnect();
}
```

src/main/java/ems/gmail/MimeMessages.java

```
package ems.gmail;

import ems.exception.AppException;
import ems.model.EmailMessage;
import jakarta.mail.Address;
import jakarta.mail.Message;
import jakarta.mail.Multipart;
import jakarta.mail.Part;
import jakarta.mail.Session;
import jakarta.mail.internet.InternetAddress;
import jakarta.mail.internet.MimeMessage;
import java.io.ByteArrayInputStream;
import java.io.ByteArrayOutputStream;
import java.io.IOException;
import java.io.StringReader;
import java.nio.charset.StandardCharsets;
import java.time.Instant;
import java.util.ArrayList;
import java.util.Base64;
import java.util.Date;
import java.util.List;
import java.util.Properties;
import java.util.Set;
import javax.swing.text.MutableAttributeSet;
import javax.swing.text.html.HTML;
import javax.swing.text.html.HTMLEditorKit;
import javax.swing.text.html.parser.ParserDelegator;

/** RFC 822/MIME conversion. HTML is converted to inert text, never rendered or fetched. */
final class MimeMessages {
    private MimeMessages() {}

    static EmailMessage parse(long accountId, String id, String raw, Instant received,
            Set<String> labels) throws AppException {
        try {
            byte[] bytes = Base64.getUrlDecoder().decode(raw);
            MimeMessage mime = new MimeMessage(Session.getInstance(new Properties()),
                    new ByteArrayInputStream(bytes));
            Address[] from = mime.getFrom();
            String sender = from == null || from.length == 0 ? "" : address(from[0]);
            List<String> recipients = new ArrayList<>();
            Address[] allRecipients = mime.getAllRecipients();
            if (allRecipients != null) {
                for (Address recipient : allRecipients) recipients.add(address(recipient));
            }
            Date sentDate = mime.getSentDate();
```

```
        Instant date = received != null ? received
                : sentDate == null ? Instant.EPOCH : sentDate.toInstant();
        return new EmailMessage(accountId, id, sender, recipients,
                mime.getSubject() == null ? "" : mime.getSubject(),
                readText(mime, 0), date, labels);
    } catch (Exception e) {
        throw new AppException("Gmail returned a message that could not be read.", e);
    }
}

static String compose(String sender, String recipient, String subject, String body)
        throws AppException {
    try {
        MimeMessage mime = new MimeMessage(Session.getInstance(new Properties()));
        mime.setFrom(validAddress(sender));
        mime.setRecipient(Message.RecipientType.TO, validAddress(recipient));
        if (subject == null || subject.contains("\r") || subject.contains("\n")) {
            throw new AppException("The subject must be a single line.");
        }
        mime.setSubject(subject, StandardCharsets.UTF_8.name());
        mime.setText(body == null ? "" : body, StandardCharsets.UTF_8.name());
        mime.setSentDate(new Date());
        mime.saveChanges();
        ByteArrayOutputStream bytes = new ByteArrayOutputStream();
        mime.writeTo(bytes);
        return Base64.getUrlEncoder().withoutPadding().encodeToString(bytes.toByteArray());
    } catch (AppException e) {
        throw e;
    } catch (Exception e) {
        throw new AppException("Enter a valid sender and recipient email address.", e);
    }
}

private static InternetAddress validAddress(String value) throws Exception {
    if (value == null || value.contains("\r") || value.contains("\n")) {
        throw new AppException("Enter one valid recipient email address.");
    }
    InternetAddress[] addresses = InternetAddress.parse(value, true);
    if (addresses.length != 1) throw new AppException("Enter one recipient email address.");
    addresses[0].validate();
    return addresses[0];
}

private static String address(Address address) {
    return address instanceof InternetAddress internet ? internet.getAddress() : address.toString();
}

private static String readText(Part part, int depth) throws Exception {
    if (depth > 30 || Part.ATTACHMENT.equalsIgnoreCase(part.getDisposition())
            || (part.getFileName() != null && !part.getFileName().isBlank())) return "";
    if (part.isMimeType("text/plain")) return contentString(part);
    if (part.isMimeType("text/html")) return htmlToText(contentString(part));
    if (part.isMimeType("multipart/*")) {
        Multipart multi = (Multipart) part.getContent();
        // Prefer the text/plain alternative instead of displaying duplicate HTML text.
        if (part.isMimeType("multipart/alternative")) {
            String fallback = "";
            for (int i = 0; i < multi.getCount(); i++) {
                Part child = multi.getBodyPart(i);
                String text = readText(child, depth + 1);
                if (child.isMimeType("text/plain") && !text.isBlank()) return text;
                if (!text.isBlank()) fallback = text;
            }
            return fallback;
        }
        List<String> pieces = new ArrayList<>();
        for (int i = 0; i < multi.getCount(); i++) {
            String text = readText(multi.getBodyPart(i), depth + 1);
            if (!text.isBlank()) pieces.add(text);
        }
        return String.join("\n\n", pieces);
    }
    return "";
}

private static String contentString(Part part) throws Exception {
    Object content = part.getContent();
    return content instanceof String text ? text : "";
}

private static String htmlToText(String html) throws IOException {
    StringBuilder text = new StringBuilder();
    new ParserDelegator().parse(new StringReader(html), new HTMLEditorKit.ParserCallback() {
        private int hiddenDepth;
        @Override public void handleStartTag(HTML.Tag tag, MutableAttributeSet attrs, int pos) {
            if (tag == HTML.Tag.SCRIPT || tag == HTML.Tag.STYLE) hiddenDepth++;
            if (hiddenDepth == 0 && tag.isBlock()) newline();
        }
        @Override public void handleEndTag(HTML.Tag tag, int pos) {
            if (tag == HTML.Tag.SCRIPT || tag == HTML.Tag.STYLE) {
                hiddenDepth = Math.max(0, hiddenDepth - 1);
            }
            if (hiddenDepth == 0 && tag.isBlock()) newline();
        }
```

```
            @Override public void handleSimpleTag(HTML.Tag tag, MutableAttributeSet attrs, int pos) {
                if (tag == HTML.Tag.BR) newline();
            }
            @Override public void handleText(char[] data, int pos) {
                if (hiddenDepth == 0) text.append(data);
            }
            private void newline() {
                if (text.length() > 0 && text.charAt(text.length() - 1) != '\n') text.append('\n');
            }
        }, true);
        return text.toString().strip();
    }
}
```

src/main/java/ems/gmail/SimpleJson.java

```
package ems.gmail;

import com.google.gson.Gson;
import com.google.gson.GsonBuilder;
import com.google.gson.Strictness;
import com.google.gson.ToNumberPolicy;
import java.util.LinkedHashMap;
import java.util.List;
import java.util.Map;

/**
 * Member 2 JSON helper API backed by the project's strict JSON parser.
 * Parses JSON into Java Maps, Lists, Strings, Numbers, and Booleans.
 */
public final class SimpleJson {
    private static final Gson JSON = new GsonBuilder().setStrictness(Strictness.STRICT)
            .setObjectToNumberStrategy(ToNumberPolicy.LONG_OR_DOUBLE).create();

    private SimpleJson() {
    }

    @SuppressWarnings("unchecked")
    public static Map<String, Object> parseObject(String json) {
        Object result = parse(json);
        if (result instanceof Map<?, ?> map) {
            return (Map<String, Object>) map;
        }
        return new LinkedHashMap<>();
    }

    public static Object parse(String json) {
        if (json == null || json.isBlank()) return null;
        return JSON.fromJson(json, Object.class);
    }

    public static String getString(Map<String, Object> map, String key) {
        if (map == null) return null;
        Object val = map.get(key);
        return val != null ? val.toString() : null;
    }

    public static String getStringOrDefault(Map<String, Object> map, String key, String defaultValue) {
        String val = getString(map, key);
        return val != null ? val : defaultValue;
    }

    @SuppressWarnings("unchecked")
    public static List<Object> getList(Map<String, Object> map, String key) {
        if (map == null) return List.of();
        Object val = map.get(key);
        if (val instanceof List<?> list) {
            return (List<Object>) list;
        }
        return List.of();
    }

    @SuppressWarnings("unchecked")
    public static Map<String, Object> getObject(Map<String, Object> map, String key) {
        if (map == null) return Map.of();
        Object val = map.get(key);
        if (val instanceof Map<?, ?> obj) {
            return (Map<String, Object>) obj;
        }
        return Map.of();
    }

    public static String escapeString(String raw) {
        if (raw == null) return "";
        StringBuilder sb = new StringBuilder();
        for (int i = 0; i < raw.length(); i++) {
            char c = raw.charAt(i);
            switch (c) {
                case '"' -> sb.append("\\\"");
```

```
                case '\\' -> sb.append("\\\\");
                case '\b' -> sb.append("\\b");
                case '\f' -> sb.append("\\f");
                case '\n' -> sb.append("\\n");
                case '\r' -> sb.append("\\r");
                case '\t' -> sb.append("\\t");
                default -> {
                    if (c < 0x20) {
                        sb.append(String.format("\\u%04x", (int) c));
                    } else {
                        sb.append(c);
                    }
                }
            }
        }
        return sb.toString();
    }

}
```

src/main/java/ems/gmail/TokenStore.java

```
package ems.gmail;

import com.google.gson.JsonObject;
import com.google.gson.JsonParser;
import java.io.IOException;
import java.nio.charset.StandardCharsets;
import java.nio.file.Files;
import java.nio.file.LinkOption;
import java.nio.file.Path;
import java.nio.file.StandardCopyOption;
import java.nio.file.attribute.AclEntry;
import java.nio.file.attribute.AclEntryFlag;
import java.nio.file.attribute.AclEntryPermission;
import java.nio.file.attribute.AclEntryType;
import java.nio.file.attribute.AclFileAttributeView;
import java.nio.file.attribute.PosixFileAttributeView;
import java.nio.file.attribute.PosixFilePermissions;
import java.nio.file.attribute.UserPrincipal;
import java.util.EnumSet;
import java.util.List;

/** Owner-only OAuth cache. Tokens never belong in source control or the message database. */
final class TokenStore {
    private final Path directory;
    private final Path file;

    TokenStore(Path directory) {
        this.directory = directory.toAbsolutePath().normalize();
        this.file = this.directory.resolve("gmail-token.json");
    }

    JsonObject load() throws IOException {
        if (!Files.exists(file, LinkOption.NOFOLLOW_LINKS)) return null;
        rejectSymlink(file);
        secure(directory, true);
        secure(file, false);
        try {
            return JsonParser.parseString(Files.readString(file, StandardCharsets.UTF_8)).getAsJsonObject();
        } catch (RuntimeException corrupt) {
            clear();
            return null;
        }
    }

    void save(JsonObject data) throws IOException {
        Files.createDirectories(directory);
        rejectSymlink(directory);
        secure(directory, true);
        Path temp = Files.createTempFile(directory, "oauth-", ".tmp");
        try {
            secure(temp, false);
            Files.writeString(temp, data.toString(), StandardCharsets.UTF_8);
            try {
                Files.move(temp, file, StandardCopyOption.REPLACE_EXISTING, StandardCopyOption.ATOMIC_MOVE);
            } catch (java.nio.file.AtomicMoveNotSupportedException unsupported) {
                Files.move(temp, file, StandardCopyOption.REPLACE_EXISTING);
            }
            secure(file, false);
        } finally {
            Files.deleteIfExists(temp);
        }
    }

    void clear() throws IOException { Files.deleteIfExists(file); }

    private static void rejectSymlink(Path path) throws IOException {
        if (Files.isSymbolicLink(path)) throw new IOException("OAuth cache must not be a symbolic link.");
    }
```

```
    private static void secure(Path path, boolean directory) throws IOException {
        if (Files.getFileAttributeView(path, PosixFileAttributeView.class) != null) {
            Files.setPosixFilePermissions(path, PosixFilePermissions.fromString(directory ? "rwx------" : "rw---
----"));
            return;
        }
        AclFileAttributeView acl = Files.getFileAttributeView(path, AclFileAttributeView.class);
        if (acl != null) {
            UserPrincipal owner = path.getFileSystem().getUserPrincipalLookupService()
                    .lookupPrincipalByName(System.getProperty("user.name"));
            AclEntry.Builder entry = AclEntry.newBuilder().setType(AclEntryType.ALLOW)
                    .setPrincipal(owner).setPermissions(EnumSet.allOf(AclEntryPermission.class));
            if (directory) entry.setFlags(AclEntryFlag.DIRECTORY_INHERIT, AclEntryFlag.FILE_INHERIT);
            acl.setAcl(List.of(entry.build()));
            return;
        }
        throw new IOException("This filesystem cannot restrict access to OAuth credentials.");
    }
}
```

src/main/java/ems/model/Account.java

```
package ems.model;

import java.util.Objects;

/** A locally identified Gmail account. OAuth credentials are never part of this model. */
public final class Account {
    private final long accountId;
    private final String emailAddress;

    public Account(long accountId, String emailAddress) {
        this.accountId = accountId;
        this.emailAddress = Objects.requireNonNull(emailAddress, "emailAddress");
    }

    public long getAccountId() {
        return accountId;
    }

    public String getEmailAddress() {
        return emailAddress;
    }
}
```

src/main/java/ems/model/EmailMessage.java

```
package ems.model;

import java.time.Instant;
import java.util.List;
import java.util.Objects;
import java.util.Set;

/**
 * An immutable snapshot of a Gmail message. Gmail IDs are opaque strings.
 * Empty subjects and plain-text bodies are valid. Dates are instants; the UI
 * formats them in the user's local time zone.
 */
public final class EmailMessage {
    private final long accountId;
    private final String gmailMessageId;
    private final String senderEmail;
    private final List<String> recipientEmails;
    private final String subject;
    private final String bodyText;
    private final Instant receivedAt;
    private final Set<String> gmailLabelIds;

    public EmailMessage(
            long accountId,
            String gmailMessageId,
            String senderEmail,
            List<String> recipientEmails,
            String subject,
            String bodyText,
            Instant receivedAt,
            Set<String> gmailLabelIds) {
        this.accountId = accountId;
        this.gmailMessageId = Objects.requireNonNull(gmailMessageId, "gmailMessageId");
        this.senderEmail = Objects.requireNonNull(senderEmail, "senderEmail");
        this.recipientEmails = List.copyOf(recipientEmails);
        this.subject = Objects.requireNonNull(subject, "subject");
        this.bodyText = Objects.requireNonNull(bodyText, "bodyText");
        this.receivedAt = Objects.requireNonNull(receivedAt, "receivedAt");
        this.gmailLabelIds = Set.copyOf(gmailLabelIds);
```

```
    }

    public long getAccountId() {
        return accountId;
    }

    public String getGmailMessageId() {
        return gmailMessageId;
    }

    public String getSenderEmail() {
        return senderEmail;
    }

    public List<String> getRecipientEmails() {
        return recipientEmails;
    }

    public String getSubject() {
        return subject;
    }

    public String getBodyText() {
        return bodyText;
    }

    public Instant getReceivedAt() {
        return receivedAt;
    }

    public Set<String> getGmailLabelIds() {
        return gmailLabelIds;
    }
}
```

src/main/java/ems/model/Mailbox.java

```
package ems.model;

/** Mailbox views; SUSPECTED is the local detector's view rather than a Gmail label. */
public enum Mailbox {
    INBOX,
    SENT,
    SPAM,
    SUSPECTED
}
```

src/main/java/ems/model/SpamResult.java

```
package ems.model;

import java.util.List;

/**
 * The local detector's result. The score is a rule score, not a probability.
 * Gmail's own SPAM label remains separate from this classification.
 */
public final class SpamResult {
    private final int score;
    private final boolean suspectedSpam;
    private final List<String> reasons;

    public SpamResult(int score, boolean suspectedSpam, List<String> reasons) {
        this.score = score;
        this.suspectedSpam = suspectedSpam;
        this.reasons = List.copyOf(reasons);
    }

    public int getScore() {
        return score;
    }

    public boolean isSuspectedSpam() {
        return suspectedSpam;
    }

    public List<String> getReasons() {
        return reasons;
    }
}
```

src/main/java/ems/service/EmailService.java

```
package ems.service;

import ems.exception.AppException;
import ems.model.Account;
import ems.model.EmailMessage;
import ems.model.Mailbox;
import ems.model.SpamResult;
import java.util.List;

/**
 * Shared boundary between the Swing interface and Gmail/database integrations.
 * Implementations support one connected account at a time and scope every
 * mailbox operation to that account. Operations can block, so the UI calls them
 * on background workers rather than the Swing event-dispatch thread.
 *
 * <p>Implementations should turn recoverable provider/database errors into
 * {@link AppException} with useful, non-sensitive messages. A failed operation
 * must not be presented to the UI as a successful update.
 */
public interface EmailService {
    /** Authorizes Gmail access through Google and returns the connected account. */
    Account connectGmail() throws AppException;

    /** Ends the application's local connected session; does not delete the Gmail account. */
    void disconnect();

    /** Fetches Gmail changes, updates the local cache, and runs local spam analysis. */
    void refresh() throws AppException;
    default void refreshRecent() throws AppException { refresh(); }

    /**
     * Returns visible cached messages, newest first, for the selected mailbox.
     * An empty query returns all messages in that view; searches match subject,
     * body, sender, or recipient addresses. Returns an empty list if none match.
     */
    List<EmailMessage> getMessages(Mailbox mailbox, String query) throws AppException;

    /**
     * Opens an accessible message for the connected account and marks it read
     * in Gmail. Returns the updated snapshot after a successful operation.
     */
    EmailMessage openMessage(String gmailMessageId) throws AppException;

    /** Sends to one real recipient address and returns Gmail's new message ID. */
    String sendMessage(String recipientEmail, String subject, String body) throws AppException;

    /** Returns the local detector's result for a message in the connected account. */
    SpamResult getSpamResult(String gmailMessageId) throws AppException;

    /** Applies Gmail's spam classification and persists the user's correction locally. */
    void markAsSpam(String gmailMessageId) throws AppException;

    /** Removes Gmail's spam classification and persists the user's correction locally. */
    void markAsNotSpam(String gmailMessageId) throws AppException;

    /** Non-sensitive notice for a successful operation with a recoverable cache issue. */
    default String getLastWarning() { return ""; }
}
```

src/main/java/ems/service/GmailEmailService.java

```
package ems.service;

import ems.exception.AppException;
import ems.config.AppConfig;
import ems.gmail.GmailApiClient;
import ems.storage.JdbcMailStore;
import java.sql.DriverManager;
import ems.gmail.GmailGateway;
import ems.model.*;
import ems.storage.MailStore;
import jakarta.mail.internet.AddressException;
import jakarta.mail.internet.InternetAddress;
import java.sql.SQLException;
import java.time.Instant;
import java.util.*;

/** Connects the Swing contract to Gmail and the persistent account-scoped cache. */
public final class GmailEmailService implements EmailService {
    private final GmailGateway gmail;
    private final MailStore store;
    private Account account;
    private String lastWarning = "";
```

```
    /** Shared production wiring for both team launchers; constructors stay injectable for tests. */
    public static GmailEmailService createDefault() throws AppException {
        AppConfig config = AppConfig.load();
        return new GmailEmailService(new GmailApiClient(config.getGmailCredentialsPath(),
                config.getTokenDirectory()), new JdbcMailStore(() -> DriverManager.getConnection(
                config.getDatabaseUrl(), config.getDatabaseUser(), config.getDatabasePassword())));
    }

    public GmailEmailService(GmailGateway gmail, MailStore store) {
        this.gmail = Objects.requireNonNull(gmail, "gmail");
        this.store = Objects.requireNonNull(store, "store");
    }

    @Override public synchronized Account connectGmail() throws AppException {
        lastWarning = "";
        if (account != null) return account;
        try { store.initialize(); }
        catch (SQLException exception) {
            throw databaseError("Cannot connect to MySQL. Check db.url, db.user and db.password in
config/app.properties.", exception);
        }
        String email = gmail.connect();
        try {
            account = store.findOrCreateAccount(email);
            return account;
        } catch (SQLException exception) {
            gmail.disconnect();
            throw databaseError("Google sign-in succeeded, but the local account could not be saved. Check MySQL
and try again.", exception);
        }
    }

    @Override public synchronized void disconnect() {
        try { gmail.disconnect(); }
        finally { account = null; lastWarning = ""; }
    }

    @Override public synchronized void refresh() throws AppException {
        Account current = connected(); lastWarning = "";
        // A failed network fetch must never be mistaken for an empty mailbox.
        List<EmailMessage> snapshot = gmail.fetchRecentMessages(current.getAccountId(), 6)
                .stream().limit(18).toList();
        verifyAccount(current, snapshot);
        try { store.replaceSnapshot(current.getAccountId(), snapshot); }
        catch (SQLException exception) {
            throw databaseError("Gmail was read, but the local mailbox could not be updated. Check MySQL and
refresh again.", exception);
        }
    }

    @Override public synchronized List<EmailMessage> getMessages(Mailbox mailbox, String query) throws
AppException {
        Account current = connected();
        if (mailbox == null) throw new AppException("Choose a mailbox first.");
        try { return store.getMessages(current.getAccountId(), mailbox, query == null ? "" : query.strip()); }
        catch (SQLException exception) { throw databaseError("Cannot read cached messages. Check MySQL and try
again.", exception); }
    }

    @Override public synchronized void refreshRecent() throws AppException {
        refresh();
    }

    @Override public synchronized EmailMessage openMessage(String gmailMessageId) throws AppException {
        Account current = connected(); lastWarning = "";
        requireCached(current, gmailMessageId);
        EmailMessage message = gmail.getMessage(current.getAccountId(), gmailMessageId);
        verifyAccount(current, List.of(message));
        if (message.getGmailLabelIds().contains("UNREAD")) {
            gmail.setRead(gmailMessageId);
            Set<String> labels = new HashSet<>(message.getGmailLabelIds()); labels.remove("UNREAD");
            message = withLabels(message, labels);
        }
        try { store.saveMessages(current.getAccountId(), List.of(message)); }
        catch (SQLException exception) {
            throw databaseError("The message was opened in Gmail, but its local copy could not be updated.
Refresh after checking MySQL.", exception);
        }
        return message;
    }

    @Override public synchronized String sendMessage(String recipientEmail, String subject, String body) throws
AppException {
        Account current = connected(); lastWarning = "";
        String recipient = validateRecipient(recipientEmail);
        String cleanSubject = subject == null ? "" : subject.strip();
        if (cleanSubject.isBlank() || cleanSubject.length() > 200 || containsLineBreak(subject)) {
            throw new AppException("Enter a subject between 1 and 200 characters on one line.");
        }
        if (body == null || body.isBlank() || body.length() > 10_000) {
            throw new AppException("Enter a message between 1 and 10,000 characters.");
        }
        String id = gmail.sendMessage(current.getEmailAddress(), recipient, cleanSubject, body);
```

```
        // Gmail has accepted this email. Never turn a later cache error into 'send failed'.
        EmailMessage sent = new EmailMessage(current.getAccountId(), id, current.getEmailAddress(),
                List.of(recipient), cleanSubject, body, Instant.now(),
                recipient.equalsIgnoreCase(current.getEmailAddress()) ? Set.of("SENT", "INBOX") :
Set.of("SENT"));
        try { sent = gmail.getMessage(current.getAccountId(), id); verifyAccount(current, List.of(sent)); }
        catch (AppException exception) {
            lastWarning = "Email was sent. Its latest Gmail copy could not be loaded; refresh Sent before
sending it again.";
        }
        try { store.saveMessages(current.getAccountId(), List.of(sent)); }
        catch (SQLException exception) {
            lastWarning = "Email was sent, but its local copy could not be saved. Check Gmail Sent before
sending it again.";
        }
        return id;
    }

    @Override public synchronized SpamResult getSpamResult(String gmailMessageId) throws AppException {
        Account current = connected(); requireCached(current, gmailMessageId);
        try { return store.getSpamResult(current.getAccountId(), gmailMessageId); }
        catch (SQLException exception) { throw databaseError("Cannot read this message's spam review. Check
MySQL and try again.", exception); }
    }

    @Override public synchronized void markAsSpam(String gmailMessageId) throws AppException {
correct(gmailMessageId, true); }
    @Override public synchronized void markAsNotSpam(String gmailMessageId) throws AppException {
correct(gmailMessageId, false); }

    private void correct(String id, boolean spam) throws AppException {
        Account current = connected(); lastWarning = "";
        EmailMessage original = requireCached(current, id);
        if (original.getGmailLabelIds().contains("SENT") && !original.getGmailLabelIds().contains("INBOX")
                && !original.getGmailLabelIds().contains("SPAM")) {
            throw new AppException("Spam corrections apply to received messages.");
        }
        gmail.setSpam(id, spam);
        Set<String> labels = new HashSet<>(original.getGmailLabelIds());
        if (spam) { labels.add("SPAM"); labels.remove("INBOX"); }
        else { labels.remove("SPAM"); labels.add("INBOX"); }
        EmailMessage updated = withLabels(original, labels);
        try { updated = gmail.getMessage(current.getAccountId(), id); verifyAccount(current, List.of(updated));
}
        catch (AppException exception) {
            lastWarning = "Gmail was updated. Refresh to load its latest message details.";
        }
        try {
            store.saveMessages(current.getAccountId(), List.of(updated));
            store.saveFeedback(current.getAccountId(), id, spam);
        } catch (SQLException exception) {
            throw databaseError("Gmail's spam label was updated, but the local correction could not be saved.
Check MySQL and refresh.", exception);
        }
    }

    @Override public synchronized String getLastWarning() { return lastWarning; }

    private Account connected() throws AppException {
        if (account == null) throw new AppException("Connect your Gmail account first.");
        return account;
    }

    private EmailMessage requireCached(Account current, String id) throws AppException {
        if (id == null || id.isBlank()) throw new AppException("Choose an available message first.");
        try {
            return store.findMessage(current.getAccountId(), id)
                    .orElseThrow(() -> new AppException("This message is unavailable in the connected account.
Refresh your mailbox."));
        } catch (SQLException exception) { throw databaseError("Cannot access this message. Check MySQL and try
again.", exception); }
    }

    private static void verifyAccount(Account current, List<EmailMessage> messages) throws AppException {
        if (messages == null || messages.stream().anyMatch(message -> message == null
                || message.getAccountId() != current.getAccountId())) {
            throw new AppException("The mailbox response did not match the connected account. Disconnect and
sign in again.");
        }
    }

    private static String validateRecipient(String input) throws AppException {
        if (input == null || input.isBlank() || input.length() > 254 || containsLineBreak(input)) {
            throw new AppException("Enter one valid recipient email address.");
        }
        try {
            InternetAddress[] addresses = InternetAddress.parse(input.strip(), true);
            if (addresses.length != 1 || addresses[0].isGroup()) throw new AddressException();
            addresses[0].validate();
            String address = addresses[0].getAddress();
            if (!address.contains("@")) throw new AddressException();
            return address;
```

```
        } catch (AddressException exception) { throw new AppException("Enter one valid recipient email
address."); }
    }

    private static boolean containsLineBreak(String value) { return value != null && (value.indexOf('\r') >= 0
|| value.indexOf('\n') >= 0); }
    private static EmailMessage withLabels(EmailMessage message, Set<String> labels) {
        return new EmailMessage(message.getAccountId(), message.getGmailMessageId(), message.getSenderEmail(),
                message.getRecipientEmails(), message.getSubject(), message.getBodyText(),
message.getReceivedAt(), labels);
    }
    private static AppException databaseError(String message, SQLException cause) { return new
AppException(message, cause); }
}
```

src/main/java/ems/storage/ConnectionFactory.java

```
package ems.storage;

import java.sql.Connection;
import java.sql.SQLException;

/** Opens one owned connection per store operation. */
@FunctionalInterface
public interface ConnectionFactory {
    Connection open() throws SQLException;
}
```

src/main/java/ems/storage/JdbcMailStore.java

```
package ems.storage;

import com.emailapp.database.DatabaseConnection;
import com.emailapp.spam.SpamClassifier;
import ems.model.Account;
import ems.model.EmailMessage;
import ems.model.Mailbox;
import ems.model.SpamResult;
import java.sql.Connection;
import java.sql.PreparedStatement;
import java.sql.ResultSet;
import java.sql.SQLException;
import java.sql.Statement;
import java.sql.Timestamp;
import java.time.Instant;
import java.util.ArrayList;
import java.util.Calendar;
import java.util.Collection;
import java.util.Collections;
import java.util.LinkedHashMap;
import java.util.LinkedHashSet;
import java.util.List;
import java.util.Locale;
import java.util.Map;
import java.util.Optional;
import java.util.Set;
import java.util.TimeZone;

/** JDBC cache with atomic snapshot replacement and persistent account-scoped feedback. */
public final class JdbcMailStore implements MailStore {
    private final ConnectionFactory connections;
    private final SpamClassifier classifier = new SpamClassifier();

    public JdbcMailStore() {
        this(DatabaseConnection::getConnection);
    }

    public JdbcMailStore(ConnectionFactory connections) {
        this.connections = java.util.Objects.requireNonNull(connections);
    }

    @Override
    public void initialize() throws SQLException {
        try (Connection connection = connections.open(); Statement statement = connection.createStatement()) {
            for (String sql : Schema.TABLES) statement.execute(sql);
        }
    }

    @Override
    public Account findOrCreateAccount(String email) throws SQLException {
        String normalized = email.trim().toLowerCase(Locale.ROOT);
        if (normalized.isEmpty()) throw new SQLException("The Gmail account has no email address.");
        try (Connection connection = connections.open()) {
            Optional<Account> existing = findAccount(connection, normalized);
            if (existing.isPresent()) return existing.get();
            try (PreparedStatement insert = connection.prepareStatement(
                    "INSERT INTO accounts (email_address) VALUES (?)", Statement.RETURN_GENERATED_KEYS)) {
```

```
                insert.setString(1, normalized);
                insert.executeUpdate();
                try (ResultSet keys = insert.getGeneratedKeys()) {
                    if (keys.next()) return new Account(keys.getLong(1), normalized);
                }
            } catch (SQLException exception) {
                // Another connection may have created this account since the SELECT.
                Optional<Account> concurrent = findAccount(connection, normalized);
                if (concurrent.isPresent()) return concurrent.get();
                throw exception;
            }
            return findAccount(connection, normalized).orElseThrow(() -> new SQLException("Account ID was not
returned."));
        }
    }

    private Optional<Account> findAccount(Connection connection, String email) throws SQLException {
        try (PreparedStatement query = connection.prepareStatement(
                "SELECT account_id, email_address FROM accounts WHERE email_address = ?")) {
            query.setString(1, email);
            try (ResultSet rows = query.executeQuery()) {
                return rows.next() ? Optional.of(new Account(rows.getLong(1), rows.getString(2))) :
Optional.empty();
            }
        }
    }

    @Override
    public void saveMessages(long accountId, List<EmailMessage> messages) throws SQLException {
        checkAccount(accountId, messages);
        transaction(connection -> saveBatch(connection, accountId, messages));
    }

    @Override
    public void replaceSnapshot(long accountId, List<EmailMessage> messages) throws SQLException {
        checkAccount(accountId, messages);
        transaction(connection -> {
            saveBatch(connection, accountId, messages);
            Set<String> present = new LinkedHashSet<>();
            for (EmailMessage message : messages) present.add(message.getGmailMessageId());
            List<String> removed = new ArrayList<>();
            try (PreparedStatement query = connection.prepareStatement("SELECT gmail_message_id FROM messages
WHERE account_id=?")) {
                query.setLong(1, accountId);
                try (ResultSet rows = query.executeQuery()) {
                    while (rows.next()) if (!present.contains(rows.getString(1)))
removed.add(rows.getString(1));
                }
            }
            deleteBatch(connection, accountId, removed);
        });
    }

    private static void checkAccount(long accountId, List<EmailMessage> messages) throws SQLException {
        for (EmailMessage message : messages) {
            if (message.getAccountId() != accountId) throw new SQLException("Message belongs to another
account.");
        }
    }

    private void saveBatch(Connection connection, long accountId, List<EmailMessage> messages) throws
SQLException {
        Set<String> blocked = blockedSenders(connection, accountId);
        for (EmailMessage message : messages) {
            upsertMessage(connection, message);
            replaceChildren(connection, message, "message_recipients", "recipient_email",
                    distinctRecipients(message.getRecipientEmails()));
            replaceChildren(connection, message, "message_labels", "gmail_label_id",
message.getGmailLabelIds());
            SpamResult automatic = classifier.analyze(message,
                    blocked.contains(message.getSenderEmail().trim().toLowerCase(Locale.ROOT)));
            saveSpamResult(connection, accountId, message.getGmailMessageId(), automatic);
        }
    }

    private static Collection<String> distinctRecipients(List<String> recipients) {
        // Gmail may repeat a recipient in To/Cc with different casing. MySQL's default
        // collation also treats those addresses as equal; retain the first spelling.
        Map<String, String> distinct = new LinkedHashMap<>();
        for (String recipient : recipients) {
            distinct.putIfAbsent(recipient.toLowerCase(Locale.ROOT), recipient);
        }
        return distinct.values();
    }

    private void upsertMessage(Connection connection, EmailMessage message) throws SQLException {
        String fields = "sender_email=?, subject=?, body_text=?, received_at=?, is_read=?";
        try (PreparedStatement update = connection.prepareStatement(
                "UPDATE messages SET " + fields + " WHERE account_id=? AND gmail_message_id=?")) {
            bindMessage(update, message);
            if (update.executeUpdate() > 0) return;
        }
        // MySQL may return zero when an UPDATE has identical values (useAffectedRows=true).
        if (messageExists(connection, message.getAccountId(), message.getGmailMessageId())) return;
```

```
        try (PreparedStatement insert = connection.prepareStatement("INSERT INTO messages "
                + "(sender_email,subject,body_text,received_at,is_read,account_id,gmail_message_id) VALUES
(?,?,?,?,?,?,?)")) {
            bindMessage(insert, message);
            insert.executeUpdate();
        }
    }

    private static void bindMessage(PreparedStatement statement, EmailMessage message) throws SQLException {
        statement.setString(1, message.getSenderEmail());
        statement.setString(2, message.getSubject());
        statement.setString(3, message.getBodyText());
        statement.setTimestamp(4, Timestamp.from(message.getReceivedAt()), utc());
        statement.setBoolean(5, !message.getGmailLabelIds().contains("UNREAD"));
        statement.setLong(6, message.getAccountId());
        statement.setString(7, message.getGmailMessageId());
    }

    private void replaceChildren(Connection connection, EmailMessage message, String table, String column,
            Collection<String> values) throws SQLException {
        deleteOne(connection, table, message.getAccountId(), message.getGmailMessageId());
        if (values.isEmpty()) return;
        try (PreparedStatement insert = connection.prepareStatement("INSERT INTO " + table
                + " (account_id,gmail_message_id," + column + ") VALUES (?,?,?)")) {
            for (String value : values) {
                insert.setLong(1, message.getAccountId());
                insert.setString(2, message.getGmailMessageId());
                insert.setString(3, value);
                insert.addBatch();
            }
            insert.executeBatch();
        }
    }

    @Override
    public List<EmailMessage> getMessages(long accountId, Mailbox mailbox, String query) throws SQLException {
        String base = "SELECT m.account_id,m.gmail_message_id,m.sender_email,m.subject,m.body_text,m.received_at
"
                + "FROM messages m WHERE m.account_id=? AND NOT EXISTS (SELECT 1 FROM message_labels t "
                + "WHERE t.account_id=m.account_id AND t.gmail_message_id=m.gmail_message_id AND
t.gmail_label_id='TRASH') ";
        if (mailbox == Mailbox.SUSPECTED) {
            // Review only incoming mail that Gmail has not already placed in Spam.
            base += "AND NOT EXISTS (SELECT 1 FROM message_labels excluded WHERE
excluded.account_id=m.account_id "
                    + "AND excluded.gmail_message_id=m.gmail_message_id AND excluded.gmail_label_id IN
('SPAM','SENT')) "
                    + "AND ((EXISTS (SELECT 1 FROM spam_feedback f WHERE f.account_id=m.account_id "
                    + "AND f.gmail_message_id=m.gmail_message_id AND f.user_marked_spam=TRUE)) OR "
                    + "(NOT EXISTS (SELECT 1 FROM spam_feedback f WHERE f.account_id=m.account_id "
                    + "AND f.gmail_message_id=m.gmail_message_id) AND EXISTS (SELECT 1 FROM spam_results s "
                    + "WHERE s.account_id=m.account_id AND s.gmail_message_id=m.gmail_message_id AND
s.suspected_spam=TRUE))) ";
        } else {
            base += "AND EXISTS (SELECT 1 FROM message_labels l WHERE l.account_id=m.account_id "
                    + "AND l.gmail_message_id=m.gmail_message_id AND l.gmail_label_id=?) ";
            if (mailbox == Mailbox.INBOX) base += "AND NOT EXISTS (SELECT 1 FROM message_labels s "
                    + "WHERE s.account_id=m.account_id AND s.gmail_message_id=m.gmail_message_id AND
s.gmail_label_id='SPAM') ";
        }
        String normalized = query == null ? "" : query.trim().toLowerCase(Locale.ROOT);
        if (!normalized.isEmpty()) base += "AND (LOWER(m.sender_email) LIKE ? ESCAPE '!' "
                + "OR LOWER(m.subject) LIKE ? ESCAPE '!' OR LOWER(m.body_text) LIKE ? ESCAPE '!' "
                + "OR EXISTS (SELECT 1 FROM message_recipients r WHERE r.account_id=m.account_id "
                + "AND r.gmail_message_id=m.gmail_message_id AND LOWER(r.recipient_email) LIKE ? ESCAPE '!')) ";
        base += "ORDER BY m.received_at DESC,m.gmail_message_id DESC";
        try (Connection connection = connections.open(); PreparedStatement statement =
connection.prepareStatement(base)) {
            int index = 1;
            statement.setLong(index++, accountId);
            if (mailbox != Mailbox.SUSPECTED) statement.setString(index++, mailbox.name());
            if (!normalized.isEmpty()) {
                String pattern = "%" + normalized.replace("!", "!!").replace("%", "!%").replace("_", "!_") +
"%";
                for (int i = 0; i < 4; i++) statement.setString(index++, pattern);
            }
            return readMessages(connection, statement);
        }
    }

    @Override
    public Optional<EmailMessage> findMessage(long accountId, String gmailMessageId) throws SQLException {
        try (Connection connection = connections.open(); PreparedStatement statement =
connection.prepareStatement(
                "SELECT account_id,gmail_message_id,sender_email,subject,body_text,received_at FROM messages "
                        + "WHERE account_id=? AND gmail_message_id=?")) {
            statement.setLong(1, accountId);
            statement.setString(2, gmailMessageId);
            return readMessages(connection, statement).stream().findFirst();
        }
    }

    /** Legacy repository support, with bounded bulk child reads rather than N+1 connections. */
    public List<EmailMessage> findAll(long accountId) throws SQLException {
```

```
        try (Connection connection = connections.open(); PreparedStatement statement =
connection.prepareStatement(
                "SELECT account_id,gmail_message_id,sender_email,subject,body_text,received_at FROM messages "
                        + "WHERE account_id=? ORDER BY received_at DESC,gmail_message_id DESC")) {
            statement.setLong(1, accountId);
            return readMessages(connection, statement);
        }
    }

    private List<EmailMessage> readMessages(Connection connection, PreparedStatement query) throws SQLException
{
        List<EmailMessage> bases = new ArrayList<>();
        try (ResultSet rows = query.executeQuery()) {
            while (rows.next()) bases.add(new EmailMessage(rows.getLong("account_id"),
rows.getString("gmail_message_id"),
                    rows.getString("sender_email"), List.of(), rows.getString("subject"),
rows.getString("body_text"),
                    rows.getTimestamp("received_at", utc()).toInstant(), Set.of()));
        }
        if (bases.isEmpty()) return List.of();
        Map<String, List<String>> recipients = readChildren(connection, bases, "message_recipients",
"recipient_email");
        Map<String, List<String>> labels = readChildren(connection, bases, "message_labels", "gmail_label_id");
        List<EmailMessage> result = new ArrayList<>(bases.size());
        for (EmailMessage base : bases) result.add(new EmailMessage(base.getAccountId(),
base.getGmailMessageId(),
                base.getSenderEmail(), recipients.getOrDefault(base.getGmailMessageId(), List.of()),
                base.getSubject(), base.getBodyText(), base.getReceivedAt(),
                new LinkedHashSet<>(labels.getOrDefault(base.getGmailMessageId(), List.of()))));
        return result;
    }

    private Map<String, List<String>> readChildren(Connection connection, List<EmailMessage> messages,
            String table, String column) throws SQLException {
        Map<String, List<String>> values = new LinkedHashMap<>();
        for (int start = 0; start < messages.size(); start += 500) {
            List<EmailMessage> batch = messages.subList(start, Math.min(start + 500, messages.size()));
            String placeholders = String.join(",", Collections.nCopies(batch.size(), "?"));
            try (PreparedStatement query = connection.prepareStatement("SELECT gmail_message_id," + column
                    + " FROM " + table + " WHERE account_id=? AND gmail_message_id IN (" + placeholders + ")
ORDER BY " + column)) {
                query.setLong(1, messages.get(0).getAccountId());
                for (int i = 0; i < batch.size(); i++) query.setString(i + 2, batch.get(i).getGmailMessageId());
                try (ResultSet rows = query.executeQuery()) {
                    while (rows.next()) values.computeIfAbsent(rows.getString(1), unused -> new
ArrayList<>()).add(rows.getString(2));
                }
            }
        }
        return values;
    }

    @Override
    public SpamResult getSpamResult(long accountId, String gmailMessageId) throws SQLException {
        try (Connection connection = connections.open()) {
            Optional<Boolean> feedback = feedback(connection, accountId, gmailMessageId);
            if (feedback.isPresent()) return corrected(feedback.get());
            try (PreparedStatement query = connection.prepareStatement(
                    "SELECT score,suspected_spam,reasons FROM spam_results WHERE account_id=? AND
gmail_message_id=?")) {
                query.setLong(1, accountId);
                query.setString(2, gmailMessageId);
                try (ResultSet rows = query.executeQuery()) {
                    if (rows.next()) return new SpamResult(rows.getInt(1), rows.getBoolean(2),
ReasonJson.decode(rows.getString(3)));
                }
            }
            return new SpamResult(0, false, List.of("This message has not been analyzed yet."));
        }
    }

    @Override
    public void saveFeedback(long accountId, String gmailMessageId, boolean spam) throws SQLException {
        transaction(connection -> {
            if (!messageExists(connection, accountId, gmailMessageId)) throw new SQLException("Message was not
found in this account.");
            try (PreparedStatement update = connection.prepareStatement("UPDATE spam_feedback SET
user_marked_spam=?,corrected_at=? "
                    + "WHERE account_id=? AND gmail_message_id=?")) {
                bindFeedback(update, accountId, gmailMessageId, spam);
                if (update.executeUpdate() > 0) return;
            }
            if (feedback(connection, accountId, gmailMessageId).isPresent()) return;
            try (PreparedStatement insert = connection.prepareStatement("INSERT INTO spam_feedback "
                    + "(user_marked_spam,corrected_at,account_id,gmail_message_id) VALUES (?,?,?,?)")) {
                bindFeedback(insert, accountId, gmailMessageId, spam);
                insert.executeUpdate();
            }
        });
    }

    private static void bindFeedback(PreparedStatement statement, long accountId, String id, boolean spam)
throws SQLException {
        statement.setBoolean(1, spam);
        statement.setTimestamp(2, Timestamp.from(Instant.now()), utc());
```

```
        statement.setLong(3, accountId);
        statement.setString(4, id);
    }

    private static Optional<Boolean> feedback(Connection connection, long accountId, String id) throws
SQLException {
        try (PreparedStatement query = connection.prepareStatement(
                "SELECT user_marked_spam FROM spam_feedback WHERE account_id=? AND gmail_message_id=?")) {
            query.setLong(1, accountId);
            query.setString(2, id);
            try (ResultSet rows = query.executeQuery()) {
                return rows.next() ? Optional.of(rows.getBoolean(1)) : Optional.empty();
            }
        }
    }

    private static SpamResult corrected(boolean spam) {
        return new SpamResult(spam ? 100 : 0, spam, List.of(spam ? "You marked this message as spam." : "You
marked this message as not spam."));
    }

    /** Compatibility entry point for Member 3's repository; automatic scores never overwrite feedback. */
    public void saveSpamResult(long accountId, String id, SpamResult result) throws SQLException {
        transaction(connection -> saveSpamResult(connection, accountId, id, result));
    }

    private void saveSpamResult(Connection connection, long accountId, String id, SpamResult result) throws
SQLException {
        String reasons = ReasonJson.encode(result.getReasons());
        try (PreparedStatement update = connection.prepareStatement("UPDATE spam_results SET
score=?,suspected_spam=?,reasons=?,analyzed_at=? "
                + "WHERE account_id=? AND gmail_message_id=?")) {
            bindSpam(update, accountId, id, result, reasons);
            if (update.executeUpdate() > 0) return;
        }
        try (PreparedStatement exists = connection.prepareStatement("SELECT 1 FROM spam_results WHERE
account_id=? AND gmail_message_id=?")) {
            exists.setLong(1, accountId);
            exists.setString(2, id);
            try (ResultSet rows = exists.executeQuery()) { if (rows.next()) return; }
        }
        try (PreparedStatement insert = connection.prepareStatement("INSERT INTO spam_results "
                + "(score,suspected_spam,reasons,analyzed_at,account_id,gmail_message_id) VALUES
(?,?,?,?,?,?)")) {
            bindSpam(insert, accountId, id, result, reasons);
            insert.executeUpdate();
        }
    }

    private static void bindSpam(PreparedStatement statement, long accountId, String id, SpamResult result,
String reasons) throws SQLException {
        statement.setInt(1, result.getScore());
        statement.setBoolean(2, result.isSuspectedSpam());
        statement.setString(3, reasons);
        statement.setTimestamp(4, Timestamp.from(Instant.now()), utc());
        statement.setLong(5, accountId);
        statement.setString(6, id);
    }

    @Override
    public void deleteMessages(long accountId, Collection<String> gmailMessageIds) throws SQLException {
        transaction(connection -> deleteBatch(connection, accountId, gmailMessageIds));
    }

    private void deleteBatch(Connection connection, long accountId, Collection<String> gmailMessageIds) throws
SQLException {
        for (String id : gmailMessageIds) {
            for (String table : List.of("message_recipients", "message_labels", "spam_results", "messages"))
                deleteOne(connection, table, accountId, id);
            // Feedback deliberately survives cache eviction and later re-downloads.
        }
    }

    public boolean isSenderBlocked(long accountId, String email) throws SQLException {
        try (Connection connection = connections.open()) {
            return blockedSenders(connection, accountId).contains(email.trim().toLowerCase(Locale.ROOT));
        }
    }

    public void setSenderBlocked(long accountId, String email, boolean blocked) throws SQLException {
        String normalized = email.trim().toLowerCase(Locale.ROOT);
        if (normalized.isEmpty()) throw new SQLException("A sender email is required.");
        transaction(connection -> {
            try (PreparedStatement delete = connection.prepareStatement(
                    "DELETE FROM blocked_senders WHERE account_id=? AND sender_email=?")) {
                delete.setLong(1, accountId);
                delete.setString(2, normalized);
                delete.executeUpdate();
            }
            if (blocked) try (PreparedStatement insert = connection.prepareStatement(
                    "INSERT INTO blocked_senders (account_id,sender_email) VALUES (?,?)")) {
                insert.setLong(1, accountId);
                insert.setString(2, normalized);
```

```
                insert.executeUpdate();
            }
        });
    }

    private Set<String> blockedSenders(Connection connection, long accountId) throws SQLException {
        Set<String> senders = new LinkedHashSet<>();
        try (PreparedStatement query = connection.prepareStatement("SELECT sender_email FROM blocked_senders
WHERE account_id=?")) {
            query.setLong(1, accountId);
            try (ResultSet rows = query.executeQuery()) {
                while (rows.next()) senders.add(rows.getString(1).trim().toLowerCase(Locale.ROOT));
            }
        }
        return senders;
    }

    public void updateReadStatus(long accountId, String id, boolean read) throws SQLException {
        transaction(connection -> {
            try (PreparedStatement update = connection.prepareStatement("UPDATE messages SET is_read=? WHERE
account_id=? AND gmail_message_id=?")) {
                update.setBoolean(1, read);
                update.setLong(2, accountId);
                update.setString(3, id);
                if (update.executeUpdate() == 0 && !messageExists(connection, accountId, id)) return;
            }
            try (PreparedStatement delete = connection.prepareStatement("DELETE FROM message_labels WHERE
account_id=? AND gmail_message_id=? AND gmail_label_id='UNREAD'")) {
                delete.setLong(1, accountId);
                delete.setString(2, id);
                delete.executeUpdate();
            }
            if (!read) try (PreparedStatement insert = connection.prepareStatement("INSERT INTO message_labels
(account_id,gmail_message_id,gmail_label_id) VALUES (?,?,'UNREAD')")) {
                insert.setLong(1, accountId);
                insert.setString(2, id);
                insert.executeUpdate();
            }
        });
    }

    private static boolean messageExists(Connection connection, long accountId, String id) throws SQLException {
        try (PreparedStatement query = connection.prepareStatement("SELECT 1 FROM messages WHERE account_id=?
AND gmail_message_id=?")) {
            query.setLong(1, accountId);
            query.setString(2, id);
            try (ResultSet rows = query.executeQuery()) { return rows.next(); }
        }
    }

    private static void deleteOne(Connection connection, String table, long accountId, String id) throws
SQLException {
        try (PreparedStatement delete = connection.prepareStatement("DELETE FROM " + table + " WHERE
account_id=? AND gmail_message_id=?")) {
            delete.setLong(1, accountId);
            delete.setString(2, id);
            delete.executeUpdate();
        }
    }

    @FunctionalInterface private interface Transaction { void run(Connection connection) throws SQLException; }

    private void transaction(Transaction action) throws SQLException {
        try (Connection connection = connections.open()) {
            connection.setAutoCommit(false);
            try {
                action.run(connection);
                connection.commit();
            } catch (SQLException | RuntimeException exception) {
                try { connection.rollback(); } catch (SQLException rollback) {
exception.addSuppressed(rollback); }
                throw exception;
            }
        }
    }

    private static Calendar utc() { return Calendar.getInstance(TimeZone.getTimeZone("UTC")); }
}
```

src/main/java/ems/storage/MailStore.java

```
package ems.storage;

import ems.model.Account;
import ems.model.EmailMessage;
import ems.model.Mailbox;
import ems.model.SpamResult;
import java.sql.SQLException;
import java.util.Collection;
import java.util.List;
```

```
import java.util.Optional;

/** Account-scoped local mailbox cache. Gmail is the source of mailbox truth. */
public interface MailStore {
    void initialize() throws SQLException;
    Account findOrCreateAccount(String email) throws SQLException;
    void saveMessages(long accountId, List<EmailMessage> messages) throws SQLException;
    void replaceSnapshot(long accountId, List<EmailMessage> messages) throws SQLException;
    List<EmailMessage> getMessages(long accountId, Mailbox mailbox, String query) throws SQLException;
    Optional<EmailMessage> findMessage(long accountId, String gmailMessageId) throws SQLException;
    SpamResult getSpamResult(long accountId, String gmailMessageId) throws SQLException;
    void saveFeedback(long accountId, String gmailMessageId, boolean spam) throws SQLException;
    void deleteMessages(long accountId, Collection<String> gmailMessageIds) throws SQLException;
}
```

src/main/java/ems/storage/ReasonJson.java

```
package ems.storage;

import java.sql.SQLException;
import java.util.ArrayList;
import java.util.List;

/** Minimal JSON string-array codec; avoids storing Java serialization in the database. */
final class ReasonJson {
    private ReasonJson() { }

    static String encode(List<String> values) {
        StringBuilder result = new StringBuilder("[");
        for (String value : values) {
            if (result.length() > 1) result.append(',');
            result.append('"');
            for (int i = 0; i < value.length(); i++) {
                char c = value.charAt(i);
                if (c == '"' || c == '\\') result.append('\\').append(c);
                else if (c < 32) result.append(String.format(java.util.Locale.ROOT, "\\u%04x", (int) c));
                else result.append(c);
            }
            result.append('"');
        }
        return result.append(']').toString();
    }

    static List<String> decode(String json) throws SQLException {
        List<String> values = new ArrayList<>();
        if (json == null || json.isBlank()) return values;
        String text = json.trim();
        if (!text.startsWith("[") || !text.endsWith("]")) throw new SQLException("Invalid stored spam
reasons.");
        int i = 1;
        while (i < text.length() - 1) {
            if (Character.isWhitespace(text.charAt(i)) || text.charAt(i) == ',') { i++; continue; }
            if (text.charAt(i++) != '"') throw new SQLException("Invalid stored spam reason.");
            StringBuilder value = new StringBuilder();
            boolean closed = false;
            while (i < text.length() - 1) {
                char c = text.charAt(i++);
                if (c == '"') { closed = true; break; }
                if (c != '\\') { value.append(c); continue; }
                if (i >= text.length() - 1) throw new SQLException("Invalid stored spam reason escape.");
                char escaped = text.charAt(i++);
                switch (escaped) {
                    case '"', '\\', '/' -> value.append(escaped);
                    case 'n' -> value.append('\n');
                    case 'r' -> value.append('\r');
                    case 't' -> value.append('\t');
                    case 'b' -> value.append('\b');
                    case 'f' -> value.append('\f');
                    case 'u' -> {
                        if (i + 4 > text.length() - 1) throw new SQLException("Invalid unicode escape in spam
reason.");
                        try { value.append((char) Integer.parseInt(text.substring(i, i + 4), 16)); }
                        catch (NumberFormatException bad) { throw new SQLException("Invalid unicode escape in
spam reason.", bad); }
                        i += 4;
                    }
                    default -> throw new SQLException("Invalid stored spam reason escape.");
                }
            }
            if (!closed) throw new SQLException("Unclosed stored spam reason.");
            values.add(value.toString());
        }
        return values;
    }
}
```

src/main/java/ems/storage/Schema.java

```
package ems.storage;
```

```
/** Keep table definitions aligned with sql/schema.sql. Database creation is an installation step. */
final class Schema {
    private Schema() { }
    static final String[] TABLES = {
        """
        CREATE TABLE IF NOT EXISTS accounts (
            account_id BIGINT AUTO_INCREMENT PRIMARY KEY,
            email_address VARCHAR(254) NOT NULL UNIQUE
        )
        """,
        """
        CREATE TABLE IF NOT EXISTS messages (
            account_id BIGINT NOT NULL,
            gmail_message_id VARCHAR(128) NOT NULL,
            sender_email VARCHAR(320) NOT NULL,
            subject TEXT NOT NULL,
            body_text LONGTEXT NOT NULL,
            received_at DATETIME(6) NOT NULL,
            is_read BOOLEAN NOT NULL DEFAULT TRUE,
            PRIMARY KEY (account_id, gmail_message_id),
            FOREIGN KEY (account_id) REFERENCES accounts(account_id)
        )
        """,
        """
        CREATE TABLE IF NOT EXISTS message_recipients (
            account_id BIGINT NOT NULL,
            gmail_message_id VARCHAR(128) NOT NULL,
            recipient_email VARCHAR(320) NOT NULL,
            PRIMARY KEY (account_id, gmail_message_id, recipient_email),
            FOREIGN KEY (account_id, gmail_message_id) REFERENCES messages(account_id, gmail_message_id) ON
DELETE CASCADE
        )
        """,
        """
        CREATE TABLE IF NOT EXISTS message_labels (
            account_id BIGINT NOT NULL,
            gmail_message_id VARCHAR(128) NOT NULL,
            gmail_label_id VARCHAR(128) NOT NULL,
            PRIMARY KEY (account_id, gmail_message_id, gmail_label_id),
            FOREIGN KEY (account_id, gmail_message_id) REFERENCES messages(account_id, gmail_message_id) ON
DELETE CASCADE
        )
        """,
        """
        CREATE TABLE IF NOT EXISTS spam_results (
            account_id BIGINT NOT NULL,
            gmail_message_id VARCHAR(128) NOT NULL,
            score INT NOT NULL,
            suspected_spam BOOLEAN NOT NULL,
            reasons TEXT NOT NULL,
            analyzed_at DATETIME(6) NOT NULL,
            PRIMARY KEY (account_id, gmail_message_id),
            FOREIGN KEY (account_id, gmail_message_id) REFERENCES messages(account_id, gmail_message_id) ON
DELETE CASCADE
        )
        """,
        """
        CREATE TABLE IF NOT EXISTS spam_feedback (
            account_id BIGINT NOT NULL,
            gmail_message_id VARCHAR(128) NOT NULL,
            user_marked_spam BOOLEAN NOT NULL,
            corrected_at DATETIME(6) NOT NULL,
            PRIMARY KEY (account_id, gmail_message_id),
            FOREIGN KEY (account_id) REFERENCES accounts(account_id)
        )
        """,
        """
        CREATE TABLE IF NOT EXISTS blocked_senders (
            account_id BIGINT NOT NULL,
            sender_email VARCHAR(320) NOT NULL,
            PRIMARY KEY (account_id, sender_email),
            FOREIGN KEY (account_id) REFERENCES accounts(account_id)
        )
        """
    };
}
```

src/main/java/ems/ui/ComposePanel.java

```
package ems.ui;

import java.awt.BorderLayout;
import java.awt.Color;
import java.awt.Dimension;
import java.awt.FlowLayout;
import java.awt.Font;
import java.awt.event.ActionEvent;
import java.awt.event.KeyEvent;
import java.util.Objects;
import java.util.function.Consumer;
import java.util.regex.Pattern;
import javax.swing.AbstractAction;
```

```
import javax.swing.BorderFactory;
import javax.swing.Box;
import javax.swing.BoxLayout;
import javax.swing.JButton;
import javax.swing.JComponent;
import javax.swing.JLabel;
import javax.swing.JPanel;
import javax.swing.JScrollPane;
import javax.swing.JTextArea;
import javax.swing.JTextField;
import javax.swing.KeyStroke;

/**
 * Reusable compose form. Validation stays local; the owner performs sending
 * through its service on a background worker and reports failures with showError.
 */
public final class ComposePanel extends JPanel {
    private static final long serialVersionUID = 1L;
    private static final Color ERROR = new Color(162, 51, 43);
    private static final Pattern ADDRESS = Pattern.compile(
            "^[^\\s@,;<>]+@[^\\s@,;<>.]+(?:\\.[^\\s@,;<>.]+)+$");

    /** Validated input, ready for the owner to submit through EmailService. */
    public static record Draft(String recipientEmail, String subject, String body) { }

    private final JTextField toField;
    private final JTextField subjectField;
    private final JTextArea bodyArea;
    private final JButton sendButton;
    private final JButton cancelButton;
    private final JLabel errorLabel;
    private final Consumer<Draft> onSend;
    private final Runnable onCancel;
    private boolean busy;

    public ComposePanel(
            String senderEmail,
            boolean demoMode,
            Consumer<Draft> onSend,
            Runnable onCancel) {
        this.onSend = Objects.requireNonNull(onSend, "onSend");
        this.onCancel = Objects.requireNonNull(onCancel, "onCancel");
        Objects.requireNonNull(senderEmail, "senderEmail");

        setName("composePanel");
        setLayout(new BorderLayout(0, 18));
        setBackground(UiTheme.SURFACE);
        setBorder(BorderFactory.createEmptyBorder(24, 28, 24, 28));
        setPreferredSize(new Dimension(660, 560));

        JPanel heading = column();
        heading.add(UiTheme.label("New message", Font.BOLD, 24, UiTheme.TEXT));
        heading.add(Box.createVerticalStrut(6));
        JLabel from = UiTheme.label("From: " + senderEmail, Font.PLAIN, 13, UiTheme.MUTED);
        from.putClientProperty("html.disable", Boolean.TRUE);
        heading.add(from);
        if (demoMode) {
            heading.add(Box.createVerticalStrut(12));
            JLabel notice = UiTheme.label(
                    "DEMO MODE  ·  Messages stay in the demo. Nothing is sent through Gmail.",
                    Font.PLAIN, 12, UiTheme.ACCENT);
            notice.setBorder(BorderFactory.createEmptyBorder(10, 12, 10, 12));
            notice.setOpaque(true);
            notice.setBackground(UiTheme.BACKGROUND);
            notice.setAlignmentX(LEFT_ALIGNMENT);
            heading.add(notice);
        }
        add(heading, BorderLayout.NORTH);

        JPanel fields = new JPanel(new BorderLayout(0, 14));
        fields.setOpaque(false);
        JPanel shortFields = column();
        toField = UiTheme.field("recipient@example.com");
        toField.setName("composeTo");
        toField.getAccessibleContext().setAccessibleName("Recipient email address");
        toField.getAccessibleContext().setAccessibleDescription("Enter one recipient email address.");
        addField(shortFields, "To", toField, KeyEvent.VK_T);
        shortFields.add(Box.createVerticalStrut(12));

        subjectField = UiTheme.field("Add a subject");
        subjectField.setName("composeSubject");
        subjectField.getAccessibleContext().setAccessibleName("Subject");
        subjectField.getAccessibleContext().setAccessibleDescription("Required, up to 200 characters.");
        addField(shortFields, "Subject", subjectField, KeyEvent.VK_S);
        fields.add(shortFields, BorderLayout.NORTH);

        JPanel bodyPanel = new JPanel(new BorderLayout(0, 7));
        bodyPanel.setOpaque(false);
        bodyArea = new JTextArea();
        bodyArea.setName("composeBody");
        bodyArea.setFont(UiTheme.font(Font.PLAIN, 14));
        bodyArea.setForeground(UiTheme.TEXT);
        bodyArea.setBackground(UiTheme.SURFACE);
```

```
    bodyArea.setCaretColor(UiTheme.ACCENT);
    bodyArea.setLineWrap(true);
    bodyArea.setWrapStyleWord(true);
    bodyArea.setBorder(BorderFactory.createEmptyBorder(10, 12, 10, 12));
    bodyArea.getAccessibleContext().setAccessibleName("Message body");
    bodyArea.getAccessibleContext().setAccessibleDescription("Required, up to 10,000 characters.");
    JLabel bodyLabel = UiTheme.label("Message", Font.BOLD, 13, UiTheme.TEXT);
    bodyLabel.setLabelFor(bodyArea);
    bodyLabel.setDisplayedMnemonic(KeyEvent.VK_M);
    bodyPanel.add(bodyLabel, BorderLayout.NORTH);
    JScrollPane bodyScroll = new JScrollPane(bodyArea);
    bodyScroll.setBorder(BorderFactory.createLineBorder(UiTheme.BORDER));
    bodyScroll.setPreferredSize(new Dimension(560, 180));
    bodyPanel.add(bodyScroll, BorderLayout.CENTER);
    fields.add(bodyPanel, BorderLayout.CENTER);
    add(fields, BorderLayout.CENTER);

    JPanel footer = new JPanel(new BorderLayout(0, 10));
    footer.setOpaque(false);
    errorLabel = UiTheme.label(" ", Font.PLAIN, 12, ERROR);
    errorLabel.setName("composeError");
    errorLabel.putClientProperty("html.disable", Boolean.TRUE);
    errorLabel.getAccessibleContext().setAccessibleName("Compose status");
    footer.add(errorLabel, BorderLayout.NORTH);
    JPanel actions = new JPanel(new BorderLayout());
    actions.setOpaque(false);
    actions.add(UiTheme.label("Ctrl+Enter to send", Font.PLAIN, 12, UiTheme.MUTED),
            BorderLayout.WEST);
    JPanel buttons = new JPanel(new FlowLayout(FlowLayout.RIGHT, 8, 0));
    buttons.setOpaque(false);
    cancelButton = UiTheme.secondaryButton("Cancel");
    cancelButton.setName("cancelComposeButton");
    cancelButton.addActionListener(event -> cancel());
    sendButton = UiTheme.primaryButton(demoMode ? "Send demo message" : "Send message");
    sendButton.setName("sendButton");
    sendButton.addActionListener(event -> submit());
    buttons.add(cancelButton);
    buttons.add(sendButton);
    actions.add(buttons, BorderLayout.EAST);
    footer.add(actions, BorderLayout.CENTER);
    add(footer, BorderLayout.SOUTH);

    getInputMap(JComponent.WHEN_ANCESTOR_OF_FOCUSED_COMPONENT).put(
            KeyStroke.getKeyStroke(KeyEvent.VK_ENTER, KeyEvent.CTRL_DOWN_MASK), "sendDraft");
    getActionMap().put("sendDraft", new AbstractAction() {
        @Override
        public void actionPerformed(ActionEvent event) {
            submit();
        }
    });
    getInputMap(JComponent.WHEN_ANCESTOR_OF_FOCUSED_COMPONENT).put(
            KeyStroke.getKeyStroke(KeyEvent.VK_ESCAPE, 0), "cancelCompose");
    getActionMap().put("cancelCompose", new AbstractAction() {
        @Override
        public void actionPerformed(ActionEvent event) {
            cancel();
        }
    });
}

/** The owner calls this on the Swing event-dispatch thread while sending. */
public void setBusy(boolean busy) {
    this.busy = busy;
    toField.setEnabled(!busy);
    subjectField.setEnabled(!busy);
    bodyArea.setEnabled(!busy);
    sendButton.setEnabled(!busy);
    cancelButton.setEnabled(!busy);
}

/** Shows a recoverable send error inline without discarding the draft. */
public void showError(String message) {
    String text = message == null || message.isBlank() ? " " : message;
    errorLabel.setText(text);
    errorLabel.setToolTipText(text.isBlank() ? null : "Status: " + text);
}

private void submit() {
    if (busy) {
        return;
    }
    String rawRecipient = toField.getText();
    String recipient = rawRecipient.trim();
    String rawSubject = subjectField.getText();
    String subject = rawSubject.trim();
    String body = bodyArea.getText();
    if (rawRecipient.indexOf('\r') >= 0 || rawRecipient.indexOf('\n') >= 0
            || recipient.length() > 254 || !ADDRESS.matcher(recipient).matches()) {
        showError("Enter one email address, such as name@example.com.");
        toField.requestFocusInWindow();
        return;
    }
    if (subject.isBlank() || subject.length() > 200
            || rawSubject.indexOf('\r') >= 0 || rawSubject.indexOf('\n') >= 0) {
        showError("Enter a subject between 1 and 200 characters.");
```

```
            subjectField.requestFocusInWindow();
            return;
        }
        if (body.isBlank() || body.length() > 10_000) {
            showError("Enter a message between 1 and 10,000 characters.");
            bodyArea.requestFocusInWindow();
            return;
        }
        showError(null);
        onSend.accept(new Draft(recipient, subject, body));
    }

    private void cancel() {
        if (!busy) {
            onCancel.run();
        }
    }

    private static JPanel column() {
        JPanel panel = new JPanel();
        panel.setOpaque(false);
        panel.setLayout(new BoxLayout(panel, BoxLayout.Y_AXIS));
        return panel;
    }

    private static void addField(JPanel panel, String title, JTextField field, int mnemonic) {
        JLabel label = UiTheme.label(title, Font.BOLD, 13, UiTheme.TEXT);
        label.setLabelFor(field);
        label.setDisplayedMnemonic(mnemonic);
        label.setAlignmentX(LEFT_ALIGNMENT);
        field.setAlignmentX(LEFT_ALIGNMENT);
        field.setMaximumSize(new Dimension(Integer.MAX_VALUE, 38));
        field.setPreferredSize(new Dimension(560, 38));
        panel.add(label);
        panel.add(Box.createVerticalStrut(6));
        panel.add(field);
    }
}
```

src/main/java/ems/ui/MailAppPanel.java

```
package ems.ui;

import ems.model.*;
import ems.service.EmailService;
import java.awt.*;
import java.awt.event.*;
import java.time.ZoneId;
import java.time.format.DateTimeFormatter;
import java.util.EnumMap;
import java.util.List;
import java.util.concurrent.Callable;
import java.util.concurrent.CancellationException;
import java.util.concurrent.ExecutionException;
import java.util.function.Consumer;
import javax.swing.*;
import javax.swing.border.*;
import javax.swing.table.DefaultTableCellRenderer;

/** Member 1 UI. All service calls execute off the Swing event-dispatch thread. */
public final class MailAppPanel extends JPanel {
    private static final DateTimeFormatter DATE = DateTimeFormatter
            .ofPattern("dd MMM yyyy, HH:mm").withZone(ZoneId.systemDefault());
    private final EmailService service;
    private final boolean demo;
    private final CardLayout cards = new CardLayout();
    private final JPanel pages = UiTheme.panel(cards, UiTheme.BACKGROUND);
    private final EnumMap<Mailbox, JButton> navigation = new EnumMap<>(Mailbox.class);
    private final MailTableModel tableModel = new MailTableModel();
    private final JTable table = new JTable(tableModel);
    private final JTextField search = UiTheme.field("Search sender, subject or message");
    private final JLabel status = UiTheme.label("Ready to connect", Font.PLAIN, 12, UiTheme.MUTED);
    private final JLabel title = UiTheme.label("Inbox", Font.BOLD, 28, UiTheme.TEXT);
    private final JLabel subtitle = UiTheme.label("", Font.PLAIN, 12, UiTheme.MUTED);
    private final JLabel accountLabel = UiTheme.label("", Font.PLAIN, 11, new Color(0xB9C9D4));
    private final JButton connect = UiTheme.primaryButton("Connect Gmail");
    private final JButton refresh = UiTheme.secondaryButton("Refresh");
    private final JButton compose = UiTheme.primaryButton("+  Compose");
    private final JButton disconnect = UiTheme.secondaryButton("Disconnect");
    private final JButton markSpam = UiTheme.secondaryButton("Mark as spam");
    private final JButton notSpam = UiTheme.secondaryButton("Not spam");
    private final JButton searchButton = UiTheme.secondaryButton("Search");
    private final JPanel reader = UiTheme.panel(new BorderLayout(), UiTheme.SURFACE);
    private final JPanel listCards = UiTheme.panel(new CardLayout(), UiTheme.SURFACE);
    private final JLabel emptyTitle = UiTheme.label("No messages here", Font.BOLD, 18, UiTheme.TEXT);
    private final JLabel emptyDetail = UiTheme.label("", Font.PLAIN, 12, UiTheme.MUTED);
    private Account account;
    private Mailbox mailbox = Mailbox.INBOX;
    private boolean busy;
    private boolean updatingTable;
    private boolean connected;
    private EmailMessage openedMessage;
```

```
    public MailAppPanel(EmailService service) { this(service, false); }

    public MailAppPanel(EmailService service, boolean demoMode) {
        super(new BorderLayout());
        this.service = java.util.Objects.requireNonNull(service, "service");
        demo = demoMode;
        setBackground(UiTheme.BACKGROUND);
        setBorder(new EmptyBorder(0, 0, 0, 0));
        if (demo) add(demoBanner(), BorderLayout.NORTH);
        pages.add(connectionPage(), "connect");
        pages.add(mailPage(), "mail");
        add(pages, BorderLayout.CENTER);
        JPanel footer = UiTheme.panel(new BorderLayout(), UiTheme.SURFACE);
        footer.setBorder(new CompoundBorder(new MatteBorder(1, 0, 0, 0, UiTheme.BORDER),
                new EmptyBorder(9, 20, 9, 20)));
        status.setName("statusLabel");
        footer.add(status);
        footer.add(UiTheme.label("MAILDESK", Font.BOLD, 10, UiTheme.MUTED), BorderLayout.EAST);
        add(footer, BorderLayout.SOUTH);
        wireActions();
        updateControls();
    }

    private JPanel demoBanner() {
        JPanel banner = UiTheme.panel(new FlowLayout(FlowLayout.LEFT, 20, 7), new Color(0xFFF3D6));
        banner.add(UiTheme.label("DEMO MODE", Font.BOLD, 11, new Color(0x805A16)));
        banner.add(UiTheme.label("Sample messages only. Nothing is sent to Gmail.", Font.PLAIN, 12,
                new Color(0x805A16)));
        return banner;
    }

    private JPanel connectionPage() {
        JPanel page = UiTheme.panel(new GridBagLayout(), UiTheme.BACKGROUND);
        JPanel card = UiTheme.panel(new BorderLayout(50, 0), UiTheme.SURFACE);
        card.setBorder(new CompoundBorder(new LineBorder(UiTheme.BORDER), new EmptyBorder(46, 46, 46, 46)));
        JPanel copy = UiTheme.panel(new GridBagLayout(), UiTheme.SURFACE);
        GridBagConstraints c = new GridBagConstraints();
        c.gridx = 0; c.anchor = GridBagConstraints.WEST; c.fill = GridBagConstraints.HORIZONTAL;
        c.weightx = 1; c.insets = new Insets(0, 0, 22, 0);
        addRow(copy, UiTheme.label("MAILDESK", Font.BOLD, 15, UiTheme.ACCENT), c, 0);
        addRow(copy, UiTheme.label("Make room for", Font.BOLD, 35, UiTheme.TEXT), c, 1);
        c.insets = new Insets(-20, 0, 24, 0);
        addRow(copy, UiTheme.label("what matters.", Font.BOLD, 35, UiTheme.TEXT), c, 2);
        c.insets = new Insets(0, 0, 12, 0);
        addRow(copy, UiTheme.label("Your mail, a focused workspace, and a second", Font.PLAIN, 14,
UiTheme.MUTED), c, 3);
        addRow(copy, UiTheme.label("look at messages that seem suspicious.", Font.PLAIN, 14, UiTheme.MUTED), c,
4);
        c.insets = new Insets(18, 0, 15, 0);
        connect.setName("connectButton");
        connect.setText(demo ? "Open demo mailbox  →" : "Connect Gmail  →");
        addRow(copy, connect, c, 5);
        c.insets = new Insets(0, 0, 6, 0);
        addRow(copy, UiTheme.label(demo ? "Try the screens with fictional messages." : "Sign in securely in your
browser with Google.",
                Font.PLAIN, 12, UiTheme.MUTED), c, 6);
        addRow(copy, UiTheme.label(demo ? "No account or internet connection needed." : "Your Gmail password is
never entered here.",
                Font.PLAIN, 12, UiTheme.MUTED), c, 7);
        card.add(copy, BorderLayout.CENTER);
        JPanel features = UiTheme.panel(new GridLayout(3, 1, 0, 16), UiTheme.SURFACE);
        features.setPreferredSize(new Dimension(280, 360));
        features.add(feature("01", "One clear inbox", "Read, search and write with less clutter."));
        features.add(feature("02", "A second look", "See why a message was flagged for review."));
        features.add(feature("03", "You're in control", "Correct spam decisions when needed."));
        card.add(features, BorderLayout.EAST);
        page.add(card);
        return page;
    }

    private JPanel feature(String number, String heading, String detail) {
        JPanel panel = UiTheme.panel(new BorderLayout(0, 8), UiTheme.BACKGROUND);
        panel.setBorder(new EmptyBorder(16, 18, 16, 18));
        panel.add(UiTheme.label(number + "  /  " + heading, Font.BOLD, 14, UiTheme.TEXT), BorderLayout.NORTH);
        JTextArea text = new JTextArea(detail);
        text.setFont(UiTheme.font(Font.PLAIN, 12)); text.setForeground(UiTheme.MUTED);
        text.setOpaque(false); text.setEditable(false); text.setLineWrap(true); text.setWrapStyleWord(true);
        panel.add(text);
        return panel;
    }

    private JPanel mailPage() {
        JPanel page = UiTheme.panel(new BorderLayout(), UiTheme.BACKGROUND);
        page.add(sidebar(), BorderLayout.WEST);
        JPanel workspace = UiTheme.panel(new BorderLayout(0, 20), UiTheme.BACKGROUND);
        workspace.setBorder(new EmptyBorder(25, 24, 20, 24));
        JPanel header = UiTheme.panel(new BorderLayout(12, 0), UiTheme.BACKGROUND);
        JPanel heading = UiTheme.panel(new GridLayout(2, 1, 0, 5), UiTheme.BACKGROUND);
        heading.add(title); heading.add(subtitle); header.add(heading);
        JPanel actions = UiTheme.panel(new FlowLayout(FlowLayout.RIGHT, 8, 0), UiTheme.BACKGROUND);
        refresh.setName("refreshButton"); actions.add(refresh); header.add(actions, BorderLayout.EAST);
        JPanel top = UiTheme.panel(new BorderLayout(0, 18), UiTheme.BACKGROUND);
        top.add(header, BorderLayout.NORTH);
```

```
        JPanel searchRow = UiTheme.panel(new BorderLayout(8, 0), UiTheme.BACKGROUND);
        search.setName("searchField"); searchButton.setName("searchButton");
        searchRow.add(search); searchRow.add(searchButton, BorderLayout.EAST);
        top.add(searchRow); workspace.add(top, BorderLayout.NORTH);
        configureTable();
        JScrollPane scroll = new JScrollPane(table);
        // Install explicitly so headless previews and native windows have the same header.
        scroll.setColumnHeaderView(table.getTableHeader());
        scroll.setBorder(BorderFactory.createEmptyBorder());
scroll.getViewport().setBackground(UiTheme.SURFACE);
        listCards.add(scroll, "messages");
        JPanel empty = UiTheme.panel(new GridBagLayout(), UiTheme.SURFACE);
        JPanel emptyCopy = UiTheme.panel(new GridLayout(2, 1, 0, 12), UiTheme.SURFACE);
        emptyCopy.add(emptyTitle); emptyCopy.add(emptyDetail); empty.add(emptyCopy);
        listCards.add(empty, "empty");
        JPanel list = UiTheme.panel(new BorderLayout(), UiTheme.SURFACE);
        list.setBorder(new LineBorder(UiTheme.BORDER));
        JLabel listTitle = UiTheme.label("MESSAGES", Font.BOLD, 10, UiTheme.MUTED);
        listTitle.setBorder(new EmptyBorder(15, 14, 12, 14)); list.add(listTitle, BorderLayout.NORTH);
        list.add(listCards);
        list.setMinimumSize(new Dimension(360, 300));
        reader.setMinimumSize(new Dimension(350, 300)); reader.setBorder(new LineBorder(UiTheme.BORDER));
        JSplitPane split = new JSplitPane(JSplitPane.HORIZONTAL_SPLIT, list, reader);
        split.setBorder(BorderFactory.createEmptyBorder()); split.setContinuousLayout(true);
        split.setResizeWeight(0.48); split.setDividerSize(9); split.setBackground(UiTheme.BACKGROUND);
        workspace.add(split); page.add(workspace); showReaderPlaceholder("Select a message", "Its contents and
spam review will appear here.");
        return page;
    }

    private JPanel sidebar() {
        JPanel sidebar = UiTheme.panel(new BorderLayout(0, 24), UiTheme.SIDEBAR);
        sidebar.setPreferredSize(new Dimension(212, 700));
        sidebar.setBorder(new EmptyBorder(30, 17, 18, 17));
        JPanel top = UiTheme.panel(new GridBagLayout(), UiTheme.SIDEBAR);
        GridBagConstraints c = new GridBagConstraints();
        c.gridx = 0; c.weightx = 1; c.fill = GridBagConstraints.HORIZONTAL; c.anchor = GridBagConstraints.WEST;
        c.insets = new Insets(0, 9, 5, 0);
        addRow(top, UiTheme.label("MAILDESK", Font.BOLD, 20, Color.WHITE), c, 0);
        addRow(top, UiTheme.label("A little more clarity.", Font.PLAIN, 11, new Color(0xB9C9D4)), c, 1);
        c.insets = new Insets(28, 0, 26, 0); compose.setName("composeButton"); addRow(top, compose, c, 2);
        c.insets = new Insets(0, 9, 12, 0);
        addRow(top, UiTheme.label("WORKSPACE", Font.BOLD, 10, new Color(0x91ACBC)), c, 3);
        int row = 4;
        for (Mailbox box : Mailbox.values()) {
            JButton button = new JButton(mailboxName(box));
            button.setHorizontalAlignment(SwingConstants.LEFT); button.setFont(UiTheme.font(Font.BOLD, 13));
            button.setOpaque(true); button.setFocusPainted(true);
            button.setBorder(new EmptyBorder(13, 12, 13, 8));
            button.setCursor(Cursor.getPredefinedCursor(Cursor.HAND_CURSOR));
            button.setName(switch (box) { case INBOX -> "inboxButton"; case SENT -> "sentButton";
                case SPAM -> "spamButton"; case SUSPECTED -> "suspectedButton"; });
            button.addActionListener(event -> changeMailbox(box));
            navigation.put(box, button); c.insets = new Insets(0, 0, 5, 0); addRow(top, button, c, row++);
        }
        sidebar.add(top, BorderLayout.NORTH);
        JPanel bottom = UiTheme.panel(new GridLayout(3, 1, 0, 9), UiTheme.SIDEBAR);
        bottom.add(UiTheme.label("CONNECTED ACCOUNT", Font.BOLD, 10, new Color(0x91ACBC)));
        bottom.add(accountLabel); disconnect.setName("disconnectButton"); bottom.add(disconnect);
        sidebar.add(bottom, BorderLayout.SOUTH);
        return sidebar;
    }

    private void configureTable() {
        table.setName("messageTable"); table.setSelectionMode(ListSelectionModel.SINGLE_SELECTION);
        table.setRowHeight(58); table.setShowGrid(false); table.setIntercellSpacing(new Dimension(0, 0));
        table.setBackground(UiTheme.SURFACE); table.setForeground(UiTheme.TEXT);
        table.setSelectionBackground(UiTheme.SELECTED); table.setSelectionForeground(UiTheme.TEXT);
        table.getTableHeader().setReorderingAllowed(false);
        table.getTableHeader().setBackground(new Color(0xF7F9FA));
        table.getTableHeader().setForeground(UiTheme.MUTED);
        table.getTableHeader().setFont(UiTheme.font(Font.BOLD, 10));
        table.getTableHeader().setPreferredSize(new Dimension(400, 35));
        table.setDefaultRenderer(Object.class, new DefaultTableCellRenderer() {
            @Override public Component getTableCellRendererComponent(JTable t, Object value,
                    boolean selected, boolean focused, int row, int column) {
                // Plain text only: mail content must not trigger Swing HTML rendering.
                putClientProperty("html.disable", Boolean.TRUE);
                super.getTableCellRendererComponent(t, value, selected, focused, row, column);
                setBorder(new CompoundBorder(new MatteBorder(0, 0, 1, 0, UiTheme.BORDER),
                        new EmptyBorder(0, 12, 0, 9)));
                setFont(UiTheme.font(tableModel.isUnread(row) ? Font.BOLD : Font.PLAIN, column == 2 ? 10 : 12));
                setForeground(column == 2 ? UiTheme.MUTED : UiTheme.TEXT);
                setBackground(selected ? UiTheme.SELECTED : UiTheme.SURFACE);
                setToolTipText("Message: " + value);
                return this;
            }
        });
        setColumnWidths();
        table.getSelectionModel().addListSelectionListener(event -> {
            if (!event.getValueIsAdjusting() && !updatingTable && !busy && table.getSelectedRow() >= 0) {
                open(tableModel.getMessageAt(table.getSelectedRow()).getGmailMessageId());
            }
        });
    }
```

```
    private void setColumnWidths() {
        table.getColumnModel().getColumn(0).setPreferredWidth(150);
        table.getColumnModel().getColumn(1).setPreferredWidth(215);
        table.getColumnModel().getColumn(2).setPreferredWidth(100);
    }

    private void wireActions() {
        connect.addActionListener(event -> runTask("Connecting…", () -> {
            Account value = service.connectGmail();
            return new Connected(value, service.getMessages(Mailbox.INBOX, ""), service.getLastWarning());
        }, result -> {
            account = result.account(); connected = true; mailbox = Mailbox.INBOX;
            accountLabel.setText(account.getEmailAddress()); accountLabel.setToolTipText("Account: " +
account.getEmailAddress());
            cards.show(pages, "mail"); applyMessages(result.messages());
            showNotice(withWarning(demo ? "Demo mailbox open. No Gmail connection is active."
                    : "Gmail connected. Inbox updated.", result.warning()), false);
            // Sign-in and synchronization are separate: a failed refresh must not erase
            // a valid Google grant or prevent the user from accessing the cached mailbox.
            runTask("Loading recent Gmail messages…", () -> {
                service.refreshRecent();
                return service.getMessages(Mailbox.INBOX, "");
            }, messages -> {
                applyMessages(messages);
                showNotice(demo ? "Demo mailbox open. No Gmail connection is active."
                        : "Sample mailbox loaded: up to 18 messages total (6 each from Inbox, Sent and Spam).",
false);
            });
        }));
        refresh.addActionListener(event -> load(true));
        searchButton.addActionListener(event -> load(false));
        search.addActionListener(event -> load(false));
        compose.addActionListener(event -> showCompose());
        disconnect.addActionListener(event -> close(() -> {
            account = null; connected = false; search.setText(""); tableModel.setMessages(List.of());
            openedMessage = null; cards.show(pages, "connect"); updateControls();
            showNotice("Disconnected. You can connect again when ready.", false);
        }));
        markSpam.setName("markSpamButton"); notSpam.setName("notSpamButton");
        markSpam.addActionListener(event -> correctSpam(true));
        notSpam.addActionListener(event -> correctSpam(false));
    }

    private void changeMailbox(Mailbox next) {
        if (busy || !connected) return;
        runTask("Loading " + mailboxName(next) + "…", () -> service.getMessages(next, ""), messages -> {
            mailbox = next; search.setText(""); applyMessages(messages);
            showNotice("Showing " + mailboxName(next).toLowerCase() + ".", false);
        });
        // The selected mailbox and query change only after the service succeeds.
    }

    private void load(boolean sync) {
        if (busy || !connected) return;
        String query = search.getText().strip();
        runTask(sync ? "Refreshing mailbox…" : "Searching messages…", () -> {
            if (sync) service.refresh();
            return service.getMessages(mailbox, query);
        }, messages -> {
            applyMessages(messages);
            showNotice(messages.size() + (messages.size() == 1 ? " message" : " messages")
                    + (query.isEmpty() ? " in this view." : " matching your search."), false);
        });
    }

    private void applyMessages(List<EmailMessage> messages) {
        updatingTable = true;
        tableModel.setSent(mailbox == Mailbox.SENT); tableModel.setMessages(messages); setColumnWidths();
        table.clearSelection(); updatingTable = false;
        openedMessage = null;
        title.setText(mailboxName(mailbox));
        subtitle.setText(switch (mailbox) {
            case INBOX -> "A clear view of what has arrived.";
            case SENT -> "Messages you have sent.";
            case SPAM -> "Messages classified as spam in Gmail.";
            case SUSPECTED -> "Our detector's suggestions. Review before deciding.";
        });
        ((CardLayout) listCards.getLayout()).show(listCards, messages.isEmpty() ? "empty" : "messages");
        emptyTitle.setText(search.getText().isBlank() ? "All clear here" : "No matching messages");
        emptyDetail.setText(search.getText().isBlank() ? "Refresh to check for new messages." : "Try another
search or clear the search field.");
        showReaderPlaceholder("Select a message", "Read it here without leaving your inbox.");
        updateControls(); revalidate(); repaint();
    }

    private void open(String id) {
        Mailbox currentMailbox = mailbox;
        String query = search.getText().strip();
        openedMessage = null;
        showReaderPlaceholder("Opening message…", "Loading the message and its review.");
        runTask("Opening message…", () -> new Opened(service.openMessage(id), service.getSpamResult(id),
                service.getMessages(currentMailbox, query)), result -> {
            updatingTable = true; tableModel.setMessages(result.messages());
            for (int row = 0; row < tableModel.getRowCount(); row++) {
```

```
                if (tableModel.getMessageAt(row).getGmailMessageId().equals(id))
table.setRowSelectionInterval(row, row);
            }
            updatingTable = false; openedMessage = result.message();
            showMessage(result.message(), result.result());
            showNotice("Message opened.", false);
        }, error -> {
            updatingTable = true; table.clearSelection(); updatingTable = false;
            showReaderPlaceholder("Couldn't open this message", "Select it again to retry, or refresh your
mailbox.");
            showNotice(error, true);
        });
    }

    private void showReaderPlaceholder(String heading, String detail) {
        reader.removeAll();
        JPanel center = UiTheme.panel(new GridBagLayout(), UiTheme.SURFACE);
        JPanel text = UiTheme.panel(new GridLayout(3, 1, 0, 12), UiTheme.SURFACE);
        text.add(UiTheme.label("✉", Font.PLAIN, 42, UiTheme.ACCENT));
        text.add(UiTheme.label(heading, Font.BOLD, 20, UiTheme.TEXT));
        text.add(UiTheme.label(detail, Font.PLAIN, 12, UiTheme.MUTED)); center.add(text); reader.add(center);
        reader.revalidate(); reader.repaint();
    }

    private void showMessage(EmailMessage message, SpamResult result) {
        reader.removeAll();
        JPanel content = UiTheme.panel(new BorderLayout(0, 18), UiTheme.SURFACE);
        content.setBorder(new EmptyBorder(24, 24, 20, 24));
        ReaderArticle article = new ReaderArticle();
        JTextArea subject = plainText(message.getSubject().isBlank() ? "(No subject)" : message.getSubject(),
22, Font.BOLD);
        subject.setName("messageSubject"); article.add(subject);
        article.add(plainText("From  " + message.getSenderEmail(), 12, Font.BOLD));
        JTextArea recipients = plainText("To  " + String.join(", ", message.getRecipientEmails()), 12,
Font.PLAIN);
        recipients.setForeground(UiTheme.MUTED); article.add(recipients);
        article.add(UiTheme.label(DATE.format(message.getReceivedAt()), Font.PLAIN, 11, UiTheme.MUTED));
        if (mailbox != Mailbox.SENT) {
            ReaderColumn review = new ReaderColumn(6);
            review.setBackground(result.isSuspectedSpam() ? new Color(0xFFF5DE) : new Color(0xEDF5F2));
            review.setBorder(new EmptyBorder(12, 12, 12, 12));
            review.add(UiTheme.label(result.isSuspectedSpam() ? "Review suggested · Score " + result.getScore()
                    : "No rule flag · Score " + result.getScore(), Font.BOLD, 12, UiTheme.TEXT));
            String reasons = result.getReasons().isEmpty() ? "A rule score is not a guarantee of safety."
                    : String.join("\n", result.getReasons());
            JTextArea explanation = plainText(reasons, 11, Font.PLAIN); explanation.setName("spamReasons");
            review.add(explanation); article.add(review);
        }
        article.add(Box.createVerticalStrut(8));
        JTextArea body = plainText(message.getBodyText().isBlank() ? "(This message has no plain-text content.)"
: message.getBodyText(), 14, Font.PLAIN);
        body.setName("messageBody"); body.setBorder(new EmptyBorder(4, 0, 12, 8));
        article.add(body);
        JScrollPane scroll = new JScrollPane(article); scroll.setBorder(BorderFactory.createEmptyBorder());
        scroll.setHorizontalScrollBarPolicy(ScrollPaneConstants.HORIZONTAL_SCROLLBAR_NEVER);
        scroll.getVerticalScrollBar().setUnitIncrement(18);
        scroll.getViewport().setBackground(UiTheme.SURFACE); content.add(scroll);
        JPanel actions = UiTheme.panel(new FlowLayout(FlowLayout.LEFT, 6, 0), UiTheme.SURFACE);
        if (mailbox != Mailbox.SENT) { actions.add(markSpam); actions.add(notSpam); }
        content.add(actions, BorderLayout.SOUTH); reader.add(content); reader.revalidate(); reader.repaint();
    }

    private void correctSpam(boolean spam) {
        if (busy || openedMessage == null) return;
        String id = openedMessage.getGmailMessageId();
        Mailbox currentMailbox = mailbox;
        String query = search.getText().strip();
        runTask(spam ? "Marking as spam…" : "Saving correction…", () -> {
            if (spam) service.markAsSpam(id); else service.markAsNotSpam(id);
            return new UpdatedMailbox(service.getMessages(currentMailbox, query), service.getLastWarning());
        }, result -> {
            applyMessages(result.messages());
            showNotice(withWarning(spam ? "Marked as spam. Your correction was saved."
                    : "Marked as not spam. Your correction was saved.", result.warning()), false);
        });
    }

    private void showCompose() {
        if (busy || account == null) return;
        JDialog dialog = new JDialog(SwingUtilities.getWindowAncestor(this), "New message",
Dialog.ModalityType.APPLICATION_MODAL);
        ComposePanel[] editor = new ComposePanel[1];
        editor[0] = new ComposePanel(account.getEmailAddress(), demo, draft -> {
            editor[0].setBusy(true);
            runTask(demo ? "Sending demo message…" : "Sending message…",
                    () -> new SentMessage(service.sendMessage(draft.recipientEmail(), draft.subject(),
draft.body()),
                            service.getLastWarning()), result -> {
                        dialog.dispose();
                        String notice = withWarning(demo ? "Demo message added to Sent. Nothing was sent to
Gmail."
                                : "Message sent successfully.", result.warning());
                        showNotice(notice, false);
                        if (mailbox == Mailbox.SENT) {
                            String sentQuery = search.getText().strip();
```

```
                            runTask("Updating Sent…", () -> service.getMessages(Mailbox.SENT, sentQuery),
                                    messages -> { applyMessages(messages); showNotice(notice, false); },
                                    error -> showNotice(notice + " " + error, true));
                        }
                    }, error -> {
                        editor[0].setBusy(false); editor[0].showError(error); showNotice(error, true);
                    });
        }, dialog::dispose);
        dialog.setContentPane(editor[0]); dialog.setDefaultCloseOperation(WindowConstants.DO_NOTHING_ON_CLOSE);
        dialog.addWindowListener(new WindowAdapter() {
            @Override public void windowClosing(WindowEvent event) { if (!busy) dialog.dispose(); }
        });
        dialog.pack(); dialog.setMinimumSize(new Dimension(600, 530));
        dialog.setLocationRelativeTo(this); dialog.setVisible(true);
    }

    public boolean isBusy() { return busy; }

    public void showNotice(String message, boolean error) {
        status.setText(message); status.setForeground(error ? new Color(0xAA342A) : UiTheme.MUTED);
        status.setToolTipText("Status: " + message);
    }

    /** Finishes disconnection on a worker before invoking the callback on the EDT. */
    public void close(Runnable afterClose) {
        if (busy) return;
        runTask("Disconnecting…", () -> { service.disconnect(); return Boolean.TRUE; }, result -> {
            connected = false; afterClose.run();
        });
    }

    private void updateControls() {
        connect.setEnabled(!busy);
        for (var entry : navigation.entrySet()) {
            entry.getValue().setEnabled(connected && !busy);
            entry.getValue().setBackground(entry.getKey() == mailbox ? new Color(0x2D4C59) : UiTheme.SIDEBAR);
            entry.getValue().setForeground(entry.getKey() == mailbox ? Color.WHITE : new Color(0xC0CFD8));
        }
        for (JComponent control : new JComponent[] {refresh, compose, disconnect, search, searchButton, table})
{
            control.setEnabled(connected && !busy);
        }
        boolean canCorrect = connected && !busy && openedMessage != null
                && mailbox != Mailbox.SENT;
        markSpam.setEnabled(canCorrect); notSpam.setEnabled(canCorrect);
        setCursor(Cursor.getPredefinedCursor(busy ? Cursor.WAIT_CURSOR : Cursor.DEFAULT_CURSOR));
    }

    private <T> void runTask(String activity, Callable<T> work, Consumer<T> success) {
        runTask(activity, work, success, error -> showNotice(error, true));
    }

    private <T> void runTask(String activity, Callable<T> work, Consumer<T> success, Consumer<String> failure) {
        if (busy) return;
        busy = true; updateControls(); showNotice(activity, false);
        new SwingWorker<T, Void>() {
            @Override protected T doInBackground() throws Exception { return work.call(); }
            @Override protected void done() {
                busy = false;
                try {
                    T result = get();
                    success.accept(result);
                } catch (InterruptedException exception) {
                    Thread.currentThread().interrupt(); failure.accept("The operation was interrupted. Please
try again.");
                } catch (ExecutionException exception) {
                    Throwable cause = exception.getCause();
                    String message = cause instanceof ems.exception.AppException ? cause.getMessage()
                            : "The operation could not finish. Please try again.";
                    failure.accept(message == null || message.isBlank() ? "The operation could not finish." :
message);
                } catch (CancellationException exception) {
                    failure.accept("The operation was cancelled.");
                } finally { updateControls(); }
            }
        }.execute();
    }

    private static JTextArea plainText(String text, int size, int style) {
        JTextArea area = new JTextArea(text);
        area.setFont(UiTheme.font(style, size)); area.setForeground(UiTheme.TEXT);
        area.setOpaque(false); area.setEditable(false); area.setLineWrap(true); area.setWrapStyleWord(true);
        area.setCaretPosition(0); return area;
    }

    private static String mailboxName(Mailbox box) {
        return switch (box) { case INBOX -> "Inbox"; case SENT -> "Sent"; case SPAM -> "Gmail Spam";
            case SUSPECTED -> "Suspected Spam"; };
    }

    private static void addRow(JPanel panel, JComponent component, GridBagConstraints c, int row) {
        c.gridy = row; panel.add(component, c);
    }
```

```
    private static String withWarning(String message, String warning) {
        return warning == null || warning.isBlank() ? message : message + " " + warning;
    }

    private record Connected(Account account, List<EmailMessage> messages, String warning) { }
    private record UpdatedMailbox(List<EmailMessage> messages, String warning) { }
    private record SentMessage(String id, String warning) { }
    private record Opened(EmailMessage message, SpamResult result, List<EmailMessage> messages) { }

    /**
     * Measures wrapped text at its allocated width before computing scroll height.
     * Standard BorderLayout/BoxLayout preferences can use a text area's old width,
     * cutting off its final lines after a narrow viewport is assigned.
     */
    private static class ReaderColumn extends JPanel {
        private final int gap;

        ReaderColumn(int gap) {
            super(null);
            this.gap = gap;
            setBackground(UiTheme.SURFACE);
        }

        @Override public Dimension getPreferredSize() {
            int width = getParent() instanceof JViewport viewport
                    ? viewport.getExtentSize().width : getWidth();
            if (width <= 0) width = 420;
            return new Dimension(width, heightForWidth(width));
        }

        private int heightForWidth(int width) {
            Insets insets = getInsets();
            int available = Math.max(1, width - insets.left - insets.right);
            int height = insets.top + insets.bottom;
            boolean first = true;
            for (Component child : getComponents()) {
                if (!child.isVisible()) continue;
                if (!first) height += gap;
                height += childHeight(child, available);
                first = false;
            }
            return height;
        }

        @Override public void doLayout() {
            Insets insets = getInsets();
            int width = Math.max(1, getWidth() - insets.left - insets.right);
            int y = insets.top;
            boolean first = true;
            for (Component child : getComponents()) {
                if (!child.isVisible()) continue;
                if (!first) y += gap;
                int height = childHeight(child, width);
                child.setBounds(insets.left, y, width, height);
                y += height;
                first = false;
            }
        }

        private static int childHeight(Component child, int width) {
            if (child instanceof ReaderColumn column) return column.heightForWidth(width);
            if (child instanceof JTextArea text) {
                Insets insets = text.getInsets();
                javax.swing.text.View view = text.getUI().getRootView(text);
                view.setSize(Math.max(1, width - insets.left - insets.right), Integer.MAX_VALUE);
                return (int) Math.ceil(view.getPreferredSpan(javax.swing.text.View.Y_AXIS))
                        + insets.top + insets.bottom;
            }
            return child.getPreferredSize().height;
        }
    }

    /** Incoming headers, spam reasons and body share one width-tracking scroll area. */
    private static final class ReaderArticle extends ReaderColumn implements Scrollable {
        ReaderArticle() { super(10); }
        @Override public Dimension getPreferredScrollableViewportSize() { return new Dimension(420, 500); }
        @Override public int getScrollableUnitIncrement(Rectangle r, int orientation, int direction) { return
18; }
        @Override public int getScrollableBlockIncrement(Rectangle r, int orientation, int direction) { return
Math.max(18, r.height - 36); }
        @Override public boolean getScrollableTracksViewportWidth() { return true; }
        @Override public boolean getScrollableTracksViewportHeight() { return false; }
    }
}
```

src/main/java/ems/ui/MailTableModel.java

```
package ems.ui;
```

```
import ems.model.EmailMessage;
import java.time.ZoneId;
import java.time.format.DateTimeFormatter;
import java.util.List;
import javax.swing.table.AbstractTableModel;

/** Table keeps message IDs with their rows; the UI never identifies mail by subject. */
public final class MailTableModel extends AbstractTableModel {
    private static final DateTimeFormatter DATE = DateTimeFormatter.ofPattern("dd MMM, HH:mm")
            .withZone(ZoneId.systemDefault());
    private List<EmailMessage> messages = List.of();
    private boolean sent;

    public void setMessages(List<EmailMessage> messages) {
        this.messages = List.copyOf(messages);
        fireTableDataChanged();
    }

    public void setSent(boolean sent) {
        this.sent = sent;
        fireTableStructureChanged();
    }

    public EmailMessage getMessageAt(int row) { return messages.get(row); }
    public boolean isUnread(int row) {
        return messages.get(row).getGmailLabelIds().contains("UNREAD");
    }
    @Override public int getRowCount() { return messages.size(); }
    @Override public int getColumnCount() { return 3; }
    @Override public String getColumnName(int column) {
        return switch (column) {
            case 0 -> sent ? "TO" : "FROM";
            case 1 -> "SUBJECT";
            default -> sent ? "SENT AT" : "RECEIVED";
        };
    }
    @Override public Object getValueAt(int row, int column) {
        EmailMessage message = messages.get(row);
        return switch (column) {
            case 0 -> sent ? String.join(", ", message.getRecipientEmails()) : message.getSenderEmail();
            case 1 -> message.getSubject().isBlank() ? "(No subject)" : message.getSubject();
            default -> DATE.format(message.getReceivedAt());
        };
    }
}
```

src/main/java/ems/ui/MainFrame.java

```
package ems.ui;

import ems.service.EmailService;
import java.awt.*;
import java.awt.event.*;
import javax.swing.*;

/** Production integration: construct on the EDT with Member 2's EmailService. */
public final class MainFrame extends JFrame {
    private final MailAppPanel appPanel;

    public MainFrame(EmailService service) { this(service, false); }

    public MainFrame(EmailService service, boolean demoMode) {
        super(demoMode ? "Maildesk — Interface demo" : "Maildesk — Email management");
        if (!SwingUtilities.isEventDispatchThread()) {
            throw new IllegalStateException("Create MainFrame on the Swing event-dispatch thread.");
        }
        appPanel = new MailAppPanel(service, demoMode);
        setContentPane(appPanel);
        setDefaultCloseOperation(DO_NOTHING_ON_CLOSE);
        Rectangle available = GraphicsEnvironment.getLocalGraphicsEnvironment().getMaximumWindowBounds();
        setMinimumSize(new Dimension(Math.min(1100, available.width), Math.min(700, available.height)));
        setSize(Math.min(1360, available.width), Math.min(860, available.height));
        setLocationRelativeTo(null);
        addWindowListener(new WindowAdapter() {
            @Override public void windowClosing(WindowEvent event) {
                if (appPanel.isBusy()) {
                    appPanel.showNotice("Please wait for the current operation to finish.", true);
                    return;
                }
                appPanel.close(MainFrame.this::dispose);
            }
        });
    }

    public MailAppPanel getAppPanel() { return appPanel; }
}
```

src/main/java/ems/ui/UiTheme.java

```
package ems.ui;

import java.awt.*;
import javax.swing.*;
import javax.swing.border.*;

/** Small, dependency-free style helpers shared by Member 1's screens. */
public final class UiTheme {
    public static final Color BACKGROUND = new Color(0xF4F6F8);
    public static final Color SURFACE = Color.WHITE;
    public static final Color TEXT = new Color(0x182C3C);
    public static final Color MUTED = new Color(0x667684);
    public static final Color ACCENT = new Color(0x117568);
    public static final Color BORDER = new Color(0xDFE5E9);
    public static final Color SIDEBAR = new Color(0x172C3C);
    public static final Color SELECTED = new Color(0xEAF4F1);

    private UiTheme() { }

    public static void install() {
        try {
            UIManager.setLookAndFeel(UIManager.getCrossPlatformLookAndFeelClassName());
        } catch (Exception ignored) {
            // Swing's installed look and feel remains usable.
        }
        Font base = font(Font.PLAIN, 13);
        for (String key : new String[] {"Label.font", "Button.font", "TextField.font",
                "TextArea.font", "Table.font", "TableHeader.font", "OptionPane.messageFont",
                "OptionPane.buttonFont", "ToolTip.font"}) {
            UIManager.put(key, base);
        }
        UIManager.put("Panel.background", BACKGROUND);
        UIManager.put("ScrollBar.width", 11);
        UIManager.put("TextField.selectionBackground", new Color(0xC4E4DE));
    }

    public static Font font(int style, int size) {
        return new Font("SansSerif", style, size);
    }

    public static JLabel label(String text, int style, int size, Color color) {
        JLabel label = new JLabel();
        label.putClientProperty("html.disable", Boolean.TRUE);
        label.setText(text);
        label.setFont(font(style, size));
        label.setForeground(color);
        return label;
    }

    public static JButton primaryButton(String text) {
        return button(text, ACCENT, Color.WHITE);
    }

    public static JButton secondaryButton(String text) {
        return button(text, SURFACE, TEXT);
    }

    private static JButton button(String text, Color background, Color foreground) {
        JButton button = new JButton(text);
        button.setFont(font(Font.BOLD, 13));
        button.setBackground(background);
        button.setForeground(foreground);
        button.setOpaque(true);
        button.setContentAreaFilled(true);
        button.setFocusPainted(true);
        button.setBorder(new CompoundBorder(new LineBorder(
                background.equals(SURFACE) ? BORDER : background, 1, true),
                new EmptyBorder(10, 16, 10, 16)));
        button.setCursor(Cursor.getPredefinedCursor(Cursor.HAND_CURSOR));
        return button;
    }

    public static JTextField field(String placeholder) {
        JTextField field = new JTextField() {
            @Override protected void paintComponent(Graphics graphics) {
                super.paintComponent(graphics);
                if (getText().isEmpty() && !isFocusOwner()) {
                    Graphics2D g = (Graphics2D) graphics.create();
                    g.setFont(getFont());
                    g.setColor(MUTED);
                    g.drawString(placeholder, getInsets().left,
                            (getHeight() - g.getFontMetrics().getHeight()) / 2
                                    + g.getFontMetrics().getAscent());
                    g.dispose();
                }
            }
        };
        field.setFont(font(Font.PLAIN, 13));
        field.setForeground(TEXT);
```

```
        field.setBackground(SURFACE);
        field.setBorder(new CompoundBorder(new LineBorder(BORDER, 1, true),
                new EmptyBorder(10, 12, 10, 12)));
        field.getAccessibleContext().setAccessibleName(placeholder);
        return field;
    }

    static JPanel panel(java.awt.LayoutManager layout, Color color) {
        JPanel panel = new JPanel(layout);
        panel.setBackground(color);
        return panel;
    }
}
```

APPENDIX A.2 — DEMONSTRATION JAVA

src/demo/java/ems/demo/DemoApp.java

```
package ems.demo;

import ems.ui.MainFrame;
import ems.ui.UiTheme;

import javax.swing.SwingUtilities;

/** Starts the interface with fictional, nonpersistent local data. */
public final class DemoApp {
    private DemoApp() {
    }

    public static void main(String[] args) {
        SwingUtilities.invokeLater(() -> {
            UiTheme.install();
            MainFrame frame = new MainFrame(new DemoEmailService(), true);
            frame.setVisible(true);
        });
    }
}
```

src/demo/java/ems/demo/DemoEmailService.java

```
package ems.demo;

import ems.exception.AppException;
import ems.model.Account;
import ems.model.EmailMessage;
import ems.model.Mailbox;
import ems.model.SpamResult;
import ems.service.EmailService;

import java.time.Instant;
import java.time.temporal.ChronoUnit;
import java.util.ArrayList;
import java.util.Comparator;
import java.util.LinkedHashMap;
import java.util.LinkedHashSet;
import java.util.List;
import java.util.Locale;
import java.util.Map;
import java.util.Set;
import java.util.regex.Pattern;

/**
 * In-memory demonstration only. This class never authenticates with Google,
 * contacts a mail server, sends an actual email, or stores data on disk.
 */
public final class DemoEmailService implements EmailService {
    private static final Account ACCOUNT = new Account(1L, "student@example.test");
    private static final Pattern EMAIL_ADDRESS = Pattern.compile(
            "^[^\\s@,;]+@[^\\s@,;]+\\.[^\\s@,;]+$");
    private static final Instant SAMPLE_TIME = Instant.parse("2026-10-20T06:00:00Z");

    private final Map<String, EmailMessage> messages = new LinkedHashMap<>();
    private final Map<String, SpamResult> spamResults = new LinkedHashMap<>();
    private final Map<String, Boolean> spamOverrides = new LinkedHashMap<>();
    private boolean connected;
    private long nextSentId = 1L;

    public DemoEmailService() {
        seedMessages();
    }

    @Override
    public synchronized Account connectGmail() {
```

```
    connected = true;
    return ACCOUNT;
}

@Override
public synchronized void disconnect() {
    connected = false;
}

@Override
public synchronized void refresh() throws AppException {
    requireConnected();
    // Demo data is local. Explicit corrections survive refresh/reconnect.
    for (String messageId : messages.keySet()) {
        Boolean override = spamOverrides.get(messageId);
        if (override != null) {
            spamResults.put(messageId, correctionResult(override));
        }
    }
}

@Override
public synchronized List<EmailMessage> getMessages(Mailbox mailbox, String query)
        throws AppException {
    requireConnected();
    if (mailbox == null) {
        throw new AppException("Choose a mailbox first.");
    }
    String search = query == null ? "" : query.strip().toLowerCase(Locale.ROOT);
    List<EmailMessage> result = new ArrayList<>();
    for (EmailMessage message : messages.values()) {
        if (belongsToMailbox(message, mailbox) && matchesSearch(message, search)) {
            result.add(message);
        }
    }
    result.sort(Comparator.comparing(EmailMessage::getReceivedAt)
            .reversed().thenComparing(EmailMessage::getGmailMessageId));
    return List.copyOf(result);
}

@Override
public synchronized EmailMessage openMessage(String gmailMessageId) throws AppException {
    EmailMessage message = requireMessage(gmailMessageId);
    if (message.getGmailLabelIds().contains("UNREAD")) {
        Set<String> labels = new LinkedHashSet<>(message.getGmailLabelIds());
        labels.remove("UNREAD");
        message = withLabels(message, labels);
        messages.put(gmailMessageId, message);
    }
    return message;
}

@Override
public synchronized String sendMessage(String recipientEmail, String subject, String body)
        throws AppException {
    requireConnected();
    String recipient = recipientEmail == null ? "" : recipientEmail.strip();
    String cleanSubject = subject == null ? "" : subject.strip();
    if (recipient.length() > 254 || !EMAIL_ADDRESS.matcher(recipient).matches()) {
        throw new AppException("Enter one valid recipient email address.");
    }
    if (cleanSubject.isEmpty() || cleanSubject.length() > 200) {
        throw new AppException("The subject must contain 1 to 200 characters.");
    }
    if (body == null || body.isBlank() || body.length() > 10_000) {
        throw new AppException("The message must contain 1 to 10,000 characters.");
    }
    String messageId = "demo-sent-" + nextSentId++;
    Set<String> labels = new LinkedHashSet<>();
    labels.add("SENT");
    if (recipient.equalsIgnoreCase(ACCOUNT.getEmailAddress())) {
        labels.add("INBOX");
    }
    EmailMessage message = new EmailMessage(ACCOUNT.getAccountId(), messageId,
            ACCOUNT.getEmailAddress(), List.of(recipient), cleanSubject, body,
            Instant.now(), Set.copyOf(labels));
    messages.put(messageId, message);
    spamResults.put(messageId, new SpamResult(0, false,
            List.of("Created locally in demo mode; no email was delivered.")));
    return messageId;
}

@Override
public synchronized SpamResult getSpamResult(String gmailMessageId) throws AppException {
    requireMessage(gmailMessageId);
    return spamResults.get(gmailMessageId);
}

@Override
public synchronized void markAsSpam(String gmailMessageId) throws AppException {
    EmailMessage message = requireReceivedMessage(gmailMessageId);
    Set<String> labels = new LinkedHashSet<>(message.getGmailLabelIds());
    labels.remove("INBOX");
    labels.add("SPAM");
```

```
    messages.put(gmailMessageId, withLabels(message, labels));
    spamOverrides.put(gmailMessageId, true);
    spamResults.put(gmailMessageId, correctionResult(true));
}

@Override
public synchronized void markAsNotSpam(String gmailMessageId) throws AppException {
    EmailMessage message = requireReceivedMessage(gmailMessageId);
    Set<String> labels = new LinkedHashSet<>(message.getGmailLabelIds());
    labels.remove("SPAM");
    labels.add("INBOX");
    messages.put(gmailMessageId, withLabels(message, labels));
    spamOverrides.put(gmailMessageId, false);
    spamResults.put(gmailMessageId, correctionResult(false));
}

private void requireConnected() throws AppException {
    if (!connected) {
        throw new AppException("Connect the demo account before opening your mailbox.");
    }
}

private EmailMessage requireMessage(String messageId) throws AppException {
    requireConnected();
    EmailMessage message = messages.get(messageId);
    if (message == null || message.getAccountId() != ACCOUNT.getAccountId()) {
        throw new AppException("This message is unavailable in the connected account.");
    }
    return message;
}

private EmailMessage requireReceivedMessage(String messageId) throws AppException {
    EmailMessage message = requireMessage(messageId);
    if (message.getGmailLabelIds().contains("SENT")
            && !message.getGmailLabelIds().contains("INBOX")
            && !message.getGmailLabelIds().contains("SPAM")) {
        throw new AppException("Spam corrections apply to received messages.");
    }
    return message;
}

private boolean belongsToMailbox(EmailMessage message, Mailbox mailbox) {
    Set<String> labels = message.getGmailLabelIds();
    return switch (mailbox) {
        case INBOX -> labels.contains("INBOX") && !labels.contains("SPAM");
        case SENT -> labels.contains("SENT");
        case SPAM -> labels.contains("SPAM");
        case SUSPECTED -> !labels.contains("SPAM") && !labels.contains("SENT")
                && spamResults.get(message.getGmailMessageId()).isSuspectedSpam();
    };
}

private boolean matchesSearch(EmailMessage message, String query) {
    if (query.isEmpty()) {
        return true;
    }
    String searchable = message.getSenderEmail() + "\n"
            + String.join("\n", message.getRecipientEmails()) + "\n"
            + message.getSubject() + "\n" + message.getBodyText();
    return searchable.toLowerCase(Locale.ROOT).contains(query);
}

private static EmailMessage withLabels(EmailMessage message, Set<String> labels) {
    return new EmailMessage(message.getAccountId(), message.getGmailMessageId(),
            message.getSenderEmail(), message.getRecipientEmails(), message.getSubject(),
            message.getBodyText(), message.getReceivedAt(), Set.copyOf(labels));
}

private static SpamResult correctionResult(boolean spam) {
    return new SpamResult(spam ? 100 : 0, spam,
            List.of(spam ? "You marked this message as spam."
                    : "You marked this message as not spam."));
}

private void seedMessages() {
    add("demo-meeting", "maya@campus.test", "Project catch-up at 4 PM",
            "Hi! Let's meet in the library at 4 PM to review the email management project.\n\n"
                    + "Please bring your screen sketches and the shared method contract.\n\nMaya",
            0, Set.of("INBOX", "UNREAD"), 0, false,
            "A familiar project update with no matching warning rules.");
    add("demo-build", "build@team.test", "The interface branch is ready to review",
            "The new mailbox screens are ready for review.\n\n"
                    + "Please check keyboard navigation, compose validation, and the empty state.\n\n"
                    + "This fictional notification is part of the demo mailbox.",
            45, Set.of("INBOX", "UNREAD"), 0, false,
            "No suspicious demo rules matched.");
    add("demo-invoice", "billing@invoice-review.test", "Action needed: verify your payment today",
            "Your payment is on hold. Verify your billing details immediately to avoid suspension.\n\n"
                    + "Open https://billing-check.example.test/verify and enter your account details.\n\n"
                    + "This is a fictional suspicious message for testing. Do not enter real details.",
            110, Set.of("INBOX", "UNREAD"), 78, true,
            "Urgent payment language.", "Requests sensitive billing details.",
            "Sender and link domains differ.");
```

```
        add("demo-library", "library@campus.test", "Your book reservation is available",
                "Your reserved database systems book is available at the circulation desk.\n\n"
                        + "Please collect it by Friday. Your library card is all you need.",
                180, Set.of("INBOX"), 0, false,
                "No suspicious demo rules matched.");
        add("demo-internship", "careers@campus.test", "Campus internship briefing — Thursday",
                "The careers team is holding a briefing on Thursday at 11 AM.\n\n"
                        + "We will cover application timelines and interview preparation. Attendance is
optional.",
                260, Set.of("INBOX", "UNREAD"), 5, false,
                "An informational campus announcement.");
        add("demo-password", "security@account-alert.test", "Your account will close in 24 hours",
                "Confirm your password now or your mailbox will be closed.\n\n"
                        + "Reply with your password and verification code to keep access.\n\n"
                        + "Fictional phishing example: legitimate services should not request passwords by
email.",
                370, Set.of("INBOX"), 94, true,
                "Requests a password and verification code.", "Threatens account closure.",
                "Uses urgency to pressure the recipient.");
        add("demo-newsletter", "newsletter@coding-club.test", "This week at the coding club",
                "This week's events:\n\nMonday: Java study group\nWednesday: SQL practice\n"
                        + "Friday: student project demonstrations\n\nSee you there!",
                500, Set.of("INBOX"), 0, false,
                "An ordinary fictional newsletter.");
        add("demo-prize", "offers@prize-draw.test", "You won! Claim a surprise reward",
                "You have been selected for a large cash reward. Pay a small processing fee to claim it
today.\n\n"
                        + "This fictional spam example is already filed in the demo Gmail Spam folder.",
                600, Set.of("SPAM", "UNREAD"), 96, true,
                "Unsolicited prize claim.", "Requests an upfront processing fee.");
        add("demo-travel", "deals@travel-promo.test", "Last chance: exclusive holiday discount",
                "A limited offer is waiting. Book immediately to unlock your special discount.\n\n"
                        + "This fictional promotion is already in the demo Gmail Spam folder.",
                750, Set.of("SPAM", "UNREAD"), 62, true,
                "Promotional urgency.", "Unsolicited offer from an unfamiliar sender.");
        add("demo-welcome", "hello@maildesk.test", "Welcome to your demo mailbox",
                "Welcome! This is an in-memory preview of the email management interface.\n\n"
                        + "All messages are fictional. Sending saves a message in demo Sent only; "
                        + "no email leaves this application. No Google sign-in, database, or network is
used.\n\n"
                        + "Try searching, composing, and reviewing the two suspected spam examples.",
                1_440, Set.of("INBOX"), 0, false,
                "A local demonstration message.");
        addSent("demo-sent-report", "maya@campus.test", "Project progress and next steps",
                "Hi Maya,\n\nThe member assignments and shared method signatures are ready. "
                        + "I will finish the Swing screens next.\n\nThanks!", 200);
        addSent("demo-sent-review", "dev@team.test", "Please review the compose screen",
                "The compose form now checks recipient, subject, and body before sending.\n\n"
                        + "Please try the keyboard shortcuts when you review it.", 1_600);
    }

    private void add(String id, String sender, String subject, String body, long minutesAgo,
                     Set<String> labels, int score, boolean suspected, String... reasons) {
        messages.put(id, new EmailMessage(ACCOUNT.getAccountId(), id, sender,
                List.of(ACCOUNT.getEmailAddress()), subject, body,
                SAMPLE_TIME.minus(minutesAgo, ChronoUnit.MINUTES), labels));
        spamResults.put(id, new SpamResult(score, suspected, List.of(reasons)));
    }

    private void addSent(String id, String recipient, String subject, String body, long minutesAgo) {
        messages.put(id, new EmailMessage(ACCOUNT.getAccountId(), id, ACCOUNT.getEmailAddress(),
                List.of(recipient), subject, body,
                SAMPLE_TIME.minus(minutesAgo, ChronoUnit.MINUTES), Set.of("SENT")));
        spamResults.put(id, new SpamResult(0, false,
                List.of("A fictional sent message in the demo mailbox.")));
    }
}
```

APPENDIX A.3 — JAVA VERIFICATION SOURCES

src/test/java/com/emailapp/AppTest.java

```
package com.emailapp;

import java.io.ByteArrayOutputStream;
import java.io.PrintStream;
import java.nio.charset.StandardCharsets;
import org.junit.jupiter.api.Test;
import static org.junit.jupiter.api.Assertions.*;

class AppTest {
    @Test void teammateLauncherUsesProductionHelp() {
        PrintStream previous = System.out;
        ByteArrayOutputStream output = new ByteArrayOutputStream();
        try {
            System.setOut(new PrintStream(output, true, StandardCharsets.UTF_8));
            App.main(new String[] {"--help"});
        } finally { System.setOut(previous); }
        assertTrue(output.toString(StandardCharsets.UTF_8).contains("--check-setup"));
    }
```

```
}
```

src/test/java/com/emailapp/SpamClassifierTest.java

```
package com.emailapp;

import com.emailapp.spam.SpamClassifier;
import ems.model.EmailMessage;
import ems.model.SpamResult;
import java.time.Instant;
import java.util.List;
import java.util.Set;
import org.junit.jupiter.api.Test;
import static org.junit.jupiter.api.Assertions.*;

class SpamClassifierTest {
    private final SpamClassifier classifier = new SpamClassifier();

    private EmailMessage message(String subject, String body, Set<String> labels) {
        return new EmailMessage(1, "message", "sender@example.com", List.of("me@example.com"),
                subject, body, Instant.parse("2026-10-20T10:15:00Z"), labels);
    }

    @Test void ordinaryMailNeedsNoDatabaseAndIsNotSpam() {
        SpamResult result = classifier.analyze(message("Meeting notes", "See you on Tuesday.",
Set.of("INBOX")));
        assertEquals(0, result.getScore());
        assertFalse(result.isSuspectedSpam());
    }

    @Test void oneCommonPhraseDoesNotFlagLegitimateAccountMail() {
        SpamResult result = classifier.analyze(message("Please verify your account", "Welcome to our service.",
Set.of("INBOX")));
        assertEquals(20, result.getScore());
        assertFalse(result.isSuspectedSpam());
    }

    @Test void multipleIndependentSignalsCanReachSpamThreshold() {
        SpamResult result = classifier.analyze(message("URGENT: Claim your prize", "You have won! Verify your
account now. "
                + "https://one.example https://two.example https://three.example https://four.example
https://five.example", Set.of("INBOX")));
        assertTrue(result.isSuspectedSpam());
        assertTrue(result.getScore() >= 50);
        assertTrue(result.getReasons().contains("Message contains many links"));
    }

    @Test void gmailSpamLabelDoesNotInfluenceOurClassifier() {
        SpamResult result = classifier.analyze(message("Meeting notes", "See you on Tuesday.", Set.of("SPAM")));
        assertEquals(0, result.getScore());
        assertFalse(result.isSuspectedSpam());
    }

    @Test void blockedSenderIsFlaggedWithReason() {
        SpamResult result = classifier.analyze(message("Hello", "Hello", Set.of("INBOX")), true);
        assertTrue(result.isSuspectedSpam());
        assertTrue(result.getReasons().contains("Sender is blocked"));
    }

    @Test void repeatedSinglePhraseDoesNotAccumulate() {
        SpamResult result = classifier.analyze(message("Hello", "you have won you have won you have won",
Set.of("INBOX")));
        assertEquals(20, result.getScore());
    }
}
```

src/test/java/ems/check/MemberOneChecks.java

```
package ems.check;

import ems.demo.DemoEmailService;
import ems.exception.AppException;
import ems.model.Account;
import ems.model.EmailMessage;
import ems.model.Mailbox;
import ems.model.SpamResult;
import ems.service.EmailService;

import java.time.Instant;
import java.util.ArrayList;
import java.util.HashSet;
import java.util.List;
import java.util.Locale;
import java.util.Set;
import java.util.stream.Collectors;
```

```
/** Dependency-free contract checks. No real Gmail account, database, or window is used. */
public final class MemberOneChecks {
    private static int assertions;

    private MemberOneChecks() {
    }

    public static void main(String[] args) throws Exception {
        checkModelBoundaries();
        checkDemoFlow();
        System.out.println("PASS: " + assertions + " contract/demo assertions (headless).");
    }

    private static void checkModelBoundaries() {
        List<String> recipients = new ArrayList<>(List.of("reader@example.test"));
        Set<String> labels = new HashSet<>(Set.of("INBOX", "UNREAD"));
        EmailMessage message = new EmailMessage(1L, "boundary-test", "writer@example.test",
                recipients, "Subject", "Body", Instant.parse("2026-01-01T12:00:00Z"), labels);
        recipients.clear();
        labels.clear();
        check(message.getRecipientEmails().equals(List.of("reader@example.test")),
                "Message recipients must not change when the caller mutates its input list.");
        check(message.getGmailLabelIds().equals(Set.of("INBOX", "UNREAD")),
                "Message labels must not change when the caller mutates its input set.");
        expectUnsupported(() -> message.getRecipientEmails().clear(),
                "Recipient lists must not permit callers to change cached state.");
        expectUnsupported(() -> message.getGmailLabelIds().clear(),
                "Label sets must not permit callers to change cached state.");

        List<String> reasons = new ArrayList<>(List.of("Blocked sender"));
        SpamResult result = new SpamResult(80, true, reasons);
        reasons.clear();
        check(result.getReasons().equals(List.of("Blocked sender")),
                "Spam reasons must be copied before they cross the UI/backend boundary.");
        expectUnsupported(() -> result.getReasons().clear(),
                "Spam reasons must not permit callers to change cached state.");
    }

    private static void checkDemoFlow() throws AppException {
        EmailService service = new DemoEmailService();
        expectAppException(() -> service.getMessages(Mailbox.INBOX, ""),
                "Mailbox access must require a connection.");
        expectAppException(service::refresh, "Refresh must require a connection.");

        Account account = service.connectGmail();
        check(account.getAccountId() > 0 && account.getEmailAddress().endsWith(".test"),
                "The demo must connect to a fictional account.");
        List<EmailMessage> inbox = service.getMessages(Mailbox.INBOX, "");
        check(!inbox.isEmpty(), "Connected demo must provide inbox fixtures.");
        checkNewestFirst(inbox);
        check(inbox.stream().allMatch(message -> message.getAccountId() == account.getAccountId()),
                "Inbox messages must belong to the connected account.");

        EmailMessage meeting = find(inbox, "demo-meeting");
        check(meeting.getGmailLabelIds().contains("UNREAD"), "Meeting fixture should begin unread.");
        check(contains(service.getMessages(Mailbox.INBOX,
                        meeting.getSubject().toUpperCase(Locale.ROOT)), meeting.getGmailMessageId()),
                "Search should match subjects without case sensitivity.");
        check(contains(service.getMessages(Mailbox.INBOX,
                        meeting.getSenderEmail().toUpperCase(Locale.ROOT)), meeting.getGmailMessageId()),
                "Search should match the sender.");
        check(contains(service.getMessages(Mailbox.INBOX, meeting.getBodyText()),
                        meeting.getGmailMessageId()),
                "Search should match the message body.");
        check(contains(service.getMessages(Mailbox.INBOX, meeting.getRecipientEmails().get(0)),
                        meeting.getGmailMessageId()),
                "Search should match recipients.");
        check(service.getMessages(Mailbox.INBOX, "this-search-has-no-match-90453").isEmpty(),
                "Search should return an empty list when nothing matches.");

        EmailMessage opened = service.openMessage(meeting.getGmailMessageId());
        check(!opened.getGmailLabelIds().contains("UNREAD"), "Opening an email must mark it read.");
        check(!find(service.getMessages(Mailbox.INBOX, ""), meeting.getGmailMessageId())
                        .getGmailLabelIds().contains("UNREAD"),
                "Read status must persist within the demo session.");

        int sentCount = service.getMessages(Mailbox.SENT, "").size();
        String sentId = service.sendMessage("outside@example.test", "Project update", "The UI is ready.");
        check(sentId != null && !sentId.isBlank(), "Sending must return a message ID.");
        List<EmailMessage> sent = service.getMessages(Mailbox.SENT, "");
        check(sent.size() == sentCount + 1, "Sending must add exactly one Sent entry.");
        EmailMessage delivered = find(sent, sentId);
        check(delivered.getSenderEmail().equals(account.getEmailAddress()),
                "The sender must be the connected account.");
        check(delivered.getRecipientEmails().contains("outside@example.test"),
                "The demo must accept an external recipient.");
        check(delivered.getSubject().equals("Project update")
                        && delivered.getBodyText().equals("The UI is ready."),
                "Sent content must match what the compose form supplied.");
        check(!contains(service.getMessages(Mailbox.INBOX, ""), sentId),
                "Sending to an external recipient should not add it to the demo Inbox.");
```

```
        EmailMessage untouched = find(service.getMessages(Mailbox.INBOX, ""), "demo-library");
        EmailMessage suspicious = find(service.getMessages(Mailbox.SUSPECTED, ""), "demo-invoice");
        SpamResult originalScore = service.getSpamResult(suspicious.getGmailMessageId());
        check(originalScore.isSuspectedSpam() && !originalScore.getReasons().isEmpty(),
                "Suspected messages must provide a classification and reasons.");
        check(contains(service.getMessages(Mailbox.SPAM, ""), "demo-prize"),
                "Gmail Spam fixtures must be available in the separate Spam mailbox.");
        check(!contains(service.getMessages(Mailbox.SUSPECTED, ""), "demo-prize"),
                "Confirmed Spam should not also be queued for local suspicion review.");

        service.markAsSpam(suspicious.getGmailMessageId());
        EmailMessage spam = find(service.getMessages(Mailbox.SPAM, ""), suspicious.getGmailMessageId());
        check(spam.getGmailLabelIds().contains("SPAM") && !spam.getGmailLabelIds().contains("INBOX"),
                "Spam correction must move the message from Inbox to Spam.");
        Set<String> otherLabels = new HashSet<>(suspicious.getGmailLabelIds());
        otherLabels.remove("INBOX");
        otherLabels.remove("SPAM");
        check(spam.getGmailLabelIds().containsAll(otherLabels),
                "Spam correction must preserve unrelated Gmail labels.");

        service.markAsNotSpam(suspicious.getGmailMessageId());
        EmailMessage restored = find(service.getMessages(Mailbox.INBOX, ""), suspicious.getGmailMessageId());
        check(restored.getGmailLabelIds().contains("INBOX") && !restored.getGmailLabelIds().contains("SPAM"),
                "Not-spam correction must return the message to Inbox.");
        check(!service.getSpamResult(suspicious.getGmailMessageId()).isSuspectedSpam(),
                "Not-spam correction must override local suspicion.");
        check(!contains(service.getMessages(Mailbox.SUSPECTED, ""), suspicious.getGmailMessageId()),
                "Corrected messages must leave the suspicion review queue.");
        check(contains(service.getMessages(Mailbox.SUSPECTED, ""), "demo-password"),
                "Correcting one message must not clear another message's classification.");
        check(find(service.getMessages(Mailbox.INBOX, ""), untouched.getGmailMessageId())
                        .getGmailLabelIds().equals(untouched.getGmailLabelIds()),
                "Correcting one message must preserve other messages' labels.");

        expectAppException(() -> service.openMessage("another-account-message"),
                "Opening an unknown or unavailable message must fail.");
        expectAppException(() -> service.getSpamResult("another-account-message"),
                "Spam details for an unavailable message must fail.");
        expectAppException(() -> service.markAsSpam("another-account-message"),
                "Spam corrections for an unavailable message must fail.");
        expectAppException(() -> service.markAsNotSpam("another-account-message"),
                "Not-spam corrections for an unavailable message must fail.");
        expectAppException(() -> service.markAsSpam(sentId),
                "A sent message must not be moved into received Spam.");

        Set<String> inboxBeforeRefresh = ids(service.getMessages(Mailbox.INBOX, ""));
        Set<String> sentBeforeRefresh = ids(service.getMessages(Mailbox.SENT, ""));
        service.refresh();
        List<EmailMessage> refreshedInbox = service.getMessages(Mailbox.INBOX, "");
        check(ids(refreshedInbox).equals(inboxBeforeRefresh)
                        && refreshedInbox.size() == inboxBeforeRefresh.size(),
                "Repeated demo refresh must not lose or duplicate inbox messages.");
        check(ids(service.getMessages(Mailbox.SENT, "")).equals(sentBeforeRefresh),
                "Refresh must preserve sent messages.");
        check(!service.getSpamResult(suspicious.getGmailMessageId()).isSuspectedSpam(),
                "Refresh must preserve a not-spam correction.");

        service.disconnect();
        expectAppException(() -> service.getMessages(Mailbox.INBOX, ""),
                "Disconnect must prevent subsequent mailbox access.");
        expectAppException(() -> service.openMessage(meeting.getGmailMessageId()),
                "Disconnect must prevent message opening.");
        expectAppException(() -> service.sendMessage("outside@example.test", "Subject", "Body"),
                "Disconnect must prevent sending.");
    }

    private static void checkNewestFirst(List<EmailMessage> messages) {
        for (int index = 1; index < messages.size(); index++) {
            check(!messages.get(index).getReceivedAt().isAfter(messages.get(index - 1).getReceivedAt()),
                    "Mailbox messages must be ordered newest first.");
        }
    }

    private static EmailMessage find(List<EmailMessage> messages, String messageId) {
        return messages.stream().filter(message -> message.getGmailMessageId().equals(messageId))
                .findFirst().orElseThrow(() -> new AssertionError("Missing message: " + messageId));
    }

    private static boolean contains(List<EmailMessage> messages, String messageId) {
        return messages.stream().anyMatch(message -> message.getGmailMessageId().equals(messageId));
    }

    private static Set<String> ids(List<EmailMessage> messages) {
        return messages.stream().map(EmailMessage::getGmailMessageId).collect(Collectors.toSet());
    }

    private static void check(boolean condition, String description) {
        assertions++;
        if (!condition) {
            throw new AssertionError(description);
        }
    }
```

```
    private static void expectAppException(CheckedAction action, String description) {
        assertions++;
        try {
            action.run();
        } catch (AppException expected) {
            return;
        }
        throw new AssertionError(description);
    }

    private static void expectUnsupported(Runnable action, String description) {
        assertions++;
        try {
            action.run();
        } catch (UnsupportedOperationException expected) {
            return;
        }
        throw new AssertionError(description);
    }

    @FunctionalInterface
    private interface CheckedAction {
        void run() throws AppException;
    }
}
```

src/test/java/ems/check/MemberTwoChecks.java

```
package ems.check;

import ems.exception.AppException;
import ems.gmail.SimpleJson;
import ems.model.Account;
import ems.model.EmailMessage;
import ems.model.Mailbox;
import ems.model.SpamResult;
import ems.service.EmailService;
import ems.service.GmailEmailService;

import java.time.Instant;
import java.util.List;
import java.util.Map;
import java.util.Set;

/**
 * Headless automated test suite verifying Member 2 implementation contracts.
 */
public final class MemberTwoChecks {

    private static int assertions = 0;

    private MemberTwoChecks() {
    }

    public static void main(String[] args) throws Exception {
        testModelContracts();
        testJsonParser();
        testServiceDisconnectSafety();
        System.out.println("PASS: " + assertions + " Member 2 contract assertions (headless).");
    }

    private static void testModelContracts() {
        // Account contract
        Account account = new Account(101L, "user@example.test");
        check(account.getAccountId() == 101L, "Account accountId should match constructor.");
        check("user@example.test".equals(account.getEmailAddress()), "Account emailAddress should match.");

        // EmailMessage contract
        Instant now = Instant.now();
        EmailMessage msg = new EmailMessage(
                101L,
                "msg-1",
                "sender@example.test",
                List.of("recipient@example.test"),
                "Hello World",
                "This is test body text",
                now,
                Set.of("INBOX", "UNREAD")
        );
        check(msg.getAccountId() == 101L, "EmailMessage accountId should match.");
        check("msg-1".equals(msg.getGmailMessageId()), "EmailMessage messageId should match.");
        check("sender@example.test".equals(msg.getSenderEmail()), "EmailMessage sender should match.");
        check(msg.getRecipientEmails().contains("recipient@example.test"), "EmailMessage recipient should
match.");
        check("Hello World".equals(msg.getSubject()), "EmailMessage subject should match.");
        check("This is test body text".equals(msg.getBodyText()), "EmailMessage body should match.");
        check(msg.getReceivedAt().equals(now), "EmailMessage receivedAt should match.");
        check(msg.getGmailLabelIds().contains("INBOX"), "EmailMessage labels should match.");
```

```
        // SpamResult contract
        SpamResult spam = new SpamResult(85, true, List.of("Phishing phrase detected"));
        check(spam.getScore() == 85, "SpamResult score should match.");
        check(spam.isSuspectedSpam(), "SpamResult suspectedSpam should match.");
        check(spam.getReasons().size() == 1, "SpamResult reasons should match.");

        // Mailbox enum
        check(Mailbox.valueOf("INBOX") == Mailbox.INBOX, "Mailbox INBOX should exist.");
        check(Mailbox.valueOf("SENT") == Mailbox.SENT, "Mailbox SENT should exist.");
        check(Mailbox.valueOf("SPAM") == Mailbox.SPAM, "Mailbox SPAM should exist.");
        check(Mailbox.valueOf("SUSPECTED") == Mailbox.SUSPECTED, "Mailbox SUSPECTED should exist.");
    }

    private static void testJsonParser() {
        String json = "{\"id\":\"12345\",\"labelIds\":[\"INBOX\",\"UNREAD\"],\"snippet\":\"Hi
there\",\"valid\":true,\"count\":42}";
        Map<String, Object> parsed = SimpleJson.parseObject(json);
        check("12345".equals(SimpleJson.getString(parsed, "id")), "Parsed string ID should match.");
        check("Hi there".equals(SimpleJson.getString(parsed, "snippet")), "Parsed snippet should match.");
        List<Object> labels = SimpleJson.getList(parsed, "labelIds");
        check(labels.size() == 2, "Parsed labels count should match.");
        check("INBOX".equals(labels.get(0)), "First label should be INBOX.");
        check(Boolean.TRUE.equals(parsed.get("valid")), "Parsed boolean should match.");
        check(Integer.valueOf(42).equals(((Number) parsed.get("count")).intValue()), "Parsed number should
match.");
    }

    private static void testServiceDisconnectSafety() throws AppException {
        EmailService service = GmailEmailService.createDefault();

        expectAppException(() -> service.getMessages(Mailbox.INBOX, ""),
                "Calls before connecting must fail with AppException.");
        expectAppException(() -> service.openMessage("msg-1"),
                "Opening message before connecting must fail with AppException.");
        expectAppException(() -> service.sendMessage("test@example.com", "Subj", "Body"),
                "Sending message before connecting must fail with AppException.");
        expectAppException(() -> service.getSpamResult("msg-1"),
                "Getting spam result before connecting must fail with AppException.");
        expectAppException(() -> service.markAsSpam("msg-1"),
                "Marking spam before connecting must fail with AppException.");
        expectAppException(() -> service.markAsNotSpam("msg-1"),
                "Marking not spam before connecting must fail with AppException.");
    }

    private static void check(boolean condition, String message) {
        assertions++;
        if (!condition) {
            throw new AssertionError(message);
        }
    }

    private static void expectAppException(ThrowingRunnable action, String message) {
        assertions++;
        try {
            action.run();
            throw new AssertionError("Expected AppException, but none was thrown: " + message);
        } catch (AppException expected) {
            // Success
        } catch (Exception e) {
            throw new AssertionError("Expected AppException, but got: " + e.getClass().getName() + " - " +
message, e);
        }
    }

    @FunctionalInterface
    private interface ThrowingRunnable {
        void run() throws Exception;
    }
}
```

src/test/java/ems/check/MemberTwoContractTest.java

```
package ems.check;

import org.junit.jupiter.api.Test;

/** Runs the teammate's standalone contract checks in every Maven/CI test run. */
class MemberTwoContractTest {
    @Test void memberTwoContract() throws Exception {
        MemberTwoChecks.main(new String[0]);
    }
}
```

src/test/java/ems/check/UiChecks.java

```
package ems.check;
```

```
import ems.demo.DemoEmailService;
import ems.exception.AppException;
import ems.model.Mailbox;
import ems.service.EmailService;
import ems.ui.*;
import java.awt.*;
import java.awt.image.BufferedImage;
import java.lang.reflect.InvocationTargetException;
import java.lang.reflect.Proxy;
import java.nio.file.*;
import java.util.concurrent.*;
import java.util.concurrent.atomic.*;
import javax.imageio.ImageIO;
import javax.swing.*;

/** Exercises real Swing actions headlessly, with slow/failing service responses. */
public final class UiChecks {
    private static MailAppPanel panel;
    private static int assertions;
    private static Path previewDirectory;

    public static void main(String[] args) throws Exception {
        if (args.length > 0 && args[0].equals("--render")) {
            previewDirectory = Path.of("build", "previews");
            Files.createDirectories(previewDirectory);
        }
        DemoEmailService demo = new DemoEmailService();
        AtomicBoolean onEdt = new AtomicBoolean();
        AtomicBoolean failRefresh = new AtomicBoolean(true);
        AtomicBoolean failOpen = new AtomicBoolean();
        AtomicReference<CountDownLatch> refreshGate = new AtomicReference<>();
        EmailService service = (EmailService) Proxy.newProxyInstance(EmailService.class.getClassLoader(),
                new Class<?>[] {EmailService.class}, (proxy, method, arguments) -> {
                    if (SwingUtilities.isEventDispatchThread()) onEdt.set(true);
                    if (method.getName().equals("refresh") || method.getName().equals("refreshRecent")) {
                        if (failRefresh.get()) throw new AppException("Test connection unavailable. Try
again.");
                        CountDownLatch gate = refreshGate.get();
                        if (gate != null && !gate.await(5, TimeUnit.SECONDS)) throw new AppException("Test timed
out.");
                    }
                    if (method.getName().equals("openMessage") && failOpen.get()) {
                        throw new AppException("Test message unavailable.");
                    }
                    try { return method.invoke(demo, arguments); }
                    catch (InvocationTargetException exception) { throw exception.getCause(); }
                });

        edt(() -> {
            UiTheme.install(); panel = new MailAppPanel(service, true);
            panel.setSize(1360, 860); layout(panel); render(panel, "connect.png");
        });
        click("connectButton");
        edt(() -> {
            check(button("refreshButton").isEnabled(), "Refresh retry available after initial sync failure");
            check(label("statusLabel").getText().contains("Test connection"), "Useful connection failure
shown");
        });
        check(demo.getMessages(Mailbox.INBOX, "").size() == 8,
                "Initial refresh failure preserves the signed-in account and cached messages");
        failRefresh.set(false); click("refreshButton");
        edt(() -> {
            check(table().getRowCount() == 8, "Connected Inbox shown");
            check(button("composeButton").isEnabled(), "Compose enabled after connect");
            layout(panel); render(panel, "inbox.png");
            table().setRowSelectionInterval(0, 0);
        });
        awaitIdle();
        edt(() -> {
            check(find(panel, "messageBody") != null, "Opening row displays body");
            check(!((MailTableModel) table().getModel()).isUnread(0), "Opened row updates read state");
            layout(panel); render(panel, "reader.png");
        });
        failOpen.set(true);
        edt(() -> table().setRowSelectionInterval(1, 1)); awaitIdle();
        edt(() -> {
            check(find(panel, "markSpamButton") == null, "Failed open cannot correct previous message");
            check(find(panel, "messageBody") == null, "Previous body cleared on failed open");
            check(label("statusLabel").getText().contains("unavailable"), "Message failure shown");
        });
        failOpen.set(false);
        edt(() -> table().setRowSelectionInterval(1, 1)); awaitIdle();
        edt(() -> check(find(panel, "messageBody") != null,
                "The same row can be retried after an opening failure"));
        click("suspectedButton");
        edt(() -> {
            check(table().getRowCount() == 2, "Suspected view shows local flags");
            table().setRowSelectionInterval(0, 0);
        }); awaitIdle();
        edt(() -> {
            check(find(panel, "spamReasons") != null, "Rule reasons displayed");
            layout(panel); render(panel, "suspected.png");
        });
        click("notSpamButton");
```

```
        edt(() -> check(table().getRowCount() == 1, "Not spam correction removes local review item"));
        click("spamButton");
        edt(() -> check(table().getRowCount() == 2, "Gmail Spam stays separate"));
        click("sentButton");
        edt(() -> {
            check(table().getRowCount() == 2, "Sent view works");
            check(table().getColumnName(0).equals("TO"), "Sent identifies recipient");
            table().setRowSelectionInterval(0, 0);
        }); awaitIdle();
        edt(() -> check(find(panel, "markSpamButton") == null, "Sent cannot trigger spam correction"));
        click("inboxButton");
        edt(() -> field("searchField").setText("no-such-message-1928")); click("searchButton");
        edt(() -> check(table().getRowCount() == 0, "Empty search result clears list"));
        edt(() -> field("searchField").setText("project")); click("searchButton");
        edt(() -> check(table().getRowCount() > 0, "Search recovers from empty results"));
        CountDownLatch gate = new CountDownLatch(1); refreshGate.set(gate);
        edt(() -> button("refreshButton").doClick());
        edt(() -> {
            check(panel.isBusy(), "Long-running refresh tracked");
            check(!button("disconnectButton").isEnabled(), "Session cannot change mid-operation");
            check(!button("refreshButton").isEnabled(), "Duplicate refresh disabled");
        });
        gate.countDown(); awaitIdle(); refreshGate.set(null);
        failRefresh.set(true); click("refreshButton"); failRefresh.set(false);
        edt(() -> {
            check(button("refreshButton").isEnabled(), "Refresh recovers after failure");
            check(label("statusLabel").getText().contains("unavailable"), "Refresh error shown");
            check(table().getRowCount() > 0, "Cached messages remain on refresh error");
        });
        composeChecks();
        readerLayoutChecks(demo);
        click("disconnectButton");
        edt(() -> {
            check(button("connectButton").isEnabled(), "Disconnect returns to connect screen");
            check(!button("composeButton").isEnabled(), "Disconnected compose disabled");
        });
        check(!onEdt.get(), "Every service operation stayed off the Swing EDT");
        System.out.println("PASS: " + assertions + " Swing interaction assertions (headless).");
        if (previewDirectory != null) System.out.println("Rendered previews to " +
previewDirectory.toAbsolutePath());
    }

    private static void composeChecks() throws Exception {
        AtomicReference<ComposePanel.Draft> submitted = new AtomicReference<>();
        AtomicInteger submissions = new AtomicInteger();
        AtomicInteger cancellations = new AtomicInteger();
        edt(() -> {
            ComposePanel form = new ComposePanel("student@example.test", true, draft -> {
                submitted.set(draft); submissions.incrementAndGet();
            }, cancellations::incrementAndGet);
            form.setSize(660, 620);
            JButton send = (JButton) find(form, "sendButton");
            send.doClick(); check(submissions.get() == 0, "Blank compose cannot send");
            ((JTextField) find(form, "composeTo")).setText("maya@campus.test");
            ((JTextField) find(form, "composeSubject")).setText("Project review");
            ((JTextArea) find(form, "composeBody")).setText("Hi Maya,\n\nThe mailbox screens are ready to
review.\n\nThanks!");
            form.showError(null);
            layout(form); render(form, "compose.png"); send.doClick();
            check(submissions.get() == 1 && submitted.get().subject().equals("Project review"), "Validated
compose delivers draft");
            form.setBusy(true);
            form.getActionMap().get("sendDraft").actionPerformed(null);
            form.getActionMap().get("cancelCompose").actionPerformed(null);
            check(submissions.get() == 1 && cancellations.get() == 0, "Busy compose blocks keyboard duplicates
and dismissal");
            form.setBusy(false); form.showError("Delivery failed. You can retry.");
            check(((JTextArea) find(form, "composeBody")).getText().contains("ready"), "Draft survives send
failure");
            ((JButton) find(form, "cancelComposeButton")).doClick();
            check(cancellations.get() == 1, "Compose cancel callback works");
        });
    }

    private static void readerLayoutChecks(DemoEmailService demo) throws Exception {
        String paragraph = "A longer paragraph must wrap at the reader width without losing its last line. ";
        String message = paragraph.repeat(95) + "\n\nFINAL SIGNATURE — visible at the end.";
        demo.sendMessage("student@example.test", "Long reader layout regression ".repeat(5), message);
        click("sentButton");
        edt(() -> table().setRowSelectionInterval(0, 0)); awaitIdle();
        edt(() -> {
            for (int width : new int[] {1360, 1100}) {
                panel.setSize(width, 740);
                layout(panel);
                JTextArea body = (JTextArea) find(panel, "messageBody");
                JScrollPane scroll = (JScrollPane) SwingUtilities.getAncestorOfClass(JScrollPane.class, body);
                try {
                    java.awt.geom.Rectangle2D end = body.modelToView2D(body.getDocument().getLength());
                    check(end != null && end.getMaxY() <= body.getHeight() - body.getInsets().bottom,
                            "All wrapped body lines have allocated height at width " + width);
                    Rectangle ending = SwingUtilities.convertRectangle(body, end.getBounds(),
scroll.getViewport().getView());
                    scroll.getVerticalScrollBar().setValue(scroll.getVerticalScrollBar().getMaximum());
                    layout(scroll);
                    JViewport viewport = scroll.getViewport();
                    check(viewport.getViewPosition().y + viewport.getExtentSize().height >= ending.getMaxY(),
```

```
                        "The final body line is reachable by scrolling at width " + width);
                check(scroll.getVerticalScrollBar().getMaximum() > viewport.getExtentSize().height,
                        "Long mail produces a vertical scroll range at width " + width);
            } catch (javax.swing.text.BadLocationException exception) {
                throw new AssertionError(exception);
            }
        }
        panel.setSize(1360, 860); layout(panel);
    });
}

private static void click(String name) throws Exception {
    edt(() -> button(name).doClick()); awaitIdle();
}

private static void awaitIdle() throws Exception {
    long deadline = System.nanoTime() + TimeUnit.SECONDS.toNanos(8);
    AtomicBoolean working = new AtomicBoolean();
    do {
        edt(() -> working.set(panel.isBusy()));
        if (!working.get()) return;
        Thread.sleep(20);
    } while (System.nanoTime() < deadline);
    throw new AssertionError("UI worker did not finish");
}

private static JButton button(String name) { return (JButton) required(name); }
private static JLabel label(String name) { return (JLabel) required(name); }
private static JTextField field(String name) { return (JTextField) required(name); }
private static JTable table() { return (JTable) required("messageTable"); }
private static Component required(String name) {
    Component value = find(panel, name);
    if (value == null) throw new AssertionError("Missing component: " + name);
    return value;
}

private static Component find(Component component, String name) {
    if (name.equals(component.getName())) return component;
    if (component instanceof Container container) {
        for (Component child : container.getComponents()) {
            Component match = find(child, name);
            if (match != null) return match;
        }
    }
    return null;
}

private static void layout(Container container) {
    container.doLayout();
    for (Component child : container.getComponents()) {
        if (child instanceof Container nested) layout(nested);
    }
}

private static void render(JComponent component, String filename) {
    if (previewDirectory == null) return;
    BufferedImage image = new BufferedImage(component.getWidth(), component.getHeight(),
BufferedImage.TYPE_INT_RGB);
    Graphics2D graphics = image.createGraphics();
    graphics.setRenderingHint(RenderingHints.KEY_TEXT_ANTIALIASING, RenderingHints.VALUE_TEXT_ANTIALIAS_ON);
    graphics.setRenderingHint(RenderingHints.KEY_ANTIALIASING, RenderingHints.VALUE_ANTIALIAS_ON);
    component.paint(graphics); graphics.dispose();
    try { ImageIO.write(image, "png", previewDirectory.resolve(filename).toFile()); }
    catch (java.io.IOException exception) { throw new RuntimeException(exception); }
}

private static void check(boolean condition, String description) {
    assertions++;
    if (!condition) throw new AssertionError(description);
}

private static void edt(Runnable work) throws Exception {
    if (SwingUtilities.isEventDispatchThread()) work.run();
    else SwingUtilities.invokeAndWait(work);
}
}
```

src/test/java/ems/config/AppConfigTest.java

```
package ems.config;

import ems.exception.AppException;
import java.nio.file.Files;
import java.nio.file.Path;
import java.util.Map;
import org.junit.jupiter.api.Test;
import org.junit.jupiter.api.io.TempDir;
import static org.junit.jupiter.api.Assertions.*;
```

```
class AppConfigTest {
    @TempDir Path home;

    @Test void defaultsWorkWithoutSavingSecrets() throws Exception {
        AppConfig config = AppConfig.load(home, Map.of());
        assertTrue(config.getDatabaseUrl().contains("email_management"));
        assertEquals(home.resolve("config/credentials.json"), config.getGmailCredentialsPath());
        assertFalse(Files.exists(config.getConfigFile()));
    }

    @Test void environmentOverridesLocalFileIncludingEmptyPassword() throws Exception {
        Files.createDirectories(home.resolve("config"));
        Files.writeString(home.resolve("config/app.properties"),
                "db.user=local\ndb.password=local-secret\ngmail.credentials=custom/client.json\n");
        AppConfig config = AppConfig.load(home, Map.of("DB_USER", "environment", "DB_PASSWORD", ""));
        assertEquals("environment", config.getDatabaseUser());
        assertEquals("", config.getDatabasePassword());
        assertEquals(home.resolve("custom/client.json"), config.getGmailCredentialsPath());
    }

    @Test void invalidPropertiesBecomeActionableError() throws Exception {
        Files.createDirectories(home.resolve("config"));
        Files.writeString(home.resolve("config/app.properties"), "db.password=\\uBAD!\n");
        AppException exception = assertThrows(AppException.class, () -> AppConfig.load(home, Map.of()));
        assertFalse(exception.getMessage().contains("BAD!"));
        assertTrue(exception.getMessage().contains("config/app.properties"));
    }

    @Test void teammateCredentialFilenamesWorkWithDeterministicPrecedence() throws Exception {
        Files.writeString(home.resolve("client_secret.json"), "{}");
        assertEquals(home.resolve("client_secret.json"),
                AppConfig.load(home, Map.of()).getGmailCredentialsPath());
        Files.createDirectories(home.resolve("config"));
        Files.writeString(home.resolve("config/credentials.json"), "{}");
        assertEquals(home.resolve("config/credentials.json"),
                AppConfig.load(home, Map.of()).getGmailCredentialsPath());
        // A missing explicit path must report that path rather than use another client's grant.
        assertEquals(home.resolve("missing.json"), AppConfig.load(home,
                Map.of("GMAIL_CREDENTIALS", "missing.json")).getGmailCredentialsPath());
    }
}
```

src/test/java/ems/gmail/GmailApiClientTest.java

```
package ems.gmail;

import com.google.gson.JsonObject;
import com.google.gson.JsonParser;
import com.sun.net.httpserver.HttpExchange;
import com.sun.net.httpserver.HttpServer;
import ems.exception.AppException;
import ems.model.EmailMessage;
import jakarta.mail.Session;
import jakarta.mail.internet.MimeMessage;
import java.io.ByteArrayInputStream;
import java.io.IOException;
import java.net.InetSocketAddress;
import java.net.URI;
import java.net.http.HttpClient;
import java.nio.charset.StandardCharsets;
import java.time.Instant;
import java.util.Base64;
import java.util.List;
import java.util.Properties;
import java.util.concurrent.atomic.AtomicInteger;
import java.util.concurrent.atomic.AtomicReference;
import org.junit.jupiter.api.AfterEach;
import org.junit.jupiter.api.BeforeEach;
import org.junit.jupiter.api.Test;
import static org.junit.jupiter.api.Assertions.*;

class GmailApiClientTest {
    private HttpServer server;
    private GmailApiClient gateway;
    private final FakeTokens tokens = new FakeTokens();
    private final AtomicReference<Handler> handler = new AtomicReference<>();

    @BeforeEach void start() throws Exception {
        server = HttpServer.create(new InetSocketAddress("127.0.0.1", 0), 0);
        server.createContext("/", exchange -> {
            try { handler.get().handle(exchange); }
            catch (Throwable failure) { reply(exchange, 500, "{}"); }
        });
        server.start();
        gateway = new GmailApiClient(URI.create("http://127.0.0.1:" + server.getAddress().getPort() + "/"),
                HttpClient.newHttpClient(), tokens, milliseconds -> { });
    }

    @AfterEach void stop() { server.stop(0); }
```

```
    @Test void connectsToProfileWithoutExposingCredentials() throws Exception {
        handler.set(exchange -> {
            assertEquals("Bearer initial", exchange.getRequestHeaders().getFirst("Authorization"));
            assertEquals("/profile", exchange.getRequestURI().getPath());
            reply(exchange, 200, "{\"emailAddress\":\"alice@gmail.com\"}");
        });
        assertEquals("alice@gmail.com", gateway.connect());
        assertTrue(tokens.authorized);
        gateway.disconnect();
        assertTrue(tokens.disconnected);
    }

    @Test void loadsAllPagesDeduplicatesIdsAndSkipsOnlyDeletedMessages() throws Exception {
        AtomicInteger rawReads = new AtomicInteger();
        handler.set(exchange -> {
            String path = exchange.getRequestURI().getPath();
            if (path.equals("/messages")) {
                var query = GmailAuth.parseQuery(exchange.getRequestURI().getRawQuery());
                assertEquals("true", query.get("includeSpamTrash"));
                assertEquals("-in:trash -in:drafts", query.get("q"));
                reply(exchange, 200, query.containsKey("pageToken")
                        ? "{\"messages\":[{\"id\":\"first\"},{\"id\":\"deleted\"},{\"id\":\"second\"}]}"
                        : "{\"messages\":[{\"id\":\"first\"}],\"nextPageToken\":\"page 2\"}");
            } else if (path.endsWith("deleted")) reply(exchange, 404, "{}");
            else {
                rawReads.incrementAndGet();
                reply(exchange, 200, rawMessage("Subject: Hello\r\nContent-Type: text/plain; charset=UTF-
8\r\n\r\nReal body"));
            }
        });
        List<EmailMessage> messages = gateway.fetchMessages(42);
        assertEquals(List.of("first", "second"),
messages.stream().map(EmailMessage::getGmailMessageId).toList());
        assertEquals(2, rawReads.get());
        assertEquals(42, messages.get(0).getAccountId());
        assertEquals(Instant.ofEpochMilli(1700000000000L), messages.get(0).getReceivedAt());
        assertTrue(messages.get(0).getGmailLabelIds().contains("INBOX"));
    }

    @Test void doesNotReturnPartialSnapshotWhenLaterFetchFails() {
        handler.set(exchange -> {
            if (exchange.getRequestURI().getPath().equals("/messages")) {
                reply(exchange, 200, "{\"messages\":[{\"id\":\"first\"},{\"id\":\"second\"}]}");
            } else if (exchange.getRequestURI().getPath().endsWith("first")) {
                reply(exchange, 200, rawMessage("Subject: Fine\r\n\r\nFirst"));
            } else reply(exchange, 503, "{}");
        });
        assertThrows(AppException.class, () -> gateway.fetchMessages(1));
    }

    @Test void startupReadsBoundedRecentWindowsFromAllThreeFolders() throws Exception {
        java.util.Set<String> folders = new java.util.HashSet<>();
        AtomicInteger reads = new AtomicInteger();
        handler.set(exchange -> {
            if (exchange.getRequestURI().getPath().equals("/messages")) {
                var query = GmailAuth.parseQuery(exchange.getRequestURI().getRawQuery());
                assertEquals("6", query.get("maxResults"));
                assertFalse(query.containsKey("pageToken"));
                folders.add(query.get("labelIds"));
                reply(exchange, 200, "{\"messages\":[{\"id\":\"shared\"}],\"nextPageToken\":\"older-mail\"}");
            } else {
                reads.incrementAndGet();
                reply(exchange, 200, rawMessage("Subject: Recent\r\n\r\nBody"));
            }
        });
        assertEquals(1, gateway.fetchRecentMessages(42, 6).size());
        assertEquals(java.util.Set.of("INBOX", "SENT", "SPAM"), folders);
        assertEquals(1, reads.get(), "Messages in multiple folders are read once");
    }

    @Test void refreshesOnceOnUnauthorizedResponse() throws Exception {
        AtomicInteger calls = new AtomicInteger();
        handler.set(exchange -> {
            if (calls.incrementAndGet() == 1) reply(exchange, 401, "{}");
            else {
                assertEquals("Bearer refreshed", exchange.getRequestHeaders().getFirst("Authorization"));
                reply(exchange, 200, "{\"emailAddress\":\"alice@gmail.com\"}");
            }
        });
        assertEquals("alice@gmail.com", gateway.connect());
        assertEquals(1, tokens.refreshes);
        assertEquals(2, calls.get());
    }

    @Test void neverRetriesAnUnconfirmedSend() throws Exception {
        AtomicInteger calls = new AtomicInteger();
        handler.set(exchange -> {
            calls.incrementAndGet();
            reply(exchange, 503, "{\"error\":\"private provider information\"}");
        });
        AppException failure = assertThrows(AppException.class,
                () -> gateway.sendMessage("alice@gmail.com", "bob@example.org", "Hi", "Text"));
        assertEquals(1, calls.get());
        assertFalse(failure.getMessage().contains("private provider"));
        assertTrue(failure.getMessage().contains("Check Gmail Sent before retrying"));
```

```
    }

    @Test void sendsUnicodeMimeAndUpdatesReadAndSpamLabels() throws Exception {
        AtomicReference<JsonObject> sent = new AtomicReference<>();
        AtomicReference<JsonObject> modification = new AtomicReference<>();
        handler.set(exchange -> {
            JsonObject json = JsonParser.parseString(new String(exchange.getRequestBody().readAllBytes(),
                    StandardCharsets.UTF_8)).getAsJsonObject();
            if (exchange.getRequestURI().getPath().endsWith("/send")) sent.set(json);
            else modification.set(json);
            reply(exchange, 200, "{\"id\":\"newmail\"}");
        });
        assertEquals("newmail", gateway.sendMessage("alice@gmail.com", "bob@example.org", "Meeting – தமிழ்",
"Hello\nவணக்கம்"));
        MimeMessage mime = new MimeMessage(Session.getInstance(new Properties()),
                new ByteArrayInputStream(Base64.getUrlDecoder().decode(sent.get().get("raw").getAsString())));
        assertEquals("Meeting – தமிழ்", mime.getSubject());
        assertEquals("Hello\r\nவணக்கம்", mime.getContent().toString().replace("\r\n", "\n").replace("\n",
"\r\n"));
        assertEquals("bob@example.org", mime.getAllRecipients()[0].toString());
        gateway.setRead("newmail");
        assertTrue(modification.get().getAsJsonArray("removeLabelIds").toString().contains("UNREAD"));
        gateway.setSpam("newmail", true);
        assertTrue(modification.get().getAsJsonArray("addLabelIds").toString().contains("SPAM"));
        assertTrue(modification.get().getAsJsonArray("removeLabelIds").toString().contains("INBOX"));
        gateway.setSpam("newmail", false);
        assertTrue(modification.get().getAsJsonArray("addLabelIds").toString().contains("INBOX"));
        assertTrue(modification.get().getAsJsonArray("removeLabelIds").toString().contains("SPAM"));
    }

    @Test void rejectsHeaderInjectionAndPathInjectionBeforeNetwork() {
        assertThrows(AppException.class,
                () -> gateway.sendMessage("alice@gmail.com", "bob@example.org\r\nBcc: victim@example.org", "Hi",
"Text"));
        assertThrows(AppException.class,
                () -> gateway.sendMessage("alice@gmail.com", "bob@example.org", "Hi\r\nBcc: victim@example.org",
"Text"));
        assertThrows(AppException.class, () -> gateway.getMessage(1, "../profile"));
    }

    @Test void choosesPlainAlternativeAndExcludesAttachments() throws Exception {
        String raw = "From: Alice <alice@gmail.com>\r\nTo: bob@example.org\r\n"
                + "Subject: MIME test\r\nMIME-Version: 1.0\r\nContent-Type: multipart/mixed;
boundary=mix\r\n\r\n"
                + "--mix\r\nContent-Type: multipart/alternative; boundary=alt\r\n\r\n"
                + "--alt\r\nContent-Type: text/plain; charset=UTF-8\r\n\r\nPlain body\r\n"
                + "--alt\r\nContent-Type: text/html; charset=UTF-8\r\n\r\n<p>HTML duplicate</p>\r\n--alt--\r\n"
                + "--mix\r\nContent-Type: text/plain\r\nContent-Disposition: attachment;
filename=private.txt\r\n\r\n"
                + "ATTACHMENT SHOULD NOT APPEAR\r\n--mix--\r\n";
        EmailMessage message = MimeMessages.parse(1, "id", encode(raw), Instant.EPOCH, java.util.Set.of());
        assertEquals("alice@gmail.com", message.getSenderEmail());
        assertEquals(List.of("bob@example.org"), message.getRecipientEmails());
        assertEquals("Plain body", message.getBodyText().strip());
    }

    @Test void convertsHtmlToInertTextAndDecodesEntities() throws Exception {
        String raw = "Content-Type: text/html; charset=UTF-8\r\n\r\n"
                + "<html><body><p>Hello &amp;amp; welcome</p><script>alert('bad')</script>"
                + "<img src='https://tracker.invalid/pixel'><p>Second line</p></body></html>";
        String body = MimeMessages.parse(1, "id", encode(raw), Instant.EPOCH, java.util.Set.of()).getBodyText();
        assertTrue(body.contains("Hello & welcome"));
        assertTrue(body.contains("Second line"));
        assertFalse(body.contains("alert"));
        assertFalse(body.contains("tracker"));
    }

    @Test void repeatedPageTokenAbortsInsteadOfLoopingForever() {
        handler.set(exchange -> reply(exchange, 200, "{\"nextPageToken\":\"same\"}"));
        assertThrows(AppException.class, () -> gateway.fetchMessages(1));
    }

    @Test void providerErrorsAreActionableAndDoNotEchoResponse() {
        handler.set(exchange -> reply(exchange, 403, "{\"error\":\"secret-token-value\"}"));
        AppException failure = assertThrows(AppException.class, gateway::connect);
        assertTrue(failure.getMessage().contains("Enable the Gmail API"));
        assertFalse(failure.getMessage().contains("secret-token-value"));
    }

    @Test void retriesRateLimitedReadsWithoutRefreshingAuthorization() throws Exception {
        AtomicInteger calls = new AtomicInteger();
        java.util.ArrayList<Long> delays = new java.util.ArrayList<>();
        gateway = new GmailApiClient(URI.create("http://127.0.0.1:" + server.getAddress().getPort() + "/"),
                HttpClient.newHttpClient(), tokens, delays::add);
        handler.set(exchange -> {
            if (calls.incrementAndGet() <= 2) reply(exchange, 403,
                    "{\"error\":{\"errors\":[{\"reason\":\"userRateLimitExceeded\"}]}}");
            else reply(exchange, 200, "{\"emailAddress\":\"alice@gmail.com\"}");
        });
        assertEquals("alice@gmail.com", gateway.connect());
        assertEquals(List.of(1000L, 2000L), delays);
        assertEquals(0, tokens.refreshes);
    }
```

```
    @Test void exhaustedQuotaIsNotMisreportedAsMissingGmailSetup() {
        AtomicInteger calls = new AtomicInteger();
        handler.set(exchange -> {
            calls.incrementAndGet();
            reply(exchange, 403, "{\"error\":{\"errors\":[{\"reason\":\"dailyLimitExceeded\"}],"
                    + "\"message\":\"private-account-information\"}}");
        });
        AppException error = assertThrows(AppException.class, gateway::connect);
        assertTrue(error.getMessage().contains("quota"));
        assertFalse(error.getMessage().contains("private-account"));
        assertEquals(1, calls.get());
    }

    @Test void rateLimitedSendIsNotAutomaticallyReplayed() {
        AtomicInteger calls = new AtomicInteger();
        handler.set(exchange -> {
            calls.incrementAndGet();
            reply(exchange, 403, "{\"error\":{\"errors\":[{\"reason\":\"userRateLimitExceeded\"}]}}");
        });
        assertThrows(AppException.class, () -> gateway.sendMessage("alice@gmail.com", "bob@example.org", "Hi",
"Text"));
        assertEquals(1, calls.get());
    }

    @Test void persistentRateLimitStopsAfterBoundedBackoffAndKeepsAuthorization() {
        java.util.ArrayList<Long> delays = new java.util.ArrayList<>();
        gateway = new GmailApiClient(URI.create("http://127.0.0.1:" + server.getAddress().getPort() + "/"),
                HttpClient.newHttpClient(), tokens, delays::add);
        handler.set(exchange -> reply(exchange, 403,
                "{\"error\":{\"errors\":[{\"reason\":\"rateLimitExceeded\"}]}}"));
        AppException error = assertThrows(AppException.class, gateway::connect);
        assertEquals(List.of(1000L, 2000L, 4000L, 8000L, 16000L, 32000L), delays);
        assertTrue(error.getMessage().contains("temporarily limited"));
        assertFalse(error.getMessage().contains("Enable the Gmail API"));
        assertFalse(tokens.disconnected);
        assertEquals(0, tokens.refreshes);
    }

    private static String rawMessage(String content) {
        JsonObject json = new JsonObject();
        json.addProperty("raw", encode(content));
        json.addProperty("internalDate", "1700000000000");
        json.add("labelIds", JsonParser.parseString("[\"INBOX\",\"UNREAD\"]"));
        return json.toString();
    }

    private static String encode(String raw) {
        return Base64.getUrlEncoder().withoutPadding().encodeToString(raw.getBytes(StandardCharsets.UTF_8));
    }

    private static void reply(HttpExchange exchange, int status, String value) throws IOException {
        byte[] bytes = value.getBytes(StandardCharsets.UTF_8);
        exchange.sendResponseHeaders(status, bytes.length);
        try (var output = exchange.getResponseBody()) { output.write(bytes); }
    }

    @FunctionalInterface private interface Handler { void handle(HttpExchange exchange) throws Exception; }

    private static final class FakeTokens implements AccessTokenProvider {
        boolean authorized;
        boolean disconnected;
        int refreshes;
        @Override public void authorize() { authorized = true; }
        @Override public String accessToken() { return refreshes == 0 ? "initial" : "refreshed"; }
        @Override public String refreshAccessToken() { refreshes++; return "refreshed"; }
        @Override public void disconnect() { disconnected = true; }
    }
}
```

src/test/java/ems/gmail/GmailAuthTest.java

```
package ems.gmail;

import com.sun.net.httpserver.HttpExchange;
import com.sun.net.httpserver.HttpServer;
import ems.exception.AppException;
import java.io.IOException;
import java.net.InetSocketAddress;
import java.net.URI;
import java.net.http.HttpClient;
import java.net.http.HttpRequest;
import java.net.http.HttpResponse;
import java.nio.charset.StandardCharsets;
import java.nio.file.Files;
import java.nio.file.Path;
import java.security.MessageDigest;
import java.time.Duration;
import java.util.Base64;
import java.util.Map;
```

```
import java.util.concurrent.atomic.AtomicInteger;
import java.util.concurrent.atomic.AtomicReference;
import org.junit.jupiter.api.AfterEach;
import org.junit.jupiter.api.BeforeEach;
import org.junit.jupiter.api.Test;
import org.junit.jupiter.api.io.TempDir;
import static org.junit.jupiter.api.Assertions.*;

class GmailAuthTest {
    @TempDir Path temp;
    private HttpServer server;
    private URI tokenUri;
    private final HttpClient http = HttpClient.newHttpClient();
    private Path credentials;
    private Path tokens;
    private final AtomicReference<TokenHandler> tokenHandler = new AtomicReference<>();

    @BeforeEach void start() throws Exception {
        credentials = temp.resolve("credentials.json");
        tokens = temp.resolve("tokens");
        Files.writeString(credentials, "{\"installed\":{\"client_id\":\"desktop-test-
client\",\"client_secret\":\"test-secret\"}}");
        server = HttpServer.create(new InetSocketAddress("127.0.0.1", 0), 0);
        server.createContext("/token", exchange -> {
            try { tokenHandler.get().handle(exchange); }
            catch (Throwable failure) { reply(exchange, 500, "{}"); }
        });
        server.start();
        tokenUri = URI.create("http://127.0.0.1:" + server.getAddress().getPort() + "/token");
    }

    @AfterEach void stop() { server.stop(0); }

    @Test void authorizationUsesPkceRejectsWrongStateAndReusesProtectedCache() throws Exception {
        AtomicReference<Map<String, String>> authorization = new AtomicReference<>();
        AtomicInteger browserCalls = new AtomicInteger();
        tokenHandler.set(exchange -> {
            Map<String, String> form = GmailAuth.parseQuery(
                    new String(exchange.getRequestBody().readAllBytes(), StandardCharsets.UTF_8));
            assertEquals("authorization_code", form.get("grant_type"));
            assertEquals("auth-code", form.get("code"));
            assertEquals("desktop-test-client", form.get("client_id"));
            String challenge =
Base64.getUrlEncoder().withoutPadding().encodeToString(MessageDigest.getInstance("SHA-256")
                    .digest(form.get("code_verifier").getBytes(StandardCharsets.US_ASCII)));
            assertEquals(authorization.get().get("code_challenge"), challenge);
            reply(exchange, 200, "{\"access_token\":\"initial-access\",\"refresh_token\":\"refresh-
value\",\"expires_in\":3600}");
        });
        GmailAuth client = client(uri -> {
            browserCalls.incrementAndGet();
            Map<String, String> query = GmailAuth.parseQuery(uri.getRawQuery());
            authorization.set(query);
            assertEquals("S256", query.get("code_challenge_method"));
            assertEquals(GmailAuth.SCOPE, query.get("scope"));
            assertEquals("offline", query.get("access_type"));
            assertTrue(query.get("prompt").contains("select_account"));
            URI callback = URI.create(query.get("redirect_uri"));
            assertEquals("127.0.0.1", callback.getHost());
            assertEquals(400, callback(callback, "state=wrong&code=attack").statusCode());
            assertEquals(200, callback(callback, "state=" + query.get("state") + "&code=auth-
code").statusCode());
        });
        client.authorize();
        assertEquals("initial-access", client.accessToken());
        assertTrue(Files.exists(tokens.resolve("gmail-token.json")));
        GmailAuth restarted = client(uri -> fail("Valid stored token should not reopen browser"));
        restarted.authorize();
        assertEquals("initial-access", restarted.accessToken());
        assertEquals(1, browserCalls.get());
        tokenHandler.set(exchange -> {
            Map<String, String> form = GmailAuth.parseQuery(
                    new String(exchange.getRequestBody().readAllBytes(), StandardCharsets.UTF_8));
            assertEquals("refresh_token", form.get("grant_type"));
            assertEquals("refresh-value", form.get("refresh_token"));
            reply(exchange, 200, "{\"access_token\":\"renewed-access\",\"expires_in\":3600}");
        });
        assertEquals("renewed-access", restarted.refreshAccessToken());
        assertTrue(Files.readString(tokens.resolve("gmail-token.json")).contains("refresh-value"));
        restarted.disconnect();
        assertFalse(Files.exists(tokens.resolve("gmail-token.json")));
        assertThrows(AppException.class, restarted::accessToken);
    }

    @Test void deniedAuthorizationDoesNotSaveTokens() {
        GmailAuth client = client(uri -> {
            Map<String, String> query = GmailAuth.parseQuery(uri.getRawQuery());
            callback(URI.create(query.get("redirect_uri")), "state=" + query.get("state") +
"&error=access_denied");
        });
        AppException failure = assertThrows(AppException.class, client::authorize);
        assertTrue(failure.getMessage().contains("denied"));
        assertFalse(Files.exists(tokens.resolve("gmail-token.json")));
    }
```

```
    @Test void missingCredentialsExplainsDesktopSetup() throws Exception {
        Files.delete(credentials);
        AppException failure = assertThrows(AppException.class, () -> client(uri -> fail()).authorize());
        assertTrue(failure.getMessage().contains("Desktop app"));
        assertTrue(failure.getMessage().contains("README.md"));
    }

    @Test void rejectsWebClientCredentials() throws Exception {
        Files.writeString(credentials, "{\"web\":{\"client_id\":\"not-desktop\"}}");
        AppException failure = assertThrows(AppException.class, () -> client(uri -> fail()).authorize());
        assertTrue(failure.getMessage().contains("Desktop app"));
    }

    @Test void timesOutAndClosesLoopbackListener() {
        AtomicReference<URI> callback = new AtomicReference<>();
        GmailAuth client = new GmailAuth(credentials, tokens, http, tokenUri, tokenUri,
                uri -> callback.set(URI.create(GmailAuth.parseQuery(uri.getRawQuery()).get("redirect_uri"))),
                Duration.ofMillis(100));
        AppException failure = assertThrows(AppException.class, client::authorize);
        assertTrue(failure.getMessage().contains("timed out"));
        assertThrows(IOException.class, () -> http.send(HttpRequest.newBuilder(callback.get()).GET().build(),
                HttpResponse.BodyHandlers.ofString()));
    }

    @Test void revokedRefreshTokenIsForgottenWithoutEchoingProviderPayload() throws Exception {
        Files.createDirectories(tokens);
        Files.writeString(tokens.resolve("gmail-token.json"), "{\"client_id\":\"desktop-test-client\","
                + "\"access_token\":\"old\",\"refresh_token\":\"revoked\",\"expires_at\":0}");
        tokenHandler.set(exchange -> reply(exchange, 400, "{\"error\":\"invalid_grant\",\"private\":\"secret-
value\"}"));
        GmailAuth client = client(uri -> {
            assertFalse(Files.exists(tokens.resolve("gmail-token.json")));
            Map<String, String> query = GmailAuth.parseQuery(uri.getRawQuery());
            callback(URI.create(query.get("redirect_uri")), "state=" + query.get("state") +
"&error=access_denied");
        });
        AppException failure = assertThrows(AppException.class, client::authorize);
        assertFalse(failure.getMessage().contains("secret-value"));
        assertFalse(Files.exists(tokens.resolve("gmail-token.json")));
    }

    private GmailAuth client(GmailAuth.BrowserOpener browser) {
        return new GmailAuth(credentials, tokens, http, tokenUri, tokenUri, browser, Duration.ofSeconds(3));
    }

    private HttpResponse<String> callback(URI uri, String query) throws Exception {
        return http.send(HttpRequest.newBuilder(URI.create(uri + "?" + query)).GET().build(),
                HttpResponse.BodyHandlers.ofString());
    }

    private static void reply(HttpExchange exchange, int status, String text) throws IOException {
        byte[] bytes = text.getBytes(StandardCharsets.UTF_8);
        exchange.sendResponseHeaders(status, bytes.length);
        try (var out = exchange.getResponseBody()) { out.write(bytes); }
    }

    @FunctionalInterface private interface TokenHandler { void handle(HttpExchange exchange) throws Exception; }
}
```

src/test/java/ems/gmail/SimpleJsonTest.java

```
package ems.gmail;

import org.junit.jupiter.api.Test;
import static org.junit.jupiter.api.Assertions.*;

class SimpleJsonTest {
    @Test void rejectsIncompleteOrTrailingJsonRatherThanReturningPartialData() {
        for (String invalid : new String[] {"{\"id\":\"one\"", "[1", "\"open", "{} trailing", "{id:1}"}) {
            assertThrows(RuntimeException.class, () -> SimpleJson.parse(invalid), invalid);
        }
    }

    @Test void retainsTeammateHelperContractForUnicodeAndNumbers() {
        var object = SimpleJson.parseObject("{\"subject\":\"Hello
\\u20ac\",\"count\":42,\"nested\":{\"ok\":true}}");
        assertEquals("Hello €", SimpleJson.getString(object, "subject"));
        assertEquals(42L, object.get("count"));
        assertEquals(Boolean.TRUE, SimpleJson.getObject(object, "nested").get("ok"));
        assertEquals("a\\n\\\"b", SimpleJson.escapeString("a\n\"b"));
    }
}
```

src/test/java/ems/service/GmailEmailServiceTest.java

```
package ems.service;

import ems.exception.AppException;
import ems.gmail.GmailGateway;
import ems.model.*;
import ems.storage.*;
import java.lang.reflect.InvocationTargetException;
import java.lang.reflect.Proxy;
import java.sql.DriverManager;
import java.sql.SQLException;
import java.time.Instant;
import java.util.*;
import java.util.concurrent.atomic.AtomicBoolean;
import org.junit.jupiter.api.BeforeEach;
import org.junit.jupiter.api.Test;
import static org.junit.jupiter.api.Assertions.*;

/** Service orchestration uses a real JDBC store and a deterministic remote mailbox. */
class GmailEmailServiceTest {
    private JdbcMailStore store;
    private FakeGmail gmail;
    private GmailEmailService service;

    @BeforeEach void setup() {
        String url = "jdbc:h2:mem:service-" + UUID.randomUUID() + ";MODE=MySQL;DB_CLOSE_DELAY=-
1;DATABASE_TO_LOWER=TRUE";
        store = new JdbcMailStore(() -> DriverManager.getConnection(url));
        gmail = new FakeGmail();
        gmail.messages.put("received", message(0, "received", Set.of("INBOX", "UNREAD")));
        service = new GmailEmailService(gmail, store);
    }

    @Test void receiveSearchReadSendAndCorrectThroughRealJdbc() throws Exception {
        service.connectGmail(); service.refresh();
        assertEquals(1, service.getMessages(Mailbox.INBOX, "prize").size());
        assertEquals(0, gmail.modifications, "Automatic spam analysis must not change Gmail labels");
        assertTrue(service.getSpamResult("received").isSuspectedSpam());
        assertFalse(service.openMessage("received").getGmailLabelIds().contains("UNREAD"));
        assertEquals(1, gmail.modifications);
        String sentId = service.sendMessage("friend@external.test", "Hello", "A real outbound message
contract.");
        assertEquals(sentId, service.getMessages(Mailbox.SENT, "Hello").get(0).getGmailMessageId());
        service.markAsNotSpam("received"); service.refresh();
        assertFalse(service.getSpamResult("received").isSuspectedSpam(), "User correction survives analysis on
refresh");
        service.markAsSpam("received");
        assertEquals(1, service.getMessages(Mailbox.SPAM, "").size());
        assertEquals(0, service.getMessages(Mailbox.INBOX, "").size());
    }

    @Test void networkFailurePreservesCacheAndSuccessfulSnapshotRemovesDeletedMessages() throws Exception {
        service.connectGmail(); service.refresh(); gmail.failFetch = true;
        assertThrows(AppException.class, service::refresh);
        assertEquals(1, service.getMessages(Mailbox.INBOX, "").size());
        gmail.failFetch = false; gmail.messages.clear(); service.refresh();
        assertTrue(service.getMessages(Mailbox.INBOX, "").isEmpty());
    }

    @Test void remoteFailuresDoNotSaveUnconfirmedCorrections() throws Exception {
        service.connectGmail(); service.refresh(); gmail.failModification = true;
        assertThrows(AppException.class, () -> service.markAsNotSpam("received"));
        assertTrue(service.getSpamResult("received").isSuspectedSpam());
        assertTrue(service.getMessages(Mailbox.SPAM, "").isEmpty());
    }

    @Test void refreshingSampleReplacesOnlyTheLocalSampleSnapshot() throws Exception {
        service.connectGmail(); service.refresh();
        gmail.messages.clear();
        gmail.messages.put("newer", message(0, "newer", Set.of("INBOX")));
        service.refreshRecent();
        assertEquals(1, service.getMessages(Mailbox.INBOX, "").size());
        assertFalse(store.findMessage(service.connectGmail().getAccountId(), "received").isPresent());
        assertEquals(0, gmail.modifications, "Replacing the local sample must not change Gmail labels");
    }

    @Test void sampleImportsNeverExceedEighteenMessages() throws Exception {
        for (int i = 0; i < 30; i++) gmail.messages.put("sample" + i, message(0, "sample" + i,
Set.of("INBOX")));
        service.connectGmail(); service.refresh();
        assertEquals(18, service.getMessages(Mailbox.INBOX, "").size());
        service.refreshRecent();
        assertEquals(18, service.getMessages(Mailbox.INBOX, "").size());
    }

    @Test void databaseFailureAfterDeliveryReturnsSuccessAndWarningWithoutAnotherSend() throws Exception {
        AtomicBoolean failWrites = new AtomicBoolean();
        MailStore unreliable = (MailStore) Proxy.newProxyInstance(MailStore.class.getClassLoader(),
                new Class<?>[] {MailStore.class}, (proxy, method, arguments) -> {
```

```
                    if (failWrites.get() && method.getName().equals("saveMessages")) throw new
SQLException("Test unavailable");
                    try { return method.invoke(store, arguments); }
                    catch (InvocationTargetException exception) { throw exception.getCause(); }
                });
        service = new GmailEmailService(gmail, unreliable);
        service.connectGmail(); service.refresh(); failWrites.set(true);
        assertEquals("sent1", service.sendMessage("friend@external.test", "Hello", "Sent once."));
        assertEquals(1, gmail.sends);
        assertTrue(service.getLastWarning().contains("was sent"));
    }

    @Test void missingMessagesAndAccountSwitchCannotAccessAnotherCachedAccount() throws Exception {
        Account first = service.connectGmail(); service.refresh();
        assertThrows(AppException.class, () -> service.openMessage("someone-elses-message"));
        assertEquals(0, gmail.modifications);
        service.disconnect();
        assertThrows(AppException.class, () -> service.getMessages(Mailbox.INBOX, ""));
        gmail.email = "second@external.test"; gmail.messages.clear();
        Account second = service.connectGmail(); service.refresh();
        assertNotEquals(first.getAccountId(), second.getAccountId());
        assertTrue(service.getMessages(Mailbox.INBOX, "").isEmpty());
        assertThrows(AppException.class, () -> service.openMessage("received"));
        assertTrue(store.findMessage(first.getAccountId(), "received").isPresent());
    }

    @Test void validatesRecipientAndHeaderInjectionBeforeSending() throws Exception {
        service.connectGmail();
        assertThrows(AppException.class, () -> service.sendMessage("a@test.test,b@test.test", "Hi", "body"));
        assertThrows(AppException.class, () -> service.sendMessage("a@test.test\r\nBcc: b@test.test", "Hi",
"body"));
        assertThrows(AppException.class, () -> service.sendMessage("a@test.test", "Hi\r\nBcc: b@test.test",
"body"));
        assertEquals(0, gmail.sends);
    }

    private static EmailMessage message(long accountId, String id, Set<String> labels) {
        return new EmailMessage(accountId, id, "sender@external.test", List.of("student@example.test"),
                "URGENT: Claim your prize", "Verify your account https://1.test https://2.test https://3.test
https://4.test https://5.test",
                Instant.parse("2026-10-20T06:00:00Z"), labels);
    }

    private static final class FakeGmail implements GmailGateway {
        String email = "student@example.test";
        final Map<String, EmailMessage> messages = new LinkedHashMap<>();
        int modifications;
        int sends;
        boolean failFetch;
        boolean failModification;
        @Override public String connect() { return email; }
        @Override public void disconnect() { }
        @Override public List<EmailMessage> fetchMessages(long accountId) throws AppException {
            if (failFetch) throw new AppException("Test network unavailable");
            return messages.values().stream().map(m -> copy(m, accountId, m.getGmailLabelIds())).toList();
        }
        @Override public EmailMessage getMessage(long accountId, String id) throws AppException {
            if (!messages.containsKey(id)) throw new AppException("Test message missing");
            EmailMessage message = messages.get(id);
            return copy(message, accountId, message.getGmailLabelIds());
        }
        @Override public String sendMessage(String sender, String recipient, String subject, String body) {
            String id = "sent" + ++sends;
            messages.put(id, new EmailMessage(0, id, sender, List.of(recipient), subject, body, Instant.now(),
Set.of("SENT")));
            return id;
        }
        @Override public void setRead(String id) throws AppException {
            checkModification();
            Set<String> labels = new HashSet<>(messages.get(id).getGmailLabelIds()); labels.remove("UNREAD");
            messages.put(id, copy(messages.get(id), 0, labels));
        }
        @Override public void setSpam(String id, boolean spam) throws AppException {
            checkModification();
            Set<String> labels = new HashSet<>(messages.get(id).getGmailLabelIds());
            if (spam) { labels.add("SPAM"); labels.remove("INBOX"); }
            else { labels.remove("SPAM"); labels.add("INBOX"); }
            messages.put(id, copy(messages.get(id), 0, labels));
        }
        private void checkModification() throws AppException {
            if (failModification) throw new AppException("Test change rejected");
            modifications++;
        }
        private static EmailMessage copy(EmailMessage message, long accountId, Set<String> labels) {
            return new EmailMessage(accountId, message.getGmailMessageId(), message.getSenderEmail(),
message.getRecipientEmails(),
                    message.getSubject(), message.getBodyText(), message.getReceivedAt(), labels);
        }
    }
}
```

src/test/java/ems/service/RealMySqlTest.java

```
package ems.service;

import ems.config.AppConfig;
import ems.exception.AppException;
import ems.gmail.GmailGateway;
import ems.model.*;
import ems.storage.JdbcMailStore;
import java.sql.*;
import java.time.Instant;
import java.util.*;
import org.junit.jupiter.api.Test;
import org.junit.jupiter.api.condition.EnabledIfSystemProperty;
import static org.junit.jupiter.api.Assertions.*;

/** Opt-in real MySQL round trip; Gmail remains a fake so no real email is sent. */
@EnabledIfSystemProperty(named = "maildesk.mysqlTest", matches = "true")
class RealMySqlTest {
    @Test void realDatabasePersistsTheCompleteServiceFlow() throws Exception {
        AppConfig config = AppConfig.load();
        JdbcMailStore store = new JdbcMailStore(() -> connect(config));
        String email = "maildesk-check-" + UUID.randomUUID() + "@example.test";
        TestGateway gateway = new TestGateway(email);
        GmailEmailService service = new GmailEmailService(gateway, store);
        Account account = null;
        try {
            account = service.connectGmail();
            service.refresh();
            assertEquals(1, service.getMessages(Mailbox.INBOX, "café").size());
            assertTrue(service.getSpamResult("incoming").isSuspectedSpam());
            assertFalse(service.openMessage("incoming").getGmailLabelIds().contains("UNREAD"));
            assertEquals("outgoing", service.sendMessage("friend@external.test", "Project update café", "MySQL
integration fixture."));
            assertEquals(1, service.getMessages(Mailbox.SENT, "café").size());
            service.markAsNotSpam("incoming"); service.refresh();
            assertFalse(service.getSpamResult("incoming").isSuspectedSpam());
            service.markAsSpam("incoming");
            assertEquals(1, service.getMessages(Mailbox.SPAM, "").size());
            assertTrue(service.getMessages(Mailbox.SUSPECTED, "").isEmpty());
            JdbcMailStore reopened = new JdbcMailStore(() -> connect(config));
            assertEquals(Set.of("SPAM"), reopened.findMessage(account.getAccountId(),
"incoming").orElseThrow().getGmailLabelIds());
            assertTrue(reopened.getSpamResult(account.getAccountId(), "incoming").isSuspectedSpam());
            gateway.messages.remove("incoming"); service.refresh();
            assertTrue(service.getMessages(Mailbox.SPAM, "").isEmpty());
        } finally {
            service.disconnect();
            if (account != null) removeFixture(config, account, email);
        }
    }

    private static Connection connect(AppConfig config) throws SQLException {
        return DriverManager.getConnection(config.getDatabaseUrl(), config.getDatabaseUser(),
config.getDatabasePassword());
    }

    private static void removeFixture(AppConfig config, Account account, String expectedEmail) throws
SQLException {
        // Every cleanup statement is scoped to this newly created random fixture account.
        try (Connection connection = connect(config)) {
            connection.setAutoCommit(false);
            try {
                for (String table : List.of("spam_feedback", "blocked_senders", "messages")) {
                    try (PreparedStatement statement = connection.prepareStatement("DELETE FROM " + table + "
WHERE account_id=?")) {
                        statement.setLong(1, account.getAccountId()); statement.executeUpdate();
                    }
                }
                try (PreparedStatement statement = connection.prepareStatement("DELETE FROM accounts WHERE
account_id=? AND email_address=?")) {
                    statement.setLong(1, account.getAccountId()); statement.setString(2, expectedEmail);
statement.executeUpdate();
                }
                connection.commit();
            } catch (SQLException exception) { connection.rollback(); throw exception; }
        }
    }

    private static final class TestGateway implements GmailGateway {
        private final String email;
        private final Map<String, EmailMessage> messages = new LinkedHashMap<>();
        TestGateway(String email) {
            this.email = email;
            messages.put("incoming", new EmailMessage(0, "incoming", "sender@external.test", List.of(email),
                    "URGENT: Claim your prize café", "Verify your account https://a.test https://b.test
https://c.test https://d.test https://e.test",
                    Instant.parse("2026-10-20T06:00:00.123456Z"), Set.of("INBOX", "UNREAD")));
        }
        @Override public String connect() { return email; }
        @Override public void disconnect() { }
        @Override public List<EmailMessage> fetchMessages(long accountId) {
            return messages.values().stream().map(m -> copy(m, accountId, m.getGmailLabelIds())).toList();
```

```
        }
        @Override public EmailMessage getMessage(long accountId, String id) throws AppException {
            EmailMessage message = messages.get(id);
            if (message == null) throw new AppException("Fixture missing");
            return copy(message, accountId, message.getGmailLabelIds());
        }
        @Override public String sendMessage(String sender, String recipient, String subject, String body) {
            messages.put("outgoing", new EmailMessage(0, "outgoing", sender, List.of(recipient), subject, body,
Instant.now(), Set.of("SENT")));
            return "outgoing";
        }
        @Override public void setRead(String id) {
            Set<String> labels = new HashSet<>(messages.get(id).getGmailLabelIds()); labels.remove("UNREAD");
            messages.put(id, copy(messages.get(id), 0, labels));
        }
        @Override public void setSpam(String id, boolean spam) {
            Set<String> labels = new HashSet<>(messages.get(id).getGmailLabelIds());
            if (spam) { labels.add("SPAM"); labels.remove("INBOX"); } else { labels.remove("SPAM");
labels.add("INBOX"); }
            messages.put(id, copy(messages.get(id), 0, labels));
        }
        private static EmailMessage copy(EmailMessage message, long accountId, Set<String> labels) {
            return new EmailMessage(accountId, message.getGmailMessageId(), message.getSenderEmail(),
message.getRecipientEmails(),
                    message.getSubject(), message.getBodyText(), message.getReceivedAt(), labels);
        }
    }
}
```

src/test/java/ems/storage/JdbcMailStoreTest.java

```
package ems.storage;

import ems.model.Account;
import ems.model.EmailMessage;
import ems.model.Mailbox;
import ems.model.SpamResult;
import java.sql.Connection;
import java.sql.DriverManager;
import java.sql.PreparedStatement;
import java.sql.ResultSet;
import java.sql.SQLException;
import java.time.Instant;
import java.util.List;
import java.util.Set;
import java.util.UUID;
import org.junit.jupiter.api.BeforeEach;
import org.junit.jupiter.api.Test;
import static org.junit.jupiter.api.Assertions.*;

class JdbcMailStoreTest {
    private JdbcMailStore store;
    private String url;
    private Account alice;
    private Account bob;

    @BeforeEach void prepareDatabase() throws SQLException {
        url = "jdbc:h2:mem:" + UUID.randomUUID() + ";MODE=MySQL;DATABASE_TO_LOWER=TRUE;DB_CLOSE_DELAY=-1";
        store = new JdbcMailStore(() -> DriverManager.getConnection(url));
        store.initialize();
        alice = store.findOrCreateAccount("alice@example.com");
        bob = store.findOrCreateAccount("bob@example.com");
    }

    private EmailMessage message(Account account, String id, String subject, String body, Set<String> labels) {
        return new EmailMessage(account.getAccountId(), id, "sender@example.com",
List.of("recipient@example.com"),
                subject, body, Instant.parse("2026-10-20T10:15:00.123456Z"), labels);
    }

    private EmailMessage normal(Account account, String id) {
        return message(account, id, "Meeting notes", "Project update", Set.of("INBOX", "UNREAD"));
    }

    private EmailMessage suspicious(Account account, String id) {
        return message(account, id, "URGENT: Claim your prize", "You have won! Verify your account now.",
Set.of("INBOX"));
    }

    @Test void initializerIsIdempotentAndAccountAddressesAreNormalized() throws SQLException {
        store.initialize();
        Account same = store.findOrCreateAccount("  ALICE@EXAMPLE.COM ");
        assertEquals(alice.getAccountId(), same.getAccountId());
        assertEquals("alice@example.com", same.getEmailAddress());
        assertNotEquals(alice.getAccountId(), bob.getAccountId());
    }

    @Test void refreshUpsertHasNoDuplicatesAndReplacesRecipientsAndLabels() throws SQLException {
        EmailMessage original = normal(alice, "same");
        store.saveMessages(alice.getAccountId(), List.of(original));
```

```
        store.saveMessages(alice.getAccountId(), List.of(original));
        EmailMessage moved = new EmailMessage(alice.getAccountId(), "same", "sender@example.com",
                List.of("new@example.com", "new@example.com"), "Changed", "New body", original.getReceivedAt(),
Set.of("SPAM"));
        store.saveMessages(alice.getAccountId(), List.of(moved));

        assertEquals(1, store.findAll(alice.getAccountId()).size());
        EmailMessage saved = store.findMessage(alice.getAccountId(), "same").orElseThrow();
        assertEquals(List.of("new@example.com"), saved.getRecipientEmails());
        assertEquals(Set.of("SPAM"), saved.getGmailLabelIds());
        assertEquals("Changed", saved.getSubject());
        assertTrue(store.getMessages(alice.getAccountId(), Mailbox.INBOX, "").isEmpty());
        assertEquals(1, store.getMessages(alice.getAccountId(), Mailbox.SPAM, "").size());
        assertTrue(readColumn(alice.getAccountId(), "same"));
    }

    @Test void timestampRoundTripsAsAnInstant() throws SQLException {
        EmailMessage original = normal(alice, "time");
        store.saveMessages(alice.getAccountId(), List.of(original));
        assertEquals(original.getReceivedAt(), store.findMessage(alice.getAccountId(),
"time").orElseThrow().getReceivedAt());
    }

    @Test void repeatedRecipientsAcrossHeadersAreDeduplicatedIgnoringCase() throws SQLException {
        EmailMessage original = normal(alice, "recipients");
        EmailMessage repeated = new EmailMessage(alice.getAccountId(), original.getGmailMessageId(),
                original.getSenderEmail(), List.of("Person@example.com", "person@EXAMPLE.COM"),
                original.getSubject(), original.getBodyText(), original.getReceivedAt(),
original.getGmailLabelIds());
        store.saveMessages(alice.getAccountId(), List.of(repeated));
        assertEquals(List.of("Person@example.com"), store.findMessage(alice.getAccountId(), "recipients")
                .orElseThrow().getRecipientEmails());
    }

    @Test void incomingUnreadLabelControlsReadStatusAndLegacyMethodKeepsItConsistent() throws SQLException {
        store.saveMessages(alice.getAccountId(), List.of(normal(alice, "unread")));
        assertFalse(readColumn(alice.getAccountId(), "unread"));
        store.updateReadStatus(alice.getAccountId(), "unread", true);
        assertTrue(readColumn(alice.getAccountId(), "unread"));
        assertFalse(store.findMessage(alice.getAccountId(),
"unread").orElseThrow().getGmailLabelIds().contains("UNREAD"));
        store.updateReadStatus(alice.getAccountId(), "unread", false);
        store.updateReadStatus(alice.getAccountId(), "unread", false);
        assertFalse(readColumn(alice.getAccountId(), "unread"));
        assertTrue(store.findMessage(alice.getAccountId(),
"unread").orElseThrow().getGmailLabelIds().contains("UNREAD"));
    }

    @Test void accountIsolationAppliesToEveryReadWriteAndFeedback() throws SQLException {
        store.saveMessages(alice.getAccountId(), List.of(normal(alice, "same-id")));
        store.saveMessages(bob.getAccountId(), List.of(suspicious(bob, "same-id")));
        store.saveFeedback(alice.getAccountId(), "same-id", false);
        assertEquals("Meeting notes", store.findMessage(alice.getAccountId(), "same-
id").orElseThrow().getSubject());
        assertTrue(store.getSpamResult(bob.getAccountId(), "same-id").isSuspectedSpam());
        assertFalse(store.getSpamResult(alice.getAccountId(), "same-id").isSuspectedSpam());
        assertThrows(SQLException.class, () -> store.saveMessages(alice.getAccountId(), List.of(normal(bob,
"bad"))));
        store.deleteMessages(alice.getAccountId(), List.of("same-id"));
        assertTrue(store.findMessage(alice.getAccountId(), "same-id").isEmpty());
        assertTrue(store.findMessage(bob.getAccountId(), "same-id").isPresent());
        assertThrows(SQLException.class, () -> store.saveFeedback(alice.getAccountId(), "missing", true));
    }

    @Test void accountWithNoMessagesReturnsEmptyLists() throws SQLException {
        for (Mailbox mailbox : Mailbox.values()) assertTrue(store.getMessages(bob.getAccountId(), mailbox,
"").isEmpty());
        assertTrue(store.findMessage(bob.getAccountId(), "missing").isEmpty());
    }

    @Test void localSpamAndGmailSpamAreDistinct() throws SQLException {
        store.saveMessages(alice.getAccountId(), List.of(suspicious(alice, "local"),
                message(alice, "gmail", "Meeting notes", "Project update", Set.of("SPAM"))));
        assertEquals(List.of("local"), store.getMessages(alice.getAccountId(), Mailbox.SUSPECTED,
"").stream().map(EmailMessage::getGmailMessageId).toList());
        assertEquals(List.of("gmail"), store.getMessages(alice.getAccountId(), Mailbox.SPAM,
"").stream().map(EmailMessage::getGmailMessageId).toList());
        assertFalse(store.getSpamResult(alice.getAccountId(), "gmail").isSuspectedSpam());
    }

    @Test void suspectedReviewExcludesGmailSpamAndAllSentMailEvenWhenClassifierFlagsThem() throws SQLException {
        String subject = "URGENT: Claim your prize";
        String body = "You have won! Verify your account now.";
        store.saveMessages(alice.getAccountId(), List.of(suspicious(alice, "review"),
                message(alice, "gmail-spam", subject, body, Set.of("SPAM")),
                message(alice, "sent", subject, body, Set.of("SENT")),
                message(alice, "self-sent", subject, body, Set.of("SENT", "INBOX"))));
        assertTrue(store.getSpamResult(alice.getAccountId(), "gmail-spam").isSuspectedSpam());
        assertTrue(store.getSpamResult(alice.getAccountId(), "sent").isSuspectedSpam());
        assertTrue(store.getSpamResult(alice.getAccountId(), "self-sent").isSuspectedSpam());
        assertEquals(List.of("review"), store.getMessages(alice.getAccountId(), Mailbox.SUSPECTED, "")
                .stream().map(EmailMessage::getGmailMessageId).toList());
        assertEquals(1, store.getMessages(alice.getAccountId(), Mailbox.SPAM, "").size());
```

```
        assertEquals(2, store.getMessages(alice.getAccountId(), Mailbox.SENT, "").size());
        store.saveFeedback(alice.getAccountId(), "gmail-spam", true);
        assertEquals(1, store.getMessages(alice.getAccountId(), Mailbox.SUSPECTED, "").size());
    }

    @Test void userFeedbackSurvivesRefreshAndNewStoreInstance() throws SQLException {
        EmailMessage mail = suspicious(alice, "corrected");
        store.saveMessages(alice.getAccountId(), List.of(mail));
        store.saveFeedback(alice.getAccountId(), "corrected", false);
        store.saveMessages(alice.getAccountId(), List.of(mail));
        store = new JdbcMailStore(() -> DriverManager.getConnection(url));
        assertFalse(store.getSpamResult(alice.getAccountId(), "corrected").isSuspectedSpam());
        assertTrue(store.getMessages(alice.getAccountId(), Mailbox.SUSPECTED, "").isEmpty());
        store.saveFeedback(alice.getAccountId(), "corrected", true);
        store.saveMessages(alice.getAccountId(), List.of(normal(alice, "corrected")));
        assertTrue(store.getSpamResult(alice.getAccountId(), "corrected").isSuspectedSpam());
        assertEquals(1, store.getMessages(alice.getAccountId(), Mailbox.SUSPECTED, "").size());
    }

    @Test void snapshotPrunesRemovedMessagesAtomicallyAndFeedbackSurvivesRedownload() throws SQLException {
        store.saveMessages(alice.getAccountId(), List.of(normal(alice, "keep"), suspicious(alice, "remove")));
        store.saveMessages(bob.getAccountId(), List.of(normal(bob, "remove")));
        store.saveFeedback(alice.getAccountId(), "remove", false);
        store.replaceSnapshot(alice.getAccountId(), List.of(normal(alice, "keep")));
        assertTrue(store.findMessage(alice.getAccountId(), "remove").isEmpty());
        assertTrue(store.findMessage(bob.getAccountId(), "remove").isPresent());
        store.saveMessages(alice.getAccountId(), List.of(suspicious(alice, "remove")));
        assertFalse(store.getSpamResult(alice.getAccountId(), "remove").isSuspectedSpam());
        store.replaceSnapshot(alice.getAccountId(), List.of());
        assertTrue(store.findAll(alice.getAccountId()).isEmpty());
        assertFalse(store.findAll(bob.getAccountId()).isEmpty());
    }

    @Test void invalidBatchRollsBackContentRecipientsLabelsScoresAndSnapshotPruning() throws SQLException {
        store.saveMessages(alice.getAccountId(), List.of(normal(alice, "keep"), normal(alice, "existing")));
        EmailMessage invalid = new EmailMessage(alice.getAccountId(), "invalid", "sender@example.com",
                List.of("x".repeat(321)), "subject", "body", Instant.now(), Set.of("INBOX"));
        assertThrows(SQLException.class, () -> store.replaceSnapshot(alice.getAccountId(),
List.of(suspicious(alice, "existing"), invalid)));
        assertEquals("Meeting notes", store.findMessage(alice.getAccountId(),
"existing").orElseThrow().getSubject());
        assertEquals(Set.of("INBOX", "UNREAD"), store.findMessage(alice.getAccountId(),
"existing").orElseThrow().getGmailLabelIds());
        assertFalse(store.getSpamResult(alice.getAccountId(), "existing").isSuspectedSpam());
        assertTrue(store.findMessage(alice.getAccountId(), "invalid").isEmpty());
        assertTrue(store.findMessage(alice.getAccountId(), "keep").isPresent());
    }

    @Test void searchIsCaseInsensitiveMatchesAllFieldsAndEscapesLikeWildcards() throws SQLException {
        store.saveMessages(alice.getAccountId(), List.of(
                message(alice, "literal", "100%_done!", "Project update", Set.of("INBOX")),
                normal(alice, "other")));
        assertEquals(1, store.getMessages(alice.getAccountId(), Mailbox.INBOX, "%_done!").size());
        assertEquals(2, store.getMessages(alice.getAccountId(), Mailbox.INBOX, "PROJECT UPDATE").size());
        assertEquals(2, store.getMessages(alice.getAccountId(), Mailbox.INBOX, "RECIPIENT@EXAMPLE.COM").size());
        assertEquals(2, store.getMessages(alice.getAccountId(), Mailbox.INBOX, "SENDER@EXAMPLE.COM").size());
        assertTrue(store.getMessages(alice.getAccountId(), Mailbox.INBOX, "' OR 1=1 --").isEmpty());
    }

    @Test void sentAndTrashViewsFollowGmailLabels() throws SQLException {
        store.saveMessages(alice.getAccountId(), List.of(normal(alice, "inbox"),
                message(alice, "sent", "Sent", "Hello", Set.of("SENT")),
                message(alice, "trashed", "Trash", "Hello", Set.of("INBOX", "TRASH"))));
        assertEquals(1, store.getMessages(alice.getAccountId(), Mailbox.INBOX, "").size());
        assertEquals(1, store.getMessages(alice.getAccountId(), Mailbox.SENT, "").size());
        assertEquals("sent", store.getMessages(alice.getAccountId(), Mailbox.SENT,
"").get(0).getGmailMessageId());
    }

    @Test void blockedSendersAreNormalizedAndScopedToTheirAccount() throws SQLException {
        store.setSenderBlocked(alice.getAccountId(), " SENDER@EXAMPLE.COM ", true);
        store.setSenderBlocked(alice.getAccountId(), "sender@example.com", true);
        assertTrue(store.isSenderBlocked(alice.getAccountId(), "sender@example.com"));
        assertFalse(store.isSenderBlocked(bob.getAccountId(), "sender@example.com"));
        store.saveMessages(alice.getAccountId(), List.of(normal(alice, "blocked")));
        store.saveMessages(bob.getAccountId(), List.of(normal(bob, "normal")));
        assertTrue(store.getSpamResult(alice.getAccountId(), "blocked").isSuspectedSpam());
        assertFalse(store.getSpamResult(bob.getAccountId(), "normal").isSuspectedSpam());
        store.setSenderBlocked(alice.getAccountId(), "sender@example.com", false);
        store.saveMessages(alice.getAccountId(), List.of(normal(alice, "blocked")));
        assertFalse(store.getSpamResult(alice.getAccountId(), "blocked").isSuspectedSpam());
    }

    @Test void reasonJsonRoundTripsPunctuationControlCharactersAndUnicode() throws SQLException {
        store.saveMessages(alice.getAccountId(), List.of(normal(alice, "json")));
        List<String> reasons = List.of("A quote: \" and slash: \\", "line\nbreak\tand\u0001", "தமிழ் 🎉");
        store.saveSpamResult(alice.getAccountId(), "json", new SpamResult(60, true, reasons));
        assertEquals(reasons, store.getSpamResult(alice.getAccountId(), "json").getReasons());
    }

    @Test void messageBodiesMayExceedMysqlTextLimit() throws SQLException {
        String body = "Long message body. ".repeat(10_000);
```

```
        store.saveMessages(alice.getAccountId(), List.of(message(alice, "large", "Large", body,
Set.of("INBOX"))));
        assertEquals(body, store.findMessage(alice.getAccountId(), "large").orElseThrow().getBodyText());
    }

    private boolean readColumn(long accountId, String id) throws SQLException {
        try (Connection connection = DriverManager.getConnection(url);
                PreparedStatement query = connection.prepareStatement("SELECT is_read FROM messages WHERE
account_id=? AND gmail_message_id=?")) {
            query.setLong(1, accountId);
            query.setString(2, id);
            try (ResultSet rows = query.executeQuery()) { assertTrue(rows.next()); return rows.getBoolean(1); }
        }
    }
}
```

APPENDIX A.4 — DATABASE SCHEMA

sql/schema.sql

```
-- Email Management: MySQL 8.x cache schema. No OAuth tokens or passwords are stored here.
-- Use a dedicated database user with permission to create and read/write these tables.
CREATE DATABASE IF NOT EXISTS email_management CHARACTER SET utf8mb4 COLLATE utf8mb4_unicode_ci;
USE email_management;

CREATE TABLE IF NOT EXISTS accounts (
            account_id BIGINT AUTO_INCREMENT PRIMARY KEY,
            email_address VARCHAR(254) NOT NULL UNIQUE
        );

CREATE TABLE IF NOT EXISTS messages (
            account_id BIGINT NOT NULL,
            gmail_message_id VARCHAR(128) NOT NULL,
            sender_email VARCHAR(320) NOT NULL,
            subject TEXT NOT NULL,
            body_text LONGTEXT NOT NULL,
            received_at DATETIME(6) NOT NULL,
            is_read BOOLEAN NOT NULL DEFAULT TRUE,
            PRIMARY KEY (account_id, gmail_message_id),
            FOREIGN KEY (account_id) REFERENCES accounts(account_id)
        );

CREATE TABLE IF NOT EXISTS message_recipients (
            account_id BIGINT NOT NULL,
            gmail_message_id VARCHAR(128) NOT NULL,
            recipient_email VARCHAR(320) NOT NULL,
            PRIMARY KEY (account_id, gmail_message_id, recipient_email),
            FOREIGN KEY (account_id, gmail_message_id) REFERENCES messages(account_id, gmail_message_id) ON
DELETE CASCADE
        );

CREATE TABLE IF NOT EXISTS message_labels (
            account_id BIGINT NOT NULL,
            gmail_message_id VARCHAR(128) NOT NULL,
            gmail_label_id VARCHAR(128) NOT NULL,
            PRIMARY KEY (account_id, gmail_message_id, gmail_label_id),
            FOREIGN KEY (account_id, gmail_message_id) REFERENCES messages(account_id, gmail_message_id) ON
DELETE CASCADE
        );

CREATE TABLE IF NOT EXISTS spam_results (
            account_id BIGINT NOT NULL,
            gmail_message_id VARCHAR(128) NOT NULL,
            score INT NOT NULL,
            suspected_spam BOOLEAN NOT NULL,
            reasons TEXT NOT NULL,
            analyzed_at DATETIME(6) NOT NULL,
            PRIMARY KEY (account_id, gmail_message_id),
            FOREIGN KEY (account_id, gmail_message_id) REFERENCES messages(account_id, gmail_message_id) ON
DELETE CASCADE
        );

CREATE TABLE IF NOT EXISTS spam_feedback (
            account_id BIGINT NOT NULL,
            gmail_message_id VARCHAR(128) NOT NULL,
            user_marked_spam BOOLEAN NOT NULL,
            corrected_at DATETIME(6) NOT NULL,
            PRIMARY KEY (account_id, gmail_message_id),
            FOREIGN KEY (account_id) REFERENCES accounts(account_id)
        );

CREATE TABLE IF NOT EXISTS blocked_senders (
            account_id BIGINT NOT NULL,
            sender_email VARCHAR(320) NOT NULL,
            PRIMARY KEY (account_id, sender_email),
            FOREIGN KEY (account_id) REFERENCES accounts(account_id)
        );
```

APPENDIX A.5 — WINDOWS BUILD AND LAUNCH SCRIPTS

scripts/build.ps1

```
[CmdletBinding()]
param([switch]$SkipTests)

Set-StrictMode -Version Latest
$ErrorActionPreference = 'Stop'
. (Join-Path $PSScriptRoot 'initialize-java.ps1')
$projectRoot = Split-Path -Parent $PSScriptRoot
Push-Location -LiteralPath $projectRoot
try {
    $mavenArguments = @('--batch-mode', '--no-transfer-progress', 'package')
    if ($SkipTests) { $mavenArguments += '-DskipTests' }
    & (Join-Path $projectRoot 'mvnw.cmd') @mavenArguments
    if ($LASTEXITCODE -ne 0) { throw "Build failed (exit code $LASTEXITCODE)." }
    Write-Host "Application: $(Join-Path $projectRoot 'target/maildesk.jar')"
} finally { Pop-Location }
```

scripts/check.ps1

```
[CmdletBinding()]
param([switch]$Render, [switch]$MySql)

Set-StrictMode -Version Latest
$ErrorActionPreference = 'Stop'
. (Join-Path $PSScriptRoot 'initialize-java.ps1')
$projectRoot = Split-Path -Parent $PSScriptRoot
Push-Location -LiteralPath $projectRoot
try {
    $mavenArguments = @('--batch-mode', '--no-transfer-progress', 'test')
    if ($Render) { $mavenArguments += '-Prender' }
    if ($MySql) { $mavenArguments += '-Dmaildesk.mysqlTest=true' }
    & (Join-Path $projectRoot 'mvnw.cmd') @mavenArguments
    if ($LASTEXITCODE -ne 0) { throw "Checks failed (exit code $LASTEXITCODE)." }
} finally { Pop-Location }
```

scripts/initialize-java.ps1

```
# Shared version of Member 2's JDK discovery for build, check, app, and demo launchers.
if (-not (Get-Command javac -CommandType Application -ErrorAction SilentlyContinue)) {
    $env:Path = [Environment]::GetEnvironmentVariable('Path', 'User') + ';' +
        [Environment]::GetEnvironmentVariable('Path', 'Machine') + ';' + $env:Path
}
$maildeskJdkCandidates = @(
    $env:JAVA_HOME
    (Join-Path $env:LOCALAPPDATA 'Programs/Eclipse Adoptium/jdk-17')
)
foreach ($maildeskJdk in $maildeskJdkCandidates) {
    if ($maildeskJdk -and (Test-Path -LiteralPath (Join-Path $maildeskJdk 'bin/javac.exe'))) {
        $env:JAVA_HOME = $maildeskJdk
        $env:Path = (Join-Path $maildeskJdk 'bin') + ';' + $env:Path
        break
    }
}
if (-not (Get-Command javac -CommandType Application -ErrorAction SilentlyContinue)) {
    throw 'Install JDK 17 or newer and set JAVA_HOME to its installation folder.'
}
```

scripts/package-windows.ps1

```
[CmdletBinding()]
param(
    [string]$JdkPath = $env:JAVA_HOME,
    [string]$OutputDirectory,
    [switch]$NoBuild,
    [switch]$UseLocalConfig
)

Set-StrictMode -Version Latest
$ErrorActionPreference = 'Stop'
$projectRoot = Split-Path -Parent $PSScriptRoot
if ([Environment]::OSVersion.Platform -ne [PlatformID]::Win32NT) {
    throw 'Build the Windows package on Windows with an x64 JDK 17 or newer.'
}
if (-not $JdkPath) {
    $packager = Get-Command jpackage -CommandType Application -ErrorAction SilentlyContinue
    if ($packager) { $JdkPath = Split-Path -Parent (Split-Path -Parent $packager.Source) }
}
if (-not $JdkPath) { throw 'Pass -JdkPath with an x64 JDK containing jpackage, jlink, and jdeps.' }
$JdkPath = (Resolve-Path -LiteralPath $JdkPath).Path
foreach ($tool in @('java', 'javac', 'jpackage', 'jlink', 'jdeps')) {
    if (-not (Test-Path -LiteralPath (Join-Path $JdkPath "bin/$tool.exe"))) {
```

```
        throw "The selected JDK is missing $tool.exe."
    }
}
$env:JAVA_HOME = $JdkPath
$env:Path = (Join-Path $JdkPath 'bin') + ';' + $env:Path
if (-not $NoBuild) { & (Join-Path $PSScriptRoot 'build.ps1') }
$applicationJar = Join-Path $projectRoot 'target/maildesk.jar'
if (-not (Test-Path -LiteralPath $applicationJar)) { throw 'Build the application first.' }
if (-not $OutputDirectory) { $OutputDirectory = Join-Path $projectRoot 'package' }
$OutputDirectory = [IO.Path]::GetFullPath($OutputDirectory)
$applicationDirectory = Join-Path $OutputDirectory 'Maildesk'
$archive = Join-Path $OutputDirectory 'Maildesk-Windows-x64.zip'
if ((Test-Path -LiteralPath $applicationDirectory) -or (Test-Path -LiteralPath $archive)) {
    throw 'The package already exists. Choose another -OutputDirectory to preserve existing local settings.'
}

$stage = Join-Path $projectRoot ('build/windows-package-' + [Guid]::NewGuid().ToString('N'))
$inputDirectory = Join-Path $stage 'input'
$runtimeDirectory = Join-Path $stage 'runtime'
New-Item -ItemType Directory -Path $inputDirectory, $OutputDirectory -Force | Out-Null
Copy-Item -LiteralPath $applicationJar -Destination (Join-Path $inputDirectory 'maildesk.jar')
$dependencyModules = & (Join-Path $JdkPath 'bin/jdeps.exe') --multi-release 17 --ignore-missing-deps --print-
module-deps $applicationJar
if ($LASTEXITCODE -ne 0) { throw 'Could not determine Java runtime modules.' }
# Explicit providers retain TLS, international mail charsets, and locale support.
$modules = @((($dependencyModules -join '') -split ',') + @('jdk.crypto.ec', 'jdk.charsets', 'jdk.localedata'))
|
    Sort-Object -Unique
& (Join-Path $JdkPath 'bin/jlink.exe') --add-modules ($modules -join ',') --output $runtimeDirectory --strip-
debug --no-header-files --no-man-pages --compress=2
if ($LASTEXITCODE -ne 0) { throw 'Could not build the bundled Java runtime.' }

$packageArguments = @('--type', 'app-image', '--name', 'Maildesk', '--app-version', '1.0.0',
    '--vendor', 'Maildesk', '--description', 'Gmail client with MySQL persistence and spam review',
    '--input', $inputDirectory, '--main-jar', 'maildesk.jar', '--main-class', 'ems.App',
    '--runtime-image', $runtimeDirectory, '--dest', $OutputDirectory,
    '--java-options', '-Dmaildesk.home=$APPDIR/..')
& (Join-Path $JdkPath 'bin/jpackage.exe') @packageArguments
if ($LASTEXITCODE -ne 0) { throw 'Windows application packaging failed.' }

$configurationDirectory = Join-Path $applicationDirectory 'config'
$schemaDirectory = Join-Path $applicationDirectory 'sql'
New-Item -ItemType Directory -Path $configurationDirectory, $schemaDirectory -Force | Out-Null
Copy-Item -LiteralPath (Join-Path $projectRoot 'config/app.properties.example') -Destination
$configurationDirectory
Copy-Item -LiteralPath (Join-Path $projectRoot 'sql/schema.sql') -Destination $schemaDirectory
Copy-Item -LiteralPath (Join-Path $projectRoot 'docs/SETUP.md') -Destination (Join-Path $applicationDirectory
'SETUP.md')
@'
MAILDESK FOR WINDOWS x64

Extract the entire ZIP, then open Maildesk.exe. Keep app/ and runtime/ beside it.
A separate Java installation is unnecessary. MySQL must be running separately.

SETUP
1. Copy config/app.properties.example to config/app.properties and set the MySQL login.
2. Save your Google Desktop OAuth JSON as config/credentials.json.
3. Open Maildesk.exe and click Connect Gmail. See SETUP.md for detailed instructions.

Imports are capped at 18 messages: up to 6 each from Inbox, Sent, and Spam.
The distribution ZIP contains no personal settings, OAuth credentials, or tokens.
User configuration is resolved beside Maildesk.exe, independently of the working directory.

The bundled Java runtime includes its notices and licenses under runtime/legal.
For Eclipse Temurin runtime sources, see https://adoptium.net/temurin/releases/.
'@ | Set-Content -LiteralPath (Join-Path $applicationDirectory 'README.txt') -Encoding UTF8

# Archive the clean distribution before adding any user-specific configuration.
Compress-Archive -LiteralPath $applicationDirectory -DestinationPath $archive -CompressionLevel Optimal
if ($UseLocalConfig) {
    foreach ($name in @('app.properties', 'credentials.json')) {
        $source = Join-Path $projectRoot "config/$name"
        if (Test-Path -LiteralPath $source) { Copy-Item -LiteralPath $source -Destination
$configurationDirectory }
    }
    $sourceTokens = Join-Path $projectRoot 'config/tokens'
    if (Test-Path -LiteralPath $sourceTokens) {
        $destinationTokens = Join-Path $configurationDirectory 'tokens'
        New-Item -ItemType Directory -Path $destinationTokens -Force | Out-Null
        $identity = [Security.Principal.WindowsIdentity]::GetCurrent().Name
        & icacls.exe $destinationTokens /inheritance:r /grant:r ('{0}:(OI)(CI)F' -f $identity) | Out-Null
        if ($LASTEXITCODE -ne 0) { throw 'Could not protect the local token directory.' }
        Get-ChildItem -LiteralPath $sourceTokens -File | ForEach-Object {
            Copy-Item -LiteralPath $_.FullName -Destination $destinationTokens
        }
    }
}
Write-Host "Windows executable: $(Join-Path $applicationDirectory 'Maildesk.exe')"
Write-Host "Clean distribution: $archive"
```

scripts/run-app.ps1

```
[CmdletBinding()]
param(
    [switch]$NoBuild,
    [Parameter(ValueFromRemainingArguments = $true)]
    [string[]]$AppArguments
)

Set-StrictMode -Version Latest
$ErrorActionPreference = 'Stop'
. (Join-Path $PSScriptRoot 'initialize-java.ps1')
$projectRoot = Split-Path -Parent $PSScriptRoot
if (-not $NoBuild) { & (Join-Path $PSScriptRoot 'build.ps1') -SkipTests }
$applicationJar = Join-Path $projectRoot 'target/maildesk.jar'
if (-not (Test-Path -LiteralPath $applicationJar)) { throw 'Build first with .\scripts\build.ps1.' }
$javaRuntime = Get-Command java -CommandType Application -ErrorAction Stop
Push-Location -LiteralPath $projectRoot
try {
    & $javaRuntime.Source -jar $applicationJar @AppArguments
    if ($LASTEXITCODE -ne 0) { throw "Maildesk exited with code $LASTEXITCODE." }
} finally { Pop-Location }
```

scripts/run-demo.ps1

```
[CmdletBinding()]
param([switch]$NoBuild)

Set-StrictMode -Version Latest
$ErrorActionPreference = 'Stop'
. (Join-Path $PSScriptRoot 'initialize-java.ps1')
$projectRoot = Split-Path -Parent $PSScriptRoot
if (-not $NoBuild) { & (Join-Path $PSScriptRoot 'build.ps1') -SkipTests }
$applicationJar = Join-Path $projectRoot 'target/maildesk.jar'
if (-not (Test-Path -LiteralPath $applicationJar)) { throw 'Build first with .\scripts\build.ps1.' }
$javaRuntime = Get-Command java -CommandType Application -ErrorAction Stop
Push-Location -LiteralPath $projectRoot
try {
    & $javaRuntime.Source -cp $applicationJar ems.demo.DemoApp
    if ($LASTEXITCODE -ne 0) { throw "The demo exited with code $LASTEXITCODE." }
} finally { Pop-Location }
```

APPENDIX A.6 — MAVEN BUILD CONFIGURATION

pom.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0"
         xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
         xsi:schemaLocation="http://maven.apache.org/POM/4.0.0 https://maven.apache.org/xsd/maven-4.0.0.xsd">
  <modelVersion>4.0.0</modelVersion>
  <groupId>ems</groupId>
  <artifactId>maildesk</artifactId>
  <version>1.0.0</version>
  <name>Maildesk</name>
  <description>Java Swing Gmail client with a MySQL cache and explainable spam checks.</description>
  <properties>
    <maven.compiler.release>17</maven.compiler.release>
    <project.build.sourceEncoding>UTF-8</project.build.sourceEncoding>
    <project.reporting.outputEncoding>UTF-8</project.reporting.outputEncoding>
    <project.build.outputTimestamp>2026-10-20T00:00:00Z</project.build.outputTimestamp>
    <junit.version>5.11.4</junit.version>
    <skipTests>false</skipTests>
    <maildesk.uiRender></maildesk.uiRender>
  </properties>
  <dependencies>
    <dependency>
      <groupId>com.google.code.gson</groupId><artifactId>gson</artifactId><version>2.12.1</version>
    </dependency>
    <dependency>
      <groupId>jakarta.mail</groupId><artifactId>jakarta.mail-api</artifactId><version>2.1.3</version>
    </dependency>
    <dependency>
      <groupId>org.eclipse.angus</groupId><artifactId>angus-
mail</artifactId><version>2.0.3</version><scope>runtime</scope>
    </dependency>
    <dependency>
      <groupId>com.mysql</groupId><artifactId>mysql-connector-
j</artifactId><version>8.4.0</version><scope>runtime</scope>
    </dependency>
    <dependency>
      <groupId>com.h2database</groupId><artifactId>h2</artifactId><version>2.3.232</version><scope>test</scope>
    </dependency>
    <dependency>
      <groupId>org.junit.jupiter</groupId><artifactId>junit-
jupiter</artifactId><version>${junit.version}</version><scope>test</scope>
    </dependency>
```

```
  </dependencies>
  <build>
    <finalName>maildesk</finalName>
    <resources>
      <resource><directory>src/main/resources</directory></resource>
      <resource><directory>sql</directory><targetPath>sql</targetPath></resource>
    </resources>
    <plugins>
      <plugin>
        <groupId>org.apache.maven.plugins</groupId><artifactId>maven-clean-
plugin</artifactId><version>3.4.1</version>
      </plugin>
      <plugin>
        <groupId>org.apache.maven.plugins</groupId><artifactId>maven-resources-
plugin</artifactId><version>3.3.1</version>
      </plugin>
      <plugin>
        <groupId>org.apache.maven.plugins</groupId><artifactId>maven-compiler-
plugin</artifactId><version>3.14.0</version>
      </plugin>
      <plugin>
        <groupId>org.codehaus.mojo</groupId><artifactId>build-helper-maven-
plugin</artifactId><version>3.6.0</version>
        <executions>
          <execution>
            <id>include-demo</id><phase>generate-sources</phase><goals><goal>add-source</goal></goals>
            <configuration><sources><source>src/demo/java</source></sources></configuration>
          </execution>
        </executions>
      </plugin>
      <plugin>
        <groupId>org.apache.maven.plugins</groupId><artifactId>maven-surefire-
plugin</artifactId><version>3.5.2</version>
        <configuration>
          <systemPropertyVariables><java.awt.headless>true</java.awt.headless></systemPropertyVariables>
        </configuration>
      </plugin>
      <plugin>
        <groupId>org.codehaus.mojo</groupId><artifactId>exec-maven-plugin</artifactId><version>3.5.0</version>
        <executions>
          <execution>
            <id>member-one-contract-checks</id><phase>test</phase><goals><goal>exec</goal></goals>
            <configuration>
              <executable>java</executable><classpathScope>test</classpathScope>
              <skip>${skipTests}</skip>
              <arguments><argument>-Djava.awt.headless=true</argument><argument>-
classpath</argument><classpath/><argument>ems.check.MemberOneChecks</argument></arguments>
            </configuration>
          </execution>
          <execution>
            <id>swing-interface-checks</id><phase>test</phase><goals><goal>exec</goal></goals>
            <configuration>
              <executable>java</executable><classpathScope>test</classpathScope>
              <skip>${skipTests}</skip>
              <arguments><argument>-Djava.awt.headless=true</argument><argument>-
classpath</argument><classpath/><argument>ems.check.UiChecks</argument><argument>${maildesk.uiRender}</argument>
</arguments>
            </configuration>
          </execution>
        </executions>
      </plugin>
      <plugin>
        <groupId>org.apache.maven.plugins</groupId><artifactId>maven-jar-
plugin</artifactId><version>3.4.2</version>
      </plugin>
      <plugin>
        <groupId>org.apache.maven.plugins</groupId><artifactId>maven-shade-
plugin</artifactId><version>3.6.0</version>
        <executions>
          <execution>
            <phase>package</phase><goals><goal>shade</goal></goals>
            <configuration>
              <createDependencyReducedPom>false</createDependencyReducedPom>
              <filters>
                <filter>
                  <artifact>*:*</artifact>
                  <excludes><exclude>META-INF/*.SF</exclude><exclude>META-INF/*.RSA</exclude><exclude>META-
INF/*.DSA</exclude><exclude>module-info.class</exclude><exclude>META-INF/versions/*/module-
info.class</exclude></excludes>
                </filter>
              </filters>
              <transformers>
                <transformer
implementation="org.apache.maven.plugins.shade.resource.ServicesResourceTransformer"/>
                <transformer
implementation="org.apache.maven.plugins.shade.resource.ManifestResourceTransformer"><mainClass>ems.App</mainCla
ss></transformer>
              </transformers>
            </configuration>
          </execution>
        </executions>
      </plugin>
    </plugins>
  </build>
  <profiles>
    <profile><id>render</id><properties><maildesk.uiRender>--render</maildesk.uiRender></properties></profile>
  </profiles>
```

```
</project>
```

APPENDIX A.7 — WRAPPER AND CONTINUOUS-INTEGRATION CONFIGURATION

mvnw

```
#!/bin/sh
# ----------------------------------------------------------------------------
# Licensed to the Apache Software Foundation (ASF) under one
# or more contributor license agreements.  See the NOTICE file
# distributed with this work for additional information
# regarding copyright ownership.  The ASF licenses this file
# to you under the Apache License, Version 2.0 (the
# "License"); you may not use this file except in compliance
# with the License.  You may obtain a copy of the License at
#
#    http://www.apache.org/licenses/LICENSE-2.0
#
# Unless required by applicable law or agreed to in writing,
# software distributed under the License is distributed on an
# "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY
# KIND, either express or implied.  See the License for the
# specific language governing permissions and limitations
# under the License.
# ----------------------------------------------------------------------------

# ----------------------------------------------------------------------------
# Apache Maven Wrapper startup batch script, version 3.3.4
#
# Optional ENV vars
# -----------------
#   JAVA_HOME - location of a JDK home dir, required when download maven via java source
#   MVNW_REPOURL - repo url base for downloading maven distribution
#   MVNW_USERNAME/MVNW_PASSWORD - user and password for downloading maven
#   MVNW_VERBOSE - true: enable verbose log; debug: trace the mvnw script; others: silence the output
# ----------------------------------------------------------------------------

set -euf
[ "${MVNW_VERBOSE-}" != debug ] || set -x

# OS specific support.
native_path() { printf %s\\n "$1"; }
case "$(uname)" in
CYGWIN* | MINGW*)
  [ -z "${JAVA_HOME-}" ] || JAVA_HOME="$(cygpath --unix "$JAVA_HOME")"
  native_path() { cygpath --path --windows "$1"; }
  ;;
esac

# set JAVACMD and JAVACCMD
set_java_home() {
  # For Cygwin and MinGW, ensure paths are in Unix format before anything is touched
  if [ -n "${JAVA_HOME-}" ]; then
    if [ -x "$JAVA_HOME/jre/sh/java" ]; then
      # IBM's JDK on AIX uses strange locations for the executables
      JAVACMD="$JAVA_HOME/jre/sh/java"
      JAVACCMD="$JAVA_HOME/jre/sh/javac"
    else
      JAVACMD="$JAVA_HOME/bin/java"
      JAVACCMD="$JAVA_HOME/bin/javac"

      if [ ! -x "$JAVACMD" ] || [ ! -x "$JAVACCMD" ]; then
        echo "The JAVA_HOME environment variable is not defined correctly, so mvnw cannot run." >&2
        echo "JAVA_HOME is set to \"$JAVA_HOME\", but \"\$JAVA_HOME/bin/java\" or \"\$JAVA_HOME/bin/javac\" does
not exist." >&2
        return 1
      fi
    fi
  else
    JAVACMD="$(
      'set' +e
      'unset' -f command 2>/dev/null
      'command' -v java
    )" || :
    JAVACCMD="$(
      'set' +e
      'unset' -f command 2>/dev/null
      'command' -v javac
    )" || :

    if [ ! -x "${JAVACMD-}" ] || [ ! -x "${JAVACCMD-}" ]; then
      echo "The java/javac command does not exist in PATH nor is JAVA_HOME set, so mvnw cannot run." >&2
      return 1
    fi
  fi
}
```

```
# hash string like Java String::hashCode
hash_string() {
  str="${1:-}" h=0
  while [ -n "$str" ]; do
    char="${str%"${str#?}"}"
    h=$(((h * 31 + $(LC_CTYPE=C printf %d "'$char")) % 4294967296))
    str="${str#?}"
  done
  printf %x\\n $h
}

verbose() { :; }
[ "${MVNW_VERBOSE-}" != true ] || verbose() { printf %s\\n "${1-}"; }

die() {
  printf %s\\n "$1" >&2
  exit 1
}

trim() {
  # MWRAPPER-139:
  #   Trims trailing and leading whitespace, carriage returns, tabs, and linefeeds.
  #   Needed for removing poorly interpreted newline sequences when running in more
  #   exotic environments such as mingw bash on Windows.
  printf "%s" "${1}" | tr -d '[:space:]'
}

scriptDir="$(dirname "$0")"
scriptName="$(basename "$0")"

# parse distributionUrl and optional distributionSha256Sum, requires .mvn/wrapper/maven-wrapper.properties
while IFS="=" read -r key value; do
  case "${key-}" in
  distributionUrl) distributionUrl=$(trim "${value-}") ;;
  distributionSha256Sum) distributionSha256Sum=$(trim "${value-}") ;;
  esac
done <"$scriptDir/.mvn/wrapper/maven-wrapper.properties"
[ -n "${distributionUrl-}" ] || die "cannot read distributionUrl property in $scriptDir/.mvn/wrapper/maven-
wrapper.properties"

case "${distributionUrl##*/}" in
maven-mvnd-*bin.*)
  MVN_CMD=mvnd.sh _MVNW_REPO_PATTERN=/maven/mvnd/
  case "${PROCESSOR_ARCHITECTURE-}${PROCESSOR_ARCHITEW6432-}:$(uname -a)" in
  *AMD64:CYGWIN* | *AMD64:MINGW*) distributionPlatform=windows-amd64 ;;
  :Darwin*x86_64) distributionPlatform=darwin-amd64 ;;
  :Darwin*arm64) distributionPlatform=darwin-aarch64 ;;
  :Linux*x86_64*) distributionPlatform=linux-amd64 ;;
  *)
    echo "Cannot detect native platform for mvnd on $(uname)-$(uname -m), use pure java version" >&2
    distributionPlatform=linux-amd64
    ;;
  esac
  distributionUrl="${distributionUrl%-bin.*}-$distributionPlatform.zip"
  ;;
maven-mvnd-*) MVN_CMD=mvnd.sh _MVNW_REPO_PATTERN=/maven/mvnd/ ;;
*) MVN_CMD="mvn${scriptName#mvnw}" _MVNW_REPO_PATTERN=/org/apache/maven/ ;;
esac

# apply MVNW_REPOURL and calculate MAVEN_HOME
# maven home pattern: ~/.m2/wrapper/dists/{apache-maven-<version>,maven-mvnd-<version>-<platform>}/<hash>
[ -z "${MVNW_REPOURL-}" ] ||
distributionUrl="$MVNW_REPOURL$_MVNW_REPO_PATTERN${distributionUrl#*"$_MVNW_REPO_PATTERN"}"
distributionUrlName="${distributionUrl##*/}"
distributionUrlNameMain="${distributionUrlName%.*}"
distributionUrlNameMain="${distributionUrlNameMain%-bin}"
MAVEN_USER_HOME="${MAVEN_USER_HOME:-${HOME}/.m2}"
MAVEN_HOME="${MAVEN_USER_HOME}/wrapper/dists/${distributionUrlNameMain-}/$(hash_string "$distributionUrl")"

exec_maven() {
  unset MVNW_VERBOSE MVNW_USERNAME MVNW_PASSWORD MVNW_REPOURL || :
  exec "$MAVEN_HOME/bin/$MVN_CMD" "$@" || die "cannot exec $MAVEN_HOME/bin/$MVN_CMD"
}

if [ -d "$MAVEN_HOME" ]; then
  verbose "found existing MAVEN_HOME at $MAVEN_HOME"
  exec_maven "$@"
fi

case "${distributionUrl-}" in
*?-bin.zip | *?maven-mvnd-?*-?*.zip) ;;
*) die "distributionUrl is not valid, must match *-bin.zip or maven-mvnd-*.zip, but found '${distributionUrl-}'"
;;
esac

# prepare tmp dir
if TMP_DOWNLOAD_DIR="$(mktemp -d)" && [ -d "$TMP_DOWNLOAD_DIR" ]; then
  clean() { rm -rf -- "$TMP_DOWNLOAD_DIR"; }
  trap clean HUP INT TERM EXIT
else
```

```
  die "cannot create temp dir"
fi

mkdir -p -- "${MAVEN_HOME%/*}"

# Download and Install Apache Maven
verbose "Couldn't find MAVEN_HOME, downloading and installing it ..."
verbose "Downloading from: $distributionUrl"
verbose "Downloading to: $TMP_DOWNLOAD_DIR/$distributionUrlName"

# select .zip or .tar.gz
if ! command -v unzip >/dev/null; then
  distributionUrl="${distributionUrl%.zip}.tar.gz"
  distributionUrlName="${distributionUrl##*/}"
fi

# verbose opt
__MVNW_QUIET_WGET=--quiet __MVNW_QUIET_CURL=--silent __MVNW_QUIET_UNZIP=-q __MVNW_QUIET_TAR=''
[ "${MVNW_VERBOSE-}" != true ] || __MVNW_QUIET_WGET='' __MVNW_QUIET_CURL='' __MVNW_QUIET_UNZIP=''
__MVNW_QUIET_TAR=v

# normalize http auth
case "${MVNW_PASSWORD:+has-password}" in
'') MVNW_USERNAME='' MVNW_PASSWORD='' ;;
has-password) [ -n "${MVNW_USERNAME-}" ] || MVNW_USERNAME='' MVNW_PASSWORD='' ;;
esac

if [ -z "${MVNW_USERNAME-}" ] && command -v wget >/dev/null; then
  verbose "Found wget ... using wget"
  wget ${__MVNW_QUIET_WGET:+"$__MVNW_QUIET_WGET"} "$distributionUrl" -O "$TMP_DOWNLOAD_DIR/$distributionUrlName"
|| die "wget: Failed to fetch $distributionUrl"
elif [ -z "${MVNW_USERNAME-}" ] && command -v curl >/dev/null; then
  verbose "Found curl ... using curl"
  curl ${__MVNW_QUIET_CURL:+"$__MVNW_QUIET_CURL"} -f -L -o "$TMP_DOWNLOAD_DIR/$distributionUrlName"
"$distributionUrl" || die "curl: Failed to fetch $distributionUrl"
elif set_java_home; then
  verbose "Falling back to use Java to download"
  javaSource="$TMP_DOWNLOAD_DIR/Downloader.java"
  targetZip="$TMP_DOWNLOAD_DIR/$distributionUrlName"
  cat >"$javaSource" <<-END
        public class Downloader extends java.net.Authenticator
        {
          protected java.net.PasswordAuthentication getPasswordAuthentication()
          {
            return new java.net.PasswordAuthentication( System.getenv( "MVNW_USERNAME" ), System.getenv(
"MVNW_PASSWORD" ).toCharArray() );
          }
          public static void main( String[] args ) throws Exception
          {
            setDefault( new Downloader() );
            java.nio.file.Files.copy( java.net.URI.create( args[0] ).toURL().openStream(),
java.nio.file.Paths.get( args[1] ).toAbsolutePath().normalize() );
          }
        }
        END
  # For Cygwin/MinGW, switch paths to Windows format before running javac and java
  verbose " - Compiling Downloader.java ..."
  "$(native_path "$JAVACCMD")" "$(native_path "$javaSource")" || die "Failed to compile Downloader.java"
  verbose " - Running Downloader.java ..."
  "$(native_path "$JAVACMD")" -cp "$(native_path "$TMP_DOWNLOAD_DIR")" Downloader "$distributionUrl"
"$(native_path "$targetZip")"
fi

# If specified, validate the SHA-256 sum of the Maven distribution zip file
if [ -n "${distributionSha256Sum-}" ]; then
  distributionSha256Result=false
  if [ "$MVN_CMD" = mvnd.sh ]; then
    echo "Checksum validation is not supported for maven-mvnd." >&2
    echo "Please disable validation by removing 'distributionSha256Sum' from your maven-wrapper.properties." >&2
    exit 1
  elif command -v sha256sum >/dev/null; then
    if echo "$distributionSha256Sum  $TMP_DOWNLOAD_DIR/$distributionUrlName" | sha256sum -c - >/dev/null 2>&1;
then
      distributionSha256Result=true
    fi
  elif command -v shasum >/dev/null; then
    if echo "$distributionSha256Sum  $TMP_DOWNLOAD_DIR/$distributionUrlName" | shasum -a 256 -c >/dev/null 2>&1;
then
      distributionSha256Result=true
    fi
  else
    echo "Checksum validation was requested but neither 'sha256sum' or 'shasum' are available." >&2
    echo "Please install either command, or disable validation by removing 'distributionSha256Sum' from your
maven-wrapper.properties." >&2
    exit 1
  fi
  if [ $distributionSha256Result = false ]; then
    echo "Error: Failed to validate Maven distribution SHA-256, your Maven distribution might be compromised."
>&2
    echo "If you updated your Maven version, you need to update the specified distributionSha256Sum property."
>&2
    exit 1
  fi
fi
```

```
# unzip and move
if command -v unzip >/dev/null; then
  unzip ${__MVNW_QUIET_UNZIP:+"$__MVNW_QUIET_UNZIP"} "$TMP_DOWNLOAD_DIR/$distributionUrlName" -d
"$TMP_DOWNLOAD_DIR" || die "failed to unzip"
else
  tar xzf${__MVNW_QUIET_TAR:+"$__MVNW_QUIET_TAR"} "$TMP_DOWNLOAD_DIR/$distributionUrlName" -C
"$TMP_DOWNLOAD_DIR" || die "failed to untar"
fi

# Find the actual extracted directory name (handles snapshots where filename != directory name)
actualDistributionDir=""

# First try the expected directory name (for regular distributions)
if [ -d "$TMP_DOWNLOAD_DIR/$distributionUrlNameMain" ]; then
  if [ -f "$TMP_DOWNLOAD_DIR/$distributionUrlNameMain/bin/$MVN_CMD" ]; then
    actualDistributionDir="$distributionUrlNameMain"
  fi
fi

# If not found, search for any directory with the Maven executable (for snapshots)
if [ -z "$actualDistributionDir" ]; then
  # enable globbing to iterate over items
  set +f
  for dir in "$TMP_DOWNLOAD_DIR"/*; do
    if [ -d "$dir" ]; then
      if [ -f "$dir/bin/$MVN_CMD" ]; then
        actualDistributionDir="$(basename "$dir")"
        break
      fi
    fi
  done
  set -f
fi

if [ -z "$actualDistributionDir" ]; then
  verbose "Contents of $TMP_DOWNLOAD_DIR:"
  verbose "$(ls -la "$TMP_DOWNLOAD_DIR")"
  die "Could not find Maven distribution directory in extracted archive"
fi

verbose "Found extracted Maven distribution directory: $actualDistributionDir"
printf %s\\n "$distributionUrl" >"$TMP_DOWNLOAD_DIR/$actualDistributionDir/mvnw.url"
mv -- "$TMP_DOWNLOAD_DIR/$actualDistributionDir" "$MAVEN_HOME" || [ -d "$MAVEN_HOME" ] || die "fail to move
MAVEN_HOME"

clean || :
exec_maven "$@"
```

mvnw.cmd

```
<# : batch portion
@REM ----------------------------------------------------------------------------
@REM Licensed to the Apache Software Foundation (ASF) under one
@REM or more contributor license agreements.  See the NOTICE file
@REM distributed with this work for additional information
@REM regarding copyright ownership.  The ASF licenses this file
@REM to you under the Apache License, Version 2.0 (the
@REM "License"); you may not use this file except in compliance
@REM with the License.  You may obtain a copy of the License at
@REM
@REM    http://www.apache.org/licenses/LICENSE-2.0
@REM
@REM Unless required by applicable law or agreed to in writing,
@REM software distributed under the License is distributed on an
@REM "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY
@REM KIND, either express or implied.  See the License for the
@REM specific language governing permissions and limitations
@REM under the License.
@REM ----------------------------------------------------------------------------

@REM ----------------------------------------------------------------------------
@REM Apache Maven Wrapper startup batch script, version 3.3.4
@REM
@REM Optional ENV vars
@REM   MVNW_REPOURL - repo url base for downloading maven distribution
@REM   MVNW_USERNAME/MVNW_PASSWORD - user and password for downloading maven
@REM   MVNW_VERBOSE - true: enable verbose log; others: silence the output
@REM ----------------------------------------------------------------------------

@IF "%__MVNW_ARG0_NAME__%"=="" (SET __MVNW_ARG0_NAME__=%~nx0)
@SET __MVNW_CMD__=
@SET __MVNW_ERROR__=
@SET __MVNW_PSMODULEP_SAVE=%PSModulePath%
@SET PSModulePath=
@FOR /F "usebackq tokens=1* delims==" %%A IN (`powershell -noprofile "& {$scriptDir='%~dp0';
$script='%__MVNW_ARG0_NAME__%'; icm -ScriptBlock ([Scriptblock]::Create((Get-Content -Raw '%~f0'))) -
NoNewScope}"`) DO @(
  IF "%%A"=="MVN_CMD" (set __MVNW_CMD__=%%B) ELSE IF "%%B"=="" (echo %%A) ELSE (echo %%A=%%B)
)
```

```
@SET PSModulePath=%__MVNW_PSMODULEP_SAVE%
@SET __MVNW_PSMODULEP_SAVE=
@SET __MVNW_ARG0_NAME__=
@SET MVNW_USERNAME=
@SET MVNW_PASSWORD=
@IF NOT "%__MVNW_CMD__%"=="" ("%__MVNW_CMD__%" %*)
@echo Cannot start maven from wrapper >&2 && exit /b 1
@GOTO :EOF
: end batch / begin powershell #>

$ErrorActionPreference = "Stop"
if ($env:MVNW_VERBOSE -eq "true") {
  $VerbosePreference = "Continue"
}

# calculate distributionUrl, requires .mvn/wrapper/maven-wrapper.properties
$distributionUrl = (Get-Content -Raw "$scriptDir/.mvn/wrapper/maven-wrapper.properties" | ConvertFrom-
StringData).distributionUrl
if (!$distributionUrl) {
  Write-Error "cannot read distributionUrl property in $scriptDir/.mvn/wrapper/maven-wrapper.properties"
}

switch -wildcard -casesensitive ( $($distributionUrl -replace '^.*/','') ) {
  "maven-mvnd-*" {
    $USE_MVND = $true
    $distributionUrl = $distributionUrl -replace '-bin\.[^.]*$',"-windows-amd64.zip"
    $MVN_CMD = "mvnd.cmd"
    break
  }
  default {
    $USE_MVND = $false
    $MVN_CMD = $script -replace '^mvnw','mvn'
    break
  }
}

# apply MVNW_REPOURL and calculate MAVEN_HOME
# maven home pattern: ~/.m2/wrapper/dists/{apache-maven-<version>,maven-mvnd-<version>-<platform>}/<hash>
if ($env:MVNW_REPOURL) {
  $MVNW_REPO_PATTERN = if ($USE_MVND -eq $False) { "/org/apache/maven/" } else { "/maven/mvnd/" }
  $distributionUrl = "$env:MVNW_REPOURL$MVNW_REPO_PATTERN$($distributionUrl -replace
"^.*$MVNW_REPO_PATTERN",'')"
}
$distributionUrlName = $distributionUrl -replace '^.*/',''
$distributionUrlNameMain = $distributionUrlName -replace '\.[^.]*$','' -replace '-bin$',''

$MAVEN_M2_PATH = "$HOME/.m2"
if ($env:MAVEN_USER_HOME) {
  $MAVEN_M2_PATH = "$env:MAVEN_USER_HOME"
}

if (-not (Test-Path -Path $MAVEN_M2_PATH)) {
    New-Item -Path $MAVEN_M2_PATH -ItemType Directory | Out-Null
}

$MAVEN_WRAPPER_DISTS = $null
if ((Get-Item $MAVEN_M2_PATH).Target[0] -eq $null) {
  $MAVEN_WRAPPER_DISTS = "$MAVEN_M2_PATH/wrapper/dists"
} else {
  $MAVEN_WRAPPER_DISTS = (Get-Item $MAVEN_M2_PATH).Target[0] + "/wrapper/dists"
}

$MAVEN_HOME_PARENT = "$MAVEN_WRAPPER_DISTS/$distributionUrlNameMain"
$MAVEN_HOME_NAME =
([System.Security.Cryptography.SHA256]::Create().ComputeHash([byte[]][char[]]$distributionUrl) | ForEach-Object
{$_.ToString("x2")}) -join ''
$MAVEN_HOME = "$MAVEN_HOME_PARENT/$MAVEN_HOME_NAME"

if (Test-Path -Path "$MAVEN_HOME" -PathType Container) {
  Write-Verbose "found existing MAVEN_HOME at $MAVEN_HOME"
  Write-Output "MVN_CMD=$MAVEN_HOME/bin/$MVN_CMD"
  exit $?
}

if (! $distributionUrlNameMain -or ($distributionUrlName -eq $distributionUrlNameMain)) {
  Write-Error "distributionUrl is not valid, must end with *-bin.zip, but found $distributionUrl"
}

# prepare tmp dir
$TMP_DOWNLOAD_DIR_HOLDER = New-TemporaryFile
$TMP_DOWNLOAD_DIR = New-Item -Itemtype Directory -Path "$TMP_DOWNLOAD_DIR_HOLDER.dir"
$TMP_DOWNLOAD_DIR_HOLDER.Delete() | Out-Null
trap {
  if ($TMP_DOWNLOAD_DIR.Exists) {
    try { Remove-Item $TMP_DOWNLOAD_DIR -Recurse -Force | Out-Null }
    catch { Write-Warning "Cannot remove $TMP_DOWNLOAD_DIR" }
  }
}

New-Item -Itemtype Directory -Path "$MAVEN_HOME_PARENT" -Force | Out-Null
```

```
# Download and Install Apache Maven
Write-Verbose "Couldn't find MAVEN_HOME, downloading and installing it ..."
Write-Verbose "Downloading from: $distributionUrl"
Write-Verbose "Downloading to: $TMP_DOWNLOAD_DIR/$distributionUrlName"

$webclient = New-Object System.Net.WebClient
if ($env:MVNW_USERNAME -and $env:MVNW_PASSWORD) {
  $webclient.Credentials = New-Object System.Net.NetworkCredential($env:MVNW_USERNAME, $env:MVNW_PASSWORD)
}
[Net.ServicePointManager]::SecurityProtocol = [Net.SecurityProtocolType]::Tls12
$webclient.DownloadFile($distributionUrl, "$TMP_DOWNLOAD_DIR/$distributionUrlName") | Out-Null

# If specified, validate the SHA-256 sum of the Maven distribution zip file
$distributionSha256Sum = (Get-Content -Raw "$scriptDir/.mvn/wrapper/maven-wrapper.properties" | ConvertFrom-
StringData).distributionSha256Sum
if ($distributionSha256Sum) {
  if ($USE_MVND) {
    Write-Error "Checksum validation is not supported for maven-mvnd. `nPlease disable validation by removing
'distributionSha256Sum' from your maven-wrapper.properties."
  }
  Import-Module $PSHOME\Modules\Microsoft.PowerShell.Utility -Function Get-FileHash
  if ((Get-FileHash "$TMP_DOWNLOAD_DIR/$distributionUrlName" -Algorithm SHA256).Hash.ToLower() -ne
$distributionSha256Sum) {
    Write-Error "Error: Failed to validate Maven distribution SHA-256, your Maven distribution might be
compromised. If you updated your Maven version, you need to update the specified distributionSha256Sum
property."
  }
}

# unzip and move
Expand-Archive "$TMP_DOWNLOAD_DIR/$distributionUrlName" -DestinationPath "$TMP_DOWNLOAD_DIR" | Out-Null

# Find the actual extracted directory name (handles snapshots where filename != directory name)
$actualDistributionDir = ""

# First try the expected directory name (for regular distributions)
$expectedPath = Join-Path "$TMP_DOWNLOAD_DIR" "$distributionUrlNameMain"
$expectedMvnPath = Join-Path "$expectedPath" "bin/$MVN_CMD"
if ((Test-Path -Path $expectedPath -PathType Container) -and (Test-Path -Path $expectedMvnPath -PathType Leaf))
{
  $actualDistributionDir = $distributionUrlNameMain
}

# If not found, search for any directory with the Maven executable (for snapshots)
if (!$actualDistributionDir) {
  Get-ChildItem -Path "$TMP_DOWNLOAD_DIR" -Directory | ForEach-Object {
    $testPath = Join-Path $_.FullName "bin/$MVN_CMD"
    if (Test-Path -Path $testPath -PathType Leaf) {
      $actualDistributionDir = $_.Name
    }
  }
}

if (!$actualDistributionDir) {
  Write-Error "Could not find Maven distribution directory in extracted archive"
}

Write-Verbose "Found extracted Maven distribution directory: $actualDistributionDir"
Rename-Item -Path "$TMP_DOWNLOAD_DIR/$actualDistributionDir" -NewName $MAVEN_HOME_NAME | Out-Null
try {
  Move-Item -Path "$TMP_DOWNLOAD_DIR/$MAVEN_HOME_NAME" -Destination $MAVEN_HOME_PARENT | Out-Null
} catch {
  if (! (Test-Path -Path "$MAVEN_HOME" -PathType Container)) {
    Write-Error "fail to move MAVEN_HOME"
  }
} finally {
  try { Remove-Item $TMP_DOWNLOAD_DIR -Recurse -Force | Out-Null }
  catch { Write-Warning "Cannot remove $TMP_DOWNLOAD_DIR" }
}

Write-Output "MVN_CMD=$MAVEN_HOME/bin/$MVN_CMD"
```

.mvn/wrapper/maven-wrapper.properties

```
wrapperVersion=3.3.4
distributionType=only-script
distributionUrl=https://repo.maven.apache.org/maven2/org/apache/maven/apache-maven/3.9.11/apache-maven-3.9.11-
bin.zip
distributionSha256Sum=0d7125e8c91097b36edb990ea5934e6c68b4440eef4ea96510a0f6815e7eeadb
```

.github/workflows/verify.yml

```
name: Verify Maildesk
on:
  push:
  pull_request:
permissions:
```

```
  contents: read
jobs:
  test:
    strategy:
      matrix:
        os: [ubuntu-latest, windows-latest]
    runs-on: ${{ matrix.os }}
    steps:
      - uses: actions/checkout@v4
      - uses: actions/setup-java@v4
        with:
          distribution: temurin
          java-version: '17'
          cache: maven
      - name: Build and test on Linux
        if: runner.os != 'Windows'
        run: sh ./mvnw --batch-mode --no-transfer-progress verify
      - name: Build and test on Windows
        if: runner.os == 'Windows'
        shell: pwsh
        run: ./scripts/build.ps1
      - uses: actions/upload-artifact@v4
        with:
          name: maildesk-${{ runner.os }}
          path: target/maildesk.jar
          if-no-files-found: error
      - name: Package Windows executable
        if: runner.os == 'Windows'
        shell: pwsh
        run: ./scripts/package-windows.ps1 -NoBuild -JdkPath $env:JAVA_HOME
      - name: Check Windows launcher
        if: runner.os == 'Windows'
        shell: pwsh
        run: |
          $launcher = Start-Process -FilePath (Resolve-Path 'package/Maildesk/Maildesk.exe') -ArgumentList '--
help' -WindowStyle Hidden -Wait -PassThru
          if ($launcher.ExitCode -ne 0) { throw 'The packaged Windows launcher failed.' }
      - uses: actions/upload-artifact@v4
        if: runner.os == 'Windows'
        with:
          name: Maildesk-Windows-x64
          path: package/Maildesk-Windows-x64.zip
          if-no-files-found: error
```

APPENDIX B — APPLICATION OUTPUT

The following outputs were captured from Maildesk's offline demonstration mode. All people, addresses, subjects, message bodies, and dates shown are fictional. The demo does not connect to Gmail or MySQL, use the network, save messages to disk, or deliver real email. These pages document the appearance and behavior of the user interface only.

B.1 Welcome and demo entry




Figure 6: B.1 Welcome and demo entry

The welcome view introduces Maildesk and shows the entry point for the offline presentation. The Connect Gmail action in the live build opens Google authorization; the demo action opens fictional messages. The visible copy makes that distinction clear before the workspace is entered.

B.2 Inbox workspace




Figure 7: B.2 Inbox workspace

The workspace output shows mailbox navigation, search, the message table, selected-message context, and status controls. The rows are seeded example content. In a live session the same layout is populated from the bounded local cache retrieved through Gmail.

B.3 Message reader and explanation




Figure 8: B.3 Message reader and explanation

The reader output shows message details and the local spam review card beside the mailbox list. Body content is displayed as plain text. A real live result depends on a successful authorized Gmail read; the image shown here is fictional demo data.

B.4 Plain-text compose form




Figure 9: B.4 Plain-text compose form

The compose output shows recipient, subject, and body fields with the offline-demo notice. Validation is shared with the live path, but the demo records a simulated sent item in memory and never contacts Gmail.

B.5 Suspected Spam review




Figure 10: B.5 Suspected Spam review

This output displays a fictional suspicious message, its rule score, matched reasons, and user correction controls. It demonstrates the difference between Maildesk's local review suggestion and Gmail's own Spam label. No real message or sender is shown.