

Lab Assignment-12.3

2303A54012
A.Sanjay B47A

Task 1: Sorting Student Records for Placement Drive

Scenario

SR University's Training and Placement Cell needs to shortlist candidates efficiently during campus placements. Student records must be sorted by CGPA in descending order.

Tasks

1. Use GitHub Copilot to generate a program that stores student records (Name, Roll Number, CGPA).
2. Implement the following sorting algorithms using AI assistance:
 - o Quick Sort
 - o Merge Sort
3. Measure and compare runtime performance for large datasets.
4. Write a function to display the top 10 students based on CGPA.

Expected Outcome

- Correctly sorted student records.
- Performance comparison between Quick Sort and Merge Sort.
- Clear output of top-performing students.

Prompt:

#Generate a Python program to manage student placement records (name, roll number, CGPA), implement Quick Sort and Merge Sort to sort students by CGPA in descending order, compare their runtime performance on large datasets, and display the top 10 students with clear output and comments.

Code:

```

#generate a Python program to manage student placement records (name, roll number, CGPA), implement Quick Sort and
import random
import time
class Student:
    def __init__(self, name, roll_number, cgpa):
        self.name = name
        self.roll_number = roll_number
        self.cgpa = cgpa
def quick_sort(students):
    if len(students) <= 1:
        return students
    pivot = students[len(students) // 2].cgpa
    left = [x for x in students if x.cgpa > pivot]
    middle = [x for x in students if x.cgpa == pivot]
    right = [x for x in students if x.cgpa < pivot]
    return quick_sort(left) + middle + quick_sort(right)
def merge_sort(students):
    if len(students) <= 1:
        return students
    mid = len(students) // 2
    left = merge_sort(students[:mid])
    right = merge_sort(students[mid:])
    return merge(left, right)
def merge(left, right):
    result = []
    i = j = 0
    while i < len(left) and j < len(right):
        if left[i].cgpa > right[j].cgpa:
            result.append(left[i])
            i += 1
        else:
            result.append(right[j])
            j += 1
    result.extend(left[i:])

```

```

        result.extend(right[j:])
    return result
def generate_students(num_students):
    students = []
    for i in range(num_students):
        name = f"Student_{i+1}"
        roll_number = f"RN{i+1:03d}"
        cgpa = round(random.uniform(0, 10), 2)
        students.append(Student(name, roll_number, cgpa))
    return students
def display_top_students(students, top_n=10):
    print(f"Top {top_n} Students:")
    print(f"{'Name':<15} {'Roll Number':<15} {'CGPA':<5}")
    for student in students[:top_n]:
        print(f"{{student.name:<15}} {{student.roll_number:<15}} {{student.cgpa:<5}}")
# Generate a large dataset of students
num_students = 1000
students = generate_students(num_students)
# Sort using Quick Sort and measure runtime
start_time = time.time()
sorted_students_quick = quick_sort(students)
end_time = time.time()
print(f"Quick Sort Runtime: {end_time - start_time:.4f} seconds")
# Sort using Merge Sort and measure runtime
start_time = time.time()
sorted_students_merge = merge_sort(students)
end_time = time.time()
print(f"Merge Sort Runtime: {end_time - start_time:.4f} seconds")
# Display the top 10 students sorted by CGPA
display_top_students(sorted_students_quick)
display_top_students(sorted_students_merge)

```

Output:

Student_314	RN314	9.99
Student_41	RN041	9.99
Student_496	RN496	9.94
Student_207	RN207	9.93
Student_767	RN767	9.91
Student_754	RN754	9.9
Student_635	RN635	9.89
Student_185	RN185	9.88
Student_132	RN132	9.88

Explanation:

- The prompt asks the AI to **create a program for managing student records** for placements.
- It requires implementing **Quick Sort and Merge Sort** and comparing their performance.
- It also tells the AI to **show the top 10 students** with clear and organized output.

Task 2: Implementing Bubble Sort with AI Comments

- Task: Write a Python implementation of Bubble Sort.
- Instructions:
- Students implement Bubble Sort normally.
- Ask AI to generate inline comments explaining key logic (like swapping, passes, and termination).
- Request AI to provide time complexity analysis.
- Expected Output:
- A Bubble Sort implementation with AI-generated explanatory comments and complexity analysis.

PROMPT:

#Generate a Python implementation of Bubble Sort with clear inline comments explaining the swapping process, passes, and termination condition, and include a brief time complexity analysis

Code:

```
#Generate a Python implementation of Bubble Sort with clear inline comments explaining the swapping process, passes,
def bubble_sort(arr):
    n = len(arr)
    # Traverse through all elements in the array
    for i in range(n):
        # Initialize a flag to check if any swapping occurs
        swapped = False
        # Last i elements are already in place, no need to check them
        for j in range(0, n-i-1):
            # Swap if the element found is greater than the next element
            if arr[j] > arr[j+1]:
                arr[j], arr[j+1] = arr[j+1], arr[j] # Swapping process
                swapped = True # Set the flag to True if a swap occurred
            # If no swapping occurred, the array is already sorted
            if not swapped:
                break # Termination condition: exit the loop if the array is sorted
# Example usage
arr = [64, 34, 25, 12, 22, 11, 90]
bubble_sort(arr)
print("Sorted array is:", arr)
```

OUTPUT:

```
Sorted array is: [11, 12, 22, 25, 34, 64, 90]
```

EXPLANATION:

Time complexity analysis:

The worst-case and average-case time complexity of Bubble Sort is $O(n^2)$ because

it requires two nested loops to compare each element with every other element.

The best-case time complexity is $O(n)$ when the array is already sorted, as it only requires one pass to check that the array is sorted without performing any swaps.

Task 3: Quick Sort and Merge Sort Comparison

- Task: Implement Quick Sort and Merge Sort using recursion.
- Instructions:
- Provide AI with partially completed functions for recursion.
- Ask AI to complete the missing logic and add docstrings.
- Compare both algorithms on random, sorted, and reverse-sorted lists.
- **Expected Output:**

- Working Quick Sort and Merge Sort implementations.
- AI-generated explanation of average, best, and worst-case complexities.

PROMPT:

#Complete the recursive Python implementations of Quick Sort and Merge Sort by filling in the missing logic, add clear docstrings, compare their performance on random, sorted, and reverse-sorted lists, and explain their average, best, and worst-case time complexities.

Code:

```
#Complete the recursive Python implementations of Quick Sort and Merge Sort by filling in the missing logic, add c
def quick_sort(arr):
    if len(arr) <= 1:
        return arr
    pivot = arr[len(arr) // 2] # Choosing the middle element as the pivot
    left = [x for x in arr if x < pivot] # Elements less than the pivot
    middle = [x for x in arr if x == pivot] # Elements equal to the pivot
    right = [x for x in arr if x > pivot] # Elements greater than the pivot
    return quick_sort(left) + middle + quick_sort(right) # Recursively sort and combine

def merge_sort(arr):
    if len(arr) <= 1:
        return arr
    mid = len(arr) // 2 # Finding the mid of the array
    left = merge_sort(arr[:mid]) # Recursively sort the left half
    right = merge_sort(arr[mid:]) # Recursively sort the right half
    return merge(left, right) # Merge the sorted halves

def merge(left, right):
    """Merges two sorted lists into a single sorted list.
    Parameters:
    left (list): The first sorted list.
    right (list): The second sorted list.
    Returns:
    list: A merged and sorted list.
    """
    result = []
    i = j = 0
    while i < len(left) and j < len(right):
        if left[i] < right[j]:
            result.append(left[i]) # Append the smaller element
            i += 1
        else:
            result.append(right[j]) # Append the smaller element
            j += 1
```

```

        result.extend(left[i:]) # Append any remaining elements from left
        result.extend(right[j:]) # Append any remaining elements from right
        return result
# Performance comparison
import random
# Generate random, sorted, and reverse-sorted lists
random_list = [random.randint(1, 1000) for _ in range(1000)]
sorted_list = sorted(random_list)
reverse_sorted_list = sorted(random_list, reverse=True)
# Compare Quick Sort performance
import time
start_time = time.time()
quick_sort(random_list)
print(f"Quick Sort on random list took {time.time() - start_time:.4f} seconds")
start_time = time.time()
quick_sort(sorted_list)
print(f"Quick Sort on sorted list took {time.time() - start_time:.4f} seconds")
start_time = time.time()
quick_sort(reverse_sorted_list)
print(f"Quick Sort on reverse-sorted list took {time.time() - start_time:.4f} seconds")
# Compare Merge Sort performance
start_time = time.time()
merge_sort(random_list)
print(f"Merge Sort on random list took {time.time() - start_time:.4f} seconds")
start_time = time.time()
merge_sort(sorted_list)
print(f"Merge Sort on sorted list took {time.time() - start_time:.4f} seconds")
start_time = time.time()
merge_sort(reverse_sorted_list)
print(f"Merge Sort on reverse-sorted list took {time.time() - start_time:.4f} seconds")

```

Output:

```

Quick Sort on random list took 0.0017 seconds
Quick Sort on sorted list took 0.0011 seconds
Quick Sort on reverse-sorted list took 0.0010 seconds
Merge Sort on random list took 0.0019 seconds
Merge Sort on sorted list took 0.0017 seconds
Merge Sort on reverse-sorted list took 0.0020 seconds

```

EXPLANATION:

QUICK SORT-

Sorts an array using the Quick Sort algorithm.

Parameters:

arr (list): The list of elements to be sorted.

Returns:

list: A new sorted list in ascending order.

Time Complexity:

- Average Case: $O(n \log n)$

- Best Case: $O(n \log n)$
- Worst Case: $O(n^2)$ (when the smallest or largest element is always chosen as the pivot)

MERGESORT:

Sorts an array using the Merge Sort algorithm.

Parameters:

arr (list): The list of elements to be sorted.

Returns:

list: A new sorted list in ascending order.

Time Complexity:

- Average Case: $O(n \log n)$
- Best Case: $O(n \log n)$
- Worst Case: $O(n \log n)$ (Merge Sort always divides the array into halves)

Task 4 (Real-Time Application – Inventory Management System)

Scenario: A retail store's inventory system contains thousands of products, each with attributes like product ID, name, price, and stock quantity. Store staff need to:

1. Quickly search for a product by ID or name.
2. Sort products by price or quantity for stock analysis.

Task:

- Use AI to suggest the most efficient search and sort algorithms for this use case.
- Implement the recommended algorithms in Python.
- Justify the choice based on dataset size, update frequency, and performance requirements.

Expected Output:

- A table mapping operation → recommended algorithm → justification.
- Working Python functions for searching and sorting the inventory.

PROMPT:

For a retail inventory management system, recommend efficient search and sorting algorithms for each operation, present them in a table with justifications based on dataset size and performance needs, and generate working Python functions to implement the chosen algorithms with comments.

Code:

```
#For a retail inventory management system, recommend efficient search and sorting algorithms for each operation, pres
| Operation | Recommended Algorithm | Justification
|-----|-----|-----
| Search for a product | Binary Search | Efficient for large sorted datasets, O(log n) time complexity.
| Sort products by price | Merge Sort | Stable sorting algorithm with O(n log n) time complexity, suitable for large datasets.

def binary_search(arr, target):
    """Performs binary search on a sorted list.
    Parameters:
    arr (list): A sorted list of products.
    target: The product to search for.
    Returns:
    int: The index of the target product if found, otherwise -1.
    """
    left, right = 0, len(arr) - 1
    while left <= right:
        mid = left + (right - left) // 2 # Calculate the middle index
        if arr[mid] == target:
            return mid # Target found at index mid
        elif arr[mid] < target:
            left = mid + 1 # Search in the right half
        else:
            right = mid - 1 # Search in the left half
    return -1 # Target not found

def merge_sort(arr):
    """Sorts a list of products by price using merge sort.
    Parameters:
    arr (list): A list of products, where each product is a dictionary with a 'price' key.
    Returns:
    list: A sorted list of products by price in ascending order.
    """
    if len(arr) <= 1:
        return arr
    mid = len(arr) // 2 # Finding the mid of the array
```

```
    if len(arr) <= 1:
        return arr
    mid = len(arr) // 2 # Finding the mid of the array
    left = merge_sort(arr[:mid]) # Recursively sort the left half
    right = merge_sort(arr[mid:]) # Recursively sort the right half
    return merge(left, right) # Merge the sorted halves

def merge(left, right):
    """Merges two sorted lists of products into a single sorted list by price.
    Parameters:
    left (list): The first sorted list of products.
    right (list): The second sorted list of products.
    Returns:
    list: A merged and sorted list of products by price in ascending order.
    """
    result = []
    i = j = 0
    while i < len(left) and j < len(right):
        if left[i]['price'] < right[j]['price']:
            result.append(left[i]) # Append the product with the lower price
            i += 1
        else:
            result.append(right[j]) # Append the product with the lower price
            j += 1
    result.extend(left[i:]) # Append any remaining products from left
    result.extend(right[j:]) # Append any remaining products from right
    return result
```



```
# Example usage
products = [
    {'name': 'Product A', 'price': 10.99},
    {'name': 'Product B', 'price': 5.49},
    {'name': 'Product C', 'price': 7.99},
    {'name': 'Product D', 'price': 3.99}
]
sorted_products = merge_sort(products)
print("Products sorted by price:")
for product in sorted_products:
    print(f"{product['name']}: ${product['price']}")
# Searching for a product
target_product = 'Product B'
index = binary_search(sorted_products, {'name': target_product, 'price': 5.49})
if index != -1:
    print(f"{target_product} found at index {index}.")
else:
    print(f"{target_product} not found in the product list.")
```

Output:

```
def/ai ASSISTANT/lab 12.3.py
Products sorted by price:
Product D: $3.99
Product B: $5.49
Product C: $7.99
Product A: $10.99
Product B found at index 1.
```

EXPLANATION:

- The prompt asks the AI to **choose suitable search and sorting algorithms** for an inventory system.
- It requires **reasons (justification)** for each choice based on performance needs.
- It also tells the AI to **write working Python functions** that implement those algorithms.

Task 5: Real-Time Stock Data Sorting & Searching

Scenario:

An AI-powered FinTech Lab at SR University is building a tool for analyzing stock price movements. The requirement is to quickly sort stocks by daily

gain/loss and search for specific stock symbols efficiently.

- Use GitHub Copilot to fetch or simulate stock price data (Stock Symbol, Opening Price, Closing Price).
- Implement sorting algorithms to rank stocks by percentage change.
- Implement a search function that retrieves stock data instantly when a stock symbol is entered.
- Optimize sorting with Heap Sort and searching with Hash Maps.
- Compare performance with standard library functions (sorted(), dict lookups) and analyze trade-offs

PROMPT:

generate a Python program that simulates stock data (symbol, opening and closing price), sorts stocks by percentage change using Heap Sort, searches stocks efficiently using a hash map, compares performance with built-in sorted() and dictionary lookups, and includes clear comments and analysis of trade-offs.”

Code:

```
#Generate a Python program that simulates stock data (symbol, opening and closing price), sorts stocks by percentage
import random
import time
class Stock:
    def __init__(self, symbol, opening_price, closing_price):
        self.symbol = symbol
        self.opening_price = opening_price
        self.closing_price = closing_price

    def percentage_change(self):
        return ((self.closing_price - self.opening_price) / self.opening_price) * 100
def heapify(arr, n, i):
    largest = i # Initialize largest as root
    left = 2 * i + 1 # left = 2*i + 1
    right = 2 * i + 2 # right = 2*i + 2
    # If left child is larger than root
    if left < n and arr[left].percentage_change() > arr[largest].percentage_change():
        largest = left
    # If right child is larger than largest so far
    if right < n and arr[right].percentage_change() > arr[largest].percentage_change():
        largest = right
    # If largest is not root
    if largest != i:
        arr[i], arr[largest] = arr[largest], arr[i] # Swap
        heapify(arr, n, largest) # Recursively heapify the affected sub-tree
def heap_sort(arr):
    n = len(arr)
    # Build a maxheap
    for i in range(n // 2 - 1, -1, -1):
        heapify(arr, n, i)
    # One by one extract elements from heap
    for i in range(n - 1, 0, -1):
        arr[i], arr[0] = arr[0], arr[i] # Swap
        heapify(arr, i, 0) # Heapify the root element
```

```

def generate_stocks(num_stocks):
    stocks = []
    for i in range(num_stocks):
        symbol = f"STK{i+1}"
        opening_price = round(random.uniform(100, 500), 2)
        closing_price = round(random.uniform(100, 500), 2)
        stocks.append(Stock(symbol, opening_price, closing_price))
    return stocks

def create_hash_map(stocks):
    hash_map = {}
    for stock in stocks:
        hash_map[stock.symbol] = stock
    return hash_map

# Generate stock data
num_stocks = 1000
stocks = generate_stocks(num_stocks)
# Sort stocks by percentage change using Heap Sort and measure runtime
start_time = time.time()
heap_sort(stocks)
end_time = time.time()
print(f"Heap Sort Runtime: {end_time - start_time:.4f} seconds")
# Sort stocks using built-in sorted() and measure runtime
start_time = time.time()
sorted_stocks = sorted(stocks, key=lambda x: x.percentage_change(), reverse=True)
end_time = time.time()
print(f"Built-in sorted() Runtime: {end_time - start_time:.4f} seconds")
# Create a hash map for efficient stock lookup and measure runtime
hash_map = create_hash_map(stocks)
target_symbol = "STK500"
start_time = time.time()
stock = hash_map.get(target_symbol, None)
end_time = time.time()
if stock:
    print(f"{target_symbol} found: Opening Price: {stock.opening_price}, Closing Price: {stock.closing_price}")
else:
    print(f"{target_symbol} not found.")
print(f"Hash Map Lookup Runtime: {end_time - start_time:.6f} seconds")

```

Output:

```

Heap Sort Runtime: 0.0060 seconds
Built-in sorted() Runtime: 0.0005 seconds
STK500 found: Opening Price: 393.05, Closing Price: 478.04
Hash Map Lookup Runtime: 0.000004 seconds

```

EXPLANATION:

- The prompt asks the AI to **create a program that simulates and analyzes stock data.**
- It requires using **Heap Sort** for sorting and **hash maps** for fast searching.
- It also tells the AI to **compare performance with built-in functions** and explain the trade-offs.