


# Distribution assumptions

GARCH MODELS IN PYTHON



**Chelsea Yang**  
Data Science Instructor

# Why make assumptions

- Volatility is not directly observable
- GARCH model use residuals as volatility shocks

$$r_t = \mu_t + \epsilon_t$$

- Volatility is related to the residuals:

$$\epsilon_t = \sigma_t * \zeta(WhiteNoise)$$

# Standardized residuals

- Residual = predicted return - mean return

$$residuals = \epsilon_t = r_t - \mu_t$$


- Standardized residual = residual / return volatility

$$std\ Resid = \frac{\epsilon_t}{\sigma_t}$$

# Residuals in GARCH


```
gm_std_resid = gm_result.resid / gm_result.conditional_volatility
```

```
plt.hist(gm_std_resid, facecolor = 'orange', label = 'standardized residuals')
```




# Fat tails

- Higher probability to observe large (positive or negative) returns than under a normal distribution




# Skewness

- Measure of asymmetry of a probability distribution



# Student's t-distribution



$\nu$  parameter of a Student's t-distribution indicates its shape

# GARCH with t-distribution

```
arch_model(my_data, p = 1, q = 1,  
           mean = 'constant', vol = 'GARCH',  
           dist = 't')
```

## Distribution

	coef	std err	t	P> t	95.0% Conf. Int.
nu	4.9249	0.507	9.709	2.766e-22	[ 3.931, 5.919]



# GARCH with skewed t-distribution

```
arch_model(my_data, p = 1, q = 1,  
           mean = 'constant', vol = 'GARCH',  
           dist = 'skewt')
```

## Distribution

	coef	std err	t	P> t	95.0% Conf. Int.
nu	5.2437	0.575	9.118	7.681e-20	[ 4.117, 6.371]
lambda	-0.0822	2.541e-02	-3.235	1.216e-03	[-0.132, -3.241e-02]

# Let's practice!

GARCH MODELS IN PYTHON

# Mean model specifications

GARCH MODELS IN PYTHON



**Chelsea Yang**  
Data Science Instructor

# Constant mean by default

- `constant` mean: generally works well with most financial return data

```
arch_model(my_data, p = 1, q = 1,  
           mean = 'constant', vol = 'GARCH')
```

```
Constant Mean - GARCH Model Results  
=====
```

Dep. Variable:	Return	R-squared:	-0.001
Mean Model:	<u>Constant Mean</u>	Adj. R-squared:	-0.001
Vol Model:	GARCH	Log-Likelihood:	-2771.96
Distribution:	Normal	AIC:	5551.93
Method:	Maximum Likelihood	BIC:	5574.95
		No. Observations:	2336
Date:	Fri, Dec 20 2019	Df Residuals:	2332
Time:	05:26:46	Df Model:	4

```
Mean Model  
=====
```

	coef	std err	t	P> t	95.0% Conf. Int.
<u>mu</u>	0.0772	1.445e-02	5.345	9.031e-08	[4.892e-02, 0.106]

# Zero mean assumption

- `zero` mean: use when the mean has been modeled separately

```
arch_model(my_data, p = 1, q = 1,  
           mean = 'zero', vol = 'GARCH')
```

```
Zero Mean - GARCH Model Results  
=====
```

Dep. Variable:	Return	R-squared:	0.000
Mean Model:	<u>Zero Mean</u>	Adj. R-squared:	0.000
Vol Model:	GARCH	Log-Likelihood:	-2786.65
Distribution:	Normal	AIC:	5579.30
Method:	Maximum Likelihood	BIC:	5596.57
		No. Observations:	2336
Date:	Fri, Dec 20 2019	Df Residuals:	2333
Time:	05:36:28	Df Model:	3

```
-----
```

# Autoregressive mean

- **AR** mean: model the mean as an autoregressive (AR) process

```
arch_model(my_data, p = 1, q = 1,  
           mean = 'AR', lags = 1, vol = 'GARCH')
```

```
AR - GARCH Model Results
=====
Dep. Variable:          Return    R-squared:          0.001
Mean Model:              AR      Adj. R-squared:       0.000
Vol Model:              GARCH    Log-Likelihood:     -2690.07
Distribution: Standardized Student's t    AIC:          5392.13
Method:              Maximum Likelihood    BIC:          5426.66
                                           No. Observations: 2335
Date:              Fri, Dec 20 2019    Df Residuals:    2329
Time:              05:39:58            Df Model:        6
                                           Mean Model
=====
              coef    std err          t      P>|t|      95.0% Conf. Int.
-----
Const          0.0877    1.293e-02     6.783  1.181e-11  [6.234e-02, 0.113]
Return[1]    -0.0541    2.060e-02    -2.625  8.670e-03 [-9.444e-02,-1.369e-02]
```

# Let's practice!

GARCH MODELS IN PYTHON

# Volatility models for asymmetric shocks

GARCH MODELS IN PYTHON




**Chelsea Yang**  
Data Science Instructor




# Asymmetric shocks in financial data

*News impact curve:*



# Leverage effect

- Debt-equity Ratio = Debt / Equity
- Stock price goes down, debt-equity ratio goes up
- Riskier!



# GJR-GARCH

$$\sigma_t^2 = \omega + (\alpha + \gamma I_{t-1}) \varepsilon_{t-1}^2 + \beta \sigma_{t-1}^2$$

$$I_{t-1} := \begin{cases} 0 & \text{if } r_{t-1} \geq \mu \\ 1 & \text{if } r_{t-1} < \mu \end{cases}$$

# GJR-GARCH in Python

```
arch_model(my_data, p = 1, q = 1, o = 1,  
           mean = 'constant', vol = 'GARCH')
```

```
=====
                        Constant Mean - GJR-GARCH Model Results
=====
Dep. Variable:                Return    R-squared:                -0.000
Mean Model:                  Constant Mean    Adj. R-squared:            -0.000
Vol Model:                   GJR-GARCH      Log-Likelihood:          -2641.12
Distribution:                Standardized Student's t    AIC:                    5294.23
Method:                     Maximum Likelihood    BIC:                    5328.77
                                           No. Observations:        2336
Date:                       Tue, Dec 10 2019    Df Residuals:            2330
Time:                       11:19:41           Df Model:                 6
                                           Mean Model
=====
                        coef    std err          t      P>|t|      95.0% Conf. Int.
-----
mu                0.0554  1.227e-02      4.521  6.163e-06  [3.141e-02,7.949e-02]
=====
                        Volatility Model
=====
                        coef    std err          t      P>|t|      95.0% Conf. Int.
-----
omega             0.0298  5.609e-03      5.317  1.054e-07  [1.883e-02,4.082e-02]
alpha[1]          0.0000  2.338e-02      0.000      1.000  [-4.583e-02,4.583e-02]
gamma[1]         0.3267  4.852e-02      6.733  1.663e-11  [ 0.232,  0.422]
beta[1]           0.8121  2.257e-02     35.978  1.835e-283  [ 0.768,  0.856]
```

# EGARCH

- A popular option to model asymmetric shocks
- Exponential GARCH
- Add a conditional component to model the asymmetry in shocks similar to the GJR-GARCH
- No non-negative constraints on alpha, beta so it runs faster

# EGARCH in Python

```
arch_model(my_data, p = 1, q = 1, o = 1,  
           mean = 'constant', vol = 'EGARCH')
```


```
=====
                        Constant Mean - EGARCH Model Results
=====
Dep. Variable:          Return      R-squared:          -0.000
Mean Model:             Constant Mean  Adj. R-squared:      -0.000
Vol Model:              EGARCH      Log-Likelihood:    -2628.40
Distribution:           Standardized Student's t  AIC:              5268.79
Method:                Maximum Likelihood  BIC:              5303.33
                                     No. Observations:      2336
Date:                  Tue, Dec 10 2019  Df Residuals:      2330
Time:                  11:19:42          Df Model:          6
                                     Mean Model
=====

              coef    std err          t      P>|t|      95.0% Conf. Int.
-----
mu              0.0493   9.578e-03      5.146  2.663e-07  [3.051e-02,6.806e-02]
              Volatility Model
=====
              coef    std err          t      P>|t|      95.0% Conf. Int.
-----
omega          -0.0202   7.350e-03     -2.743  6.094e-03  [-3.457e-02,-5.753e-03]
alpha[1]         0.1707   2.279e-02      7.490  6.874e-14   [ 0.126,  0.215]
gamma[1]       -0.2360   2.598e-02     -9.087  1.019e-19   [-0.287, -0.185]
beta[1]          0.9547   9.191e-03    103.869  0.000      [ 0.937,  0.973]
```

# Which model to use

*GJR-GARCH or EGARCH?*

Which model is better depends on the data




# Let's practice!

GARCH MODELS IN PYTHON



# GARCH rolling window forecast

GARCH MODELS IN PYTHON




**Chelsea Yang**  
Data Science Instructor

# Rolling window for out-of-sample forecast

An exciting part of financial modeling: predict the unknown



**Rolling window forecast:** repeatedly perform model fitting and forecast as time rolls forward



# Expanding window forecast

Continuously add new data points to the sample



# Motivations of rolling window forecast

- Avoid lookback bias
- Less subject to overfitting
- Adapt forecast to new observations


# Implement expanding window forecast

Expanding window forecast:

```
for i in range(120):  
    gm_result = basic_gm.fit(first_obs = start_loc,  
                             last_obs = i + end_loc, disp = 'off')  
    temp_result = gm_result.forecast(horizon = 1).variance
```

# Fixed rolling window forecast

New data points are added while old ones are dropped from the sample



# Implement fixed rolling window forecast

Fixed rolling window forecast:


```
for i in range(120):  
    # Specify rolling window range for model fitting  
    gm_result = basic_gm.fit(first_obs = i + start_loc,  
                             last_obs = i + end_loc, disp = 'off')  
    temp_result = gm_result.forecast(horizon = 1).variance
```

# How to determine window size

*Usually determined on a case-by-case basis*

- Too wide window size: include obsolete data that may lead to high bias
- Too narrow window size: exclude relevant data that may lead to higher variance

**The optimal window size: trade-off to balance bias and variance**





# Let's practice!

GARCH MODELS IN PYTHON