

**Pivotal Cloud Foundry**

## Overview

Pivotal Cloud Foundry®, powered by Cloud Foundry, delivers a turnkey PaaS experience on multiple infrastructures with leading application and data services.

## Features

- ❑ Commercially supported release based on Cloud Foundry open source
- ❑ Instant, horizontal application tier scaling
- ❑ Web console for resource management and administration of applications and services
- ❑ Applications benefit from built-in services like load balancing and DNS, automated health management, logging and auditing

- ❑ Java Spring support through provided Java buildpack
- ❑ Optimized developer experience for Spring framework
- ❑ MySQL Service for rapid development and testing
- ❑ Automatic application binding and service provisioning for Pivotal Services such as Pivotal RabbitMQ and MySQL for PCF.



**Pivotal Cloud Foundry Runtime  
for Windows**



**Microsoft Azure Service Broker  
for PCF**



**Pivotal Cloud Foundry Log  
Search**



**Pivotal Cloud Foundry Service  
Broker for AWS**



**Push Notification for PCF**



**Single Sign-On for PCF**



**Spring Cloud Services for PCF**



**GCP Service Broker for PCF**



**Pivotal Cloud Foundry Elastic  
Runtime**



**Pivotal Cloud Foundry Metrics**



**Pivotal tc Server**



**Pivotal Cloud Foundry JMX  
Bridge (Ops Metrics)**



**Pivotal Cloud Foundry  
Operations Manager**



**IPsec Add-on for PCF**



**Pivotal Cloud Foundry Isolation  
Segment**

## **Spring Cloud Services for PCF**



## Spring Cloud Services for PCF

Spring Cloud (<http://projects.spring.io/spring-cloud/>) provides tools for Spring developers to quickly apply some of the common patterns found in distributed systems (e.g. configuration management, service discovery, circuit breakers, intelligent routing, micro-proxy, control bus).

Coordination of distributed systems leads to boiler plate patterns, and using Spring Cloud, developers can quickly stand up services and applications that implement those patterns.

The Spring Cloud Services suite adds several of the central coordination services found in Spring Cloud to the Pivotal Cloud Foundry Marketplace.


## **Features**

- ❑ Config Server (based on Spring Cloud Config Server)
- ❑ Service Registry (based on Eureka via Spring Cloud Netflix)
- ❑ Circuit Breaker Dashboard (based on Hystrix and Turbine via Spring Cloud Netflix)



## **Config Server for Pivotal Cloud Foundry**

- ❑ Config Server for Pivotal Cloud Foundry (PCF) is an externalized application configuration service, which gives us a central place to manage an application's external properties across all environments.
- ❑ As an application moves through the deployment pipeline from development to test and into production, we can use Config Server to manage the configuration between environments and be certain that the application has everything it needs to run when we migrate it.
- ❑ Config Server easily supports labelled versions of environment-specific configurations and is accessible to a wide range of tooling for managing the content.



The concepts on both client and server map identically to the Spring Environment and PropertySource abstractions. They work very well with Spring applications, but can be applied to applications written in any language.

The default implementation of the server storage backend uses Git. HashiCorp Vault is also supported.

Config Server for Pivotal Cloud Foundry is based on Spring Cloud Config Server.

## **Creating an Instance**

We can create a Config Server service instance using either

- ❑ The Cloud Foundry Command Line Interface tool (cf CLI) or
- ❑ Pivotal Cloud Foundry® Apps Manager

## Using the cf CLI

Begin by targeting the correct org and space.

**\$ cf target -o scp -s development**

api endpoint: <https://api.run.pivotal.io>

api version: 2.97.0

user: jbossramana@gmail.com

org: scp

space: development

We can view plan details for the Config Server product:

## **\$ cf marketplace**

Getting services from marketplace in org scp / space development as user...

OK

service	plans	description
p-circuit-breaker-dashboard	standard	Circuit Breaker Dashboard for Spring Cloud Applications
p-config-server	standard	Config Server for Spring Cloud Applications
p-mysql	100mb-dev	MySQL service for application development and testing
p-rabbitmq	standard	RabbitMQ is a robust and scalable high-performance multi-protocol messaging broker.
p-service-registry	standard	Service Registry for Spring Cloud Applications



To create an instance, specifying settings for Git configuration sources :

```
cf create-service -c '{ "git": { "uri": "https://github.com/spring-cloud-services-samples/cook-config", "label": "master" } }' p-config-server standard config-server
```

(OR)

using json file:

```
cf create-service p-config-server standard config-server -c data.json
```

data.json file contains:

```
{  
  
  "git": {  
    "uri": "https://github.com/spring-cloud-services-samples/cook-config",  
    "label": "master"  
  }  
}
```

To create an instance, specifying settings for Git configuration sources and that three nodes should be provisioned:

```
$ cf create-service -c '{"git": { "uri": "https://github.com/spring-cloud-  
samples/config-repo", "repos": { "cook": { "pattern": "cook*", "uri":  
"https://github.com/spring-cloud-services-samples/cook-config" } } }, "count": 3 }'  
p-config-server standard config-server
```

## Using Apps Manager

Log into Apps Manager as a Space Developer. In the Marketplace, select Config Server

The screenshot displays the Pivotal Apps Manager interface. The top header is dark blue with the Pivotal logo (a white 'P' on a green square) and the text "Pivotal Apps Manager" on the left, and a user profile "user" with a dropdown arrow on the right. A dark blue sidebar on the left contains navigation links: "ORG" (with a sub-menu showing "myorg" and a dropdown arrow), "SPACES" (with a sub-menu showing "development"), "Accounting Report", "Marketplace" (highlighted with a red vertical bar), "Docs", and "Tools". The main content area is white and titled "Marketplace". Below the title is a subtitle: "Get started with our free marketplace services. Upgrade select plans to gain access to premium service plans." A search bar contains the text "config server". Below the search bar is a section titled "Services" with a small upward arrow. The first service listed is "Config Server", which has a green circular icon with a white gear and the letters "CF". The text "Config Server" is in blue, and "Config Server for Spring Cloud Applications" is in black. A mouse cursor is hovering over the service, and a right-pointing chevron is visible on the right side of the service card.

Pivotal Apps Manager

user ▾

ORG

myorg ▾

SPACES

development

Accounting Report

Marketplace

Docs



Tools

## Marketplace

Get started with our free marketplace services. Upgrade select plans to gain access to premium service plans.


🔍 config server

Services ▲

 **Config Server** 

Config Server for Spring Cloud Applications >

Select the desired plan for the new service instance.

 Pivotal Apps Manager user ▾

ORG

myorg ▾

SPACES

development


Accounting Report

Marketplace

Docs

Tools

SERVICE

 **Config Server**  
Config Server for Spring Cloud Applications  
[Docs](#) | [Support](#)

ABOUT THIS SERVICE

Provides server and client-side support for externalized configuration in a distributed system deployed to Pivotal Cloud Foundry.

COMPANY

Pivotal

standard

standard

- Single-tenant
- Backed by user-provided Git repository

Select this plan

Provide a name for the service instance (for example, “config-server”). Click the Add button.

P

Pivotal Apps Manager

user ▾

ORG

myorg ▾

SPACES

development


Accounting Report

Marketplace

Docs

Tools

SERVICE

 **Config Server**  
Config Server for Spring Cloud Applications  
[Docs](#) | [Support](#)

ABOUT THIS SERVICE

Provides server and client-side support for externalized configuration in a distributed system deployed to Pivotal Cloud Foundry.

COMPANY

Pivotal

standard

- Single-tenant
- Backed by user-provided Git repository

Configure Instance

Instance Name

config-server

Add to Space

development ▾

Bind to App

[do not bind] ▾

Show Advanced Options

Cancel

Add

In the **Services** list, click the **Manage** link under the listing for the new service instance

P

Pivotal Apps Manager

user ▾

ORG

myorg ▾

SPACES

development

Accounting Report

Marketplace

Docs

Tools

✓ Service instance "config-server" was successfully created ✕

SPACE

development

1 Running

1 Stopped

0 Crashed

Apps (2)




Services (3)

Security


Settings

Services

Add Service

SERVICE	NAME	BOUND APPS	PLAN	
 Circuit Breaker	circuit-breaker-da...	0	free -	>
 Service Registry	service-registry	2	free -	>
 Config Server	config-server	0	free -	>

It may take a few minutes to provision the service instance; while it is being provisioned, we will see a “The service instance is initializing” message. When the instance is ready, its dashboard will load automatically.

 **Spring Cloud Services** user ▾

myorg > development > config-server

## Config Server

Instance ID: d4ab1728-e104-4cfe-9d4e-978a77af54e7

```
{  
  "count": 1  
}
```

[Copy to clipboard](#)



## Updating an Instance

cf update-service SERVICE\_NAME -c '{ "PARAMETER": "VALUE" }',  
where SERVICE\_NAME is the name of the service instance  
PARAMETER is a supported parameter  
VALUE is the value for the parameter

Parameter	Function	Example
count	The number of nodes to provision: 1 by default, more for running in high-availability mode	'{"count": 3}'
upgrade	Whether to upgrade the instance	'{"upgrade": true}'
force	When upgrade is set to true, whether to force an upgrade of the instance, even if the instance is already at the latest available service version	'{"force": true}'

## Configuring with Git

Git is a distributed version control system (DVCS). It encourages parallel development through simplified branching and merging, optimizes performance by conducting many operations on the local copy of the repository, and uses SHA-1 hashes for checksums to assure integrity and guard against corruption of repository data.

**Spring Cloud Config** provides a Git backend so that the Spring Cloud Config Server can serve configuration stored in Git.

The Spring Cloud Services Config Server supports this backend and can serve configuration stored in Git to client applications when given the URL to a Git repository (for example, the URL of a repository hosted on GitHub or Bitbucket).

### **General Configuration**

Parameters used to configure configuration sources are part of a JSON object called git, as in {"git": { "uri": "http://example.com/config" } }

Parameter	Function
uri	The URI (http://, https://, or ssh://) of a repository that can be used as the default configuration source
label	The default “label” that can be used with the default repository if a request is received without a label (e.g., if the spring.cloud.config.label property is not set in a client application)
searchPaths	A pattern used to search for configuration-containing subdirectories in the default repository
cloneOnStart	Whether the Config Server should clone the default repository when it starts up (by default, the Config Server will only clone the repository when configuration is first requested from the repository). Valid values are true and false
username	The username used to access the default repository (if protected by HTTP Basic authentication)
password	The password used to access the default repository (if protected by HTTP Basic authentication)
skipSslValidation	For a https:// URI, whether to skip validation of the SSL certificate on the default repository’s server. Valid values are true and false

## Configuring with Vault

HashiCorp Vault is a secrets management tool, which encrypts and stores credentials, API keys, and other secrets for use in distributed systems. It provides support for access control lists, secret revocation, auditing, and leases and renewals, and includes special capabilities for common infrastructure and systems such as AWS, MySQL, and RabbitMQ, among others.



## General Configuration

Parameters used to configure a configuration source are part of a JSON object called vault, as in {"vault": { "host": "127.0.0.1", "port": "8200" } }.

Parameter	Function
host	The host of the Vault server
port	The port of the Vault server
scheme	The URI scheme used in accessing the Vault server (default value: http)
backend	The name of the Vault backend from which to retrieve configuration (default value: secret)
defaultKey	The default key from which to retrieve configuration (default value: application)
profileSeparator	The value used to separate profiles (default value: ,)
skipSslValidation	Whether to skip validation of the SSL certificate on the Vault server. Valid values are true and false

## **Declarative Composite Backends**

The Spring Cloud Services Config Server provides the ability to serve configuration properties from a composite of multiple backends, such as from multiple GitHub repositories and a HashiCorp Vault server.

This feature builds upon the Composite Environment Repositories.

```
{
  "composite": [
    {
      "git": {
        "uri": "https://github.com/spring-cloud-services-samples/cook-config"
      }
    },
    {
      "git": {
        "uri": "https://github.com/spring-cloud-samples/config-repo"
      }
    },
    {
      "vault": {
        "host": "127.0.0.1",
        "port": 8200,
        "scheme": "https",
        "backend": "secret",
        "defaultKey": "application",
        "profileSeparator": ","
      }
    }
  ]
}
```

## **Configuration Properties**

The Config Server can serve configuration properties from either Git or HashiCorp Vault configuration sources.

Configuration properties can be applicable to all applications that use the Config Server, specific to an application, or specific to a Spring application profile, and can be stored in encrypted form.

## Global Configuration

We can store configuration properties so that they are served to all applications which use the Config Server.

In the configuration repository, a file named `application.yml` or `application.properties` contains configuration which will be served to all applications that access the Config Server.

## Application-Specific Configuration

We can store configuration properties so that they are served only to a specific application.

In the configuration repository, a file named [APP-NAME].yml or [APP-NAME].properties, where [APP-NAME] is the name of an application, contains configuration which will be served only to the APP-NAME application



## Profile-Specific Configuration

We can store configuration properties so that they are served only to applications which have activated a specific Spring application profile.

In the configuration repository, a file named [APP-NAME]-[PROFILE-NAME].yml or [APP-NAME]-[PROFILE-NAME].properties, where [APP-NAME] is the name of an application and [PROFILE-NAME] is the name of an application profile

## Encrypted Configuration

We can store configuration properties in encrypted form and have these properties decrypted by the Config Server before they are served to applications.

In a file within the configuration repository, properties whose values are prefixed with {cipher} will be decrypted before they are served to client applications.

To use this feature, you must configure the Config Server with an encryption key.

An example of an encrypted property value in an application.yml file:

secretMenu:

```
'{cipher}AQA90Q3GIRAMu6ToMqwS++En2iFzMXIWX99G66yaZFRHrQNq64CntqOzWymd  
3xE7uJp  
ZKQc9XBIkfyRz/HUGhXRdf3KZQ9bqclwmR5vkiLmN9DHIAXS+6biT+7f8ptKo3fzQ0gGOBaR4  
kTnWLBxmValkjq1  
Qze4algsgUWuhbEek+3znkH9+Mc+5zNPvwN8hhgDMDVzgZLB+4YnvWJAq3Au4wEevakAH  
HxVY0mXcxj1Ro+H+Zel  
IzfF8K2AvC3vmvImxy9Y49Zjx0RhMzUx17eh3mAB8UMMRJZyUG2a2uGCXmz+UunTA5n/d  
WWOvR3VcZyzXPFSFkhN  
ekw3db9XZ7goceJSPrRN+5s+GjLCPr+KSnhLmUt1XAScMeqTieNCHT5I='
```

Configuration Clients

Config Server client applications can be written in any language. The interface for retrieving configuration is HTTP, and the endpoints are protected by OAuth 2.0.

To be given a base URI and client credentials for accessing a Config Server instance, a Cloud Foundry application needs to bind to the instance.

P

Pivotal Apps Manager

user ▾

ORG

myorg ▾

SPACES

development

Accounting Report

Marketplace


Docs

Tools

SERVICE

INSTANCE NAME

SERVICE PLAN

 **Config Server** config-server standard

[Manage](#) | [Docs](#) | [Support](#)

App Bindings Plan Settings

Bound Apps

Bind Apps

Bind an App to this Service

No Apps have been bound to this Service

P

Pivotal Apps Manager

user ▾

ORG

myorg ▾

SPACES

development

Accounting Report

Marketplace


Docs

Tools

SERVICE

INSTANCE NAME

SERVICE PLAN

 **Config Server** config-server standard

[Manage](#) | [Docs](#) | [Support](#)

App Bindings Plan Settings

Bound Apps

cancel Save

cook ☒

Cloud Foundry Command Line Interface tool (cf CLI)

```
$ cf bind-service cook config-server
```

Binding service config-server to app cook in org myorg / space development as admin...  
OK

TIP: Use 'cf restage cook' to ensure your env variable changes take effect

## **Writing Client Applications**



## **pom.xml**

Our application must declare spring-cloud-services-starter-config-client as a dependency.

If using Maven, include in pom.xml:

```
<dependencies>
  <dependency>
    <groupId>io.pivotal.spring.cloud</groupId>
    <artifactId>spring-cloud-services-starter-config-client</artifactId>
  </dependency>
</dependencies>
```

## **Add Self-Signed SSL Certificate to JVM Truststore**

```
$ cf set-env cook TRUST_CERTS api.cf.wise.com
```

Setting env variable 'TRUST\_CERTS' to 'api.cf.wise.com' for app cook in  
org myorg / space development as user...  
OK

TIP: Use 'cf restage' to ensure your env variable changes take effect

```
$ cf restage cook
```

## Use Configuration Values

When the application requests a configuration from the Config Server, it will use a path containing the application name. We can declare the application name in `bootstrap.properties`, `bootstrap.yml`, `application.properties`, or `application.yml`.

In `bootstrap.yml`:

```
spring:  
  application:  
    name: cook
```

This application will use a path with the application name cook, so the Config Server will look in its configuration source for files whose names begin with cook, and return configuration properties from those files.

Now you can (for example) inject a configuration property value using the `@Value` annotation. The Menu class reads the value of special from the cook.special configuration property.

```
@RefreshScope
@Component
public class Menu {

    @Value("${cook.special}")
    String special;

    //...

    public String getSpecial() {
        return special;
    }

    //...

}
```

## Vary Configurations Based on Profiles

We can provide configurations for multiple profiles by including appropriately-named .yml or .properties files in the Config Server instance's configuration source (the Git repository).

Filenames follow the format {application}-{profile}.{extension}, as in cook-production.yml.

applications:

- name: cook

host: cookie

services:

- config-server

env:

SPRING\_PROFILES\_ACTIVE: production

Spring Boot Actuator Dependency

## View Client Application Configuration

Spring Boot Actuator adds an env endpoint to the application and maps it to /env. This endpoint displays the application's profiles and property sources from the Spring ConfigurableEnvironment.

```
<dependency>  
  <groupId>org.springframework.boot</groupId>  
  <artifactId>spring-boot-starter-actuator</artifactId>  
</dependency>
```

We can now visit /env to see the application environment's

```
$ curl http://cookie.apps.wise.com/env
```



## Refresh Client Application Configuration

Spring Boot Actuator also adds a refresh endpoint to the application. This endpoint is mapped to /refresh, and a POST request to the refresh endpoint refreshes any beans which are annotated with @RefreshScope. You can thus use @RefreshScope to refresh properties which were initialized with values provided by the Config Server.

```
$ curl -X POST http://cookie.apps.wise.com/refresh  
["cook.special"]
```


## **Spring Cloud Connectors**

To connect client applications to the Config Server, Spring Cloud Services uses Spring Cloud Connectors, including the Spring Cloud Cloud Foundry Connector, which discovers services bound to applications running in Cloud Foundry.

Spring Cloud Connectors provides a simple abstraction for JVM-based applications running on cloud platforms to discover bound services and deployment information at runtime, and provides support for registering discovered services as Spring beans

## **Service Registry for Pivotal Cloud Foundry**

Service Registry for Pivotal Cloud Foundry (PCF) provides the applications with an implementation of the Service Discovery pattern, one of the key tenets of a microservice-based architecture.



When a client registers with the Service Registry, it provides metadata about itself, such as its host and port.

The Registry expects a regular heartbeat message from each service instance. If an instance begins to consistently fail to send the heartbeat, the Service Registry will remove the instance from its registry.

Service Registry for Pivotal Cloud Foundry is based on Eureka, Netflix's Service Discovery server and client.

## **Enabling Peer Replication**

We can configure a Service Registry service instance to replicate service registrations with a peer Service Registry service instance.

This functionality supports two models:

### Peer replication across separate Pivotal Cloud Foundry (PCF) deployments:

We can configure peer replication to allow access to services registered with a Service Registry service instance in a PCF deployment located in a separate datacenter.

### Peer replication across PCF organizations and spaces:

We can configure peer replication to allow access to services registered with a Service Registry service instance in another organization or space within the same PCF deployment.

## Configuration Parameters

To enable peer replication for a Service Registry service instance, we must specify the peer Service Registry instance's URI using the peers JSON array, which contains an object for each Service Registry peer.

We can find a Service Registry service instance's URI on its dashboard

A Service Registry peer can be expressed as shown in the following JSON:

```
{
  "peers": [
    { "uri": "https://eureka-e280160b-d3e3-41ad-93a6-479f9b298ca6.wise2.com" }
  ]
}
```

```
$ cf create-service p-service-registry standard service-registry -c '{ "peers": [ {"uri":  
"https://eureka-e280160b-d3e3-41ad-93a6-479f9b298ca6.wise2.com"} ] }'
```

```
$ cf update-service service-registry -c '{ "peers": [ {"uri": "https://eureka-e280160b-  
d3e3-41ad-93a6-479f9b298ca6.wise2.com"} ] }'
```



To find the dashboard, navigate in Pivotal Cloud Foundry Apps Manager to the Service Registry service instance's space, click the listing for the service instance, and then click Manage.

The screenshot displays the Pivotal Apps Manager interface. On the left is a dark sidebar with a 'P' logo and 'Pivotal Apps Manager' text. Below this are sections for 'ORG' (myorg), 'SPACES' (development), and a list of links: Accounting Report, Marketplace, Docs, and Tools. The main content area has a header with 'SERVICE' (Service Registry), 'INSTANCE NAME' (service-registry), and 'SERVICE PLAN' (standard). Below the header is a 'Manage' link with a cursor pointing to it, along with 'Docs' and 'Support' links. A sub-header shows 'App Bindings', 'Plan', and 'Settings'. The main section is titled 'Bound Apps' and contains the text 'Bind an App to this Service' and 'No Apps have been bound to this Service'.

Pivotal Apps Manager

user ▾

ORG

myorg ▾

SPACES

development

Accounting Report

Marketplace

Docs

Tools

SERVICE

Service Registry

INSTANCE NAME

service-registry

SERVICE PLAN

standard

Manage | Docs | Support

App Bindings | Plan | Settings

Bound Apps

Bind an App to this Service

No Apps have been bound to this Service



myorg > development > service-registry

[🏠 Home](#) [🕒 History](#)

## Service Registry Status

### Registered Apps

Application	Availability Zones	Status
EUREKA-SERVER	default (2)	🟢 UP (2)

### System Status

Parameter	Value
Current time	2016-10-06T22:17:36 +0000
Server URL	https://eureka-5be054a9-838d-456b-bd28-c4b1a3c5b854.wise.com
High Availability (HA) count	1
Peers	https://eureka-f9831c89-d55c-4670-81d5-918e60f939ab.otherwise.com
Lease expiration enabled	true


# Circuit Breaker Dashboard

Circuit Breaker Dashboard provides Spring applications with an implementation of the Circuit Breaker pattern.

Cloud-native architectures are typically composed of multiple layers of distributed services.

End-user requests may comprise multiple calls to these services, and if a lower-level service fails, the failure can cascade up to the end user and spread to other dependent services.

Heavy traffic to a failing service can also make it difficult to repair. Using Circuit Breaker Dashboard, we can prevent failures from cascading and provide fallback behavior until a failing service is restored to normal operation.



When applied to a service, a circuit breaker watches for failing calls to the service. If failures reach a certain threshold, it “opens” the circuit and automatically redirects calls to the specified fallback mechanism. This gives the failing service time to recover.

Circuit Breaker Dashboard is based on Hystrix, Netflix’s latency and fault-tolerance library

## **Client Dependencies**

If using Maven, include in pom.xml:

```
<dependencies>
  <dependency>
    <groupId>io.pivotal.spring.cloud</groupId>
    <artifactId>spring-cloud-services-starter-circuit-breaker</artifactId>
  </dependency>
</dependencies>
```



## Use a Circuit Breaker

To work with a Circuit Breaker Dashboard instance, your application must include the `@EnableCircuitBreaker` annotation on a configuration class.

```
import org.springframework.cloud.client.circuitbreaker.EnableCircuitBreaker;  
//...
```

```
@SpringBootApplication  
@EnableDiscoveryClient  
@RestController  
@EnableCircuitBreaker  
public class AgencyApplication {  
    //...
```

To apply a circuit breaker to a method, annotate the method with `@HystrixCommand`, giving the annotation the name of a fallbackMethod.

```
@HystrixCommand(fallbackMethod = "getBackupGuide")
public String getGuide() {
    return restTemplate.getForObject("http://company/available",
String.class);
}
```

## **Use a Circuit Breaker with a Feign Client**

We cannot apply `@HystrixCommand` directly to a Feign client interface at this time. Instead, we can call Feign client methods from a service class that is autowired as a Spring bean (either through the `@Service` or `@Component` annotations or by being declared as a `@Bean` in a configuration class) and then annotate the service class methods with `@HystrixCommand`.

AgencyApplication class is annotated with @EnableFeignClients.

```
import org.springframework.cloud.netflix.feign.EnableFeignClients;
```

```
@SpringBootApplication
```

```
@EnableDiscoveryClient
```

```
@RestController
```

```
@EnableCircuitBreaker
```

```
@EnableFeignClients
```

```
public class AgencyApplication {
```

The application has a Feign client called CompanyClient.

```
package agency;
```

```
import org.springframework.stereotype.Component;
```

```
import org.springframework.cloud.netflix.feign.FeignClient;
```

```
import org.springframework.web.bind.annotation.RequestMapping;
```

```
import static org.springframework.web.bind.annotation.RequestMethod.GET;
```

```
@FeignClient("https://company")
```

```
interface CompanyClient {
```

```
    @RequestMapping(value="/available", method = GET)
```

```
    String availableGuide();
```

```
}
```

## Using the Dashboard

P

Pivotal Apps Manager

user ▾

ORG

myorg ▾

SPACES

development


Accounting Report

Marketplace

SERVICE

INSTANCE NAME

SERVICE PLAN

Circuit Breaker

circuit-breaker-dashboard

standard

Manage

Docs


Support

App Bindings

Plan

Settings

Bound Apps

Circuit Breaker Dashboard

user ▾

myorg > development > circuit-breaker-dashboard

Circuit

Sort: Error then Volume | Alphabetical | Volume | Error | Mean | Median | 90 | 99 | 99.5

Success | Short-Circuited | Timeout | Rejected | Failure | Error %

agency.getGuide

0

0

0.0 %

Host: 0.0/s

Cluster: 0.0/s

Circuit Closed

Hosts

1

90th

0ms

Median

0ms

99th

0ms

Mean

0ms

99.5th

0ms

Thread Pools

Sort: Alphabetical | Volume |

TravelAgent

Host: 0.0/s

Cluster: 0.0/s

Active

0

Max Active

0

Queued

0

Executions

0

Pool Size


10

Queue Size

5

# **Cloud Foundry Architecture**





## **How Cloud Foundry Works**

To flexibly serve and scale apps online, Cloud Foundry has subsystems that perform specialized functions.

# Pivotal Cloud Foundry Commercialization Model

Open source software provides the basis for the platform

Commercial distribution provides value add features, enterprise services, support, docs, certs, etc.



## How the Cloud Balances Its Load

Clouds balance their processing loads over multiple machines, optimizing for efficiency and resilience against point failure.

A Cloud Foundry installation accomplishes this at three levels:

**BOSH** creates and deploys virtual machines (VMs) on top of a physical computing infrastructure, and deploys and runs Cloud Foundry on top of this cloud. To configure the deployment, BOSH follows a manifest document.

The CF **Cloud Controller** runs the apps and other processes on the cloud's VMs, balancing demand and managing app lifecycles.

The **router** routes incoming traffic from the world to the VMs that are running the apps that the traffic demands, usually working with a customer-provided load balancer.

## **Component : BOSH**

Bosh is a project that unifies release engineering, deployment, and lifecycle management of small and large-scale cloud software.

BOSH can provision and deploy software over hundreds of VMs.

It also performs monitoring, failure recovery, and software updates with zero-to-minimal downtime.

While BOSH was developed to deploy Cloud Foundry PaaS, it can also be used to deploy almost any other software (Hadoop, for instance). BOSH is particularly well-suited for large distributed systems

## **Component: Cloud Controller**

The Cloud Controller provides REST API endpoints for clients to access the system.

The Cloud Controller maintains a database with tables for orgs, spaces, services, user roles, and more.

## **Diego Auction**

The Cloud Controller uses the Diego Auction to balance application processes over the cells in a Cloud Foundry installation.

The **Diego** Auction balances application processes, also called jobs, over the virtual machines (VMs) in a Cloud Foundry installation.


When new processes need to be allocated to VMs, the Diego Auction determines which ones should run on which machines.

The auction algorithm balances the load on VMs and optimizes application availability and resilience. This topic explains how the Diego Auction works at a conceptual level.

**Component: Gorouter**

The Gorouter routes traffic coming into Cloud Foundry to the appropriate component, whether it is an operator addressing the Cloud Controller or an application user accessing an app running on a Diego Cell.





## **Diego Brain**

Diego Brain components distribute Tasks and LRPs (Long Running Process) to Diego Cells, and correct inconsistency between ActualLRP and DesiredLRP counts to ensure fault-tolerance and long-term consistency.

The Diego Brain consists of the Auctioneer.

## **Auctioneer**

Uses the auction package to run Diego Auctions for Tasks and LRPs  
Communicates with Cell Reps over HTTP

Maintains a lock in the BBS(Bulletin Board System) that restricts auctions to one Auctioneer at a time

## **Diego Cell Components**

Diego Cell components manage and maintain Tasks and LRPs.

### **Rep**

Represents a Cell in Diego Auctions for Tasks and LRPs

Mediates all communication between the Cell and the BBS

### **Executor**

Runs as a logical process inside the Rep

### **Garden**

Provides a platform-independent server and clients to manage Garden containers

### **Metron Agent**

Forwards application logs, errors, and application and Diego metrics to the Loggregator Doppler component

**Loggregator** is the logging system used in CloudFoundry.

Loggregator Goals:

Real time streaming of logs

Producers do not experience backpressure

Logs can be routed to several consumers

Elastic and horizontal scalability

High message reliability

Low latency

Flexible consumption

Security via gRPC with mutual TLS

Opinionated log structure