Important Problematic Questions for University Exam



MODULE 1

Q1:

A benchmark program is run on a 40 MHz processor. The executed program consists of 100,000 instruction executions, with the following instruction mix and clock cycle count:

Instruction Type	Instruction Count	Cycles per Instruction
Integer arithmetic	45.000	1
Data transfer	32.000	2
Floating point	15.000	2
Control transfer	8000	2

Determine the effective CPI, MIPS rate, and execution time for this program.

- MIPS rate= $f/CPI*10^6$
  $= 40/ 1.55*10^6$
  $=40*10^6/1.55*10^6$
  $= \mathbf{25.8}$

- Given f=40 MHz ➔ $\tau = 1/40$
  $T = Ic * CPI * \tau$
  $= 100000*1.55*1/40$
  $= 100000*1.55*0.025$
  $= 3875$
  $= \mathbf{3.875\ ms}$

Prepared By Mr.EBIN PM, AP, IESCE EDULINE 5

Q2:

3 enhancement with the following speed up are proposed for a new architecture

- $Speedup_1 = 30$
- $Speedup_2 = 20$
- $Speedup_3 = 15$

If enhancement 1 and 2 are each usable for 25% of the time, what fraction of the time must enhancement 3 be used to achieve an overall speed up of 10 ?

Prepared By Mr.EBIN PM, AP, IESCE EDULINE 6

Clock speed of the Processor = 40 MHz

Instruction Type	Instruction Count	Cycles per Instruction	cycles
Integer arithmetic	45,000	1	45000
Data transfer	32,000	2	64000
Floating point	15,000	2	30000
Control transfer	8000	2	16000

- Total no: of cycles required to execute complete program
  - ➔ 45000+64000+30000+16000
  - ➔ 155000 cycles

C=155000 cycles

- Effective CPI= C/Ic
  - ➔ 155000/100000

CPI = 1.55

Ans:

$$\text{Speedup}_{\text{overall}} = \left[\frac{1}{(1-\text{Fraction}_{\text{enhanced}}) + \frac{\text{Fraction}_{\text{enhanced}}}{\text{Speedup}_{\text{enhanced}}}}\right]$$

$$= \left\{(1-(FE_1+FE_2+FE_3)) + \left[\frac{FE_1}{SE_1} + \frac{FE_2}{SE_2} + \frac{FE_3}{SE_3}\right]\right\}^{-1}$$

$$10 = \left\{(1-(0.25+0.25+FE_3)) + \left[\frac{0.25}{30} + \frac{0.25}{20} + \frac{FE_3}{15}\right]\right\}^{-1}$$

$$10 = \left\{(0.5-FE_3) + \left[\frac{0.5+0.75+4FE_3}{60}\right]\right\}^{-1}$$

$$10 = \frac{60}{30-60FE_3+1.25+4FE_3}$$

$$-56FE_3 = 6 - 31.25$$

$$FE_3 = -25.25/-56 = 0.45$$

MODULE 2

Q: Consider the design of a 3 level memory hierarchy with following features

Memory level	Access time	Capacity	Cost/kbyte
Cache	t1= 25 ns	s1= 512 Kbytes	c1= $1.25
Main memory	t2= **unknown**	s2= 32 Mbytes	c2= $.2
Disk array	t3= 4 ms	s3= **unknown**	c3= $0.0002

- Aim is to achieve effective memory access time Teff=850 ns
  - Cache hit ratio h_1 =0.98
  - Main memory Hit ratio h_2 =0.99
  - Disk array hit ratio h_3 =1
  - Total cost is upper bounded by$15000

Calculate the unknown specifications based on the given conditions ?

Q3:

Determine the frequency of the pipeline if the stage delays are τ1 = 3ns, τ2 = τ3=5ns and τ4 =8 ns and the latch delay is 1 ns.

$\tau_{max=}$ 8ns

d = 1ns

$\tau = \tau_{max} + d = 8 * 10^{-9} + 1 * 10^{-9} = 9 * 10^{-9}$

$f = \frac{1}{\tau} = = \frac{1}{9 * 10^{-9}} = 111.11$ MHz

EDULINE 17

Prepared By Mr.EBIN PM, AP, IESCE

- $C_{total} = c_1 s_1 + c_2 s_2 + c_3 s_3 <= 15000$

  15000=1.25*512+.2*32000+.0002*s3

  15000 = 640+6400+.0002*s3

  .0002*s3 =15000-640-6400

  =7960/.0002

  = 39800000x 10^{-6}

  s3 = 39.8

EDULINE 9

Prepared By Mr.EBIN PM, AP, IESCE

$T_{eff} = h_1 t_1 + (1- h_1) h_2 t_2 + (1- h_1)(1- h_2) h_3 t_3$

T_{eff} = h1 t_1 +(1- h_1) $h_2 t_2$+(1- h_1)(1- h_2) h_3 t_3 <=850 ns

850x10^{-9} = .98*25x10^{-9}+.02*.99* t_2 +.02*.01*1*4*10^{-3}

850x10^{-9} = 24.5x10^{-9}+.0198t2+.0008x10^{-3}

.0198t2 = 850x10^{-9}-24.5x10^{-9}-.0008x10^{-3}

= 825.5x10^{-9}-.0008x10^{-3}

= 825.5x10^{-9}-800x10^{-9}

= 25.5x10^{-9}

= 25.5x10^{-9}/.0198

t_2 = 1287 x 10^{-9}

EDULINE 10

Prepared By Mr.EBIN PM, AP, IESCE