Program 4:
Build Logistic Regression Model for a given dataset

Screenshot:

	DATE:
2/4/2	s whose we want to reading
4	a consider binary plays treation problem where we want to predict who
	as strain was faint and leasted parameter The
	regression model has been more of strong hours
	segression model has prest thereof of strong hows
	(a) With legistic degression up tou this problem
	D(112) 1(1) = 1
	1+ e-(-5+0811)
	(h) can have a sailte that shaked who studies for 7 her will an
	(b) calculate probability that student who studing for 7 his will po
	$p(log) = \frac{1}{1 + (-0.6)} = \frac{0.6439}{1 + (-0.6)} = \frac{1}{1 + (-0.6)}$
	1+(
	21 and elect for that Inchest hard on August
	(c) Determine predicted class for this Suchent bound on flyelied o
#	if p(pass) >0.5, Student will pract also he will fail
(0) Consider = 2 (2,1,0) for their claims, apply softmax fin to
10	peop of values there classes
	SOFTMOX (20) =
	SOFMOX(20) = exk \$ eli
	F 10 04 15 04 14 01 1
	$p(1) = e^2 = 0.665$
	e2+e'+c0
	and make the state of the state
	$p(2) = e^1 = 0.295$ $e^2 + e^1 + e^0$
	e2+e'+10/
	b(3) = 60.00
	e2+e'+e0
7	

3	DATE: PAGE:
9	After building logistic segretion models, answer following question:
-	(it) which regionles did you identify as having on direct and clear injust
_	on employee resention? way?
_	(ii) what was accuracy of your logistic segretaion model 9 Do you trunk this
	is good accuracy? why or why nor?
	as arm of Andrew to built forther worder at the
190	an artugent, about many tops and blues an prestitution in
(2)	For 200 datajet
	in Did you perform any data prycocensing steps? If yes, what were
1 119	they, and way there they increasing?
	(ii) was there any uniting or intensitent reduct in dataset? How also you
	hand, them?
	(iii) What doy' confusion matrix tell you about personance of your model
	W, which closes types were most frequently nivelanitied? Why do you
	think this happened?
9150	A restricted positions around process to an analysis of the same
	Answey:
(1)	i a Lather Line Line
(1)	in South on I well in company
	-) time spout in company -> Number of project
	2) 2 (2)
	They raciably are thosen based on trends in Idata visualization
,	The accuracy of logistic segression was 78%. This accuracy is fairly good, st suggest that model saythers must of properties offering employee seeknsion.
	fairly good st suggest that model earther must of properties
	offering employee reknsion.

	P
(23)	24 15 4000 000
1	i) Yes
- //	- Despond 'animal name' column
- 11	- wiered for moting roung if needed
11	-> Deeppred animal name tours -> elucised for musting radius if needed -> converted caregorical wariable if needed
	No musting values fluid in dataget. 1895 in our of
1 ais	to autising values found in extension. It is some mode inventor
1100	inconsistences, we could have used to the first affections
#	No musting values found in dataset. If it are of inconsistency we could have used mean/mode injustation semant mem
11	Les Automotives
(FEE)	is any well the madel predicted different their types. I
11	It shows how well the madel greateded distant than types I have to prediction, along diagnos of matrix sudicates good
lina	
1100	performance
11 .	
11(1V) -	huph bans, histy septiles
11	
Reason	
Reason	Since they have similar teaning decision boundaring.
Reason	Since they have similar teaning decision boundaring.
Reason>	
	Legistic segression arsumes linear decision boundaring . may not work will for complex clar separation.
Keasen >	Legistic segression arsumes linear decision boundaring . may not work will for complex clar separation.
	Ligible segression arrumes linear electron boundaring may not week will for complex clark separation.
	Legistic segression arsumes linear decision boundaring . may not work will for complex clar separation.
90	Ligital segression arsumes livear decision boundaring may not week will for complex clar separation.
90	Ligible segression arrumes linear electron boundaring may not week will for complex clark separation.
1946	Ligital segression arsumes livear decision boundaring may not week will for complex clar separation.
90	Ligital segression assumes linear decision boundaring may not usek will for complex clark separation.
90	Ligital segression assumes linear decision boundaring may not unest will for complex clark separation.
90	Ligital segression assumes linear decision boundaring may not usek will for complex clark separation.
90	Ligital segression assumes liveas decision boundaring may not usek will for complex clark separation.
90	Ligital segression assumes linear decision boundaring may not unest will for complex clark separation.
90	Ligital segression assumes liveas decision boundaring may not usek will for complex clark separation.
90	Ligital segression assumes liveas decision boundaring may not usek will for complex clark separation.

Code:

#LogisticRegression_Multiclass.ipynb

Import necessary libraries

import pandas as pd

from sklearn.datasets import load_iris

from sklearn.model_selection import train_test_split

from sklearn.linear_model import LogisticRegression

from sklearn.metrics import accuracy_score

from sklearn import metrics

import matplotlib.pyplot as plt

```
# Load the Iris dataset
iris = pd.read_csv("/content/iris (2).csv")
iris.head()
X=iris.drop('species',axis='columns')# Features (sepal length, sepal width, petal length, petal width)
y = iris.species # Target labels (0: Setosa, 1: Versicolor, 2: Virginica)
# Split the dataset into 80% training and 20% testing
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)
# Initialize the Multinomial Logistic Regression model
# Use 'multinomial' for multi-class classification and 'lbfgs' solver
model = LogisticRegression(multi_class='multinomial')
# Train the model on the training data
model.fit(X_train, y_train)
# Make predictions on the test data
y_pred = model.predict(X_test)
# Calculate the accuracy of the model on the test data
accuracy = accuracy_score(y_test, y_pred)
# Display the accuracy
```

```
print(f"Accuracy of the Multinomial Logistic Regression model on the test set: {accuracy:.2f}")
confusion_matrix = metrics.confusion_matrix(y_test, y_pred)
cm_display = metrics.ConfusionMatrixDisplay(confusion_matrix = confusion_matrix, display_labels =
["Setosa", "Versicolor", "Virginica"])
cm_display.plot()
plt.show()
Binary Classification:
#LogisticRegression_Binary.ipynb
# Commented out IPython magic to ensure Python compatibility.
import pandas as pd
from matplotlib import pyplot as plt
# %matplotlib inline
#"%matplotlib inline" will make your plot outputs appear and be stored within the notebook.
df = pd.read_csv("/content/insurance_data (1).csv")
df.head()
plt.scatter(df.age,df.bought_insurance,marker='+',color='red')
from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test =
```

```
train_test_split(df[['age']],df.bought_insurance,train_size=0.9,random_state=10)
X_train.shape
X_test
from sklearn.linear_model import LogisticRegression
model = LogisticRegression()
model.fit(X_train, y_train)
X_test
y_test
y_predicted = model.predict(X_test)
y_predicted
model.score(X_test,y_test)
model.predict_proba(X_test)
y_predicted = model.predict([[60]])
y_predicted
```

```
\#model.coef\_indicates\ value\ of\ m\ in\ y=m*x+b\ equation
model.coef_
\#model.intercept\_indicates\ value\ of\ b\ in\ y=m*x+b\ equation
model.intercept_
#Lets defined sigmoid function now and do the math with hand
import math
def sigmoid(x):
 return 1/(1 + \text{math.exp}(-x))
def prediction_function(age):
 z = 0.127 * age - 4.973 # 0.12740563 \sim 0.0127  and -4.97335111 \sim -4.97
 y = sigmoid(z)
 return y
age = 35
prediction_function(age)
"""0.37 is less than 0.5 which means person with 35 will not buy the insurance"""
```