

1BM22CS241

SANJEET PRAJWAL PANDIT

```
import re

def occurs_check(var, x):
    """Checks if var occurs in x (to prevent circular
    substitutions)."""
    if var == x:
        return True
    elif isinstance(x, list): # If x is a compound expression (like a
        function or predicate)
        return any(occurs_check(var, xi) for xi in x)
    return False

def unify_var(var, x, subst):
    """Handles unification of a variable with another term."""
    if var in subst: # If var is already substituted
        return unify(subst[var], x, subst)
    elif isinstance(x, (list, tuple)) and tuple(x) in subst: # Handle
        compound expressions
        return unify(var, subst[tuple(x)], subst)
    elif occurs_check(var, x): # Check for circular references
        return "FAILURE"
    else:
        # Add the substitution to the set (convert list to tuple for
        hashability)
        subst[var] = tuple(x) if isinstance(x, list) else x
        return subst

def unify(x, y, subst=None):
    """
    Unifies two expressions x and y and returns the substitution set if
    they can be unified.
    Returns 'FAILURE' if unification is not possible.
    """
    if subst is None:
        subst = {} # Initialize an empty substitution set

    # Step 1: Handle cases where x or y is a variable or constant
    if x == y: # If x and y are identical
        return subst
    elif isinstance(x, str) and x.islower(): # If x is a variable
        return unify_var(x, y, subst)
    elif isinstance(y, str) and y.islower(): # If y is a variable
        return unify_var(y, x, subst)
```

```

        elif isinstance(x, list) and isinstance(y, list): # If x and y are
compound expressions (lists)
            if len(x) != len(y): # Step 3: Different number of arguments
                return "FAILURE"

            # Step 2: Check if the predicate symbols (the first element)
match
            if x[0] != y[0]: # If the predicates/functions are different
                return "FAILURE"

            # Step 5: Recursively unify each argument
            for xi, yi in zip(x[1:], y[1:]): # Skip the predicate (first
element)
                subst = unify(xi, yi, subst)
                if subst == "FAILURE":
                    return "FAILURE"
            return subst
        else: # If x and y are different constants or non-unifiable
structures
            return "FAILURE"

def unify_and_check(expr1, expr2):
    """
    Attempts to unify two expressions and returns a tuple:
    (is_unified: bool, substitutions: dict or None)
    """
    result = unify(expr1, expr2)
    if result == "FAILURE":
        return False, None
    return True, result

def display_result(expr1, expr2, is_unified, subst):
    print("Expression 1:", expr1)
    print("Expression 2:", expr2)
    if not is_unified:
        print("Result: Unification Failed")
    else:
        print("Result: Unification Successful")
        print("Substitutions:", {k: list(v) if isinstance(v, tuple)
else v for k, v in subst.items()})

def parse_input(input_str):
    """Parses a string input into a structure that can be processed by
the unification algorithm."""
    # Remove spaces and handle parentheses
    input_str = input_str.replace(" ", "")

```

```

# Handle compound terms (like p(x, f(y)) -> ['p', 'x', ['f', 'y']])
def parse_term(term):
    # Handle the compound term
    if '(' in term:
        match = re.match(r'([a-zA-Z0-9_+]\((.*)\)', term)
        if match:
            predicate = match.group(1)
            arguments_str = match.group(2)
            arguments = [parse_term(arg.strip()) for arg in
arguments_str.split(',')]
            return [predicate] + arguments
        return term

    return parse_term(input_str)

# Main function to interact with the user
def main():
    while True:
        # Get the first and second terms from the user
        expr1_input = input("Enter the first expression (e.g., p(x,
f(y)): ")
        expr2_input = input("Enter the second expression (e.g., p(a,
f(z)): ")

        # Parse the input strings into the appropriate structures
        expr1 = parse_input(expr1_input)
        expr2 = parse_input(expr2_input)

        # Perform unification
        is_unified, result = unify_and_check(expr1, expr2)

        # Display the results
        display_result(expr1, expr2, is_unified, result)

        # Ask the user if they want to run another test
        another_test = input("Do you want to test another pair of
expressions? (yes/no): ").strip().lower()
        if another_test != 'yes':
            break

if __name__ == "__main__":
    main()

```

OUTPUT:

```
Enter the first expression (e.g., p(x, f(y))): p(b,x,f(g(z)))
Enter the second expression (e.g., p(a, f(z))): p(z,f(y),f(y))
Expression 1: ['p', 'b', 'x', ['f', ['g', 'z']]]
Expression 2: ['p', 'z', ['f', 'y'], ['f', 'y']]
Result: Unification Successful
Substitutions: {'b': 'z', 'x': ['f', 'y'], 'y': ['g', 'z']}
Do you want to test another pair of expressions? (yes/no): yes
Enter the first expression (e.g., p(x, f(y))): p(x,h(y))
Enter the second expression (e.g., p(a, f(z))): p(a,f(z))
Expression 1: ['p', 'x', ['h', 'y']]
Expression 2: ['p', 'a', ['f', 'z']]
Result: Unification Failed
Do you want to test another pair of expressions? (yes/no): yes
Enter the first expression (e.g., p(x, f(y))): p(f(a),g(y))
Enter the second expression (e.g., p(a, f(z))): p(x,x)
Expression 1: ['p', ['f', 'a'], ['g', 'y']]
Expression 2: ['p', 'x', 'x']
Result: Unification Failed
Do you want to test another pair of expressions? (yes/no): no
```