

DAILY TASK-18

NAME : SANJEEV N

DATE : 01-09-2025

```
[
  {
    "id": 1,
    "breed": "Siberian Husky",
    "line": "Straight",
    "age": 1
  },
  {
    "id": 2,
    "breed": "German Shepherd",
    "line": "Double Bush Coat",
    "age": 1
  },
  {
    "id": 3,
    "breed": "Golden Retriever",
    "line": "Cross",
    "age": 1
  }
]
```

MODELS.CS

```
namespace PetApi.Models
{
    public class Dog
    {
        public int Id { get; set; }
        public string Breed { get; set; }
        public string Line { get; set; }
        public int Age { get; set; }
    }
}
```

APPDBCONTEXT.CS

```
using Microsoft.EntityFrameworkCore;
using PetApi.Models;

namespace PetApi.Data
{
```

```

public class AppDbContext : DbContext
{
    public AppDbContext(DbContextOptions<AppDbContext> options) :
base(options) { }

    public DbSet<Dog> Dogs { get; set; }
}

```

CONTROLLER.CS

```

using Microsoft.AspNetCore.Mvc;
using PetApi.Data;
using PetApi.Models;
using Microsoft.EntityFrameworkCore;

namespace PetApi.Controllers
{
    [Route("api/[controller]")]
    [ApiController]
    public class DogsController : ControllerBase
    {
        private readonly AppDbContext _context;

        public DogsController(AppDbContext context)
        {
            _context = context;
        }

        [HttpGet("GetDogList")]
        public async Task<ActionResult<IEnumerable<Dog>>> GetDogs()
        {
            return await _context.Dogs.ToListAsync();
        }

        [HttpPost("AddDogs")]
        public async Task<ActionResult<Dog>> PostDog(Dog dog)
        {

```

```

        _context.Dogs.Add(dog);
        await _context.SaveChangesAsync();
        return CreatedAtAction(nameof(GetDogs), new { id = dog.Id },
dog);
    }

    [HttpGet("GetDogByName/{name}")]
    public async Task<ActionResult<Dog>> GetDogByName(string name)
    {
        var dog = await _context.Dogs
            .FirstOrDefaultAsync(d => d.Breed.ToLower() ==
name.ToLower());
        return Ok(dog);
    }
}
}

```

PROGRAM.CS

```

using PetApi.Data;
using Microsoft.EntityFrameworkCore;
using Microsoft.OpenApi.Models;

var builder = WebApplication.CreateBuilder(args);

builder.Services.AddDbContext<AppDbContext>(options =>

options.UseSqlServer(builder.Configuration.GetConnectionString("PetDbConne
ction")));

builder.Services.AddControllers();
builder.Services.AddEndpointsApiExplorer();
builder.Services.AddSwaggerGen(c =>
{

```

```
        c.SwaggerDoc("v1", new OpenApiInfo { Title = "Pet API", Version = "v1"
    });
    });

var app = builder.Build();

if (app.Environment.IsDevelopment())
{
    app.UseSwagger();
    app.UseSwaggerUI(c =>
    {
        c.SwaggerEndpoint("/swagger/v1/swagger.json", "Pet API V1");
    });
}

app.UseAuthorization();
app.MapControllers();

app.Run();
```