

Modern, Buildable Projects

with IBM i Project Explorer and Bob

Edmund Reinhardt

Product Architect - IBM i Application Development

edmund.reinhardt@ca.ibm.com

Sanjula Ganepola

Software Developer

Sanjula.Ganepola@ibm.com



Agenda

- Challenges with Building on IBM I
- Bob (Better Object Builder) for IBM I
- Local Development
- IBM i Project Explorer
- Demo


Challenges with Building on IBM i

General Challenges

- SRC-PF
 - 10 char names
 - Fixed record length
 - Not accessible to open ecosystem, including Git and Make
 - Source of the same type stored in QxxxSRC to avoid name conflicts (member type does not disambiguate)
- Libraries
 - Only 2 level hierarchy to organize, with only short 10 char names
- Source control
 - None (sequence number dates)
 - Home grown
 - Proprietary IBM i systems
 - Cost
 - Smaller market = less investment
- Build system
 - Individual CRTXXXMOD + CRTPGM
 - CL Scripts
 - A couple of vendors have dependency-based build


RDİ Projects – Lessons Learned

- Supports git but ...
- Mapping from i Project to exactly one library was too inflexible
 - Some customers target many libraries from one project (program / data / source)
 - Other customers have huge libraries
- Metadata was very hard to maintain
 - Having a parallel directory hierarchy under .ibmi meant that any time a SRC-PF or member changed names the metadata was lost
- Mapping rigidly to SRC-PF meant inheriting all its limitations
 - Fixed line length
 - Fixed directory hierarchy of basically 1 level with only 10 characters
- Build was very limited
 - No disambiguating of PGM vs MOD
 - No understanding of binding relationships
 - No incremental ability (i.e. only build what had changed)



Existing Bob By S4i


- Open-source project by Jeff Berman (<https://github.com/s4isystems/Bob>)
 - Incremental compile ability based on gmake
 - Some level of ILE binding understanding
 - Not bound to library and SRC-PF structure/naming
 - Member level specific metadata using gmake variable
 - Consideration of target EBCDIC CCSID for compiler
 - Support of old languages whose compilers do not have IFS support yet (DDS, UIM)
 - Retrieval of all EVFEVENT files to enable compiler feedback
- Limitations
 - Uppercase names required
 - Single target library
 - Single directory containing source
 - No metadata on environment prerequisites (i.e. LIBL, ASP, where to find includes, etc.)
 - Install was complex – not yum-enabled
 - No 1 to 1 mapping of file extensions to compile (i.e. are we targeting MOD or PGM)



Bob (Better Object Builder) for IBM i

- Enhancements
 - Project definition
 - Know how to build yourself
 - Know where to resolve includes
 - Know how to set up environment
 - Still flexible so that what is stored in Git does not have to be modified for each developer or deployment scenario
 - No limit on number of directories and their nesting
 - No limit on directory naming
 - No limit on number of object libraries
 - Unambiguous mapping from file name to compile type
- Usability
 - PASE command line
 - Windows/Mac command line with rsync/scp to do file transfer
 - Any VS Code extension for IBM i development (ie. Code for IBM I and Project Explorer)
 - RDi


Project Structure (Source Code)




MYLIB

- QRPGLSRC
 - PROGRAMA.RPGLE
 - PROGRAMB.RPGLE
 - PROGRAMC.RPGLE
- QSQLSRC
 - CUSTOMERS.SQL
 - INVENTORY.SQL
- QCLLESRC
 - STARTJOB.CLLE
- QCMDSRC
 - STARTJOB.CMD


Project Structure (Metadata)



Project Structure (Build/Compile Output)



Project Structure (Rules.mk)



Build and Compile Process



Command	Description
makei init	Create iproj.json
makei cvtsrcpf	Convert QSYS members to Unicode IFS stream files
makei build	Build the entire project
makei b -t <object>	Build target object
makei b -d <directory>	Build all objects in the specified directory (based on Rules.mk)
makei compile -f <stream file>	Compile target object of specified stream file
makei compile -files file1: file2: ...	Compile target objects of all specified stream files

- A

Local Development

Different (But Similar) File System

MYLIB

- QRPGLSRC
 - PROGRAMA.RPGLE
 - PROGRAMB.RPGLE
 - PROGRAMC.RPGLE
- QSQLSRC
 - CUSTOMERS.SQL
 - INVENTORY.SQL
- QCLLESRC
 - STARTJOB.CLLE
- QCMDSRC
 - STARTJOB.CMD

/COPY and /INCLUDE

Distributed Development



Version Control with Git

Development with Git



IBM i Project Explorer

Overview

The ultimate tool for local development on IBM i!

Set variables


Manage library list

Modify include paths

Build and Compile

Local source vs. IFS source


View job logs



Installation


1

Download
Visual Studio Code




2

Download
IBM i Project Explorer





3

Download
Code for IBM i



Create a New Project

- Create and open a folder for your project
- Create an `iproj.json`
- Set the project description
- Connect to an IBM i (using Code for IBM i)



Migrate Source from QSYS

CVTSRCPF
from BOB




QSYS members in
source physical files
↓
Properly encoded,
terminated, and named
source files in an IFS
directory

↓
Download to local
project



↓
Rename extensions
↓
Convert includes/copy
directives to Unix style
paths

Source Orbit



Source and Deployment


- Set deploy location
 - Where source gets uploaded to
 - Typically set one
 - Each developer gets a unique location
 - Each repository gets a unique location
- Set deployment method
 - Compare (typically the safest)
 - Changes
 - Working Changes
 - Staged Changes
 - All
- Deploy project
 - Moves files to deploy location based on deployment method



Work with Variables


- View and set variables (for libraries, include paths, or build/compile commands)
- Browse for libraries and assign values to variables
- Configure hardcoded values as variables

Do not push .env file to Git!




Manage the Library List

- Add to beginning/end of library list (preUsrlibl and postUsrlibl) and set current library (curlib in iproj.json)
- Reorder library list
- Browse objects and members
- Manage libraries, objects, and members




Browse Object Libraries

- Another place to manage libraries in iproj.json (curlib, objlib, preUsrLibl, postUsrLibl)
- Manage libraries, objects, and members



Manage Include Paths



- Add, remove, and reorder include paths
- Visualize if includes resolve locally or to remote IFS



Build and Compile


- 1 **Deploy**
↓
- 2 **Run build or compile command**
↓
- 3 **Download logs and event files**

- Building
 - Set build command
 - Run Build
- Compiling
 - Set compile command
 - Run compile
 - On active editor
 - On file or directory in File Explorer
 - On file or directory in Source




Run Actions

Run Code for IBM i's custom workspace actions to have more control of the command which is executed




View Diagnostics

- Evfevent file diagnostics are dumped in .evfevent directory after a build or compile
- Visualize diagnostics in the Problems view
- Diagnostics are also rendered inline in the source file




View Job Logs


- Job log and spool files are dumped in .logs directory after a build or compile
- Job log view is used to visualize and manage these logs
- Track up to 10 of the previous logs in memory
- Organized by the ILE objects being built
- Filter by failed objects or severity



Integration



ARCAD-Elias



What can you integrate with IBM i Project Explorer's API?

Demo

