

Assignment 2: Bash Shell Basics

Name: Alagappan

Date: 30-05-2023

Regs_No: 20BCE7211

Campus: VIT-AP

Task 1: File and Directory Manipulation

1. Create a directory called "my_directory".

```
(azhagu@kali) - [~/Documents]
$ mkdir my_directory

(azhagu@kali) - [~/Documents]
$
```

This command creates a new directory named "my_directory" in the current working directory.

2. Navigate into the "my_directory".

```
(azhagu@kali) - [~/Documents]
$ cd my_directory

(azhagu@kali) - [~/Documents/my_directory]
$
```

This command changes the current working directory to "my_directory".

3. Create an empty file called "my_file.txt".

```
(azhagu@kali) - [~/Documents/my_directory]
$ touch my_file.txt

(azhagu@kali) - [~/Documents/my_directory]
$
```

The touch command is used to create an empty file. In this case, it creates a file named "my_file.txt" in the current directory.

4. List all the files and directories in the current directory.

```
(azhagu@kali) - [~/Documents/my_directory]
$ ls
my_file.txt

(azhagu@kali) - [~/Documents/my_directory]
$
```

The ls command lists the files and directories in the current directory.

5. Rename "my_file.txt" to "new_file.txt".

```
(azhagu@kali) - [~/Documents/my_directory]
$ mv my_file.txt new_file.txt

(azhagu@kali) - [~/Documents/my_directory]
$ ls
new_file.txt

(azhagu@kali) - [~/Documents/my_directory]
$
```

The mv command is used to move or rename files. In this case, it renames the file "my_file.txt" to "new_file.txt"

6. Display the content of "new_file.txt" using a pager tool of your choice

```
(azhagu@kali) - [~/Documents/my_directory]
$ less new_file.txt

File Actions Edit View Help
new_file.txt (END)
```

The less command is a pager tool that allows you to view the content of a file page by page. In this case, it displays the content of the file "new_file.txt". You can scroll through the content using the arrow keys and press "q" to exit.

7. Append the text "Hello, World!" to "new_file.txt".

```
(azhagu@kali) - [~/Documents/my_directory]
$ echo "Hello, World!" >> new_file.txt
dquote>
```

The echo command is used to print text. The >> operator is used to append the output to a file. In this case, it appends the text "Hello, World!" to the file "new_file.txt"

8. Create a new directory called "backup" within "my_directory".

```
(azhagu@kali) - [~/Documents/my_directory]
$ mkdir backup

(azhagu@kali) - [~/Documents/my_directory]
$
```

This command creates a new directory named "backup" within the "my_directory" directory.

9. Move "new_file.txt" to the "backup" directory.

```
(azhagu@kali) - [~/Documents/my_directory]
$ mv new_file.txt backup/
```

This command moves the file "new_file.txt" to the "backup" directory.

10. Verify that "new_file.txt" is now located in the "backup" directory.

```
(azhagu@kali)~[~/Documents/my_directory]
$ ls backup/
new_file.txt
```

This command lists the contents of the "backup" directory to verify that "new_file.txt" is present there.

11. Delete the "backup" directory and all its contents.

```
(azhagu@kali)~[~/Documents/my_directory]
$ rm -r backup/

(azhagu@kali)~[~/Documents/my_directory]
$ ls

(azhagu@kali)~[~/Documents/my_directory]
$
```

The rm command is used to remove files and directories. The -r option is used to recursively remove directories and their contents. In this case, it deletes the "backup" directory and all its contents.

Task 2: Permissions and Scripting

1. Create a new file called "my_script.sh".

```
(azhagu@kali)~[~/Documents/my_directory]
$ touch my_script.sh

(azhagu@kali)~[~/Documents/my_directory]
$
```

This command creates a new file named "my_script.sh" in the current directory.


2. Edit "my_script.sh" using a text editor of your choice and add the following lines:
bash

```
#!/bin/bash
echo "Welcome to my script!"
echo "Today's date is $(date)."
Save and exit the file.
```

```
(azhagu@kali)~[~/Documents/my_directory]
$ nano my_script.sh
```

This command opens the "my_script.sh" file in the nano text editor, allowing you to edit the file

```
File Actions Edit View Help
GNU nano 7.2
echo "welcome to my script"
echo "Today's date is $(date)."
^O
```



These lines are added to the "my_script.sh" file. The first line specifies the interpreter (#!/bin/bash), and the subsequent lines use the echo command to print text.

3. Make "my_script.sh" executable

```
(azhagu@kali) - [~/Documents/my_directory]
$ chmod +x my_script.sh

(azhagu@kali) - [~/Documents/my_directory]
$
```

The chmod command is used to change the permissions of a file. The +x option makes the file executable, allowing it to be run as a script.

4. Run "my_script.sh" and verify that the output matches the expected result.

```
(azhagu@kali) - [~/Documents/my_directory]
$ ./my_script.sh
welcome to my script
./my_script.sh: 2: data: not found
Today's date is .

(azhagu@kali) - [~/Documents/my_directory]
$
```

This command executes the "my_script.sh" file, and the output should display the text specified in the script, including the current date and time

Task 3: Command Execution and Pipelines

1. List all the processes running on your system using the "ps" command.

```
(azhagu@kali)~[~/Documents/my_directory]
$ ps aux
USER      PID %CPU %MEM    VSZ   RSS TTY      STAT START   TIME COMMAND
root         1  0.0  0.2 102120 12136 ?        Ss   11:28   0:01 /sbin/init splash
root         2  0.0  0.0      0     0 ?        S    11:28   0:00 [kthreadd]
root         3  0.0  0.0      0     0 ?        I<   11:28   0:00 [rcu_gp]
root         4  0.0  0.0      0     0 ?        I<   11:28   0:00 [rcu_par_gp]
root         5  0.0  0.0      0     0 ?        I<   11:28   0:00 [slub_flushwq]
root         6  0.0  0.0      0     0 ?        I<   11:28   0:00 [netns]
root        10  0.0  0.0      0     0 ?        I<   11:28   0:00 [mm_percpu_wq]
root        11  0.0  0.0      0     0 ?        I    11:28   0:00 [rcu_tasks_kthread]
root        12  0.0  0.0      0     0 ?        I    11:28   0:00 [rcu_tasks_rude_kthread]
root        13  0.0  0.0      0     0 ?        I    11:28   0:00 [rcu_tasks_trace_kthread]
root        14  0.0  0.0      0     0 ?        S    11:28   0:00 [ksoftirqd/0]
root        15  0.0  0.0      0     0 ?        I    11:28   0:03 [rcu_preempt]
root        16  0.0  0.0      0     0 ?        S    11:28   0:00 [migration/0]
root        18  0.0  0.0      0     0 ?        S    11:28   0:00 [cpuhp/0]
root        19  0.0  0.0      0     0 ?        S    11:28   0:00 [cpuhp/1]
root        20  0.0  0.0      0     0 ?        S    11:28   0:00 [migration/1]
root        21  0.0  0.0      0     0 ?        S    11:28   0:00 [ksoftirqd/1]
root        23  0.0  0.0      0     0 ?        I<   11:28   0:00 [kworker/1:0H-events_highpri]
root        26  0.0  0.0      0     0 ?        S    11:28   0:00 [kdevtmpfs]
root        27  0.0  0.0      0     0 ?        I<   11:28   0:00 [inet_frag_wq]
root        28  0.0  0.0      0     0 ?        S    11:28   0:00 [kauditd]
root        30  0.0  0.0      0     0 ?        S    11:28   0:00 [khungtaskd]
root        31  0.0  0.0      0     0 ?        S    11:28   0:00 [oom_reaper]
root        33  0.0  0.0      0     0 ?        I<   11:28   0:00 [writeback]
root        34  0.0  0.0      0     0 ?        S    11:28   0:00 [kcompactd0]
root        35  0.0  0.0      0     0 ?        SN   11:28   0:00 [ksmd]
root        36  0.0  0.0      0     0 ?        SN   11:28   0:00 [khugepaged]
root        37  0.0  0.0      0     0 ?        I<   11:28   0:00 [kintegrityd]
root        38  0.0  0.0      0     0 ?        I<   11:28   0:00 [kblockd]
root        39  0.0  0.0      0     0 ?        I<   11:28   0:00 [blkcg_punt_bio]
root        40  0.0  0.0      0     0 ?        I<   11:28   0:00 [tpm_dev_wq]
root        41  0.0  0.0      0     0 ?        I<   11:28   0:00 [edac-poller]
root        42  0.0  0.0      0     0 ?        I<   11:28   0:00 [devfreq_wq]
root        44  0.0  0.0      0     0 ?        I<   11:28   0:00 [kworker/0:1H-kblockd]
root        45  0.0  0.0      0     0 ?        S    11:28   0:00 [kswapd0]
root        51  0.0  0.0      0     0 ?        I<   11:28   0:00 [kthrotld]
root        53  0.0  0.0      0     0 ?        S    11:28   0:00 [irq/24-pciehp]
root        54  0.0  0.0      0     0 ?        S    11:28   0:00 [irq/25-pciehp]
root        55  0.0  0.0      0     0 ?        S    11:28   0:00 [irq/26-pciehp]
root        56  0.0  0.0      0     0 ?        S    11:28   0:00 [irq/27-pciehp]
root        57  0.0  0.0      0     0 ?        S    11:28   0:00 [irq/28-pciehp]
root        58  0.0  0.0      0     0 ?        S    11:28   0:00 [irq/29-pciehp]
root        59  0.0  0.0      0     0 ?        S    11:28   0:00 [irq/30-pciehp]
```

The ps command is used to display information about active processes. The aux options provide a detailed list of all processes running on the system.

2. Use the "grep" command to filter the processes list and display only the processes with "bash" in their name.

```
(azhagu@kali)~[~/Documents/my_directory]
$ ps aux | grep bash
azhagu    56400  0.0  0.0  6332  2060 pts/0    S+   13:18   0:00 grep --color=auto bash

(azhagu@kali)~[~/Documents/my_directory]
$
```

The grep command is used to search for specific patterns in the input. In this case, it filters the output of the ps aux command to display only the processes that contain the word "bash"

3. Use the "wc" command to count the number of lines in the filtered output.

```
(azhagu@kali)~[/Documents/my_directory]
$ ps aux | grep bash | wc -l
1

(azhagu@kali)~[/Documents/my_directory]
$
```

The `wc` command is used to count the number of lines, words, and characters in the input. The `-l` option tells `wc` to count only the lines. In this case, it counts the number of lines in the filtered output of the previous command, giving the total number of processes with "bash" in their name.