Supabase setup for beginners

Creating and connecting your own Supabase account for the TAK TV India website

Version 1.0 · 30 October 2026 · For the owner and office administrator (no technical knowledge needed)

Checked against Supabase's public documentation and pricing page on 30 October 2026. The writer could not sign in to a real Supabase dashboard, so the button names come from Supabase's own documentation, not from a live screen. Supabase may rename buttons — look for the words given here, or something close to them.

How to use this guide: do the chapters in order. Tick each box as you go. Never type a password or secret key into a chat, an e-mail or a document.

> **Note:** Boxes marked "Check this — not verified" are steps that could not be confirmed. Look carefully at the screen, and ask your developer or Lovable support if the screen looks different.

Contents

1. What Supabase is, and which option to choose
2. Create the Supabase account
3. Create the project
4. Find the keys the website needs
5. Create the database
6. Storage (photos and citizen evidence)
7. Login (authentication) settings and the first admin
8. Secrets and scheduled jobs
9. Backups and safety
10. Costs and what to watch
11. Troubleshooting
12. Handover checklist (sign off)
Glossary
Sources checked (30 October 2026)

1. What Supabase is, and which option to choose

1.1 Supabase in two sentences

Supabase is the “engine room” behind the website: it keeps the database (stories, videos, citizen issues, the team list), the login system for the newsroom, the private file storage (photos and citizen evidence) and the scheduled jobs. Without it, the website can show nothing and nobody can sign in.

1.2 What Lovable Cloud is

The website was built with Lovable. Lovable has its own service called **Lovable Cloud**. Lovable Cloud quietly creates a Supabase project for you and runs it for you. You do not need a Supabase account for it.

The difference is **who is in control**:

Question	(a) Lovable Cloud	(b) Your own Supabase project
Who owns the account?	Lovable runs it for you	Your organisation
Can you open the Supabase dashboard?	No	Yes
Who pays for it?	Through Lovable	Your organisation pays Supabase directly
Can you download backups yourself?	Not from a Supabase dashboard	Yes, on the paid plan
Can you see the secret keys?	No	Yes (keep them safe)
Can you add other tools (reports, automation)?	Limited	Yes
Effort to set up	None (already done)	About half a day, following this guide

Facts from Supabase’s own help page about Lovable Cloud (checked 30 October 2026):

- Lovable Cloud projects do not appear in your Supabase dashboard and are not owned by your Supabase account.
- There is **no automatic way** to move a project from Lovable Cloud to your own Supabase account. It is a manual copy.
- Once Lovable Cloud is switched on for a Lovable project, it **cannot be switched off or swapped** for your own Supabase connection in that same Lovable project.
- With Lovable Cloud you cannot use the Supabase SQL editor, and the secret keys are not available to you.

1.3 Our recommendation

Recommended: option (b), your own Supabase project, set up before the website is launched.

Why:

- A news organisation must control its own data, backups and access. With (b) you can download a backup at any time and decide who has access.
- Today the site has no real stories or citizen issues yet. Moving now is quick and safe. Moving later means copying real data and citizen evidence, which is harder.

- Citizen evidence (photos and videos up to 150 MB) needs storage settings that you can only see and change in your own Supabase project.

When (a) is fine: if you only want a quick trial, or you do not want to manage any technical account. You can stay on Lovable Cloud and skip this guide, but you will depend on Lovable for backups and keys.

1.4 How to move from (a) to (b) safely

Because a Lovable Cloud project cannot be switched over, the move means **a new Lovable project connected to your own Supabase project**, carrying the same code.

1. Do chapters 2 to 7 of this guide first: create the account, the project, the database, storage and the first admin.
2. In Lovable, create a new project **connected to your own Supabase project** (do not switch on Lovable Cloud in it), and bring the TAK TV code into it (for example through the GitHub connection). Your developer or Lovable support can do this step.
3. Add the website settings (chapter 4.3) and the server secrets (chapter 8).
4. Test everything on the new site with the checklist in chapter 12.
5. Only then point your web address (domain) to the new site.
6. Keep the old Lovable Cloud project unchanged for at least 30 days, then delete it.

Check this — not verified: Lovable’s menus for creating a project with your own Supabase connection could not be checked for this guide. Lovable’s documentation says you should verify the new setup at the destination before you retire the original. If anything is unclear, ask Lovable support before deleting anything.

Warning: If real data already exists on Lovable Cloud when you move (stories, citizen issues, team accounts), it does not move by itself. The database, uploaded files and login accounts are separate things. Ask your developer or Lovable support to export them. Team members can simply be invited again on the new site.

2. Create the Supabase account

2.1 Who should own it

- Use an **e-mail address the organisation controls**, for example tech@yourdomain or admin@yourdomain. Do **not** use one person's private Gmail. If that person leaves, you could lose the account.
- Add a **second administrator** (a trusted senior person) as a back-up owner.

2.2 Steps

1. Open **supabase.com** in your browser and click **Start your project** (or **Sign up**).
2. Choose "Sign up with e-mail" and enter the organisation e-mail and a long password. Store the password in a password manager (Bitwarden, 1Password or similar), never on paper on a desk or in a chat.
3. Open the confirmation e-mail Supabase sends you and click the link.
4. Supabase asks you to create an **organisation**. Name it "TAK TV India".

> **What you will see:** A white page with the Supabase logo, a box for your e-mail and password, and a green button to continue.

2.3 Turn on two-step verification (very important)

Two-step verification (also called MFA or 2FA) means that signing in needs your password **and** a 6-digit code from an app on your phone. A stolen password alone is then not enough.

1. Install an authenticator app on your phone (Google Authenticator, Microsoft Authenticator or similar).
2. In Supabase, open your **Account** settings (click your picture or initials in a corner) and go to **Security**.
3. Choose to add multi-factor authentication. Scan the square code with the authenticator app. Type the 6-digit code to confirm.
4. Supabase signs out your other sessions. Sign in again using the code.

> **Tip:** On the paid (Pro) plan, an organisation owner can require every member to use two-step verification. Turn this on after upgrading.

2.4 Add the second administrator

1. Open the organisation settings and find **Team** (or Members).
2. Invite the second administrator's organisation e-mail with the **Owner** or **Administrator** role.
3. Ask them to turn on two-step verification too.

- ☐ Account created with an organisation e-mail
- ☐ Two-step verification turned on (owner)
- ☐ Second administrator invited and using two-step verification

3. Create the project

3.1 Steps

1. In the dashboard, click **New project**.
2. **Organisation**: TAK TV India.
3. **Project name**: taktv-india (any clear name is fine).
4. **Database password**: click the button that generates a strong password, then copy it into your password manager straight away. You will rarely need it, but if you lose it you must reset it.
5. **Region**: choose **South Asia (Mumbai)**. It is closest to your readers and keeps data in India. Its code is `ap-south-1`.
6. Choose the plan (see 3.2) and click **Create new project**. Wait a few minutes until the project is ready.

> **What you will see:** A form with boxes for Name, Database Password (with a “Generate a password” button) and a Region list. Mumbai appears as “South Asia (Mumbai)”.

> **Note:** Supabase says choosing a region controls where data is stored. It is not by itself proof of meeting any law; ask your lawyer if you need data-protection advice.

3.2 Free plan or paid plan?

Figures copied from supabase.com/pricing on 30 October 2026. Prices and limits change: **always check the pricing page before deciding.**

Item	Free plan	Pro plan (from US $25 per month)
Database size	500 MB	8 GB per project included
File storage	1 GB	100 GB included, then $0.0213 per GB
Data sent to visitors (egress)	5 GB	250 GB included, then $0.09 per GB
Largest single upload	50 MB	Up to 500 GB
Sign-ins per month (users)	50,000	Larger allowance (see pricing page)
Pausing	Paused after 1 week of low activity	Not paused for inactivity
Backups	Not included; cannot be downloaded	Daily backups kept for 7 days
Spending limit	—	“Spend cap” is on by default

What this means in plain words:

- **Free will not work for this website.** Citizens may upload videos up to 150 MB, but Free allows only 50 MB per file. Free also has no backups and may pause the site after a quiet week.
- **Choose Pro before launch.** It gives daily backups, enough storage for evidence videos, and no pausing.

- Keep the **spend cap on** at first. If storage grows past the included amount, Supabase will warn you instead of charging more. Review this every month (chapter 10).

> **Tip:** Point-in-time recovery (restoring to any minute) costs extra — the pricing page lists it from $100 per month for 7 days. You do not need it at launch.

- ☐ Project created in South Asia (Mumbai)
- ☐ Database password saved in the password manager
- ☐ Plan chosen (Pro recommended before launch)

4. Find the keys the website needs

4.1 What the keys are

A key is like a long password that lets the website talk to Supabase. There are three things you will copy:

Name in Supabase	Looks like	Is it secret?	Where it goes
Project URL	https://abcd1234.supabase.co	Not secret	Website settings
Publishable key	starts with sb_publishable_	Not secret (safe in the browser)	Website settings
Secret key	starts with sb_secret_	**SECRET — never share**	Server secrets only

Older Supabase projects show “anon” (= publishable) and “service_role” (= secret) keys instead. Supabase says these older keys are being retired by the end of 2026, so use the new publishable and secret keys.

4.2 Where to find them

1. Open your project.
2. Go to **Settings → API Keys**. (The **Connect** button at the top of the project also shows the URL and the publishable key.)
3. Copy the Project URL and the publishable key.
4. Create or reveal a **secret key**. Copy it straight into your password manager.

> **Warning:** The secret key can read and change everything, ignoring all safety rules. Never paste it into a chat, an e-mail, a document, a website page or the code. Only the server settings may hold it.

4.3 Where each value goes (names only)

In Lovable (project settings → secrets / environment) or in your hosting service’s settings, add:

Setting name	Value to paste
VITE_SUPABASE_URL	Project URL
VITE_SUPABASE_PUBLISHABLE_KEY	Publishable key
VITE_SUPABASE_PROJECT_ID	The project reference (the letters before .supabase.co)
SUPABASE_URL	Project URL
SUPABASE_PUBLISHABLE_KEY	Publishable key
SUPABASE_SERVICE_ROLE_KEY	**Secret key** (server only)

> **Check this — not verified:** When a Lovable project is connected to your own Supabase project, Lovable may fill some of these in for you. Check that all six exist. The website’s server code reads the secret key from the setting called SUPABASE_SERVICE_ROLE_KEY, so the secret key must be stored under that name.

☐ Project URL and publishable key copied into the website settings

☐ Secret key stored only in the password manager and the server secret SUPABASE_SERVICE_ROLE_KEY

5. Create the database

The website's database is described in ten files, called **migrations**, in the project folder `drizzle/migrations`. A migration is a set of instructions that builds or changes the database. They must be run **once each, in number order**: 0000, 0001 … 0009.

5.1 Using the SQL Editor (easiest)

1. Ask your developer for the files `0000_newsroom_schema.sql` to `0009_news_media_bucket.sql` (they are in the project code).
2. In Supabase open **SQL Editor** and click **New query**.
3. Open file 0000 in a text editor (Notepad is fine), select all, copy, and paste into the SQL Editor.
4. Click **Run**. Wait for "Success".
5. Repeat for 0001, 0002 and so on up to 0009. Never skip a file and never change the order.

> **Warning:** Before running file 0000, do chapter 7.1 (turn off public sign-ups). The very first account created after file 0001 automatically becomes the Admin. If sign-ups are open, a stranger could create that first account.

> **Tip:** If one file shows an error, stop. Copy the error message and send it to your developer. Do not run the next file.

5.2 Using the command line (for a developer)

A developer can run the same files in order with the Supabase command-line tool or `psql` connected to the database. The result is the same.

5.3 Check that it worked

In **Table Editor**, open each table below and check the number of rows:

Table	What you should see
categories	30 rows (Agriculture & Farmers, Education, Health …)
sources	60 rows (the trusted source library)
planner_items	45 rows (the 45-day content plan, topics only)
pages	6 rows (About, Contact, Privacy, Terms, Editorial policy, Corrections)
settings	exactly 1 row
articles, videos, queries	0 rows (empty until you add content)

In **Storage** you should see two buckets: `news-media` and `citizen-evidence`. Both must be **private** (chapter 6).

- ☐ Files 0000–0009 run in order without errors
- ☐ Row counts match the table above
- ☐ Two private buckets exist

6. Storage (photos and citizen evidence)

6.1 Private and public in plain words

- **Public** bucket: anyone with the link can open the file forever.
- **Private** bucket: nobody can open a file unless the website gives them a short-lived permission.

This website uses **only private buckets**:

- `news-media` — photos used in stories and posts. The website shows a photo only while a published story uses it.
- `citizen-evidence` — photos, videos and documents sent by citizens. Only Admins, the Editor-in-Chief and Moderators can open them, through links that expire after 15 minutes.

6.2 Settings to check

1. Open **Storage**. Click each bucket and check that it is **not** marked Public.
2. Open **Storage → Settings** and set **Global file size limit** to at least **150 MB** (citizen videos can be up to 150 MB). On the Free plan this cannot go above 50 MB — another reason to choose Pro.
3. The migrations already set the bucket limits: `citizen-evidence` 150 MB (photos, MP4/MOV videos, PDF and Word files only); `news-media` 12 MB (JPG, PNG, WebP only). A bucket's limit can never be bigger than the global limit.

> **Warning:** Never make `citizen-evidence` public. It holds evidence and may show people's faces, homes and documents.

- ☐ Both buckets private
- ☐ Global file size limit 150 MB or more

7. Login (authentication) settings and the first admin

7.1 Turn off public sign-ups (do this first)

Only people you invite should be able to have a newsroom account.

1. Open **Authentication → Sign In / Providers**.
2. Switch **off** “Allow new users to sign up”. Supabase explains: when this is off, only existing users can sign in.
3. Save.

7.2 Website address and redirect links

1. Open **Authentication → URL Configuration**.
2. **Site URL**: your real address, for example https://www.yourdomain.in
3. **Redirect URLs**: add https://www.yourdomain.in/reset-password and https://www.yourdomain.in/auth (and the Lovable preview address if you use one).

> **Check this — not verified:** The exact menu name “URL Configuration” could not be confirmed on a live screen; look for “Site URL” under Authentication.

7.3 E-mails (invitations and password resets)

- Supabase’s built-in e-mail sender is for testing only. Supabase’s production checklist lists a very low default limit (2 e-mails per hour).
- Before launch, connect your own e-mail sender: **Authentication → E-mails → SMTP settings** (or similar). An e-mail service such as Resend gives you SMTP details; use a sender like newsroom@yourdomain.in.
- Under the e-mail **templates**, check the “Invite user” and “Reset password” messages. Keep them short and add your organisation name.

7.4 Create the first admin safely

1. Make sure sign-ups are OFF (7.1) and the migrations are done (chapter 5).
2. Open **Authentication → Users → Add user → Create new user**.
3. Enter the owner’s organisation e-mail and a strong password (from the password manager). Tick “auto confirm” if offered.
4. Because no newsroom roles exist yet, this first user automatically becomes **Admin**. No password is stored in the website code.
5. Open the website at /admin and sign in. Go to **Account** and change the password if you wish.

7.5 Adding, changing and removing team members

Do this inside the website, not in Supabase:

- **Add**: Newsroom → **Team** → Invite member → name, e-mail, role → Send invitation. The person receives an e-mail and sets their own password.
- **Change role**: Team → choose a new role in the list next to the person.
- **Remove**: Team → the bin icon next to the person. They can no longer open the newsroom.
- The website will not let you remove the last Admin, or change your own role.

☐ Public sign-ups OFF

☐ Site URL and redirect links set

- ☐ Own e-mail sender (SMTP) connected and templates checked
- ☐ First admin created and able to sign in

8. Secrets and scheduled jobs

8.1 Server secrets

Add these in Lovable's secrets (or your hosting settings). They are never put in the code or the browser.

Secret name	What it is for	Where to get it	Needed?
LOVABLE_CRON_SECRET	Password that the scheduled jobs must show	Make a long random password in your password manager (Lovable may create it for you)	Yes, for jobs
TURNSTILE_SITE_KEY	"I am human" check on the Raise Issue form (public part)	Cloudflare dashboard → Turnstile → add a site	Strongly recommended
TURNSTILE_SECRET_KEY	Secret part of the same check	Same Cloudflare page	Strongly recommended
RESEND_API_KEY	Sends "new citizen issue" e-mails to moderators	Resend dashboard → API keys	Optional
NOTIFY_FROM	Sender address for those e-mails, e.g. alerts@yourdomain.in	A domain you verified in Resend	With RESEND_API_KEY
NOTIFY_EMAILS	Extra addresses to alert (comma-separated)	—	Optional
YOUTUBE_API_KEY	Fills in video description, length and date automatically	Google Cloud console → YouTube Data API v3 → credentials	Optional

> **Tip:** Without YOUTUBE_API_KEY the website still reads the title and channel of a pasted YouTube link. The team then types the description.

8.2 Scheduled jobs

The website has three jobs. Each one is a web address that must be called with the secret.

Job	Address (POST)	How often
Import new YouTube uploads as drafts	/api/cron/youtube-import	Every hour
E-mail moderators about new issues (catch-up)	/api/notify-moderators	Every hour
Check that live videos still play on YouTube	/api/cron/youtube-health	Once a week

Ways to schedule them:

- **In Lovable**: ask Lovable to "schedule an hourly POST to /api/cron/youtube-import with the cron secret", and the same for the other two.

- **In Supabase**: open **Integrations → Cron → Jobs → Create job**. Choose the type **HTTP request**, method POST, the full address (for example https://www.yourdomain.in/api/cron/youtube-health), and add a header named Authorization with the value Bearer followed by a space and your LOVABLE_CRON_SECRET. Choose the schedule (every hour, or every Monday at 06:00).

> **Check this — not verified:** The Supabase Cron screen could not be opened for this guide. Supabase's documentation confirms the Jobs page, the "Create job" button and the "HTTP request" job type, which uses the pg_net extension. Turn that extension on if Supabase asks.

> **Warning:** Anyone who sees a job's settings can see the secret in the header. Only administrators should have access to the Supabase project.

- ☐ Secrets added (at least LOVABLE_CRON_SECRET and the two Turnstile keys)
- ☐ Three jobs scheduled

9. Backups and safety

9.1 Backups

- On the **Pro** plan Supabase makes a **daily backup** and keeps it for **7 days**. See them under **Database → Backups**.
- Supabase does not let you download backups on the Free plan.
- Once a month, also keep your **own copy**. Ask your developer to make a database export (for example with `pg_dump`) and store it in the organisation's cloud drive with restricted access. Citizen evidence files are not in the database export; export the `citizen-evidence` bucket separately if your policy requires it.
- **Who may restore**: only the owner or the second administrator, after agreeing with the Editor-in-Chief. Restoring replaces today's data with the older copy.
- **Test a restore** once every three months into a separate test project.

9.2 Review who has access (every month)

1. Supabase → organisation → **Team**: remove anyone who no longer needs access.
2. Website → **Team**: remove staff who have left; check that roles are right.
3. Check that everyone with Supabase access uses two-step verification.

9.3 If a key or password leaks

Signs: you pasted it into a chat or e-mail by mistake, a laptop was lost, a former staff member had it.

1. **Secret key**: in Settings → API Keys, create a new secret key, put it in the website secret SUPABASE_SERVICE_ROLE_KEY, publish the site again, then **delete the old key**. Supabase advises rotating as soon as you have fixed the cause of the leak.
2. **Database password**: Settings → Database → reset the password; save the new one.
3. **Your Supabase login**: change the password; check two-step verification is on.
4. **Other secrets** (Turnstile, Resend, YouTube, cron secret): create a new one in that service, update the website secret, delete the old one.
5. Write down what happened and when (date, which key, who rotated it).

> **Note:** The publishable key is not secret. Its leaking is not a problem, because the database safety rules still apply.

10. Costs and what to watch

Verify every price on the Supabase pricing page — figures below were read on 30 October 2026.

Item	Free	Pro	What to watch
Monthly price	$0	From $25	Exchange rate and taxes
File storage	1 GB	100 GB, then about $0.0213 per GB	**Citizen evidence videos** — the fastest-growing item
Egress (data sent to visitors)	5 GB	250 GB, then about $0.09 per GB	Photos on the public site, evidence opened by moderators
Database	500 MB	8 GB	Grows slowly (text only)
Backups	None	Daily, 7 days	Keep monthly own copies too
Extra compute	—	$10 credit included	Only if the site gets very busy

Monthly routine:

1. Open the **Usage** page of the organisation. Note storage and egress.
2. If storage passes 70% of the included amount, agree a policy with the Editor-in-Chief, for example: delete evidence of closed, non-published issues after 12 months, if your privacy policy allows it.
3. Keep the spend cap on until you understand your normal monthly use.

11. Troubleshooting

Problem	What it means	What to do
Nobody can sign in to /admin	Wrong keys in the website settings, or the project is paused	Check chapter 4.3. On Free, open the Supabase dashboard and click Restore project; upgrade to Pro to stop pauses
“Invalid login” for one person	Wrong password or not invited	Use “Forgot password” on /auth, or invite them again from Team
Invitation e-mail never arrives	Built-in e-mail limit reached or spam folder	Connect your own SMTP sender (7.3); ask them to check spam
Photos on stories do not load	Story is not published, or the news-media bucket is missing	Publish the story; check Storage has news-media (file 0009)
Citizen upload says the file is too large	Storage limit lower than 150 MB	Storage → Settings → Global file size limit ≥ 150 MB (needs Pro)
Citizen upload rejected “not allowed”	File type not accepted	Only JPG, PNG, WebP, HEIC, MP4, MOV, PDF, DOCX are allowed
Website shows “News will appear here soon”	No published stories yet, or wrong database connected	Publish a story; check the Project URL in the settings
Website shows “This page didn’t load”	The settings row is missing or keys are wrong	Run migration 0007 (creates the settings row); check keys
A migration shows an error	A file was skipped, run twice in a wrong state, or edited	Stop. Send the exact error to the developer. Do not continue
“Project paused” message	Free plan inactivity	Restore it from the dashboard; upgrade to Pro
Hindi pages give “not found”	Hindi is switched off	Website → Site Settings → Show Hindi (only after native-speaker review)
Scheduled job does nothing	Wrong address or missing “Bearer” header	Check the job’s address and header; the website answers 401 to a wrong secret

12. Handover checklist (sign off)

Owner: _____ Date: _____ Second administrator: _____

- ☐ Supabase account owned by an organisation e-mail, two-step verification on
- ☐ Second administrator added, two-step verification on
- ☐ Project in South Asia (Mumbai) on the Pro plan, spend cap on
- ☐ Database password and secret key stored in the password manager only
- ☐ Website settings filled (chapter 4.3); secret key only in SUPABASE_SERVICE_ROLE_KEY
- ☐ Migrations 0000–0009 run in order; row counts checked
- ☐ Both buckets private; global upload limit 150 MB or more
- ☐ Public sign-ups off; Site URL and redirect links set; own SMTP sender connected
- ☐ First admin created and signed in
- ☐ Turnstile keys, cron secret and optional e-mail/YouTube keys added
- ☐ Three scheduled jobs created
- ☐ First backup visible under Database → Backups; first own export stored safely
- ☐ Restore tested in a separate project
- ☐ Test citizen issue submitted (with a small photo), seen by a moderator, then deleted
- ☐ Test video published from a YouTube link, then unpublished
- ☐ Old Lovable Cloud project kept for 30 days, then deleted (if you moved)

Glossary

Word	Meaning
Database	Where all the website's text and lists are kept
Migration	A numbered file of instructions that builds or changes the database
Bucket	A folder for files in Supabase Storage
Private / public	Private = only with permission; public = anyone with the link
Key	A long password that lets the website talk to Supabase
Publishable key	The key that is safe in the browser
Secret key	The powerful key that must stay on the server
Secret (setting)	A private value stored in the hosting settings, never in the code
Two-step verification (MFA, 2FA)	Signing in with a password plus a code from your phone
Region	The city where the data centre is (choose Mumbai)
Egress	Data sent out from Supabase to visitors
Backup / restore	A saved copy / putting a saved copy back
SMTP	The standard way to send e-mails through an e-mail service
Cron job / scheduled job	A task that runs automatically at set times
CAPTCHA (Turnstile)	The "I am human" check on public forms
Lovable Cloud	Lovable's service that runs a Supabase project for you

Sources checked (30 October 2026)

- Supabase pricing: supabase.com/pricing
- Lovable Cloud and Supabase: supabase.com/docs/guides/troubleshooting/cant-access-supabase-project-lovable-cloud
- API keys: supabase.com/docs/guides/getting-started/api-keys
- Sign-up setting: supabase.com/docs/guides/auth/general-configuration
- File size limits: supabase.com/docs/guides/storage/uploads/file-limits
- Regions: supabase.com/docs/guides/platform/regions
- Two-step verification: supabase.com/docs/guides/platform/multi-factor-authentication
- Production checklist: supabase.com/docs/guides/deployment/going-into-prod
- Cron: supabase.com/docs/guides/cron/quickstart
- Lovable self-hosting: docs.lovable.dev/tips-tricks/self-hosting