

PHASE 4 – onChange CLIENT SCRIPT

1. Client Script: Auto Set Urgency for High Impact

1.1 Objective

The objective of this Client Script is to automatically set the **Urgency** field to **High** whenever the Incident **Impact** is changed to 1 – High.

An information message is also displayed to notify the user that the Urgency value has been automatically updated.

2. Client Script Configuration

Configuration	Value
Client Script Name	Auto set urgency for high impact
Table	Incident
Type	onChange
Field Name	Impact
Active	True

3. Script

```
function onChange(control, oldValue, newValue, isLoading) {  
  
    if (isLoading || newValue == '') {  
        return;  
    }  
}
```

```

    if (newValue == '1') {
        g_form.setValue('urgency', '1');
        g_form.addInfoMessage(
            'Urgency set to High for High impact incident.'
        );
    }
}

```

4. Expected Result

When the **Impact** field is changed to 1 – High:

- The **Urgency** field is automatically set to 1 – High.
- An information message is displayed to the user.
- The user is notified that the Urgency value has been automatically updated.

5. Test Scenario

Test Case	Action	Expected Result
TC01	Change Impact to High	Urgency is automatically set to High
TC02	Change Impact to another value	Script does not automatically set Urgency
TC03	Open an existing Incident	Script does not execute during form loading
TC04	Change Impact to High	Information message is displayed

6. Final Outcome

The **onChange Client Script** automates the Urgency value based on Impact and provides immediate feedback to the user, reducing manual data entry and improving consistency.

PHASE 5 – onSubmit CLIENT SCRIPT

1. Client Script: Prevent Save if Assigned To Missing

1.1 Objective

The objective of this Client Script is to prevent an Incident from being saved when the Incident has **High Impact** but the **Assigned To** field is empty.

This validation ensures that high-impact Incidents are assigned to an appropriate user before the record is submitted.

2. Client Script Configuration

Configuration	Value
Client Script	Prevent save if Assigned To
Name	missing
Table	Incident
Type	onSubmit
Active	True
Validation	Assigned To

3. Script

```
function onSubmit() {  
  
    if (g_form.getValue('impact') == '1' &&  
        g_form.getValue('assigned_to') == '') {  
  
        g_form.showErrorMessage(  
            'assigned_to',  
            'Assigned To is mandatory for High impact incidents.'  
        );  
    }  
}
```

```
        return false;
    }

    return true;
}
```

4. Expected Result

If:

Impact = 1 – High

and:

Assigned To = Empty

Then:

- The record cannot be saved.
- An error message is displayed against the **Assigned To** field.
- The user is instructed to provide an Assigned To value.

If the Assigned To field contains a valid value, the Incident can be submitted.

5. Test Scenario

Test Case	Impact	Assigned To	Expected Result
TC01	High	Empty	Save is blocked
TC02	High	User selected	Record can be submitted
TC03	Medium/		