


Experiment No. 08

Aim: To understand Docker Architecture and Container Life Cycle, install Docker and execute docker commands to manage images and interact with containers.

Theory: Docker is a containerization technology that allows developers to package their applications and dependencies into lightweight, portable containers. These containers can then be run on any system that supports Docker, making it easier to deploy and manage applications in various environments. Docker Architecture:



The Docker architecture consists of the following components:

Docker Client: This is the primary interface that developers use to interact with Docker. It sends commands to the Docker daemon and displays the output.


Docker Daemon: This is the background process that runs on the host machine and manages Docker objects such as images, containers, networks, and volumes.

Docker Registry: This is a storage and distribution system for Docker images. It allows developers to share and distribute their images with others.

Docker Image: This is a lightweight, standalone, executable package that includes everything needed to run an application, including the application code, runtime, libraries, dependencies, and system tools.

Docker Container: This is a runtime instance of a Docker image. It is isolated from the host system and other containers, providing a secure and predictable environment for the application to run in.

Container LifeCycle:



The lifecycle of a Docker container consists of the following stages:



Create: To create a container, you start by creating an image that includes all the necessary components to run the application. This image is then used to create the container.

Start: Once the container is created, you can start it using the docker start command. This launches the container and runs the application inside it.

Run: Once the container is started, you can interact with the application inside the container. You can run commands, access files, and make changes to the application.


Stop: When you're done using the container, you can stop it using the docker stop command. This stops the application inside the container and shuts down the container.

Remove: Finally, when you no longer need the container, you can remove it using the docker rm command. This removes the container from the system and frees up any resources it was using.

Steps for Installation:


Step 01: Open docker.com

Scroll down, Click on 'Get started for free' tab.



Step 02: Click on Docker Desktop, Download it.





Step 03: After downloading, Open 'Docker Desktop Installer' & start installation.



Docker Desktop 4.6.0

Unpacking files...


```
Unpacking file: resources/docker-desktop.iso
Unpacking file: resources/config-options.json
Unpacking file: resources/componentsVersion.json
Unpacking file: resources/componentsVersion.json
Unpacking file: resources/bin/docker-compose
Unpacking file: resources/gitignore
Unpacking file: InstallerCli.pdb
Unpacking file: InstallerCli.exe.config
Unpacking file: InstallerCli.exe.config
Unpacking file: frontend/vk_swiftshader_icd.json
Unpacking file: frontend/v8_context_snapshot.bin
Unpacking file: frontend/snapshot_blob.bin
Unpacking file: frontend/resources/regedit/vbs/regUni.vbs
Unpacking file: frontend/resources/regedit/vbs/regUni.vbs
```




Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Step 04: After Installation, Restart your device.



Step 05: Accept the terms and conditions, Click on Accept.



The following window should pop up. Click on the link - https://aka.ms/wsl2kernel. (Do not close this window).






Download the WSL2 Linux kernel update package for x64 machines.




After Download is complete, Run the .msipackage.




Click on next.






After, the setup is complete, Click on finish.




Open Powershell as an Administrator.





Run the following Command:

wsl --setdefault-version 2



Now, Click on Restart



Docker should now restart. Click on Start.



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science



The following window should pop up. This means, Installation is now complete.



Output:

Open Command Prompt, run the following commands:

- To check the version of

Docker: docker --version

- To install image of ubuntu docker pull ubuntu

Check downloaded images, docker images



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

```
PS C:\Users\Lenovo> docker images
REPOSITORY TAG IMAGE ID CREATED SIZE
ubuntu latest ff0fea8310f3 4 days ago 72.8MB
PS C:\Users\Lenovo> _
```

- Run ubuntu OS docker run -it ubuntu /bin/bash

```
- PS C:\Users\Lenovo> docker run -it ubuntu /bin/bash
root@f45775828da6:/# _
```

docker ps docker

container Is -a

docker container rm b71e3e6b1118 //copy docker id for remove but first (Use your container ID in the above command) stop your docker

- 1) docker container stop b71e3e6b1118
- 2) docker container rm b71e3e6b1118
- 3) docker ps
- 4) docker //list all docker commands
- 5) docker images
- 6) docker image rm ff0fea8310f3 // copy image id from previous output (Use your image ID in the above command)
- 7) docker run -it ubuntu /bin/bash //check output

```
PS C:\Users\Lenovo> docker ps
CONTAINER ID
                         COMMAND
                                                             STATUS
               IMAGE
                                       CREATED
                                                                                 PORTS
                                                                                           NAMES
                         "/bin/bash"
f45775828da6
               ubuntu
                                       About a minute ago
                                                            Up About a minute
                                                                                            nostalgic_elion
PS C:\Users\Lenovo> docker container ls
CONTAINER ID IMAGE
f45775828da6 ubuntu
                       COMMAND CREATED
"/bin/bash" About a minute ago
                                                             STATUS
                                                                                 PORTS
                                                                                           NAMES
f45775828da6
                                                            Up About a minute
                                                                                            nostalgic_elion
PS C:\Users\Lenovo> docker container rm f45775828da6
Error response from daemon: You cannot remove a running container f45775828da6297e793470cd07835cf764532a3d5eded8e4094ffc
bc0f687858. Stop the container before attempting removal or force remove
PS C:\Users\Lenovo> docker container stop f45775828da6
f45775828da6
PS C:\Users\Lenovo> docker container rm f45775828da6
f45775828da6
PS C:\Users\Lenovo> docker ps
CONTAINER ID IMAGE
                       COMMAND
                                  CREATED STATUS
PS C:\Users\Lenovo> docker images
REPOSITORY TAG
                      IMAGE ID
                                      CREATED
             latest
                       ff@fea831@f3
                                                    72,8MB
ubuntu.
                                      4 days ago
PS C:\Users\Lenovo> docker image rm f45775828da6
Error: No such image: f45775828da6
PS C:\Users\Lenovo> docker image rm ff0fea8310f3
Untagged: ubuntu:latest
Untagged: ubuntu@sha256;bea6d19168bbfd6af8d77c2cc3c572114eb5d113e6f422573c93cb605a0e2ffb
Deleted: sha256:ff0fea8310f3957d9b1e6ba494f3e4b63cb348c76160c6c15578e65995ffaa87
Deleted: sha256:867d0767a47c392f80acb51572851923d6d3e55289828b0cd84a96ba342660c7
PS C:\Users\Lenovo> docker images
                       IMAGE ID CREATED SIZE
REPOSITORY TAG
PS C:\Users\Lenovo> _
```

Conclusion:



Q1. What is the difference between containerization and virtualization?

- Containerization involves packaging an application and its dependencies into a container that can run on any system, without the need for a separate operating system. It provides lightweight isolation and shares the host system's kernel.
- Virtualization, on the other hand, involves creating virtual machines (VMs) that run a separate operating system on top of a hypervisor. Each VM requires its own operating system, resulting in higher resource overhead compared to containers.

Q2. What is Docker Daemon?

The Docker Daemon is a background process that runs on the host machine and manages Docker objects such as images, containers, networks, and volumes. It listens for Docker API requests from the Docker Client and performs the requested actions, such as pulling images, creating containers, and starting/stopping containers.