

HOW TO EXTRACT PL LOGS USING STORED PROCEDURE

21 August 2026 07:02

WHAT WE WILL LEARN IN THIS SESSION

1. WHY PL LOGGING IS REQUIRED
2. CREATE A CENTRLIZED PL LOG TABLE
3. CREATE A REUSABLE LOGIN STORED PROCEDURE
4. CAPTURE PIPELINE_ID ,PL_RUN_ID, MAPPING_ID,PL_NAME
5. CAPTURE SOURCE AND DESTINATION DETAILS
6. CAPTURE COPY ACTIVITY START AND END TIME
7. CAPTURE RECORDS RELATED TO FILES READ AND FILES WRITTEN
8. CAPTURE STATUS - SUCCESS/FAILED
9. CAPTURE ERROR MESSAGE

WHY PL LOGGING IS REQUIRED

DEVELOPEMNT

- WE CAN CHECK MANUALLY RUNNING PIPELINE

PROD ENV

WHAT HAPPENED IF WE NOT MAINTAIN PL LOGS

WE CANNNOT IDENTIFY

1. PL FAILED
2. WHICH SOURCE
3. WHICH MAPPING - TABLE
4. WHEN DID IT FAILED
5. HOW MUCH DATA LOSS
6. WHY DID IT FAILED

WHAT HAPPENED IF WE MAINTAIN PL LOGS CAN IDENTIFY

1. PL EXECUTION
2. MONITOR
3. PL_DURATION
4. PERFORMANCE

EXECUTION INFORMATION

1. PIPELINE RUN_ID
2. PL_NAME
3. MAPPING_ID
4. START_TIME
5. END_TIME
6. STATUS

SOURCE_INFORMATION

1. SOURCE_NAME
2. SOURCE_TYPE

DESTINATION_INFORMATION

1. SINK_DETAILS

DATA_DETAILS

1. RECORDS READ
2. RECORDS WRITTEN
3. FILES READ
4. FILES WRITTEN

FAILURE_INFORMATION

1. ERROR_MESSAGE
2. WHICH ACTIVITY GOT FAILED

CREATE A LOG DETAILS TABLE

```
CREATE TABLE pipeline_logs
(
    pipeline_run_id    VARCHAR(1000),
    pipeline_name      VARCHAR(255),
    pipeline_id        INT,
    mapping_id         INT,
    source_name        VARCHAR(100),
    source_type        VARCHAR(50),
    source_object      VARCHAR(500),
    sink_path          VARCHAR(500),
    load_type          VARCHAR(50),
    copy_start_time    DATETIME2(6),
    copy_end_time      DATETIME2(6),
    copy_Duration      INT,
    status             VARCHAR(50),
    records_read       BIGINT,
    records_written    BIGINT,
    files_read         INT,
    files_written      INT,
    error_message      VARCHAR(2000),
    created_dt         DATETIME2(6)
);
```

How to create a stored procedure

Create procedure sample_data

As

Begin

Select * from cust where country = india

End:

Exec sample_data

Create procedure update_log_tbl

```
@pipeline_run_id    VARCHAR(1000),
@pipeline_name      VARCHAR(255),
@pipeline_id        INT,
@mapping_id         INT,
@source_name        VARCHAR(100),
@source_type        VARCHAR(50),
@source_object      VARCHAR(500),
@sink_path          VARCHAR(500),
@load_type          VARCHAR(50),
@copy_start_time    DATETIME2(6),
@copy_end_time      DATETIME2(6),
@copy_Duration      INT,
@status             VARCHAR(50),
@records_read       BIGINT,
@records_written    BIGINT,
@files_read         INT,
@files_written      INT,
@error_message      VARCHAR(2000),
@created_dt         datetime
```

Create proc proc_name
@id int

As

Begin

Insert into pl_log
Pipeline_id

As

Begin

```
Insert into pipeline_logs (
    pipeline_run_id ,
    pipeline_name ,
    pipeline_id ,
    mapping_id ,
```

end

```

source_name ,
source_type ,
source_object ,
sink_path ,
load_type ,
copy_start_time ,
copy_end_time ,
copy_duration ,
status ,
records_read ,
records_written ,
files_read ,
files_written ,
error_message ,
created_dt )

```

```

VALUES
(
    @pipeline_run_id,
    @pipeline_name,
    @pipeline_id,
    @mapping_id,
    @source_name,
    @source_type,
    @source_object,
    @sink_path,
    @load_type,
    @copy_start_time,
    @copy_end_time,
    @copy_duration,
    @status,
    @records_read,
    @records_written,
    @files_read,
    @files_written,
    @error_message,
    GETDATE()
);

```

```
END;
```