

01

121-244 • WK 18


SUNDAY
2022 MAY

Python

M	T	W	T	F	S	S
30	31				1	05
2	3	4	5	6	7	8
9	10	11	12	13	14	15
16	17	18	19	20	21	22
23	24	25	26	27	28	29

06
Jun
2022

M T
6 7
13 14
20 21
27 28



List

- ① mutable data type
- ② List is a container
- ③ contain diff. types of object and is used to iterate objects.
- ④ List iteration is slower
- ⑤ List consumes more memory
- ⑥ syntax → list = ['a', 'b']

Tuple

- ⑦ immutable data type
- ⑧ Tuple is also similar to list but contain immutable objects.
- ⑨ Tuple processing is faster than list.
- ⑩ Tuple consumes less memory
- ⑪ tuples = ('a', 'b')

What is Decorator & explain with example.
→ Decorator is a funct' that takes another funct' as an argument, add some kind of functionality and then returns another funct'.
→ All of this without altering the source code of the original funct' that you passed in.

Ques:

a) How to delete a file in python

→ import os
os.remove('demofile.txt') {for file}

import os
os.rmdir('my folder') {for folder}

Output

4

5

6

7

Shm

nega

F S S 05
6 7 8 May
13 14 15 2022
20 21 22
27 28 29

06 M T W T F S S
Jun 6 7 8 9 10 11 12
13 14 15 16 17 18 19
20 21 22 23 24 25 26
27 28 29 30

MONDAY
MAY 2022

02
122-243 • WK 19

9 def decorator_func(func):
10 def wrapper_func():
11 print("wrapper_func worked")
12 return func()
13 print("decorator_func worked")
14 return wrapper_func

1 def show():
2 print("show worked")
3 decorator_show = decorator_func(show)
4 decorator_show()

5 Output -

6 decorator_func worked.
7 wrapper_func worked
8 show worked

9 String -: String is a sequence of characters.
10 integer -

11 negative indexing -: inserting start from end is
12 negative index

S S 05
1 May
2 8 2022
3 14
4 15
5 21 22
6 28 29

06 M T W T F S S
Jun 1 2 3 4 5
13 14 15 16 17 18 19
20 21 22 23 24 25 26
27 28 29 30

WEDNESDAY
MAY 2022

04

124-241 • WK 19

on ~~How~~ Python memory managed in python

→ Memory management in python involves a private heap containing all python objects and data structures.

→ Interpreter takes care of python heap and that the programmer has no access to it

→ The allocation of heap space for python objects is done by python memory manager. The core API of python provides some tools for the programmer to code reliable and more robust program.

→ Python also has a built-in garbage collector which recycles all the unused memory. When an object is no longer referenced by the program, the heap space it occupies can be freed. The garbage collector determines objects which no longer referenced by the program frees the occupied memory and make it available to the heap space.

→ The gc module defines functions to enable/disable garbage collector.

→ `gc.enable()` — Enables automatic garbage collector
`gc.disable()` — disable automatic garbage collector

05

125-240 • WK 19

THURSDAY
2022 MAY

Diff
betn
generator and iterator

M	T	W	T	F	S	S	05
30	31						1
2	3	4	5	6	7	8	May
9	10	11	12	13	14	15	2022
16	17	18	19	20	21	22	
23	24	25	26	27	28	29	

9 Q Generator :-

10 ↗

→ Generators are iterators which can only ship

11

✓ Generator uses "yield" keyword.

12

→ Generators are mostly used to in loops to generate an iterator by returning all the values in the loop without affecting the iteration of the loop.

3 → Every generator is an iterator.

4 Ex - :-

def sqr(n):
 for i in range (1,n+1):
 yield i*i
a = sqr(5)
print (next(a))
print (next(a))
print (next(a))

Output :- +, 25.

I
4
J

06

Jun

2022

13

14

20

21

27

28

IT

10

co

it

12

✓

1

C

2

→

3

Exa

4

i

5

An

6

An

7

Outp

A

B

C

S
1
8
15
22
29
05
May
2022

06 M T W T F S S
Jun 1 2 3 4 5
13 14 15 16 17 18 19
20 21 22 23 24 25 26
27 28 29 30

for more - it will object of iterator
next : next value

FRIDAY
MAY 2022

06

126-239 • WK 19

Iterators

An iterator is an object which contains a countable number of values and it is used to iterate over iterable objects like list, tuples, sets etc.

✓ Iterators are used mostly to iterate or convert other objects to an iterator `iter()` function.

✓ Iterator uses `__iter__()` and `next()` functions.

- Every iterator is not a generator

Example:

4 iter_list = iter(['A', 'B', 'C'])

5 print(next(iter_list))

6 print(next(iter_list))

7 print(next(iter_list))

Output

A

B

C

05
May
2022

06	M	T	W	T	F	S	S
	1	2	3	4	5		
Jun	6	7	8	9	10	11	12
2022	13	14	15	16	17	18	19
	20	21	22	23	24	25	26
	27	28	29	30			

Arts 06 - June

SUNDAY
MAY 2022

08
128-237 • WK 19

~~06 - init -- () function -;~~

minimum one argument

10 The fix - ()

11 The --init-- method is similar to constructors
in C++ and Java. Constructors are used to
12 initialize the object's state.

Ex:

1 # A sample class with init method

2 class Person :

init method or constructor

3 def __init__(self, name):
 self.name = name

4

Sample method.

5 def say_hi(self):

print("Hello, my name is", self.name)

6

P = Person("Nitin")

Output:

7 P.say_hi() Hello, my name is Nitin

S
1
8
15
22
29
05
May
2022

06 M T W T F S S
Jun 6 7 8 9 10 11 12
13 14 15 16 17 18 19
20 21 22 23 24 25 26
27 28 29 30

SUNDAY
MAY 2022

08

128-237 • WK 19

~~06 - init -- () function -:~~

minimum one argument

06 - June

10 The ~~init -- ()~~ name is not common at all
11 The ~~init --~~ method is similar to constructors
in C++ and Java. Constructors are used to
12 initialize the object's state.
Ex:

1 # A sample class with init method
2 class Person:
3 # init method or constructor
4 def __init__(self, name):
5 self.name = name
6
6 # sample method.
7 def say_hi(self):
8 print("Hello, my name is", self.name)
9
9 p = Person("Nitin")
10 p.say_hi() Output: Hello, my name is Nitin

09

129-236 • WK 20

MONDAY
2022 MAY

diff b/w
module and
package

M	T	W	F	S	S	05
30	31					1
1	2	3	4	5	6	8
7	9	10	11	12	13	15
14	16	17	18	19	20	22
15	23	24	25	26	27	29

M	T	06
Jun	6	7
13	14	14
20	21	21
27	28	28

modules :-

The modules is a simple python file that contains collections of functions and global variables and with having a .py extension file. It is an executable file and to organize all the modules we have the concept called package in python.

A module is a single file (or files) that are imported under one import and used.

Eg:-
`import <my-module> #`
`import numpy. #`

Packages :-

The packages is a simple directory having collections of modules. This directory containing python modules and also having `--init--.py` file by which the interpreter interprets it as a package. The package is simply a namespace. The package also contains sub-packages inside it.

A package is a collection of modules in ~~directories~~ directories that give a package hierarchy.

Eg:-
`from my-package.abc import a.`

S 05
1
8
15
22
29
May 2022

06 M T W T F S S
Jun 2022 1 2 3 4 5
6 7 8 9 10 11 12
13 14 15 16 17 18 19
20 21 22 23 24 25 26
27 28 29 30

diff b/w
range() and
xrange()

TUESDAY
MAY 2022

10
130-235 • WK 20

9. What is

10 Parameters	Range()	Xrange()
1] Return type	It returns a list of integers.	It returns a generator objects.
2] Memory consumption	Since range() returns a list of elements, it takes more memory.	In comparision to range(), it takes less memory.
3] Speed	Its execution speed is slower.	Its execution speed is faster.
4] Python version	Python 2, Python 3	xrange no longer exists.
5] Operations	Since it returns a list, all kinds of arithmetic operations can be performed.	Such operation cannot be performed on xrange().

Q What are built-in data types in python or
 WEDNESDAY Explain mutable and
 2022 immutable Data types in
 Python

M	T	W	T	F	S	S
30	31	1	2	3	4	5
2	3	4	5	6	7	8
9	10	11	12	13	14	15
16	17	18	19	20	21	22
23	24	25	26	27	28	29

05
 May
 2022

Q 11
 134234 * WK 20

- 1) Boolean (bool)
- 2) Integer (Int)
- 3) Float
- 4) String (Str)
- 5) tuple
- 6) frozenset
- 7) list
- 8) set
- 9) dict

Mutable / immutable

- 1) Immutable
- 2) Immutable
- 3) Immutable
- 4) Immutable
- 5) Immutable
- 6) Mutable
- 7) Mutable
- 8) Mutable

- 4) A first fundamental distinction that Python makes on data is about whether or not the values of an object changes.
 If the value can change, the object is called Mutable.
 while if the value cannot change, the object is called immutable.

- You can access global variables by any statements in the program.
 - It is stored on a fixed location decided by the compiler.

M	T	W	T	F	S	S
6	7	8	9	10	11	12
13	14	15	16	17	18	19
20	21	22	23	24	25	26
27	28	29	30			

Q Local variable

- 10) It is declared
- 11) If it is not created lost
- 12) Data sharing variable
- 1) Parameters pass access the variable
- 2) When the value function, the local variable statements, is declared
- 3) It is stored
- 4) Global variable
- 5) same global
- 6) It is declared
- 7) If it is not created starts and lost
- 8) Data sharing same global
- 9) Parameters pass as it is visible
- 10) When the value function changes

Dr
S S 05
1 May
7 8 2022
14 15
21 22
28 29

06 M T W T F S S
Jun 6 7 8 9 10 11 12
2022 13 14 15 16 17 18 19
20 21 22 23 24 25 26
27 28 29 30

Diff b/w Local and
global variable

THURSDAY
MAY 2022

12

132-233 • WK 20

6

→ Local Variable -:

- It is declared inside a function.
- If it is not initialized, a garbage value is stored.
- It is created when the function starts execution and lost when the function terminates.
- Data sharing is not possible as data of the local variable can be accessed by only one function.
- Parameters passing is required for local variable to access the value in other function.
- When the value of local variable is modified in one function, the change are not visible in another function.
- Local variables can be accessed with the help of statements, inside a function in which they are declared.
- It is stored on the stack unless specified.

Global variable -:

- It is declared outside the function.
- If it is not initialized zero is stored as a default.
- It is created before the program's global execution starts and lost when the program terminates.
- Data sharing is possible as multiple function can access the same global variable.
- Parameters passing is not necessary for a global variable as it is visible throughout the program.
- When the value of global variable is modified in one function changed and visible in the rest of the program.

13

FRIDAY
2022 MAYExplain break, continue and
pass statement

M	T	W	T	F	S	S
30	31		1	2	3	4
1	2	3	4	5	6	7
8	9	10	11	12	13	14
15	16	17	18	19	20	21
22	23	24	25	26	27	28
29	30	31				

05
May
2022

06

Jun
2022

M	T	W	T	F	S	S
6	7	8	9	10	11	12
13	14	15	16	17	18	19
20	21	22	23	24	25	26
27	28	29	30			

Self :-

- 9. The 'self' parameter of the class belongs to the
- 10. belong to the

11.

Class Person:

12. def __init__

self.name

self.age

1. def.info(self):

print("f" my

3.

4. C = Person ("

c = info()

5.

Output:

6. My name

7.

sent representation
it used to access

Break

```
for i in range(10):
    if i == 7:
        break
    print(i, end=",")
```

Output :-

0,1,2,3,4,5,6

Continue

```
for i in range(10):
    if i == 7:
        continue
    print(i, end=",")
```

Output :-

0,1,2,3,4,5,6,8,9

Pass

```
def my_func():
    print('Pass inside function')
my_func()
```

Output :-

Pass inside function

05
May
2022

06	M	T	W	T	F	S	S
Jun	1	2	3	4	5	6	7
2022	6	7	8	9	10	11	12
	13	14	15	16	17	18	19
	20	21	22	23	24	25	26
	27	28	29	30			

What is 'self' keyword in
Python

SATURDAY
MAY 2022

14

134-231 • WK 20

* Self :

The 'self' parameter is referenced to the current instance of the class, and is used to access variables that belong to the class.

Class Person:

```
1 def __init__(self, name, age):  
2     self.name = name  
3     self.age = age
```

def.info (self):

```
1     print(f"my name is {self.name}. I am {self.age} years old.")
```

```
1 c = Person ("Nitin", 23)  
2 c.info()
```

5

Output:

```
1 my name is Nitin. I am 23 years old.
```

7

self represent the instance of a class and it used to access the variable elements of class.

15

SUNDAY
2022 MAY

135-230 • WK 20

Diff. Betw.
pickling and
unpickling

M	T	W	T	F	S	S
30	31				1	05
1	2	3	4	5	6	7
8	9	10	11	12	13	14
15	16	17	18	19	20	21
22	23	24	25	26	27	28
29						

May 2022

06

Jun

2022

M	T	W	T	F	S	S
6	7	8	9	10	11	12
13	14	15	16	17	18	19
20	21	22	23	24	25	26
27	28	29	30			

Pickling :-

- In python, the pickle module accepts any python object; transforms it into a string representation, and dumps it into a file by using the dump funct'. This process is known as pickling. The function used for this process is pickle.dump().

Unpickling :-

- The process of retrieving the original python object from the stored string representation is called unpickling. The function used for this process is pickle.load().

- They are inverse of each other.
- Pickling - also called serialization, involves converting a python object into a series of bytes which can be written out to a file.
- Unpickling, or de-serialization, does the opposite - it converts a series of bytes into the python object it represents.

→ When you are
need to pass *args and *

→ The args keyword
arguments - It is
multiple arguments

1 → The ** keyword
number of arguments

2 → **kwargs keyword
can access each

3 → associated with a

4 → args after kwargs

5 → def sum(*args):
total = 0

6 → for a in args:
,

7 → total += a
print(total)

sum(i, 1, 2, 3, 4, 5)

output = 15

05
May
2022

06	M	T	W	T	F	S	S
Jun 2022							
6	1	2	3	4	5		
13	8	9	10	11	12		
20	14	15	16	17	18	19	
27	21	22	23	24	25	26	
	28	29	30				

what does *args and **kwargs mean by

16

MONDAY
MAY 2022

136-229 • WK 21

When you are not clear how many arguments you need to pass to a particular functn, then we use *args and **kwargs.

The *args keyword represents a varied number of arguments - It is used to add together the values of multiple arguments.

The **kwargs keyword represents an arbitrary number of arguments that are passed to a functn.

**kwargs keywords are stored in dictionary - You can access each item by referring to the keyword you

associate with an argument when you passed the argument

*args Python Example

```
def sum(*args):
    total = 0
    for a in args:
        total = total + a
    print(total)
```

sum(1, 2, 3, 4, 5)

output = 15

**kwargs python Explain

```
def show(**kwargs):
    print(kwargs)
```

show(A=1, B=2, C=3)

Output :

{'A': 1, 'B': 2, 'C': 3}

17

137-228 • WK 21

Q What is "Open" and "With" statement in python?

TUESDAY

2022 MAY

M	T	W	T	F	S	S
30	31					1
2	3	4	5	6	7	8
9	10	11	12	13	14	15
16	17	18	19	20	21	22
23	24	25	26	27	28	29

05

May
2022

06

Jun
2022

M	T	W	T	F
1	2	3	4	5
6	7	8	9	10
13	14	15	16	17
20	21	22	23	24
27	28	29	30	

9 - Both statements are used in case of file handling.

10 - With the "with" statement, you get better syntax and exception handling.

11 f = open("cognition.txt")
content = f.read()
print(content)
f.close()

12 with open("cognition.txt") as f:
content = f.read()
print(content)

13 Text mode (+):

14 o = open("cognition.txt", "w")
o.write("Python is a programming language")
o.close()

14 Read only
Open

15 set the file raises

16 in which

17 Read and
- Open

18 - Raises

19 Write only
- Open

20 - for

21 over

22 - The if the

23

24 Write and
- Opens

25 - for exists

26 -

27 Append only

28 - Open the

29 - The file is

30 - The data is end, after

S
1
8
15
22
29
05
May
2022

06 M T W T F S S
Jun 6 7 8 9 10 11 12
2022 13 14 15 16 17 18 19
20 21 22 23 24 25 26
27 28 29 30

Q Diff. ways to read and write in a file in python?

WEDNESDAY
MAY 2022

18

138-227 • WK 21

• Read only ('r'):

- Open text file for reading. The handle is positioned at the beginning of the file. If the file does not exist, raises I/O errors. This is also the default mode in which file is opened.

• Read and write ('r+'):

- Open the file for reading and writing
- Raises I/O error if the file does not exist.

• Write only ('w'):

- Open the file for writing
- For existing file, the data is truncated and overwritten.
- The handle is positioned at the start of the file if the file does not exist.

• Write and read ('w+')

- Opens the file for reading and writing.
- For existing file, data is truncated and overwritten.

• Append only ('a'):

- Open the file for writing.
- The file is created if does not exists.
- The data being written will be inserted at the end, after the existing data.

19

THURSDAY
2022 MAY

Q What is Pythonpath &

M	T	W	T	F	S	S
30	31					05
1	2	3	4	5	6	7
8	9	10	11	12	13	14
15	16	17	18	19	20	21
22	23	24	25	26	27	28
29						

M	T	W	T	F	S	S
1	2	3	4	5	6	7
8	9	10	11	12	13	14
15	16	17	18	19	20	21
22	23	24	25	26	27	28
29	30					

- 1 Pythonpath is an environment variables
- 2 which you can set to add additional directories where Python will look for modules and packages.
- 3 The 'PYTHONPATH' variable holds a strings with the name of various directories that need to be added to the sys.path directory list by Python.
- 4 The primary use of this variable is to allow users to import modules that are not made installed yet.

Q How exception handled in python?

→ Try : This block will test the exceptional error to occur.

Except : Here you can handle the error.

Else : If there is no exception then this block will be executed.

Finally : Finally block always get executed either exception is generated or not

9 try :

10 # some co-

11 except :

12 # Optional

13 # Handling

1 else :

2 # some

3 # execute

4 finally :

5 # some

6 Q Where python is

7 →

- Web Application
- Desktop Application
- Database Application
- Networking API
- Machine Learning
- Artificial Intelligence
- Data Analysis
- IoT Applications
- Games and more

S S
7 8 05
14 15 May
21 22 2022
28 29

06 M T W T F S S
Jun 6 7 8 9 10 11 12
13 14 15 16 17 18 19
20 21 22 23 24 25 26
27 28 29 30

FRIDAY
MAY 2022

20
140-225 • WK 2

9
10 try :
some code ...!
11 except :
Optional Block
Handling of exception (if required)
12
13 else :
some code ...
executed if no exception.
14
15 finally :
some code (always executed)

Q Where python is used
→

- 6 • Web Applications
- Desktop Applications
- 7 • Database Applications
- Networking Applications.
- Machine Learning
- Artificial Intelligence
- Data Analysis
- IOT Applications
- Games and many more ...!

21

SATURDAY
2022 MAY

141-224 * WK 21

How to use F string
and Format or replacement
operator ?

M	T	W	T	F	S	S	05
30	31	1	2	3	4	5	May
			10	11	12	13	14
			17	18	19	20	21
			23	24	25	26	27
			28	29	30	31	2022

9 How to use F string

10 name = "sanket"

11 role = "software engg."

12 Print(f "Hello, my name is {name} and I am {role}!")

Output =

Hello, my name is sanket and I am software engg.

3 How to use Format or replacement operator ?

4 ~~name~~
= "sanket"

5 Print(f "Hello, my name is {name} and I'm {role}")
• format(name, role))

6 Output :

Hello, my name is ~~sanket~~ sanket and I'm software engg.

06	M	T	W	T	F	S	S
Jun	6	7	8	9	10	11	12
2022	13	14	15	16	17	18	19
	20	21	22	23	24	25	26
	27	28	29	30	31		

9 Abstract

10 digit de

2) It is imp

unnecessary

12 withdraw

3) It high
of an obj
the objec

4) It focus
ing for ex
car .

5) It is su
the interfa
abstract

6) In a net
hiding in
the help
an abst

S S 05
1 May
2 8 2022
3 14 21
4 22 28
5 29

06 M T W T F S S
Jun 1 2 3 4 5
6 7 8 9 10 11 12
13 14 15 16 17 18 19
20 21 22 23 24 25 26
27 28 29 30

Abstraction

- 1 Abstraction works on the digit design levels.
- 2 It is implemented to hide unnecessary data and withdrawing relevant data.
- 3 It highlights what the work of an object instead of how the object works is.
- 4 It focuses on outside viewing, for example, shifting the car.
- 5 It is supported in java with the interface and the abstract class.
- 6 In a nutshell, abstraction is hiding implementation with the help of an interface and an abstract class.

SUNDAY
MAY 2022

22

142-223 • WK 21

Encapsulation

Encapsulation works on the application level.

It is the mechanism of hiding the code and the data together from the outside world or misuse.

It focused on inner details of how the objects works, modifications can be done later to the settings.

It focuses on internal working or inner viewing, for example, the production of the car.

Encapsulation is supported using eg. public, private and secure access modification system.

In a nutshell, encapsulation is hiding the data with the help of getters and setters.

23

MONDAY
2022 MAY

143-222 WK 22

M	T	W	T	F	S	S	05
30	31				1		
1	2	3	4	5	6	7	
8	9	10	11	12	13	14	15
15	16	17	18	19	20	21	22
22	23	24	25	26	27	28	29

M	T	W	T	F	S	S
6	7	8	9	10	11	12
13	14	15	16	17	18	19
20	21	22	23	24	25	26
27	28	29	30			

Q different betw .py and .pyc

→ .py files contain the source code of a program.
whereas .pyc file contain the bytecode of your
program.

Python can compile the .py files and
saves it as .pyc files, so it can reference them
in subsequent invocations.

The .pyc contain the compiled bytecode of
python source files. This code is then executed
by python's virtual machine.

Q can you con
9 its possible &

12 → to solution of loop

9 t1 = c1

t2 = c2

12 t1 = t1 + t2

Print ("After")

1 Output ::

2 from After

-from After

3

4 Output from 2nd

5

6 Output from 3rd

7

8

9

10

11

12

13

14

15

16

05
May
2022

S	S	S	M	T	W	T	F	S	S
1	2	3	4	5					
6	7	8	9	10	11	12			
13	14	15	16	17	18	19			
20	21	22	23	24	25	26			
27	28	29	30						

TUESDAY
MAY 2022

24
144-221 • WK 22

Q Can you concatenate two tuples? If yes, How
is it possible & since it is immutable

t1 = (1, 2, 3)
t2 = (7, 9, 10)

t3 = t1 + t2

Print ("After concatenation is : ", t3)

Output :-

After concatenation is : (1, 2, 3, 7, 9, 10)

Program runs successfully

Output :-

After concatenation is : (1, 2, 3, 7, 9, 10)

Program runs successfully

Output :-

After concatenation is : (1, 2, 3, 7, 9, 10)

Program runs successfully

Output :-

After concatenation is : (1, 2, 3, 7, 9, 10)

Program runs successfully

Output :-

After concatenation is : (1, 2, 3, 7, 9, 10)

Program runs successfully

25

WEDNESDAY
2022 MAY

145-220 * WK 22

M	T	W	T	F	S	S
30	31					05
1	2	3	4	5	6	7
8	9	10	11	12	13	14
15	16	17	18	19	20	21
22	23	24	25	26	27	28
29	30					

May 2022

06	M	T	W	T	F	S
Jun 2022	1	2	3	4	5	6
6	7	8	9	10	11	12
13	14	15	16	17	18	19
20	21	22	23	24	25	26
27	28	29	30			

Q How to read

→ By using

10

x = list (name)

11 print ("list")

12 x = [int (x)]

print ("num")

1 x = [int (x)]

2 print ("num")

3 print ("list")

Q How to for

→

* Delete by

5 d1 = []

d1.pop (4)

6 print (d1)

* Delete By

d1 = ['A']

d1.pop (4)

print (d1)

* Delete by

del d1 =

del

print

- 3] List
 - 1) This list can store the value of diff. data types
 - 2) The list cannot handle the direct arithmetic operations
 - 3) The lists are build-in data structures so we don't need to import it
 - 4) The lists are less compatible than array and much compatible than the data
- 5] It consumes large memory
- 6] It is suitable for storing the longer sequence of the data items
- 7] We can print the entire list using explicit looping
- 8] It is more compact in memory size comparatively list.
- 9] We can print the entire list without using explicit looping.

S 05
May
2022

06 M T W T F S S
Jun 1 2 3 4 5
2022 6 7 8 9 10 11 12
13 14 15 16 17 18 19
20 21 22 23 24 25 26
27 28 29 30

THURSDAY
MAY 2022

26

146-219 • WK 22

Q How to read multiple values from single input?

→ By using split()

```
x = list(map(int, input("Enter a multiple value:").split()))
print("List of values : ", x)
```

Q How to copy and delete a dictionary.

→

```
# Delete by using clear():
d1 = {'A':1, 'B':2, 'C':3}
d1.clear()
print(d1)
```

```
# Delete by using pop():
d1 = {'A':1, 'B':2, 'C':3}
d1.pop('A')
print(d1) -> {'B':2, 'C':3}
```

```
* Delete by using del():
def d1 = {'A':1, 'B':2, 'C':3}
del d1['A']
del d1['B']
print(d1) = {'C':3}
```

27

FRIDAY
2022 MAYQ. Diff b/w Anonymous
Lambda Function & and

M	T	W	T	F	S	S
30	31				1	05
2	3	4	5	6	7	May
9	10	11	12	13	14	2022
16	17	18	19	20	21	
23	24	25	26	27	28	

M	T	W	T	F	S	S
6	7	8	9	10	11	12
13	14	15	16	17	18	19
20	21	22	23	24	25	26
27	28	29	30			

Q. What is Init

1. __init__ is

python.

The __init__

object is cre

All classes h

which is alw

initiated.

Use the __in

object pr

the __init__

but only init

4

Q. What is slice

5

Python slice c

Elements from

used with string

7

Syntax :- slice

slice

7

2022 100

000 = x

(2022) 000

(X) 000

2022 000

(2022) 000

2022 000

(2022) 000

2022 000

(2022) 000

2022 000

(2022) 000

lambda function :-

- It can have any number of arguments but only one expression.
- The expression is evaluated and returned.
- Lambda function can be used wherever function objects are required.

Ans. Anonymous Function :-

- In python, anonymous function is a function that is defined without a name.
- While normal function are defined using the def keyword, anonymous functions are defined using lambda keyword.
- Hence, anonymous functions are also called lambda function.

Lambda - ex:-

```
adder = lambda x, y : x + y
print(adder(4, 8))
```

S
1
8
15
22
29
05
May
2022

06	M	T	W	T	F	S	S
			1	2	3	4	5
Jun	6	7	8	9	10	11	12
2022	13	14	15	16	17	18	19
	20	21	22	23	24	25	26
	27	28	29	30			

SATURDAY
MAY 2022

28
148-217 • WK 22

Q. What is Init function in python?

- `--init--` is one of the reserved method in python.
- The `--init--` method can be called when an object is created from the class.
- All classes have a function called `--init--()`, which is always executed when the class is being initialized.
- Use the `--init--()` function to assign values to the object properties.
- The `--init--` method doesn't create the object but only initialize the object's attributes.

func?

Q. What is slice / slicing in python.

Python slice() function is used to get a slice of elements from collection of elements - slice() function used with string, list, tuple, set, bytes or range objects

Syntax:- `slice(stop)`

`slice(start, stop, step)`

29

SUNDAY
2022 MAY

149-216 • WK 22

M	T	W	T	F	S	S
30	31				1	05
1	2	3	4	5	6	7
8	9	10	11	12	13	14
15	16	17	18	19	20	21
22	23	24	25	26	27	28
29	30					

M	T	W	T	F	S	S
1	2	3	4	5	6	5
10	11	12	13	14	15	12
17	18	19	20	21	18	19
23	24	25	26	27	25	26
28	29	30				

- Q Is the python case sensitive language.
- + Yes, Python is case sensitive language.
Because it differentiates the lower case and upper case identifiers.
- Q Is python interpreted language?

- + A python is an interpreted language.

What is scope in python?

Scope is a block of code where objects in python remain relevant.

Type of scope

Local - A variable created inside a function belongs to the local scope of that function, and can only be used inside that function.

Global -

A variable created outside of a function is global and can be used by anyone.

local scope -:

```
def myfunc():
    x = 300
    print(x)
```

myfunc()

global scope -:

```
x = 300
def myfunc():
    print(x)
myfunc()
print(x)
```

S
1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29

05
May
2022

S	M	T	W	T	F	S	S
	1	2	3	4	5		
6	7	8	9	10	11	12	
13	14	15	16	17	18	19	
20	21	22	23	24	25	26	
27	28	29	30				

MONDAY
MAY 2022

30

150-215 • WK 23

Is Indentation required in python?

→ 10. Indentation is most important for python. It specifies block of code. All.

→ 11. Indentation is a very important concept of python. because without proper indenting the python code, you will end up seeing Indentation Err. and the code will not get compiled..

→ 12. Python uses n spaces as indentation by default.

→ 13. However, the number of spaces is up to you, but a minimum of 1 space has to be used.

What is namespaces in python?

→ 14. A namespaces is naming system used to make sure that names are unique to avoid naming conflicts.

M	T	W	T	F	S	S
30	31	1	2	3	4	5
2	3	4	5	6	7	8
9	10	11	12	13	14	15
16	17	18	19	20	21	22
23	24	25	26	27	28	29

05
May
2022

31

TUESDAY
2022 MAY

What is PEP 8 and why is it important?

PEP stands for python enhancement proposal. A PEP is an official design document which provides information to the python community, or describing a new feature, for python or its processes.

PEP 8 is especially important since it documents the style guidelines for python code. Apparently contributing to python open-source community requiring you to follow these style guidelines sincerely and strictly.

What are attributes in python?

A method is a function which is defined in the class. An attribute is an instance variable defined in the class.

```
class Example(object):
```

```
    def __init__(self, name):
```

```
        self.name = name.
```

```
    def hello(self):
```

```
        print("Hi, I am " + self.name.)
```

Here hello is a method, and name is an attribute.

Action Plan

MON

TUE

WED

THU

FRI

SAT

SUN

6

7

8

9

10

11

12

Inheritance

Attributes = A value name using dotted attributes or it will

method = A functn

05
May
2022

Action Plan

ACTION PLAN JUNE 2022

06

MONTH IN VIEW

MON	6	8	13	20	27
TUE	7	14	15	21	28
WED	1	8	16	22	29
THU	2	9	17	23	30
FRI	3	10	18	24	
SAT	4	11	19	25	
SUN	5	12	19	26	

OBJECTIVES OF THE MONTH

Attributes = A value associated with an object which is referenced by name using dotted expressions. for ex: if an object o has an attribute a it would be referenced as o.a.

method = a functn which is defined inside a class.

JUNE

M	T	W	T	F	S	S
1	2	3	4	5	6	06
6	7	8	9	10	11	12
13	14	15	16	17	18	19
20	21	22	23	24	25	26
27	28	29	30			Jun 2022

01

WEDNESDAY
2022 JUNE

152-213 • WK 23

{ what is docstring in python }

- 9 What is docstring in python?
- 10 Documentation string or docstring is a multiline string used to document a specific code segment.
- 11 The docstring should describe what the function or method does.
- 12 or

- 1 How are arguments passed by value or by reference in python?

→ 3 Pass by ~~reference~~:

This is used in some programming languages where values to the argument of the function are passed by reference which means that the address of the variable is passed and then the operation is done on the value stored at these addresses.

7 Pass by ~~reference~~:

It means that the value is directly passed as the value to the argument of the function. Here, the operation is done on the value and then the value is stored at the address. Pass by value is used for a copy of the variable.

07
Jul 2022

M T
4 5
11 12
18 19
25 26

9 Call

10 while

11 func

lang

12 col

vari

1 of

used

2 accall

3 It is

varial

4

chang

5 also

of th

6 the f

7 Allows

in the

by usi

The o

modif

07
Jul
2022

	M	T	W	T	F	S	S
					1	2	3
4	5	6	7	8	9	10	
11	12	13	14	15	16	17	
18	19	20	21	22	23	24	
25	26	27	28	29	30	31	

THURSDAY
JUNE 2022

02

153-212 • WK 23

Dift bctn -

Call by reference

10 while calling a functⁿ, in a programming language instead of copying the values of variables, the address of the variable is used, it is known as 11 "call by reference."

12 It is method, a variable itself is passed.

Changes in the variable also affects the value of the variable outside the functⁿ.

Allows you to make changes in the values of variables by using functⁿ calls.

The original value is modified.

call by value.


While calling a functⁿ, when we pass values by copying variables, it is known as "call by values".

A copy of the variable is passed in a call by value.

Changes made in a copy of a variable never modify the value of the variable outside the functⁿ.

Does not allow you to make any changes in the actual variables.

Original value is not modified.



13	14	15	16	17	18	19
20	21	22	23	24	25	SUN 26
27	28	29	30			

03

FRIDAY
2022 JUNE

154.211 WK 23

decorator example ..!

When we need to change the behaviour of a function without modifying the function itself.

```
ex:- def div(a, b):
      print(a/b)
```

```
def smart_div(func):
    def inner(a, b):
        if a < b:
            a, b = b, a
        return func(a, b)
```

```
div1 = smart_div(div)
div1(2, 4)
```

06
Jun
2022

07 M T W T F S S
Jul 4 5 6 7 8 9 10
2022 11 12 13 14 15 16 17
18 19 20 21 22 23 24
25 26 27 28 29 30 31

SATURDAY
JUNE 2022

04

155-210 • WK 23

* program to check leap years + moron

```
10 year = int(input(" "))

11 if (year % 4) == 0 : # 2016 = 2019
    if (year % 100) == 0 :
        if (year % 400) == 0 : # (year)
            print ("{} is a leap year".format(year))
        else :
            print ("{} is not a leap year - 1 ".format(year))

12 else :
    print ("{} is not a leap year - 1 ".format(year))

13 else :
    print ("{} is leap year - 1 ".format(year))

14 else :
    print ("{} is not a leap year - 1 ".format(year))

15 else :
    print ("{} is leap year - 1 ".format(year))


16 else :
    print ("{} is not a leap year - 1 ".format(year))

17 else :
    print ("{} is leap year - 1 ".format(year))
```

05

156-209 • WK 23

SUNDAY
2022 JUNE



M	T	W	T	F	S	S	S
1	2	3	4	5	6	7	8
13	14	15	16	17	18	19	20
21	22	23	24	25	26	27	28
29	30						

Jun
2022

Program to check number is prime.

10 num = int(input())

11 flag = False # define flag variable

12 if num > 1: # prime number is > 1

For i in range (2, num): # if factor is
1 if (num % i) == 0 : found, set flag to true

flag = True

2 break # break out of loop.

3 if flag:

4 print (num, "is not a prime number")

else :

5 print (num, "is a prime number").

6

7

M	T	W	T	F	S	S	S
4	5	6	7	8	9	10	11
11	12	13	14	15	16	17	18
18	19	19	20	21	22	23	24
25	26						

07
Jul
2022

9

10 # fi

n

11

12 # if

i

1

e

2

3 else

4

5

6

7

06
Jun
2022

1+1+

07	M	T	W	T	F	S	S
Jul	4	5	6	7	8	9	10
2022	11	12	13	14	15	16	17
	18	19	20	21	22	23	24
	25	26	27	28	29	30	31

Fibonacci series

MONDAY

JUNE 2022

06

157-208 • WK 24

9 nterms = int(input("Enter number of terms: "))

10 # first two terms

n1, n2 = 0, 1

11 count = 0

12 # check number is valid

if nterms <= 0:

1 print("Please enter a positive number")

2 elif nterms == 1:

2 print("Fibonacci sequence upto", nterms, ":")

2 print(n1)

3 else:

3 print("Fibonacci sequence:")

4 while count < nterms:

4 print(n1)

5 nth = n1 + n2

5 n1 = n2

6 n2 = nth

6 count += 1

7

07

158-207 • WK 24

TUESDAY
2022 JUNE

$$15^3 = 1^3 + 5^3 + 3^3 = 1 + 125 + 27$$

Armstrong number
↓
sum of cube of its number
is equal to itself

M	T	W	T	F	S	06
6	7	8	9	10	11	12
13	14	15	16	17	18	19
20	21	22	23	24	25	26
27	28	29	30			

07
Jul
2022
M T
4 5
11 12
18 19
25 26

```
9 num = int(input())
sum = 0
10 temp = num
while temp >= 0:
    digit = temp % 10
    sum += digit ** 3
    temp //= 10
11 if num == sum:
    print(f'{num}, "is an Armstrong number")'
else:
    print(f'{num}, is not an Armstrong number")')
12
```

string is Palindrome or not

07	M	T	W	T	F	S	S
Jul 2022	4	5	6	7	8	9	10
	11	12	13	14	15	16	17
	18	19	20	21	22	23	24
	25	26	27	28	29	30	31

WEDNESDAY
JUNE 2022

08

159-206 • WK 24

9 my-str = 'aIbonPhobit' signi = part
make it suitable for careless comparison

10 ~~my-str~~ → my-str = my-str[::-1]

11 # reverse the string.

rev-str = reversed(my-str)

12 # check if the string is equal to its reverse

if list(my-str) == list(rev-str):

print("The string is palindrome")

else:

print("The string is not palindrome")

3 ((+ve)) + ((-ve)) = 0

4 : -WQWD

5 : 10001 10000 01000 00100

6

7

09

count number of vowels

count vowels of string.

THURSDAY

2022 JUNE

160-205 • WK 24

M	T	W	T	F	S	S	S
6	7	8	9	10	11	12	06
13	14	15	16	17	18	19	Jun
20	21	22	23	24	25	26	2022
27	28	29	30				

9 string = input ("Enter the string : ")

count = 0

10 string = string.lower()

for i in string :

11 if i == 'a' or i == 'e' or i == 'i'

or i == 'o' or i == 'u' :

12 # if true

count += 1

~~check if any vowels found~~

if count == 0 :

2 print ('No vowels found')

else :

3 print ('Total vowels are : ' + str(count))

4 output - :

Enter the string :санкел

5 Output Total vowels : 2

6

7

06
Jun
2022

07	M	T	W	T	F	S	S
Jul					1	2	3
2022	4	5	6	7	8	9	10
	11	12	13	14	15	16	17
	18	19	20	21	22	23	24
	25	26	27	28	29	30	31

Half Pyramid

1 2 3
1 2 3 4
1 2 3 4 5

FRIDAY

JUNE 2022

10

161-204 • WK 24

9 rows = 5

for i in range (0, rows):

10 for j in range (0, i+1):

Print (*", end = " ")

11 Print ("\\n")

12

13 Downward half pyramid

2 rows = 5

for i in range (rows + 1, 0, -1):

3 for j in range (0, i-1):

Print (*", end = " ")

4 Print ("\\n")

5

6 Right angled triangle with all 2-2 pattern

7 It is possible to form triangle by

8 rows of 1's and 5 rows of 2's

9 printing " " - " " in between each A or row

10 It is possible to do this by 2 rows

11 printing 5's and 2's in between each row

12 It is possible to do this by 2 rows

162-203 • WK 24

SATURDAY
2022 JUNE

What is Access modifier, and its types

M	T	W	T	F	S	S
1	2	3	4	5		
6	7	8	9	10	11	12
13	14	15	16	17	18	19
20	21	22	23	24	25	26
27	28	29	30			

06
Jun
2022

07
Jul
2022

M T
4 5
11 12
18 19
25 26

9 ~~Pass in python~~

10 ~~Pass is keyword represents a null operator in python. It is generally used.~~

11 Access modifier :-

12

Access modifier are keywords in object oriented programming language that set the accessibility of classes & methods.

①

1 Public - Any member declared as public can be accessed from outside the class through an object. All members in python class are public by default.

②

2 Protected - The data member of the class is declared protected by adding a single underscore ("_") and this prevent it from access.

③

3 Private - A double underscore ("__") makes the variable private as well as secure. It is not possible to access them outside the class because it will throw an error.

9 ~~(S)~~

10 ~~→~~

11 ~~a~~

12 ~~of~~

1 ~~SPL~~

2 ~~one~~

3 ~~process~~

- ④ Requirements
- ⑤ Design
- ⑥ Implementation
- ⑦ Testing
- ⑧ Deployment
- ⑨ Maintenance
- ⑩ Project Management
- ⑪ Tools

S
06
Jun
2022

07	M	T	W	T	F	S	S
					1	2	3
Jul	4	5	6	7	8	9	10
2022	11	12	13	14	15	16	17
	18	19	20	21	22	23	24
	25	26	27	28	29	30	31

SUNDAY
JUNE 2022

12
163-202 • WK 24

Q. What are SDLC phases

The software development life cycle is a structured process that enables the production of high-quality, low-cost software, in the shortest production time.

SDLC is a framework that defines activities that are performed during the software development process.

There are 6 phases in SDLC :-

- 1] Requirement
- 2] Design
- 3] Implementation
- 4] Testing
- 5] Deployment
- 6] Maintenance.

13

MONDAY
2022 JUNE

164-201 • WK 25

M	T	W	T	F	S	S
		1	2	3	4	5
6	7	8	9	10	11	12
13	14	15	16	17	18	19
20	21	22	23	24	25	26
27	28	29	30			

M	T	W	T	F	S	S
07						
Jul						
2022	4	5	6	7	8	9
	11	12	13	14	15	16
	18	19	20	21	22	23
	25	26	27	28	29	30

- Q What is Type casting in python.
- There are two types
- ① Implicit type casting
- ② Explicit type casting.

Implicit type casting :-

conversion performed

Implicit type casting is automatically by the interpreter, without user intervention.

Python automatically converts one data type to another data type

Explicit type casting -

In this type casting / conversion the user or programmer converts the data type of an object to the required data type.

In python we use predefined function like int(), float(), str(), bool() etc to perform explicit type casting.

13

164-201 • WK 25

MONDAY
2022 JUNE

M	T	W	T	F	S	S
1	2	3	4	5	6	06
6	7	8	9	10	11	12
13	14	15	16	17	18	19
20	21	22	23	24	25	26
27	28	29	30			2022

07
Jul
2022

- Q What is Type casting in python?
- There are two types
- ① Implicit type casting
 - ② Explicit type casting.

1 Implicit type casting -

- Implicit type casting is performed by the interpreter, without user intervention.
- Python automatically converts one data type to another data type.

2 Explicit type casting -

- In this type casting / conversion the user or programmer converts the data type of an object to the required data type.

In python we use predefined function like int(), float(), str(), bool() etc to perform explicit type casting.