Lab 10 : 13/02/24

a) Demonstrate inter process communication.

```
class Q {
    int n;
    boolean valueSet = false;
    synchronized int get() {
        while(!valueSet)
            try {
                System.out.println("\n consumer waiting\n");
                wait();
            }
            catch(InterruptedException e) {
                System.out.println("Interrupted Exception
                caught");
            }
        System.out.println("Got: " + n);
        valueSet = false;
        System.out.println("\n Intimate Producer\n");
        notify();
        return n;
    }
    synchronized void put(int n) {
        while(valueSet)
            try {
                System.out.println("\n Producer waiting\n");
                wait();
            }
            catch(InterruptedException e) {
                System.out.println("Interrupted Exception
                caught");
            }
```

```
        this.n=n;
        valueSet=true;
        System.out.println("Put:"+n);
        System.out.println("In Intimate Consumer\n");
        notify();
    }
}

class Producer implements Runnable{
    Q q;
    Producer(Q q){
        this.q=q;
        new Thread(this, "Producer").start();
    }
    public void run(){
        int i=0;
        while(i<3){
            q.put(i++);
        }
    }
}

class Consumer implements Runnable{
    Q q;
    Consumer(Q q){
        this.q=q;
        new Thread(this,"consumer").start();
    }
    public void run(){
        int i=0;
        while(i<3){
            int r=q.get();
            System.out.println("Consumed:"+r);
            i++;
        }
```

class PCFixed{

public static void main(String[] args){

Q q = new Q();

new Producer(q);

new Consumer(q);

System.out.println("Press Control-c to stop.");

}

}

Output:

Put:0

Intimate Consumer

Producer waiting

Press control-c to stop.

Got:0

Intimate Producer

consumed:0

Put:1

Intimate Consumer

Producer waiting

Got: 1

Intimate Producer

consumed:1

Put:2

Intimate Consumer

Producer waiting

Got:2

Intimate Producer

consumed:2

Saaketh. M. Hanasi 1BM22CS242

8) Demonstrate DeadLock

```
class A {
    synchronized void foo(B b) {
        String name = Thread.currentThread().getName();
        System.out.println(name + " entered A.foo");
        try {
            Thread.sleep(1000);
        }
        catch(Exception e) {
            System.out.println("A Interrupted");
        }
        System.out.println(name + "trying to call B.last()");
        b.last();
    }
    void last() {
        System.out.println("Inside A.last");
    }
}

class B {
    synchronized void bar(A a) {
        String name = Thread.currentThread().getName();
        System.out.println(name + "entered B.bar");
        try {
            Thread.sleep(1000);
        }
        catch(Exception e) {
            System.out.println("B Interrupted");
        }
        System.out.println(name + "trying to call A.last()");
        a.last();
    }
}
```

```
void last(){
    System.out.println("Inside A.last");
}
}

class Deadlock implements Runnable{
A a = new A();
B b = new B();
Deadlock(){
    Thread.currentThread().setName("MainThread");
    Thread t = new Thread(this, "RacingThread");
    t.start();
    a.foo(b);
    System.out.println("Back in main thread");
}
public void run(){
    b.bar(a);
    System.out.println("Back in other thread");
}
public static void main(String args[]){
    new Deadlock();
}
}
```

Output:

```
MainThread entered A.foo
RacingThread entered B.bar
RacingThread trying to call A.last()
Inside A.last
Back in other thread
MainThread trying to call B.last()
Inside A.last
Back in main thread
```

13-2-24