

ROS Programming (C/C++)

Ivan Marković Matko Orsag Damjan Miklić

Automation and Robotics
Robot Programming and Simulation

2020



UNIVERSITY OF ZAGREB

Faculty of Electrical
Engineering and
Computing

Before we begin

- You have all the required packages already installed for this class
- We will go through the process of creating and building a C/C++ ROS package
- We will write a C/C++ publisher and a subscriber that will work with the `turtlesim` simulator

Creating the package

- Navigate in your /src catkin workspace folder
- Create turtle_lawnmower package that we will use in this class

```
$ catkin_create_pkg turtle_lawnmower turtlesim roscpp \
  geometry_msgs
```

- Refresh the package list and roscd into the project

```
$ rospack profile
$ roscd turtle_lawnmower
```

Writing the subscriber in C/C++

- Create a `turtle_lawnmower_node.cpp` file in the `/src` folder of your `turtle_lawnmower` package
- Program a node that will subscribe to the turtle's `turtlesim/Pose` message and write it into the console (use `ROS_INFO`)

// Required headers for the node

#include "ros/ros.h"

#include "geometry_msgs/Twist.h" // turtle's cmd_vel

#include "turtlesim/Pose.h" // reading turtle's position

Writing the subscriber in C/C++

```
int main(int argc, char **argv)
{
    // Initialize the node and an object that will process data
    ros::init(argc, argv, "turtle_lawnmower_node");

    TurtleLawnmower TtMower;

    ros::spin();

    return 0;
}
```

Writing the subscriber in C/C++

- Object will consist of a `NodeHandle` that will handle communication in the ROS system, a subscriber and the callback function named `turtleCallback`

```
class TurtleLawnmower
{
    ros::NodeHandle nh_;

    ros::Subscriber sub_
public:
    TurtleLawnmower(); // Class constructor
    ~TurtleLawnmower(); // Class destructor

    void turtleCallback
    (const turtlesim::Pose::ConstPtr& msg);
};
```

Writing the subscriber in C/C++

- Define the class constructor and destructor

```
TurtleLawnmower::TurtleLawnmower()  
{  
    sub_ = nh_.subscribe("turtle1/pose", 1,  
        &TurtleLawnmower::turtleCallback, this);  
}
```

```
TurtleLawnmower::~~TurtleLawnmower()  
{}
```

- In the constructor we are initializing the subscriber and telling it to call `turtleCallback` which is method in the `TurtleLawnmower` class
- The destructor is empty

Writing the subscriber in C/C++

- Write the callback function `turtleCallback` that will be called each time a message is published on the `turtle1/pose` topic

```
void TurtleLawnmower::turtleCallback
(const turtlesim::Pose::ConstPtr& msg)
{
    ROS_INFO("Turtle lawnmower[%f, %f, %f]",
        msg->x, msg->y, msg->theta);
}
```

- The message has been passed in a `boost_shared_ptr` and member of the class being pointed to can be accessed using the dereferencing operator `'->'`

Building the project

- Open the `CMakeLists.txt`
- Check that `find_package` looks for all dependencies
- This will create variables needed in the linking stage (including headers and linking libraries)
- Add your node as an executable (uncomment `add_executable`)
- Link with the required libraries (uncomment `target_link_libraries`)

Building the project

- In the end your CMakeLists.txt should look like this

```
cmake_minimum_required(VERSION 2.8.3)
project(turtle_lawnmower)
## Find catkin macros and libraries
find_package(catkin REQUIRED COMPONENTS
  roscpp
  geometry_msgs
  turtlesim
)
catkin_package()
# include_directories(include)
include_directories(
  ${catkin_INCLUDE_DIRS}
)
```

Building the project

- CMakeLists.txt continued ...

```
## Declare a cpp executable
add_executable(
    turtle_lawnmower_node src/turtle_lawnmower_node.cpp
)
## Specify libraries to link a library or
## executable target against
target_link_libraries(turtle_lawnmower_node
    ${catkin_LIBRARIES}
)
```

- Call catkin_make from the workspace root folder and build the turtle_lawnmower project

Testing the node

- Run the turtlesim and then your node to see if the callback is running

```
$ roscore  
$ rosrun turtlesim turtlesim_node  
$ rosrun turtle_lawnmower turtle_lawnmower_node
```

- In the terminal your program should be outputting the turtle's pose (position + orientation)

- Now we need to add a publisher to our node
- Since we already have a subscriber, and we want to publish in the callback function, we will need to declare a publisher as member in the TurtleLawnmower class

```
ros::Publisher pub_;
```

- Now setup the publisher in the class constructor

```
pub_ = nh_.advertise<geometry_msgs::Twist>  
("turtle1/cmd_vel", 1);
```

Publishing velocity commands

- In the `turtleCallback` method define the command velocities and publish them

```
geometry_msgs::Twist turtle_cmd_vel;
```

```
turtle_cmd_vel.linear.x = 1;  
pub_.publish(turtle_cmd_vel);
```

- The turtle will be moving forward with the designated velocity