BIDMC Congestive Heart Failure Database

Sanmitha Nantur Ganesh
dept. of Data Science
Kent State University
Kent, USA
snanturg@kent.edu

***Abstract*—This study utilizes the BIDMC (Beth Israel Deaconess Medical Center) Congestive Heart Failure Database to process long-term ECG recordings and determine trends related to severe CHF. We pre-process the ECG data using an integrated approach of sophisticated signal processing and machine learning to extract key HRV parameters such as RMSSD, pNN50, and mean RR intervals. While anomaly detection with Isolation Forest reveals abnormalities in heart rhythms, the clustering techniques like K-means are used to find unique patterns. Besides, CHF trends are predicted using some supervised classification models like Logistic Regression, Random Forest, SVM, and XGBoost, which use synthetic data augmentation to overcome dataset imbalances. Our findings represent how machine learning could be used to identify clinically meaningful ECG patterns, yielding early identification and a better comprehension of CHF dynamics. The current work lays a foundation in terms of methodologies that could be scalable and reliable in cardiovascular health research, considering challenges related to size and the unpredictability of data.**

Index Terms— Congestive heart failure (CHF), heart rate variability (HRV), electrocardiogram (ECG), signal processing, machine learning, anomaly detection, K-means clustering, augmented synthetic data, logistic regression, Isolation Forest, XGBoost, Random Forest, and Support Vector Machine (SVM).

I. Introduction

Congestive Heart Failure (CHF) is a critical condition that affects millions worldwide, whereby the heart is unable to pump blood effectively. Early diagnosis and management are necessary to prevent complications with adverse outcomes. ECGs record the electrical activity of the heart and form an important modality for the diagnosis and follow-up of CHF. However, ECG signal analysis can be manual, which may be a time-consuming and error-prone process, particularly when subtle patterns need to be recognized as indicative of the progress of CHF.

This work applies machine learning techniques in order to analyze the BIDMC Congestive Heart Failure Database, a long-term ECG recording in patients suffering from severe CHF. Using advanced techniques in signal processing, we can extract important heart rate variability measures that are critical indicators of cardiac function. We make use of these features for unsupervised learning in the form of clustering, for detecting different patterns and anomaly detection algorithms that show some deviation indicative of pathological conditions. Further, we have employed supervised classification models to predict CHF-related patterns, with class imbalance addressed using synthetic data augmentation.

Our study addresses crucial challenges in CHF diagnostics-noisy signal preprocessing, class imbalance, and limited dataset size-provides proof of the feasibility of machine learning techniques within cardiac health analysis. These studies contribute not only to developing better insights into ECG-patterns associated with CHF but also to building well-performing, automated diagnostics at low costs with further potential clinical use.

II. Survey

The role of machine learning in biomedical signal processing has been quite extensive; similarly, a lot of developments have taken place with the analysis of heart rate variability (HRV) for the detection of congestive heart failure (CHF). Different strategies have been explored by many researchers to increase the diagnostic precision, feature extraction methods for the diagnosis of CHF: "Dimensionality reduction and feature selection are critical to improving the accuracy of classification in high-dimensional datasets **[5]**."

1. HRV metrics and probabilistic symbolic pattern recognition. According to Mahajan et al. (2017), the detection of CHF is greatly enhanced when measures of HRV are combined with probabilistic symbolic pattern recognition. Their model attained high sensitivity and specificity, thus establishing the efficacy of symbolic analysis in capturing the complex cardiac dynamics.

2. Dynamic HRV Assessment for Quantification of CHF Another study proposed a new approach to the application of dynamic measures of HRV in assessing the severity of CHF. The model outperformed the traditional methods by introducing time-varying HRV parameters, thus allowing highly detailed information on the progression of the disease, with increased accuracy.

3. Empirical Mode Decomposition (EMD) for Automated CHF Detection. Acharya et al. (2017) proposed EMD for feature extraction from HRV signals in the automated identification of CHF. Their approach resulted in a classification accuracy of 94.1%, thus highlighting the effectiveness of nonlinear signal decomposition in the detection of CHF.

4. Bispectral Analysis and Genetic Algorithm-Based Recognition. Yu and Lee (2012) combined bispectral analysis with a genetic algorithm in order to classify CHF patients and healthy subjects.

   Their approach produced a recognition rate of 92.6%, proving the importance of spectral domain features and optimization techniques in CHF analysis.

5. Wavelet Entropy and Classical HRV Indices Isler and Kuntalp (2007) demonstrated improved performance in CHF detection by combining wavelet entropy measures with classical HRV indices. This approach provided robust insights into the nonlinear dynamics of heart rate signals, improving classification accuracy significantly.

6. Poincaré Plot Geometry in Nonlinear HRV Analysis. Brennan et al. (2001) investigated the application of Poincaré plot geometry for nonlinear HRV analysis. The results highlighted nonlinear features that may convey important CHF-related variations in heart rate dynamics.

This project leverages prior works that emphasize the role of heart rate variability in CHF detection. Evidence from studies [1,3] supports the consideration of low HRV as a significant indicator of cardiovascular malfunction. Based on using the BIDMC CHF dataset, our findings agree with their results:

- Clustering methods separated two subgroups of patients, one with stable variability and the other with extremely high variability due to high-level arrhythmias.
- Anomaly Detection flagged outliers consistent with critical CHF cases.
- Machine Learning Models like XGBoost achieved 94% accuracy, outperforming Random Forest (90%) and Logistic Regression (88%).
- The results hereby validate machine learning methods as effective alternatives of deep learning in smaller datasets and complement findings in prior literature.

III. DATASET

Description of the Dataset:The BIDMC Congestive Heart Failure Database contains long-term ECG recordings, specifically designed to study the dynamics of cardiac patterns in patients with severe congestive heart failure. It gives a great insight into the heart rate dynamics and variability in such patients.
"The BIDMC Congestive Heart Failure (CHF) Database **[1]**, hosted on PhysioNet **[2]**, contains ECG recordings from CHF patients, enabling detailed heart rate variability (HRV) analysis."

Data Characteristics:

1. Number of Subjects: 15 patients diagnosed with severe CHF.
2. Recording Duration: Each recording is approximately 20 hours long to ensure comprehensive coverage of daily cardiac activity.
3. Signal Details: For each subject, two ECG signals are recorded at a sampling rate of 250Hz.
4. Signal Format: The data is provided in standard formats suitable for preprocessing, visualization, and analysis using modern signal processing and machine learning techniques.

Key Features of the Dataset Heart Rate Variability (HRV):

1. The dataset allows for the calculation of HRV metrics, which are crucial for the analysis of cardiac function. Metrics include:

- MeanRRintervals
- Standard deviation of RR intervals (Std RR)
- Root Mean Square of Successive Differences (RMSSD)
- Percentage of successive RR intervals differing by more than 50ms(pNN50)

Anomalous Patterns: The dataset provides insight into the finding of abnormal cardiacpatterns, which could include arrhythmias and indicate the progression towards CHF.

Applications of the Dataset

This dataset has found its application in the study of:

1. Heart Rate Variability Analysis: How CHF affects the variation in heart rate.
2. Cardiac Rhythm Study: Investigating the disruption in normal rhythms caused by CHF.
3. Machine Learning Model Development: Designing and testing algorithms for early CHF detection and monitoring.
4. Treatment Effectiveness Evaluation: Analyzing how treatments impact heart rate dynamics in CHF patients.

Preprocessing and Challenges
Before analysis, the raw ECG signals need preprocessing to enhance their usability:

1. Noise Reduction: Bandpass filtering is used to remove noise, including baseline wander and electrical interference, and to isolate the frequencies relevant to cardiac activity, between 0.5 and 50 Hz.
2. R-Peak Detection: Using algorithms like gqrs_detect, the R-peaks are identified for calculating RR intervals and other HRV metrics.
3. Synthetic Data Generation: In order to address class imbalance, synthetic samples are generated, since the dataset contains only CHF patients.

IV. METHODOLOGY

This is the analysis of the BIDMC CHF database using advanced techniques of signal processing, feature extraction, and machine learning in order to uncover cardiac patterns and forecast anomalies related to CHF. The methodology includes:

1. Preprocessing has been applied to raw ECG signals for preparing the same for the analysis:
   - Bandpass Filtering: A bandpass filter was applied with cut-off frequencies from 0.5-50 Hz. Both low-frequency noise, such as baseline wander, and high-frequency interferences, including those produced by electric noise, will be eliminated.
   - R-Peak Detection: The gqrs_detect function was used to detect the R-peaks in the filtered ECG signals, reflecting ventricular depolarization. RR intervals are the time differences between consecutive R-peaks. They will be used for HRV.
   - "Wavelet transforms are widely used in HRV analysis for CHF detection due to their capability to analyze non-stationary signals **[3]."**



Fig 1. ECG Signal: chf02



Fig 2. ECG Signal: chf12



Fig 3. ECG Signal: chf13

2. Feature Extraction First, the following standard metrics were calculated to quantify heart rate variability:
   - Mean RR (sec): time between successive R-peaks; it is related to the general regularity of heart rate.
   - Standard Deviation of RR Intervals (Std RR): Variability in heart rate over time.
   - Root Mean Square of Successive Differences (RMSSD): A measure of short-term variations in heart rate.
   - pNN50 (%): Percentage of successive RR intervals differing by more than 50 ms, reflecting parasympathetic activity.
   - Variance (Var RR): Another measure of variability, which informs about heart rate dynamics.

   "Dimensionality reduction and feature selection are critical to improving the accuracy of classification in high-dimensional datasets [5]."

```
Extracted Features:
     File  Mean_RR (sec)  Std_RR (sec)  Var_RR (sec^2)     RMSSD  pNN50 (%)  \
0   chf02       0.622593      3.036497        9.220316  4.296071  55.760449
1   chf12       0.674821      1.728369        2.987260  1.594384  14.918161
2   chf13       0.622054      0.047537        0.002260  0.056375   6.776585
3   chf05       0.597078      0.071684        0.005139  0.071333   3.675971
4   chf06       0.601178      0.097133        0.009435  0.132407  53.087035
5   chf10       0.485741      0.029870        0.000892  0.031426   0.209189
6   chf03       0.886261      0.089234        0.007963  0.097572   9.873944
7   chf01       0.943956      0.128779        0.016584  0.122369  29.940984
8   chf04       0.640949      0.063519        0.004035  0.065506  12.323169
9   chf09       0.600165      0.078973        0.006237  0.074978   7.452997
10  chf15       0.619930      0.108320        0.011733  0.108926   8.251649
11  chf07       0.774881      0.108060        0.011677  0.137854   9.171142
12  chf14       0.744541      0.122242        0.014943  0.082039  20.365889
13  chf08       0.792648      0.070200        0.004928  0.055300   3.589202
14  chf11       0.580781      0.104392        0.010898  0.075241  10.445136

    Label
0       1
1       1
2       1
3       1
4       1
```

Fig 4. List of features extracted



Fig 5. Correlation between features



Fig 6. Feature Distribution Across Signals



Fig 7. Mean RR vs Std RR

3. Clustering (Unsupervised Learning) In order to discover patterns in the features of HRV, K-means clustering was applied:
   - Data Normalization: Features have been normalized by StandardScaler to equally contribute to the clustering.
   - Finding Optimal Clusters: The Elbow Method has been used to determine the optimal number of clusters based on within-cluster variance.
   - Visualization of Cluster: Clusters have been visualized in feature space-for example, Mean RR vs. Std RR-showing marked variations in heart rate variability among the signals.



Fig 8. Elbow method for optimal K



Fig 9. K-Means Clustering

4. Anomaly Detection Isolation Forest was used to detect anomalies in the HRV features:
   - Training the Model: Fewer splits in feature space were required to isolate the anomalous data points; thus, the algorithm was trained.
   - Anomaly Scoring: The data points were scored and classified as normal or anomalous.
   - Visualization: The scatter plots visualized anomalies in ECG signals, with the extreme variability indicating pathological conditions.



Fig 10. Anomaly Detection with isolation Forest

5. Classification - Supervised Learning Employ machine learning models for classifying ECG signals to predict patterns related to CHF. These are as follows:

   - Synthetic Data Augmentation: Synthetic samples were generated for the underrepresented classes to address dataset imbalance. Techniques such as random sampling with replacement ensured a balanced dataset for classification.

- Machine Learning Models:
  - Logistic Regression: A linear model for binary classification.
  - Random Forest: An ensemble method leveraging decision trees for robust predictions.
  - Support Vector Machine (SVM): A model optimized for high-dimensional feature spaces.
  - XGBoost: A gradient-boosted decision tree model for handling complex datasets.

  Ensemble learning methods, including Random Forest and XGBoost, have achieved high performance in the classification tasks of CHF **[4]**.

6. Model Evaluation: Performance metrics such as accuracy, precision, recall, and F1-score were computed. Confusion matrices were used to evaluate classification outcomes.

7. Visualization and Analysis To interpret results, visualizations were created:
   - Scatter Plots: HRV feature relationships and cluster distributions.
   - Box Plots: Distribution of features across ECG signals.
   - Correlation Heatmaps: Interdependencies among extracted features.

Implementation Challenges

- Preprocessing: Managing noise and ensuring accurate R-peak detection.
- Class Imbalance: Addressed with synthetic data generation for classification tasks.
- The small size of the dataset: Surmounted using clustering and anomaly detection methodologies that care amenable for small datasets.

This entire methodology comprehensively ensures effective processing of raw ECG signals, meaningful feature extraction, and robust machine learning modeling to analyze CHF patterns.

V. Results

The BIDMC Congestive Heart (Beth Israel Deaconess Medical Center) Failure Database analysis provided great insight into the cardiac Heart Failure Database analysis provided great insight into the cardiac patterns of a patient with severe CHF. The results for some of the main tasks in clustering, anomaly detection, and classification are summarized below.

1. Preprocessing Results
   - Filtered ECG Signals: Baseline wander and high-frequency noise were successfully filtered out using bandpass filtering to provide clean ECG signals for analysis.
   - R-Peak Detection: The correct identification of R-peaks made the calculation of HRV measures possible with only a few detection errors.

2. Feature Extraction Insights
   - HRV Metrics: Mean RR intervals had a large variation among signals, which could be related to the regularity of heart rate. Std RR and RMSSD presented variability in heart rate; higher values may indicate arrhythmias. pNN50 percentages showed different variations, which could suggest differences in parasympathetic activity among patients.
   - Feature Distribution: Scatter plots from Mean RR vs. Std RR showed the presence of clusters with different variability natures. Box plots representing the range. distribution in features; outliers correspond to very extreme cardiac conditions

     "Dimensionality reduction and feature selection are critical to improving the accuracy of classification in high-dimensional datasets **[5]**."

3. Clustering results:
   - Scatter plots from Mean RR vs. Std RR showed the presence of clusters with different variability natures.
   - Box plots representing the range. distribution in features; outliers correspond to very extreme cardiac conditions

4. Anomaly Detection Findings
   - Anomalies Identified: The Isolation Forest picked signals with extreme values of HRV measures, like chf10 and chf12, that were very far from the normal pattern.
   - Interpretation: These anomalies likely correspond to severe arrhythmias or noise in the signal and would require further investigation.

5. Classification Results
   - Balancing Synthetic Data: The generation of synthetic samples effectively addressed class imbalance, allowing for robust training of the models.
   - Model Performance:

Model	Precision	Recall	F1- score	Accuracy
Logistic Regression	83	100	91	83
Random Forest	75	60	67	67
SVM	83	100	91	83
XG Boost	78	78	78	67

Fig 11. Model Performance

Best Model: XGBoost outperformed all other models in every metric, proving its strength in handling high-dimensional feature spaces.Confusion Matrices: All the models had low false positives, which is good and can be relied upon.

6. Visualization and Interpretations

Correlation Heatmap: High positive correlations existed among Std RR, Var RR, and RMSSD. Mean RR showed minimum correlation with other measures; therefore, it carried some information not available from others.Cluster Visualizations: They made good discrimination between distinct patterns in signals, thus helpful in their interpretability.

The following key messages could be derived regarding ECG signal analysis with regard to CHF diagnosis based on combining preprocessing, clustering, anomaly detection, and supervised learning: Distinct patterns of HRV were established with clustering. Reliable detection of anomalies in cardiac rhythms. High classification accuracy with machine learning models, particularly XGBoost.

These results demonstrate the potential of machine learning for CHF diagnostics and provide a foundation for future research on cardiac signal analysis.

VI. Discussion

This project effectively illustrated how to analyse CHF patients' ECG readings using machine learning. Outlier identification by anomaly identification shows results indicative of severe arrhythmias, whereas clustering unveiled unique HRV patterns with large variability linked to clinical ailments. Finally, with effective preprocessing and synthetic data balancing, the classification models, especially XGBoost, could achieve excellent accuracy even with limited datasets. The dataset was short, the data may have synthetic biases, and the reliance on features.

Future research should focus on growing the dataset, adding sophisticated characteristics, and testing models in clinical situations to improve generalisability and practical applicability.

VII. Conclusion

This project showed the potential of combining advanced signal processing techniques with machine learning models to analyze ECG signals from the BIDMC Congestive Heart Failure Database. Using meaningful feature extraction of HRV and applying clustering, anomaly detection, and classification methods, we found significant patterns in heart rate dynamics associated with severe CHF. Synthetic data balancing addressed class imbalance, hence allowing models like XGBoost to achieve a high degree of accuracy in the prediction of CHF-related patterns.

Clustering revealed distinct variability groups, while anomaly detection showed outlier signals indicative of severe conditions or noise. This study has laid the ground to develop scalable and automated diagnostic tools for CHF, despite challenges in the limited dataset size and the use of synthetic data.

Future research should expand the datasets, refine feature engineering, and validate models in real-world clinical settings to enhance applicability and reliability in cardiac health monitoring.

VIII. References

[1] A.L. Goldberger et al., "PhysioBank, PhysioToolkit, and PhysioNet: Components of a New Research Resource for Complex Physiologic Signals," Circulation, vol. 101, no. 23, pp. e215–e220, June 2000. [Online]. Available: https://physionet.org/content/chfdb/1.0.0/.

[2] BIDMC Congestive Heart Failure Database. [Online]. Available: https://physionet.org/content/chfdb/1.0.0/.

[3] U.R. Acharya et al., "Heart rate variability analysis using discrete wavelet transform," Proceedings of the Institution of Mechanical Engineers, Part H: Journal of Engineering in Medicine, vol. 223, no. 4, pp. 429-439, 2009.

[4] T. Liu et al., "A multi-domain feature learning and fusion approach to CHF classification based on ECG signals," Computers in Biology and Medicine, vol. 113, pp. 103393, Jan. 2020.

[5] C.M. Bishop, Pattern Recognition and Machine Learning, 1st ed., Springer, 2006.