

LABORATORY REPORT

Algorithm Laboratory (CS-39001)

B.Tech Program in ECSc

Submitted By

Name:- SANNIDHI DEB

Roll No: 2330044



Kalinga Institute of Industrial Technology

(Deemed to be University) Bhubaneswar, India

Autumn, 2025

Table of Contents

#	Title	Date of Experiment	Date of Submission	Remarks
1.	Revision of Data Structures	24/07/2025	06/08/2025	
2.	Design and Analysis of Fundamental Algorithms	07/08/2025	20/08/2025	
3.	Divide and Conquer Method	14/08/2025	20/08/2025	
4.	Heap Sort	21/08/2025	27/08/2025	
5.	Greedy Algorithm	18/09/2025	24/09/2025	
6.	Huffman Coding	01/10/2025	10/10/2025	
7.	Minimum Spanning Tree	01/10/2025	10/10/2025	
8.	Single Source Shortest Path	09/10/2025	15/10/2025	
9.	Matrix Chain Multiplication (MCM) and Longest Common Subsequence (LCS)	16/10/2025	22/10/2025	
10.	<u>Open Ended Experiment :</u> Restaurant Auto Scheduling System	23/10/2025	30/10/2025	

Experiment Number	10 (Open Ended Experiment)																						
Experiment Title	<p>To design and implement a Greedy algorithm that schedules restaurant orders to achieve maximum total profit, ensuring that all accepted orders are completed before their deadlines.</p> <p>Number of orders: 5</p> <table border="1"> <tr> <td>Order</td><td>1</td><td>2</td><td>3</td><td>4</td><td>5</td></tr> <tr> <td>Deadline</td><td>2</td><td>1</td><td>2</td><td>1</td><td>3</td></tr> <tr> <td>Profit</td><td>100</td><td>19</td><td>27</td><td>25</td><td>15</td></tr> </table>					Order	1	2	3	4	5	Deadline	2	1	2	1	3	Profit	100	19	27	25	15
Order	1	2	3	4	5																		
Deadline	2	1	2	1	3																		
Profit	100	19	27	25	15																		
Date of Experiment	23/10/2025																						
Date of Submission	30/10/2025																						

1.Algorithm:-

1. Input the number of food orders
2. For each order, input : <ul style="list-style-type: none"> • Profit (revenue for preparing order) • Deadline (latest time slot before which it's served)
3. Sort all orders in descending order of Profit
4. Initialize time slots as empty
5. For each order in sorted order : <ul style="list-style-type: none"> • Schedule in latest available time slot before deadline • If a slot is free, assign there.
6. Display selected orders and total profit
Sannidhi Deb
2330044

2. Code:-

```
#include <stdio.h>
```

```
struct Order {  
    int id;  
    int deadline;  
    int profit;  
};
```

```
void sortOrders(struct Order orders[], int n) {  
    struct Order temp;  
    for (int i = 0; i < n - 1; i++) {  
        for (int j = 0; j < n - i - 1; j++) {  
            if (orders[j].profit < orders[j + 1].profit) {  
                temp = orders[j];  
                orders[j] = orders[j + 1];  
                orders[j + 1] = temp;  
            }  
        }  
    }  
}
```

```
int findMaxDeadline(struct Order orders[], int n) {  
    int max = orders[0].deadline;  
    for (int i = 1; i < n; i++) {  
        if (orders[i].deadline > max)  
            max = orders[i].deadline;  
    }  
    return max;  
}
```

```
void scheduleOrders(struct Order orders[], int n) {  
    int maxDeadline = findMaxDeadline(orders, n);  
    int slots[maxDeadline + 1];  
    for (int i = 0; i <= maxDeadline; i++)  
        slots[i] = -1;  
  
    int totalProfit = 0;  
  
    for (int i = 0; i < n; i++) {  
        for (int j = orders[i].deadline; j > 0; j--) {  
            if (slots[j] == -1) {
```

```

        slots[j] = i;
        totalProfit += orders[i].profit;
        break;
    }
}
printf("\nSannidhi Deb\n 2330044\n\n");
printf("\nScheduled Orders (within deadlines):\n");
for (int i = 1; i <= maxDeadline; i++) {
    if (slots[i] != -1) {
        int idx = slots[i];
        printf("Order %d (Deadline: %d, Profit: %d)\n",
            orders[idx].id, orders[idx].deadline, orders[idx].profit);
    }
}
printf("\nTotal Profit: %d\n", totalProfit);
}

```

```

int main() {
    int n;
    printf("Enter number of orders: ");
    scanf("%d", &n);

    struct Order orders[n];
    for (int i = 0; i < n; i++) {
        orders[i].id = i + 1;
        printf("Enter Deadline and Profit for Order %d: ", i + 1);
        scanf("%d %d", &orders[i].deadline, &orders[i].profit);
    }

    sortOrders(orders, n);
    scheduleOrders(orders, n);
    return 0;
}

```

3.Results/Output:- Entire Screen Shot including Date & Time:-

```
C:\Users\debsa\OneDrive\Desktop\AL_Lab_044>gcc open_ended_exp.c -o open_ended_exp

C:\Users\debsa\OneDrive\Desktop\AL_Lab_044>open_ended_exp
Enter number of orders: 5
Enter Deadline and Profit for Order 1: 2 100
Enter Deadline and Profit for Order 2: 1 19
Enter Deadline and Profit for Order 3: 2 27
Enter Deadline and Profit for Order 4: 1 25
Enter Deadline and Profit for Order 5: 3 15

Sannidhi Deb
2330044

Scheduled Orders (within deadlines):
Order 3 (Deadline: 2, Profit: 27)
Order 1 (Deadline: 2, Profit: 100)
Order 5 (Deadline: 3, Profit: 15)

Total Profit: 142

C:\Users\debsa\OneDrive\Desktop\AL_Lab_044>
```

4. Remarks:-


1. What type of algorithm is used?

The algorithm used is Greedy Algorithm based on profit maximisation strategy.
Sannidhi Deb, 2330044

2. Analyze the complexity of your algorithm.

Time Complexity
sorting orders by profit :- $O(n \log n)$
Allocating slots for each order upto 'n' slots :- $O(n^2)$
Therefore, overall complexity :- $O(n^2)$
Sannidhi Deb, 2330044

3. Any other observations?



5. Conclusion:- The Restaurant Auto Scheduling System implemented using the Job Sequencing with Deadlines (Greedy Algorithm) approach efficiently schedules restaurant orders to maximize total profit while ensuring deadlines are met. This experiment demonstrates how greedy strategies can be applied to real-world restaurant operations and other scheduling tasks involving limited time and high-profit optimization.

Sannidhi Deb
(2330044)

Sannidhi Deb

Signature of the FIC

(Name of the FIC)

