



Evaluation results

There are three levels of importance in pitfalls according to their impact on the ontology:

- **Critical** It is crucial to correct the pitfall. Otherwise, it could affect the ontology consistency, reasoning, applicability, etc.
- **Important** Though not critical for ontology function, it is important to correct this type of pitfall.
- **Minor** It is not really a problem, but by correcting it we will make the ontology nicer.

Pitfalls detected:

Results for P04: Creating unconnected ontology elements. 1 case	1 case	Minor
Results for P07: Merging different concepts in the same class.	3 cases	Minor
Results for P08: Missing annotations.	69 cases	Minor
Results for P11: Missing domain or range in properties.	8 cases	Important
Object and/or datatype properties without domain or range (or none of them) are included in the ontology. • This pitfall appears in the following elements: > http://www.w3.org/2006/time#hasDuration > http://www.w3.org/2006/time#hasTime > http://www.w3.org/2006/time#hasDurationDescription > http://purl.obolibrary.org/obo/RO_0000053 > http://purl.obolibrary.org/obo/RO_0000059 > http://www.w3.org/2006/time#day > http://www.w3.org/2006/time#year > http://www.w3.org/2006/time#month • Tip: Solving this pitfall may lead to new results for other pitfalls and suggestions. We encourage you to solve all cases when needed and see what else you can get from OOPS!		
Results for P12: Equivalent properties not explicitly declared. 1 case	1 case	Important
The ontology lacks information about equivalent properties (owl:equivalentProperty) in the cases of duplicated relationships and/or attributes. • The following relations could be defined as equivalent: > http://umaine.edu/oppo/core/v1#hasDurationDescription, http://www.w3.org/2006/time#hasDurationDescription		
Results for P13: Inverse relationships not explicitly declared.	38 cases	Minor
Results for P22: Using different naming conventions in the ontology.	Ontology*	Minor
Results for P24: Using recursive definitions.	2 cases	Important
An ontology element (a class, an object property or a datatype property) is used in its own definition. Some examples of this would be: (a) the definition of a class as the enumeration of several classes including itself; (b) the appearance of a class within its owl:equivalentClass or rdfs:subClassOf axioms; (c) the appearance of an object property in its rdfs:domain or range rdfs:range definitions; or (d) the appearance of a datatype property in its rdfs:domain definition.		



> <http://www.w3.org/2006/time#Interval>

Results for P30: Equivalent classes not explicitly declared.

2 cases

Important

This pitfall consists in missing the definition of equivalent classes (`owl:equivalentClass`) in case of duplicated concepts. When an ontology reuses terms from other ontologies, classes that have the same meaning should be defined as equivalent in order to benefit the interoperability between both ontologies.

• The following classes might be equivalent:

> http://purl.obolibrary.org/obo/BFO_0000023, http://purl.obolibrary.org/obo/BFO_0000034, <https://w3id.org/dpv/dpv-owl#Purpose>
 > http://purl.obolibrary.org/obo/BFO_0000034, <https://w3id.org/dpv/dpv-owl#Purpose>

Suggestions or warnings:

SUGGESTION: symmetric or transitive object properties| 16 cases

According to the highest importance level of pitfall found in your ontology the conformace badge suggested is "Important pitfalls" (see below). You can use the following HTML code to insert the badge within your ontology documentation:



```
<p>
<a href="http://oops.linkeddata.es">
</a>
</p>
```

References

[1] Aguado-De Cea, G., Montiel-Ponsoda, E., Poveda-Villalón, M., and Giraldo-Pasmin, O.X. (2015).

[2] Noy, N. F., McGuinness, D. L., et al. (2001).

[3] Gómez-Pérez, A. (1999).

[4] Montiel-Ponsoda, E., Vila Suero, D., Villazón-Terrazas, B., Dunsire, G., Escolano Rodríguez, E., Gómez-Pérez, A. (2011).

[5] Vrandečić, D. (2010).

[6] Gómez-Pérez, A. (2004).

[7] Rector, A., Drummond, N., Horridge, M., Rogers, J., Knublauch, H., Stevens, R., Wang, H., and Wroe, C. (2004).

[8] Hogan, A., Harth, A., Passant, A., Decker, S., and Polleres, A. (2010).



[10] Bernes-Lee Tim. (2006).

[11] Heath, T. and Bizer, C. (2011).

[12] Vatan, B. (2012).

Enter your ontology to scan:

```
<?xml version="1.0" encoding="utf-8" ?>
<rdf:RDF xmlns:rdf="http://www.w3.org/1999/02/22-rdf-syntax-ns#"
  xmlns:owl="http://www.w3.org/2002/07/owl#"
  xmlns:dc="http://purl.org/dc/terms/"
  xmlns:rdfs="http://www.w3.org/2000/01/rdf-schema#"
  xmlns:skos="http://www.w3.org/2004/02/skos/core#">

  <owl:Ontology rdf:about="http://umaine.edu/oppo/core/v1#">
```

☐ Uncheck this checkbox if you don't want us to keep a copy of your ontology.

Scan

[Advanced evaluation](#)

How to cite OOPS!

Poveda-Villalón, María, Asunción Gómez-Pérez, and Mari Carmen Suárez-Figueroa. "OOPS!(Ontology Pitfall Scanner!): An on-line tool for ontology evaluation." International Journal on Semantic Web and Information Systems (IJSWIS) 10.2 (2014): 7-34.

BibTex:

```
@article{poveda2014oops,
  title={OOPS! (Ontology Pitfall Scanner!): An On-line Tool for Ontology Evaluation},
  author={Poveda-Villalón, María and Gómez-Pérez, Asunción and Suárez-Figueroa, Mari Carmen},
  journal={International Journal on Semantic Web and Information Systems (IJSWIS)},
  volume={10},
  number={2},
  pages={7-34},
  year={2014},
  publisher={IGI Global}
}
```



Escuela Técnica
Superior de
Ingenieros Informáticos



Univ
Polit
de N

[María Poveda](#)

Contact email: [oops\(at\)delicias.dia.fi.upm.es](mailto:oops(at)delicias.dia.fi.upm.es). Latest revision April 2021