

Week-12-User-Defined Functions

Week-12-Practice Session-Coding

Question **1**

Correct

Marked out of
1.00[Flag question](#)

A binary number is a combination of 1s and 0s. Its n^{th} least significant digit is the n^{th} digit starting from the right starting with 1. Given a decimal number, convert it to binary and determine the value of the 4^{th} least significant digit.

Example

number = 23

- Convert the decimal number 23 to binary number: $23^{10} = 2^4 + 2^2 + 2^1 + 2^0 = (10111)_2$.
- The value of the 4^{th} index from the right in the binary representation is 0.

[Source code](#)

Answer: (penalty regime: 0 %)

Reset answer

```
1  /*
2  * Complete the 'fourthBit' function below.
3  *
4  * The function is expected to return an INTEGER.
5  * The function accepts INTEGER number as parameter.
6  */
7
8  int fourthBit(int number)
9  {
10     int binary[32];
11     int i=0;
12     while(number>0)
13     {
14         binary[i]=number%2;
15         number/=2;
16         i++;
17     }
18     if(i>=4)
19     {
20         return binary[3];
21     }
22     else
23     return 0;
24
25 }
```

Result

	Test	Expected	Got	
✓	printf("%d", fourthBit(32))	0	0	✓
✓	printf("%d", fourthBit(77))	1	1	✓

Passed all tests! ✓

Question **2**

Correct

Marked out of
1.00

[Flag question](#)

Determine the factors of a number (i.e., all positive integer values that evenly divide into a number) and then return the p^{th} element of the list, sorted ascending. If there is no p^{th} element, return 0.

Example

$n = 20$

$p = 3$

The factors of 20 in ascending order are {1, 2, 4, 5, 10, 20}. Using 1-based indexing, if $p = 3$, then 4 is returned. If $p > 6$, 0 would be returned.

Source code

Answer: (penalty regime: 0 %)

Reset answer

```
1  /*
2  * Complete the 'pthFactor' function below.
3  *
4  * The function is expected to return a LONG_INTEGER.
5  * The function accepts following parameters:
6  * 1. LONG_INTEGER n
7  * 2. LONG_INTEGER p
8  */
9
10 long pthFactor(long n, long p)
11 {
12     int count=0;
13     for(long i=1;i<=n;++i)
14     {
15         if(n%i==0)
16         {
17             count++;
18             if(count == p)
19             {
20                 return i;
21             }
22         }
23     }
24     return 0;
25 }
26 }
```

Result

	Test	Expected	Got	
✓	<code>printf("%ld", pthFactor(10, 3))</code>	5	5	✓
✓	<code>printf("%ld", pthFactor(10, 5))</code>	0	0	✓
✓	<code>printf("%ld", pthFactor(1, 1))</code>	1	1	✓

Passed all tests! ✓