

```

class A {
    int a = 2;
}

class B extends A {
    int a = 5;
}

class Test {
    p.s.v. main(—) {
        A x = new B();
        S.op(x.a);
    }
}

```

o/p

2

```

class A {
    static int a = 5;
}

class B extends A {
    static int a = 9;
}

class Test {
    p.s.v. main(—) {
        A x = new B();
        S.op(x.a);
    }
}

```

o/p

5

```

class A {
    void pro() {
        S.op("Hi");
    }
}

class B extends A {
    void pro() {
        S.op("Hello");
    }
}

p.s.v. main(—) {
    A x = new B();
    x.pro();
}

```

o/p

Hello

```

class A {
    static void pro() {
        S.op("Namaste");
    }
}

class B extends A {
    static void pro() {
        S.op("Namastekar");
    }
}

class Test {
    p.s.v. main(—) {
        A x = new B();
        x.pro();
    }
}

```

o/p

Namaste

```

class Car {
}

class SportsCar extends Car {
}

class Test {
    static void pro(Car car) {
        S.op("Mai Car Run");
    }

    static void pro(SportsCar sportsCar) {
        S.op("Mai Sports Car Run");
    }

    p.s.v. main(—) {
        Car car = new SportsCar();
        pro(car);
    }
}

```

o/p

Mai Car Run