Daniel Santana Bueno
Introducción al uso de python
2ºDAW

1. Crea un entorno virtual (nombre a tu elección).

```
PS C:\Users\2DAW\Documents\python> python -m venv entorno_actividad1
```

2. Activa el entorno

```
PS C:\Users\2DAW\Documents\python> .\entorno_actividad1\Scripts\activate
(entorno_actividad1) PS C:\Users\2DAW\Documents\python>
```

3. Lista los paquetes instalados.

```
(entorno_actividad1) PS C:\Users\2DAW\Documents\python> pip list
Package Version
------- -------
pip     26.2.1
```

4. Instala el paquete pandas

```
(entorno_actividad1) PS C:\Users\2DAW\Documents\python> pip install pandas
Collecting pandas
  Using cached pandas-3.0.6-cp314-cp314-win_amd64.whl.metadata (19 kB)
Collecting numpy>=2.3.3 (from pandas)
  Using cached numpy-2.5.3-cp314-cp314-win_amd64.whl.metadata (6.6 kB)
Collecting python-dateutil>=2.8.2 (from pandas)
  Using cached python_dateutil-2.9.0.post0-py2.py3-none-any.whl.metadata (8.4 kB)
Collecting tzdata (from pandas)
  Using cached tzdata-2026.4-py2.py3-none-any.whl.metadata (1.4 kB)
Collecting six>=1.5 (from python-dateutil>=2.8.2->pandas)
  Using cached six-1.17.0-py2.py3-none-any.whl.metadata (1.7 kB)
Using cached pandas-3.0.6-cp314-cp314-win_amd64.whl (9.8 MB)
Using cached numpy-2.5.3-cp314-cp314-win_amd64.whl (12.7 MB)
Using cached python_dateutil-2.9.0.post0-py2.py3-none-any.whl (229 kB)
Using cached six-1.17.0-py2.py3-none-any.whl (11 kB)
Using cached tzdata-2026.4-py2.py3-none-any.whl (347 kB)
Installing collected packages: tzdata, six, numpy, python-dateutil, pandas
Successfully installed numpy-2.5.3 pandas-3.0.6 python-dateutil-2.9.0.post0 six-1.17.0 tzdata-2026.4
```

5. Lista los paquetes instalados.

```
(entorno_actividad1) PS C:\Users\2DAW\Documents\python> pip list
Package         Version
--------------- -----------
numpy           2.5.3
pandas          3.0.6
pip             26.2.1
python-dateutil 2.9.0.post0
six             1.17.0
tzdata          2026.4
```

6. Desactiva el entorno.

Daniel Santana Bueno
Introducción al uso de python
2ºDAW

```
(entorno_actividad1) PS C:\Users\2DAW\Documents\python> deactivate

PS C:\Users\2DAW\Documents\python>
```

7. Lista los paquetes instalados.

```
PS C:\Users\2DAW\Documents\python> pip list
Package Version
------- -------
pip     26.2.1
```

8. Vuelve a activar el entorno.

```
PS C:\Users\2DAW\Documents\python> .\entorno_actividad1\Scripts\activate
(entorno_actividad1) PS C:\Users\2DAW\Documents\python>
```

9. Desinstala el paquete de pandas.

```
(entorno_actividad1) PS C:\Users\2DAW\Documents\python> pip uninstall pandas
Found existing installation: pandas 3.0.6
Uninstalling pandas-3.0.6:
  Would remove:
    c:\users\2daw\documents\python\entorno_actividad1\lib\site-packages\pandas-3.0.6.dist-info\*
    c:\users\2daw\documents\python\entorno_actividad1\lib\site-packages\pandas.libs\msvcp140-a4c2229bdc2a2a630acdc095b4d86008.dll
    c:\users\2daw\documents\python\entorno_actividad1\lib\site-packages\pandas\*
Proceed (Y/n)? Y
  Successfully uninstalled pandas-3.0.6
```

10. Lista los paquetes instalados.

```
(entorno_actividad1) PS C:\Users\2DAW\Documents\python> pip list
Package         Version
--------------- -----------
numpy           2.5.3
pip             26.2.1
python-dateutil 2.9.0.post0
six             1.17.0
tzdata          2026.4

(entorno_actividad1) PS C:\Users\2DAW\Documents\python>
```