


Tower of Hanoi – Solution #2


Prof. Wade Fagen-Ulmschneider

I ILLINOIS


Moves Made:




Moves Made:



Moves Made:



Moves Made:




`Stack[0]`

`Stack[1]`

`Stack[2]`

Moves Made:




Stack[0]

Stack[1]

Stack[2]

Moves Made:



Stack[0] Stack[1] Stack[2]

Moves Made:



Stack[0] Stack[1] Stack[2]

Moves Made:



Stack[0] Stack[1] Stack[2]

Moves Made:



Stack[0] Stack[1] Stack[2]

Moves Made:


0 → 1



Stack[0] Stack[1] Stack[2]

Moves Made:

0 → 1



Stack[0]


Stack[1]

Stack[2]

Moves Made:

0 → 1

0 → 2



Stack[0]


Stack[1]

Stack[2]

Moves Made:

0 → 1

0 → 2



Stack[0]

Stack[1]


Stack[2]

Moves Made:

0 → 1

0 → 2

1 → 2



Stack[0]

Stack[1]

Stack[2]

Moves Made:

0 → 1

0 → 2

1 → 2



Stack[0]

Stack[1]

Stack[2]


Moves Made:

0 → 1

0 → 2

1 → 2

0 → 1



Stack[0]

Stack[1]

Stack[2]


Moves Made:

0 → 1

0 → 2

1 → 2

0 → 1



Stack[0]

Stack[1]

Stack[2]


Moves Made:

0 → 1

0 → 2


1 → 2

0 → 1




Stack[0] Stack[1] Stack[2]

...unrolling, and recusing, and unrolling...
...many moves later...



Moves Planned:

`move(Source[0...3] → Target)`




Moves Planned:

move(Source[0...3] → Target)

○ → move(Source[1...3] → Spare)

○ → move(Source[0] → Target)

○ → move(Spare[1...3] → Target)



Moves Planned:


move(Source[0...3] → Target)

→ move(Source[1...3] → Spare)

SWAP: Old "Spare" is now "Target"!

→ move(Source[0] → Target)

→ Move(Spare[1...3] → Target)



Moves Planned:

move(Source[0...3] → Target)

→ move(Source[1...3] → Spare)

SWAP: Old "Spare" is now "Target"!


→ move(Source[2...3] → Spare)


→ move(Source[1] → Target)

→ Move(Spare[1...3] → Target)

→ move(Source[0] → Target)

→ Move(Spare[1...3] → Target)





Moves Planned:

move(Source[0...3] → Target)
→ move(Source[1...3] → Spare)
→ move(Source[2...3] → Spare)
→ move(Source[3...3] → Spare)
→ move(Source[2] → Target)
→ Move(Spare[3...3] → Target)
→ move(Source[1] → Target)
→ Move(Spare[1...3] → Target)
→ move(Source[0] → Target)
→ Move(Spare[1...3] → Target)

Moves Planned:

move(Source[0...3] → Target)

→ move(Source[1...3] → Spare)

→ move(Source[2...3] → Spare)

→ move(Source[3...3] → Spare) → ...

→ move(Source[2] → Target) → ...

→ Move(Spare[3...3] → Target) → ...

→ move(Source[1] → Target) → ...

→ Move(Spare[1...3] → Target) → ...

→ move(Source[0] → Target) → ...

→ Move(Spare[1...3] → Target) → ...

Moves Planned:

`move(Source[0...3] → Target)`

→ `move(Source[1...3] → Spare) → ...`

→ `move(Source[0] → Target) → ...`

→ `Move(Spare[1...3] → Target) → ...`

Moves Planned:

`move(Source[start...end] → Target)`

→ `move(Source[(start+1)...end] → Spare) → ...`

→ `move(Source[start] → Target) → ...`

→ `Move(Spare[(start+1)...end] → Target) → ...`

cpp-tower-solution2/Game.cpp

```
45 void Game::_move(  
46     unsigned start, unsigned end,  
47     Stack & source, Stack & target, Stack & spare,  
48     unsigned depth  
49 ) {  
50     cout << "Planning (depth=" << depth++ << "): Move [" << /* ... */  
51  
52     // Check if we are only moving one cube:  
53     if (start == end) {  
54         // If so, move it directly:  
55         _moveCube( source, target );  
56         cout << *this << endl;  
57     } else {  
58         // Otherwise, use our move strategy:  
59         _move(start + 1, end , source, spare , target, depth);  
60         _move(start      , start, source, target, spare , depth);  
61         _move(start + 1, end , spare , target, source, depth);  
62     }  
63 }
```