

Rajalakshmi Engineering College

Name: Santhosh G
Email: 240701473@rajalakshmi.edu.in
Roll no: 240701473
Phone: 8883772237
Branch: REC
Department: I CSE FE
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_MCQ_Updated

Attempt : 1
Total Mark : 20
Marks Obtained : 0

Section 1 : MCQ

1. Consider the provided pseudo code. How can you initialize an empty two-way linked list?

```
Define Structure Node
  data: Integer
  prev: Pointer to Node
  next: Pointer to Node
End Define
```

```
Define Structure TwoWayLinkedList
  head: Pointer to Node
  tail: Pointer to Node
End Define
```

Answer

Status : Skipped

Marks : 0/1

2. How do you reverse a doubly linked list?

Answer

-

Status : -

Marks : 0/1

3. What is a memory-efficient double-linked list?

Answer

-

Status : -

Marks : 0/1

4. What is the correct way to add a node at the beginning of a doubly linked list?

Answer

-

Status : -

Marks : 0/1

5. Which of the following is false about a doubly linked list?

Answer

-

Status : -

Marks : 0/1

6. Which pointer helps in traversing a doubly linked list in reverse order?

Answer

-

Status : -

Marks : 0/1

7. Where Fwd and Bwd represent forward and backward links to the adjacent elements of the list. Which of the following segments of code deletes the node pointed to by X from the doubly linked list, if it is assumed that X points to neither the first nor the last node of the list?

A doubly linked list is declared as

```
struct Node {  
    int Value;  
    struct Node *Fwd;  
    struct Node *Bwd;  
};
```

Answer

-

Status : -

Marks : 0/1

8. How do you delete a node from the middle of a doubly linked list?

Answer

-

Status : -

Marks : 0/1

9. What will be the output of the following program?

```
#include <stdio.h>  
#include <stdlib.h>
```

```
struct Node {  
    int data;  
    struct Node* next;  
    struct Node* prev;  
};
```

```

int main() {
    struct Node* head = NULL;
    struct Node* tail = NULL;
    for (int i = 0; i < 5; i++) {
        struct Node* temp = (struct Node*)malloc(sizeof(struct Node));
        temp->data = i + 1;
        temp->prev = tail;
        temp->next = NULL;
        if (tail != NULL) {
            tail->next = temp;
        } else {
            head = temp;
        }
        tail = temp;
    }
    struct Node* current = head;
    while (current != NULL) {
        printf("%d ", current->data);
        current = current->next;
    }
    return 0;
}

```

Answer

-

Status : -

Marks : 0/1

10. What will be the output of the following code?

```

#include <stdio.h>
#include <stdlib.h>

struct Node {
    int data;
    struct Node* next;
    struct Node* prev;
};

```

```

int main() {
    struct Node* head = NULL;
    struct Node* temp = (struct Node*)malloc(sizeof(struct Node));
    temp->data = 2;
    temp->next = NULL;
    temp->prev = NULL;
    head = temp;
    printf("%d\n", head->data);
    free(temp);
    return 0;
}

```

Answer

-

Status : -

Marks : 0/1

11. Which code snippet correctly deletes a node with a given value from a doubly linked list?

```

void deleteNode(Node** head_ref, Node* del_node) {
    if (*head_ref == NULL || del_node == NULL) {
        return;
    }
    if (*head_ref == del_node) {
        *head_ref = del_node->next;
    }
    if (del_node->next != NULL) {
        del_node->next->prev = del_node->prev;
    }
    if (del_node->prev != NULL) {
        del_node->prev->next = del_node->next;
    }
    free(del_node);
}

```

Answer

-

Status : -

Marks : 0/1

12. What is the main advantage of a two-way linked list over a one-way linked list?

Answer

-

Status : -

Marks : 0/1

13. How many pointers does a node in a doubly linked list have?

Answer

-

Status : -

Marks : 0/1

14. Consider the following function that refers to the head of a Doubly Linked List as the parameter. Assume that a node of a doubly linked list has the previous pointer as prev and the next pointer as next.

Assume that the reference of the head of the following doubly linked list is passed to the below function 1 <--> 2 <--> 3 <--> 4 <--> 5 <--> 6. What should be the modified linked list after the function call?

Procedure fun(head_ref: Pointer to Pointer of node)

temp = NULL

current = *head_ref

While current is not NULL

temp = current->prev

current->prev = current->next

current->next = temp

current = current->prev

End While

If temp is not NULL

*head_ref = temp->prev

End If

End Procedure

Answer

-

Status : -

Marks : 0/1

15. What happens if we insert a node at the beginning of a doubly linked list?

Answer

-

Status : -

Marks : 0/1

16. Which of the following statements correctly creates a new node for a doubly linked list?

Answer

-

Status : -

Marks : 0/1

17. What does the following code snippet do?

```
struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));  
newNode->data = value;  
newNode->next = NULL;  
newNode->prev = NULL;
```

Answer

-

Status : -

Marks : 0/1

18. Which of the following information is stored in a doubly-linked list's nodes?

Answer

-

Status : -

Marks : 0/1

19. Which of the following is true about the last node in a doubly linked list?

Answer

-

Status : -

Marks : 0/1

20. What will be the effect of setting the prev pointer of a node to NULL in a doubly linked list?

Answer

-

Status : -

Marks : 0/1