

Data Driven Framework (Continued)

- Create a reusable method for opening the application say navigate() in BaseTest - [View here](#)
 - Call the navigate() method from the Test method in LoginTest using the url key in projectconfig.properties file
 - navigate("appURL");
 - Create a reusable method for logging into the application say doLogin() in BaseTest - [View here](#)
 - This method accepts Username and Password
 - Create a locator property for 'Login' option on the www.zoho.com home page inside projectconfig.properties file
 - #Locators
 - LoginLink_classname=signin
 - Create a reusable method for clicking any UI element on the application say click() in BaseTest - [View here](#)
 - Create a reusable method say getElement() which intakes locatorKey and return the WebElement based on the locator type - [View here](#)
 - Call the getElement() from the click() to retrieve the WebElement and perform click operation on the retrieved WebElement - [View here](#)
 - Call the click() method from the doLogin() method in BaseTest using the locator key for Login option in projectconfig.properties file
 - click("LoginLink_classname");
 - Create a locator properties for 'Username' and 'Password' fields in the login page of www.zoho.com inside projectconfig.properties file
 - LoginUsername_id=id
 - LoginPassword_id=pwd
 - Create a reusable method for typing text into text box fields on the application say type() in BaseTest - [View here](#)
 - Pass the locatorKey to getElement() method and retrieve the WebElement based on the locator type
 - Perform type operations on the WebElement
 - Call the type() method from the doLogin() method in BaseTest using the locator key for Username field in projectconfig.properties file and actual Username
 - type("LoginUsername_id",Username);
 - Call the type() method from the doLogin() method in BaseTest using the locator key for Password field in projectconfig.properties file and actual Password
 - type("LoginPassword_id",Password);
 - Create a locator properties for 'Username' and 'Password' fields in the login page of www.zoho.com inside projectconfig.properties file
 - SignInButton_id=signin_submit
 - Call the click() method from the doLogin() method in BaseTest using the locator key for SignIn Button in projectconfig.properties file
 - click("SignInButton_id");
-