

Student 4 **ANUMULA VS SANTHOSH RADHA KRISHNA MURTHY** 192312043RA

4 / 4 submitted

Level 2 — 25 marks/question**L2-Q1. rotate an array (M)**

CODE

```
#include <stdio.h>
int main(){
    int a[]={1,2,3,4,5};
    int i,j,n,count,temp[20];
    scanf("%d",&n);
    printf("number of elements = %d",n);
    scanf("%d",&count);
    printf("\nNumber of positions to rotate = %d",count);
    for(i=0;i<n;i++){
        temp[i]=a[(i+count)%n];
    }
    for(i=0;i<n;i++)
        printf("%d",temp[i]);
    return 0;
}
```

INPUT

5
2

OUTPUT

number of elements = 5
Number of positions to rotate = 234512**L2-Q2. Employee (M)**

CODE

```
#include <stdio.h>
char EBMS()
```

OUTPUT

(no output)

L2-Q3. substring (M)

C

CODE

```
#include <stdio.h>
#include <string.h>
int main(){
    char str[100],sub[100];
    char *ptr;
    fgets(str,sizeof(str),stdin);
    str[strcspn(str, "\n")]=0;
    fgets(sub,sizeof(sub),stdin);
    sub[strcspn(sub, "\n")]=0;
    ptr=strstr(str,sub);
    if(ptr!=NULL){
        printf("Substring found at the index= %d",str-ptr);
    }else{
        printf("Substring not found");
    }
    return 0;
}
```

INPUT

```
b a n a n a
a n a
```

OUTPUT

Security Error: Disallowed code pattern detected.

L2-Q4. Inverse matrix (M)

C

CODE

```
#include <stdio.h>
int main(){
    int a[2][2]={4,7},{2,6};
    int inverse[2][2],det,i,j;
    for(i=0;i<2;i++){
        for(j=0;j<2;j++){
            det=(a[0][0]*a[1][1])-(a[0][1]*a[1][0]);
            if(det==0){
                printf("Inverse Doesn't exist");
            }else{
                inverse[0][0]=a[0][0]/det;
                inverse[0][1]=-a[0][1]/det;
                inverse[1][0]=-a[1][0]/det;
                inverse[1][1]=a[1][1]/det;
            }
            for(i=0;i<2;i++){
                for(j=0;j<2;j++){
                    printf("%d",inverse[i][j]);
                }
            }
        }
    }
    return 0;
}
```

OUTPUT

0000