

Instalacion de SSH

```
server@server:~$ sudo apt install ssh -y
Leyendo lista de paquetes... Hecho
Creando árbol de dependencias... Hecho
Leyendo la información de estado... Hecho
Se instalarán los siguientes paquetes NUEVOS:
  ssh
0 actualizados, 1 nuevos se instalarán, 0 para eliminar y 0 no actualizados.
Se necesita descargar 4.646 B de archivos.
Se utilizarán 58,4 kB de espacio de disco adicional después de esta operación.
Des:1 http://es.archive.ubuntu.com/ubuntu noble-updates/main amd64 ssh all 1:9.6p1-3ubuntu13.14 [4.646 B]
Descargados 4.646 B en 1s (7.899 B/s)
Seleccionando el paquete ssh previamente no seleccionado.
(Leyendo la base de datos ... 125347 ficheros o directorios instalados actualmente.)
Preparando para desempaquetar .../ssh_1%3a9.6p1-3ubuntu13.14_all.deb ...
Desempaquetando ssh (1:9.6p1-3ubuntu13.14) ...
Configurando ssh (1:9.6p1-3ubuntu13.14) ...
```

Prueba del estado de SSH

```
server@server:~$ sudo systemctl enable ssh
Synchronizing state of ssh.service with SysV service script with /usr/lib/systemd/systemd-sysv-install.
Executing: /usr/lib/systemd/systemd-sysv-install enable ssh
Created symlink /etc/systemd/system/ssh.service → /usr/lib/systemd/system/ssh.service.
Created symlink /etc/systemd/system/multi-user.target.wants/ssh.service → /usr/lib/systemd/system/ssh.service.
server@server:~$ sudo systemctl status ssh
• ssh.service - OpenBSD Secure Shell server
   Loaded: loaded (/usr/lib/systemd/system/ssh.service; enabled; preset: enabled)
   Active: active (running) since Wed 2025-12-03 20:08:18 UTC; 1min 53s ago
 TriggeredBy: • ssh.socket
   Docs: man:sshd(8)
        man:sshd_config(5)
  Main PID: 1060 (sshd)
    Tasks: 1 (limit: 4605)
   Memory: 2.1M (peak: 2.2M)
      CPU: 14ms
  CGroup: /system.slice/ssh.service
          └─1060 "sshd: /usr/sbin/sshd -D [listener] 0 of 10-100 startups"

dic 03 20:08:17 server systemd[1]: Starting ssh.service - OpenBSD Secure Shell server...
dic 03 20:08:18 server sshd[1060]: Server listening on 0.0.0.0 port 22.
dic 03 20:08:18 server sshd[1060]: Server listening on :: port 22.
dic 03 20:08:18 server systemd[1]: Started ssh.service - OpenBSD Secure Shell server.
server@server:~$
```

vermos las ips

```
server@server:~$ ip a
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host noprefixroute
        valid_lft forever preferred_lft forever
2: enp0s3: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group default qlen 1000
    link/ether 08:00:27:08:ac:6b brd ff:ff:ff:ff:ff:ff
    inet 10.0.2.15/24 metric 100 brd 10.0.2.255 scope global dynamic enp0s3
        valid_lft 86396sec preferred_lft 86396sec
    inet6 fd17:625c:f037:2:a00:27ff:fe08:ac6b/64 scope global dynamic mngtmpaddr noprefixroute
        valid_lft 86397sec preferred_lft 14397sec
    inet6 fe80::a00:27ff:fe08:ac6b/64 scope link
        valid_lft forever preferred_lft forever
3: enp0s8: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group default qlen 1000
    link/ether 08:00:27:25:13:09 brd ff:ff:ff:ff:ff:ff
    inet 192.168.68.103/24 metric 100 brd 192.168.68.255 scope global dynamic enp0s8
        valid_lft 7196sec preferred_lft 7196sec
    inet6 fe80::a00:27ff:fe25:1309/64 scope link
        valid_lft forever preferred_lft forever
server@server:~$
```

(el usuari1 es nomena server)

conectamos desde windows al servidor mediante ssh usando la ip del servidor

```
Instale la versión más reciente de PowerShell para obtener nuevas características y mejoras. https://aka.ms/PSWindows

PS C:\WINDOWS\system32> ssh server@192.168.68.103
The authenticity of host '192.168.68.103 (192.168.68.103)' can't be established.
ED25519 key fingerprint is SHA256:Dnc1IzNpG+uvuWjwfXoN0kHswcV5a4ewsCoIBR9QTNg.
This key is not known by any other names.
Are you sure you want to continue connecting (yes/no/[fingerprint])? y
Please type 'yes', 'no' or the fingerprint: yes
Warning: Permanently added '192.168.68.103' (ED25519) to the list of known hosts.
server@192.168.68.103's password:
Welcome to Ubuntu 24.04.3 LTS (GNU/Linux 6.8.0-84-generic x86_64)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/pro

System information as of jue 04 dic 2025 10:38:03 UTC

System load:            0.0
Usage of /:             26.5% of 24.44GB
Memory usage:          6%
Swap usage:            0%
Processes:             112
Users logged in:       1
IPv4 address for enp0s3: 10.0.2.15
IPv6 address for enp0s3: fd17:625c:f037:2:a00:27ff:fe08:ac6b

El mantenimiento de seguridad expandido para Applications está desactivado
```

canviamos/asignamos la contraseña al root del servidor

```
server@server:~$ sudo passwd root
[sudo] password for server:
New password:
Retype new password:
passwd: password updated successfully
server@server:~$
```

configuramos el archivo /ssh/sshd_config

```
GNU nano 7.2 /etc/ssh/sshd_config *
# This is the sshd server system-wide configuration file. See
# sshd_config(5) for more information.

# This sshd was compiled with PATH=/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin:/usr/>

# The strategy used for options in the default sshd_config shipped with
# OpenSSH is to specify options with their default value where
# possible, but leave them commented. Uncommented options override the
# default value.

Include /etc/ssh/sshd_config.d/*.conf

# When systemd socket activation is used (the default), the socket
# configuration must be re-generated after changing Port, AddressFamily, or
# ListenAddress.
#
# For changes to take effect, run:
#
#   systemctl daemon-reload
#   systemctl restart ssh.socket
#
#Port 22
#AddressFamily any
#ListenAddress 0.0.0.0
#ListenAddress ::

#HostKey /etc/ssh/ssh_host_rsa_key
#HostKey /etc/ssh/ssh_host_ecdsa_key
#HostKey /etc/ssh/ssh_host_ed25519_key

# Ciphers and keying
#RekeyLimit default none

# Logging
#SyslogFacility AUTH
#LogLevel INFO

# Authentication:

#LoginGraceTime 2m
PermitRootLogin no

#StrictModes yes
#MaxAuthTries 6
#MaxSessions 10
```

reiniciamos el servicio sshd

```
server@server:~$ sudo systemctl restart sshd
server@server:~$ |
```

creamos un usuario2

```
server@server:~$ sudo adduser usuari2
info: Adding user `usuari2' ...
info: Selecting UID/GID from range 1000 to 59999 ...
info: Adding new group `usuari2' (1001) ...
info: Adding new user `usuari2' (1001) with group `usuari2 (1001)' ...
info: Creating home directory `/home/usuari2' ...
info: Copying files from `/etc/skel' ...
New password:
Retype new password:
passwd: password updated successfully
Changing the user information for usuari2
Enter the new value, or press ENTER for the default
  Full Name []:
  Room Number []:
  Work Phone []:
  Home Phone []:
  Other []:
Is the information correct? [Y/n] y
info: Adding new user `usuari2' to supplemental / extra groups `users' ...
info: Adding user `usuari2' to group `users' ...
server@server:~$
```

volvemos a editar el archivo /ssh/sshd_config

```
GNU nano 7.2 /etc/ssh/sshd_config

# This is the sshd server system-wide configuration file. See
# sshd_config(5) for more information.

# This sshd was compiled with PATH=/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/usr/

# The strategy used for options in the default sshd_config shipped with
# OpenSSH is to specify options with their default value where
# possible, but leave them commented. Uncommented options override the
# default value.

Include /etc/ssh/sshd_config.d/*.conf

# When systemd socket activation is used (the default), the socket
# configuration must be re-generated after changing Port, AddressFamily, or
# ListenAddress.
#
# For changes to take effect, run:
#
#   systemctl daemon-reload
#   systemctl restart ssh.socket
#
#Port 22
#AddressFamily any
#ListenAddress 0.0.0.0
#ListenAddress ::

#HostKey /etc/ssh/ssh_host_rsa_key
#HostKey /etc/ssh/ssh_host_ecdsa_key
#HostKey /etc/ssh/ssh_host_ed25519_key

# Ciphers and keying
#RekeyLimit default none

# Logging
#SyslogFacility AUTH
#LogLevel INFO

# Authentication:

#LoginGraceTime 2m
PermitRootLogin no
AllowUsers server

#StrictModes yes
#MaxAuthTries 6
#MaxSessions 10
```

reiniciamos de nuevo el servicio ssh

```
server@server:~$ sudo systemctl restart sshd
server@server:~$
```

intentamos iniciar con el usuari2 i debería de dar error (permission denied) per al iniciar con usuari1 (server) debería dejar

```
PS C:\WINDOWS\system32> ssh usuari2@192.168.68.103
usuari2@192.168.68.103's password:
Permission denied, please try again.
usuari2@192.168.68.103's password:
Permission denied, please try again.
usuari2@192.168.68.103's password:
usuari2@192.168.68.103: Permission denied (publickey,password).
PS C:\WINDOWS\system32> ssh server@192.168.68.103
server@192.168.68.103's password:
Welcome to Ubuntu 24.04.3 LTS (GNU/Linux 6.8.0-84-generic x86_64)
```

```
* Documentation:  https://help.ubuntu.com
* Management:    https://landscape.canonical.com
* Support:        https://ubuntu.com/pro
```

System information as of jue 04 dic 2025 11:10:02 UTC

```
System load:            0.0
Usage of /:              26.5% of 24.44GB
Memory usage:           6%
Swap usage:             0%
Processes:              114
Users logged in:        1
IPv4 address for enp0s3: 10.0.2.15
IPv6 address for enp0s3: fd17:625c:f037:2:a00:27ff:fe08:ac6b
```

El mantenimiento de seguridad expandido para Applications está desactivado

Se pueden aplicar 0 actualizaciones de forma inmediata.

Active ESM Apps para recibir futuras actualizaciones de seguridad adicionales.
Vea <https://ubuntu.com/esm> o ejecute «sudo pro status»

The list of available updates is more than a week old.
To check for new updates run: sudo apt update

Last login: Thu Dec 4 10:38:04 2025 from 192.168.68.101
server@server:~\$