

Artificial Vision (VIAR25/26)

Lab 4: Encoder-Decoders: Building and Analyzing U-Net for Dense Prediction

Prof. David Olivieri

UVigo

September 29, 2025

Lab Objectives

Today's Mission

Implement, analyze, and optimize encoder-decoder architectures for semantic segmentation. You'll build a modular U-Net, experiment with skip connections, and solve a real segmentation task.

Learning Outcomes

- 1 **Build** a complete U-Net architecture from scratch
- 2 **Implement** different skip connection strategies and compare performance
- 3 **Experiment** with various loss functions for dense prediction
- 4 **Optimize** memory usage and inference speed
- 5 **Evaluate** using proper segmentation metrics

Dataset

Oxford-IIIT Pet Dataset - Semantic segmentation

- 37 pet categories with pixel-level masks
- Binary segmentation: pet vs. background
- Images: 200x200 pixels (resized for efficiency)

Lab Structure

Part 1: Core U-Net Implementation (40 min)

- **Task 1.1:** Implement encoder blocks with proper downsampling
- **Task 1.2:** Implement decoder blocks with upsampling
- **Task 1.3:** Connect encoder-decoder with skip connections
- **Task 1.4:** Create configurable U-Net class

Part 2: Skip Connection Experiments (30 min)

- **Task 2.1:** Implement concatenation-based skip connections
- **Task 2.2:** Implement addition-based skip connections
- **Task 2.3:** Implement attention-gated skip connections
- **Task 2.4:** Compare gradient flow and performance

Part 3: Loss Functions and Training (30 min)

- **Task 3.1:** Implement Dice loss
- **Task 3.2:** Implement focal loss for class imbalance
- **Task 3.3:** Create combined loss function
- **Task 3.4:** Train and evaluate models

Part 1: Building U-Net Architecture

Core Components to Implement

You'll build a modular U-Net where each component can be tested independently.

Encoder Block Requirements

- Double convolution with BatchNorm
- ReLU activation
- MaxPooling for downsampling
- Store features for skip connections
- Channel doubling: $64 \rightarrow 128 \rightarrow 256 \rightarrow 512$

Decoder Block Requirements

- Upsampling (transpose conv or bilinear)
- Skip connection fusion
- Double convolution
- Channel reduction: $512 \rightarrow 256 \rightarrow 128 \rightarrow 64$
- Handle dimension mismatches

Implementation Hints

- Use `nn.Sequential` for conv blocks
- Return both pooled and unpooled features
- Consider padding to maintain dimensions

Key Challenges

- Matching tensor dimensions for concatenation
- Choosing upsampling method
- Memory efficiency with large feature maps

Part 1: Code Structure

```
1 class EncoderBlock(nn.Module):
2     """TODO: Implement double conv + pooling"""
3     def __init__(self, in_channels, out_channels):
4         super().__init__()
5         # Task 1.1: Define your layers here
6
7     def forward(self, x):
8         # Task 1.1: Implement forward pass
9         # Return: features before pooling (for skip), features after pooling
10        pass
11
12 class DecoderBlock(nn.Module):
13     """TODO: Implement upsampling + skip connection + double conv"""
14     def __init__(self, in_channels, skip_channels, out_channels):
15         super().__init__()
16         # Task 1.2: Define your layers here
17
18     def forward(self, x, skip_features):
19         # Task 1.2: Implement forward pass with skip connection
20        pass
21
22 class UNet(nn.Module):
23     """TODO: Complete U-Net architecture"""
24     def __init__(self, in_channels=3, out_channels=1, features=[64, 128, 256, 512]):
25         super().__init__()
26         # Task 1.3: Build encoder and decoder paths
27
28     def forward(self, x):
29         # Task 1.4: Connect everything together
30        pass
31
```

Part 1.1: Double Convolution Block Algorithm

Core Building Block

The double convolution block is the fundamental unit of U-Net, appearing in both encoder and decoder paths.

Algorithm 1: DoubleConv: Two convolutions with BatchNorm and ReLU

Data: Input tensor $\mathbf{X} \in \mathbb{R}^{B \times C_{in} \times H \times W}$

Result: Output tensor $\mathbf{Y} \in \mathbb{R}^{B \times C_{out} \times H \times W}$

Parameters to Initialize:

$\mathbf{W}_1 \in \mathbb{R}^{C_{out} \times C_{in} \times 3 \times 3}$ // First conv weights

$\mathbf{b}_1 \in \mathbb{R}^{C_{out}}$ // First conv bias

$\mathbf{W}_2 \in \mathbb{R}^{C_{out} \times C_{out} \times 3 \times 3}$ // Second conv weights

$\mathbf{b}_2 \in \mathbb{R}^{C_{out}}$ // Second conv bias

$\gamma_1, \beta_1, \gamma_2, \beta_2$ // BatchNorm parameters

Forward Pass:

$\mathbf{H}_1 \leftarrow \text{Conv2D}(\mathbf{X}, \mathbf{W}_1, \mathbf{b}_1, \text{padding} = 1);$

$\mathbf{H}_2 \leftarrow \text{BatchNorm2D}(\mathbf{H}_1, \gamma_1, \beta_1);$

$\mathbf{H}_3 \leftarrow \text{ReLU}(\mathbf{H}_2);$

$\mathbf{H}_4 \leftarrow \text{Conv2D}(\mathbf{H}_3, \mathbf{W}_2, \mathbf{b}_2, \text{padding} = 1);$

$\mathbf{H}_5 \leftarrow \text{BatchNorm2D}(\mathbf{H}_4, \gamma_2, \beta_2);$

$\mathbf{Y} \leftarrow \text{ReLU}(\mathbf{H}_5);$

return \mathbf{Y} ;

Implementation Notes

- Padding=1 maintains spatial dimensions: $H_{out} = H_{in}$, $W_{out} = W_{in}$
- BatchNorm normalizes across the batch dimension for each channel
- Use `nn.Sequential` in PyTorch for cleaner implementation

Part 1.2: Encoder Block Algorithm

Algorithm 2: EncoderBlock: Feature extraction with downsampling

Data: Input tensor $\mathbf{X} \in \mathbb{R}^{B \times C_{in} \times H \times W}$

Result: Skip features \mathbf{F}_{skip} , Pooled features \mathbf{F}_{pool}

Encoder Block Processing:

```
// Apply double convolution to extract features
```

```
 $\mathbf{F}_{skip} \leftarrow \text{DoubleConv}(\mathbf{X}, C_{in} \rightarrow C_{out});$ 
```

```
// Store  $\mathbf{F}_{skip}$  for later skip connection
```

```
// Downsample spatially by factor of 2
```

```
 $\mathbf{F}_{pool} \leftarrow \text{MaxPool2D}(\mathbf{F}_{skip}, \text{kernel} = 2, \text{stride} = 2);$ 
```

```
// Output dimensions:
```

```
//  $\mathbf{F}_{skip} \in \mathbb{R}^{B \times C_{out} \times H \times W}$ 
```

```
//  $\mathbf{F}_{pool} \in \mathbb{R}^{B \times C_{out} \times H/2 \times W/2}$ 
```

```
return  $\mathbf{F}_{skip}, \mathbf{F}_{pool};$ 
```

Encoder Path Structure

- Each level doubles channels
- Each level halves spatial dims
- Skip connections preserve details

Channel Progression

- Level 1: $3 \rightarrow 64$
- Level 2: $64 \rightarrow 128$
- Level 3: $128 \rightarrow 256$
- Level 4: $256 \rightarrow 512$

Part 1.3: Decoder Block Algorithm

Algorithm 3: DecoderBlock: Upsampling with skip connection fusion

Data: Decoder input $\mathbf{X} \in \mathbb{R}^{B \times C_{in} \times H \times W}$, Skip features $\mathbf{F}_{skip} \in \mathbb{R}^{B \times C_{skip} \times 2H \times 2W}$

Result: Decoded features $\mathbf{Y} \in \mathbb{R}^{B \times C_{out} \times 2H \times 2W}$

Upsampling Step:

if *mode* = "transpose" then

$\mathbf{X}_{up} \leftarrow \text{ConvTranspose2D}(\mathbf{X}, C_{in} \rightarrow C_{in}/2, \text{kernel} = 2, \text{stride} = 2);$

else

$\mathbf{X}_{up} \leftarrow \text{Upsample}(\mathbf{X}, \text{scale} = 2, \text{mode} = \text{bilinear});$

$\mathbf{X}_{up} \leftarrow \text{Conv2D}(\mathbf{X}_{up}, C_{in} \rightarrow C_{in}/2, \text{kernel} = 1);$

end

Handle Dimension Mismatch:

if $\mathbf{X}_{up}.\text{shape}[2:] \neq \mathbf{F}_{skip}.\text{shape}[2:]$ then

$\mathbf{X}_{up} \leftarrow \text{CropOrPad}(\mathbf{X}_{up}, \text{target_shape} = \mathbf{F}_{skip}.\text{shape});$

end

Skip Connection Fusion:

$\mathbf{X}_{concat} \leftarrow \text{Concatenate}([\mathbf{X}_{up}, \mathbf{F}_{skip}], \text{dim} = 1);$

// Combined channels: $C_{in}/2 + C_{skip}$

Feature Refinement:

$\mathbf{Y} \leftarrow \text{DoubleConv}(\mathbf{X}_{concat}, (C_{in}/2 + C_{skip}) \rightarrow C_{out});$

Part 1.4: Complete U-Net Forward Pass

Algorithm 4: U-Net: Complete encoder-decoder architecture

Data: Input image $\mathbf{I} \in \mathbb{R}^{B \times 3 \times H \times W}$

Result: Segmentation map $\mathbf{S} \in \mathbb{R}^{B \times N_{classes} \times H \times W}$

Initialize: $\text{skip_connections} \leftarrow []$;

$\text{features} = [64, 128, 256, 512]$;

Encoder Path:

$\mathbf{x} \leftarrow \mathbf{I}$;

for $i = 0$ *to* $\text{len}(\text{features}) - 1$ **do**

$C_{in} \leftarrow 3$ if $i = 0$ else $\text{features}[i - 1]$;

$C_{out} \leftarrow \text{features}[i]$;

$\text{skip}_i, \mathbf{x} \leftarrow \text{EncoderBlock}(\mathbf{x}, C_{in}, C_{out})$;

$\text{skip_connections.append}(\text{skip}_i)$;

end

Bottleneck:

$\mathbf{x} \leftarrow \text{DoubleConv}(\mathbf{x}, 512 \rightarrow 1024)$;

Decoder Path:

for $i = \text{len}(\text{features}) - 1$ *down to* 0 **do**

$C_{in} \leftarrow 1024$ if $i = \text{len}(\text{features}) - 1$ else $\text{features}[i + 1]$;

$C_{out} \leftarrow \text{features}[i]$;

$\mathbf{x} \leftarrow \text{DecoderBlock}(\mathbf{x}, \text{skip_connections}[i], C_{in}, C_{out})$;

end

Part 2: Skip Connection Strategies

Comparing Information Flow Mechanisms

Different skip connection strategies affect gradient flow, memory usage, and final performance.

Three Strategies to Implement

Concatenation

- Direct feature stacking
- Preserves all information
- Higher memory usage
- $[\mathbf{F}_{\text{up}}, \mathbf{F}_{\text{skip}}]$

Addition

- Element-wise sum
- Memory efficient
- May lose information
- $\mathbf{F}_{\text{up}} + \mathbf{F}_{\text{skip}}$

Attention-Gated

- Learned importance
- Focus on relevant features
- Computational overhead
- $\alpha \odot \mathbf{F}_{\text{skip}}$

Analysis Requirements

- Measure gradient magnitude at different depths
- Compare memory consumption
- Evaluate final segmentation IoU
- Visualize attention maps (for attention-gated)

Part 2.1: Concatenation Skip Connection

Algorithm 5: Concatenation-based skip connection

Data: Decoder features $\mathbf{D} \in \mathbb{R}^{B \times C_d \times H \times W}$, Skip features $\mathbf{S} \in \mathbb{R}^{B \times C_s \times H \times W}$

Result: Fused features $\mathbf{F} \in \mathbb{R}^{B \times C_{out} \times H \times W}$

Concatenation Fusion:

```
// Concatenate along channel dimension
```

```
 $\mathbf{F}_{concat} \leftarrow \text{Concatenate}([\mathbf{D}, \mathbf{S}], \text{dim} = 1);$ 
```

```
// Output shape:  $B \times (C_d + C_s) \times H \times W$ 
```

```
// Reduce channels to desired output size
```

```
 $\mathbf{F} \leftarrow \text{Conv2D}(\mathbf{F}_{concat}, (C_d + C_s) \rightarrow C_{out}, \text{kernel} = 3, \text{padding} = 1);$ 
```

```
return  $\mathbf{F}$ ;
```

Properties

Advantages:

- Preserves all information
- No information loss
- Standard U-Net approach

Disadvantages:

- Higher memory usage
- More parameters in fusion conv
- Increased computation

Part 2.2: Addition Skip Connection

Algorithm 6: Addition-based skip connection (ResNet-style)

Data: Decoder features $\mathbf{D} \in \mathbb{R}^{B \times C_d \times H \times W}$, Skip features $\mathbf{S} \in \mathbb{R}^{B \times C_s \times H \times W}$

Result: Fused features $\mathbf{F} \in \mathbb{R}^{B \times C_d \times H \times W}$

Addition Fusion:

```
// Match channel dimensions if necessary
if  $C_s \neq C_d$  then
     $\mathbf{S}_{proj} \leftarrow \text{Conv2D}(\mathbf{S}, C_s \rightarrow C_d, \text{kernel} = 1)$ ;
    // 1x1 convolution for channel projection
else
     $\mathbf{S}_{proj} \leftarrow \mathbf{S}$ ;
end

// Element-wise addition
 $\mathbf{F} \leftarrow \mathbf{D} + \mathbf{S}_{proj}$ ;

return  $\mathbf{F}$ ;
```

Properties

Advantages:

- Memory efficient
- Gradient flow like ResNet
- Fewer parameters

Disadvantages:

- Potential information loss
- Requires channel matching
- May lose fine details

Part 2.3: Attention-Gated Skip Connection

Algorithm 7: Attention-gated skip connection

Data: Gate signal $\mathbf{G} \in \mathbb{R}^{B \times C_g \times H_g \times W_g}$, Skip features $\mathbf{S} \in \mathbb{R}^{B \times C_s \times H \times W}$

Result: Attended features $\mathbf{A} \in \mathbb{R}^{B \times C_s \times H \times W}$

Attention Mechanism:

$C_{inter} \leftarrow C_g / 2$ // Intermediate channels

// Transform gate signal

$\mathbf{W}_g \leftarrow \text{Conv2D}(\mathbf{G}, C_g \rightarrow C_{inter}, \text{kernel} = 1);$

// Transform skip features

$\mathbf{W}_s \leftarrow \text{Conv2D}(\mathbf{S}, C_s \rightarrow C_{inter}, \text{kernel} = 1);$

// Align spatial dimensions if needed

if $H_g \neq H$ **or** $W_g \neq W$ **then**

$\mathbf{W}_g \leftarrow \text{Interpolate}(\mathbf{W}_g, \text{size} = (H, W));$

end

// Compute attention coefficients

$\mathbf{Q} \leftarrow \text{ReLU}(\mathbf{W}_g + \mathbf{W}_s);$

$\alpha \leftarrow \text{Sigmoid}(\text{Conv2D}(\mathbf{Q}, C_{inter} \rightarrow 1, \text{kernel} = 1));$

// $\alpha \in [0, 1]^{B \times 1 \times H \times W}$

// Apply attention to skip features

$\mathbf{A} \leftarrow \mathbf{S} \odot \alpha$ // Element-wise multiplication

Part 3: Loss Functions for Segmentation

Dice Loss Implementation

Formula: $\mathcal{L}_{\text{Dice}} = 1 - \frac{2|Y \cap \hat{Y}| + \epsilon}{|Y| + |\hat{Y}| + \epsilon}$

Your Tasks:

- Handle multi-class case
- Add smoothing factor
- Consider class weighting

Focal Loss Implementation

Formula: $\mathcal{L}_{\text{Focal}} = -\alpha(1 - p_t)^\gamma \log(p_t)$

Your Tasks:

- Implement focusing parameter γ
- Add class balancing α
- Handle numerical stability

Combined Loss Strategy

Multi-task learning approach:

$$\mathcal{L} = \lambda_1 \mathcal{L}_{\text{CE}} + \lambda_2 \mathcal{L}_{\text{Dice}} + \lambda_3 \mathcal{L}_{\text{boundary}}$$

Implementation considerations:

- Dynamic weight scheduling
- Loss magnitude normalization
- Gradient scaling

Evaluation Metrics

- IoU (Intersection over Union)
- Dice coefficient
- Pixel accuracy
- Boundary F1 score

Training Pipeline

Data Augmentation Strategy

- Random horizontal flips
- Random rotations ($\pm 15^\circ$)
- Elastic deformations
- Color jittering
- **Important:** Apply same transform to image and mask!

Training Configuration

Hyperparameters:

- Batch size: 16
- Learning rate: 0.001
- Optimizer: Adam with weight decay
- Scheduler: ReduceLROnPlateau
- Epochs: 50

Monitoring:

- Training/validation loss curves
- IoU progression
- Learning rate schedule
- Sample predictions every 5 epochs
- Memory usage tracking

Debugging Tips

- Start with small image size (64x64) for quick iteration
- Verify dimensions at each layer with dummy input
- Use gradient clipping to prevent explosion
- Visualize intermediate feature maps

Monitoring Training and Evaluation

What to Track During Training

- **Loss curves:** training vs. validation loss
- **Learning rate schedule:** how LR changes over epochs
- **Segmentation metrics:**
 - IoU (Intersection over Union)
 - Dice coefficient
 - Pixel accuracy
- **Model statistics:** number of parameters, memory usage
- **Qualitative results:** predicted masks every few epochs

Why is this Important?

Metrics and curves help diagnose **overfitting**, **underfitting**, and **optimization issues**.

Expected Outputs and Evaluation

Deliverables

- ❶ **Complete U-Net implementation** with modular design
- ❷ **Comparison table** of skip connection strategies:
 - Final IoU scores
 - Training time per epoch
 - Memory consumption
 - Gradient flow analysis
- ❸ **Loss function analysis:**
 - Learning curves for each loss
 - Qualitative comparison of segmentation quality
- ❹ **Ablation study** removing components:
 - No skip connections
 - No batch normalization
 - Different depths

Bonus Challenges

- Implement U-Net++ with dense skip connections
- Add deep supervision at multiple scales
- Implement efficient inference with sliding window
- Create interactive visualization of attention maps

Ablation Studies in Deep Learning

What is an Ablation Study?

A systematic way to evaluate the contribution of each component in a model by **removing, replacing, or modifying** it.

Why Do We Perform Ablations?

- Understand which parts of the architecture are essential
- Separate useful design choices from unnecessary complexity
- Provide **scientific justification** for model design
- Improve reproducibility and clarity in research

Examples for U-Net

- **No skip connections**: how important are they for fine details?
- **No batch normalization**: effect on stability and convergence
- **Depth variations**: shallow vs. deep U-Net
- **Alternative skip connections**: concat, add, attention

Part 3.1: Dice Loss Algorithm

Algorithm 8: Dice Loss for Segmentation

Data: Predictions $\hat{\mathbf{Y}} \in \mathbb{R}^{B \times C \times H \times W}$ (logits), Targets $\mathbf{Y} \in \{0, 1\}^{B \times C \times H \times W}$, Smoothing factor $\epsilon = 10^{-6}$

Result: Dice loss $\mathcal{L}_{Dice} \in \mathbb{R}$

Binary Dice Loss (C=1):

// Apply sigmoid to get probabilities

$\mathbf{P} \leftarrow \text{Sigmoid}(\hat{\mathbf{Y}});$

// Flatten spatial dimensions

$\mathbf{P}_{flat} \leftarrow \text{Flatten}(\mathbf{P})$ // Shape: $(B \times HW)$

$\mathbf{Y}_{flat} \leftarrow \text{Flatten}(\mathbf{Y})$ // Shape: $(B \times HW)$

// Compute Dice coefficient

$\text{intersection} \leftarrow \sum_{i,j} \mathbf{P}_{flat}[i,j] \cdot \mathbf{Y}_{flat}[i,j];$

$\text{union} \leftarrow \sum_{i,j} \mathbf{P}_{flat}[i,j] + \sum_{i,j} \mathbf{Y}_{flat}[i,j];$

$\text{dice} \leftarrow \frac{2 \cdot \text{intersection} + \epsilon}{\text{union} + \epsilon};$

$\mathcal{L}_{Dice} \leftarrow 1 - \text{dice};$

Multi-class Dice Loss (C>1):

$\mathcal{L}_{Dice} \leftarrow 0;$

for $c = 1$ to C **do**

$\text{dice}_c \leftarrow \text{BinaryDice}(\hat{\mathbf{Y}}[:, c, :, :], \mathbf{Y}[:, c, :, :]);$

$\mathcal{L}_{Dice} \leftarrow \mathcal{L}_{Dice} + \text{dice}_c;$

end

$\mathcal{L}_{Dice} \leftarrow \mathcal{L}_{Dice} / C;$

return $\mathcal{L}_{Dice};$

Part 3.2: Focal Loss Algorithm

Algorithm 9: Focal Loss for Class Imbalance

Data: Predictions $\hat{\mathbf{Y}} \in \mathbb{R}^{B \times C \times H \times W}$, Targets $\mathbf{Y} \in \{0, 1\}^{B \times C \times H \times W}$, Balancing factor $\alpha = 0.25$, Focusing parameter $\gamma = 2.0$

Result: Focal loss $\mathcal{L}_{Focal} \in \mathbb{R}$

Focal Loss Computation:

// Apply sigmoid for probabilities

$\mathbf{P} \leftarrow \text{Sigmoid}(\hat{\mathbf{Y}})$;

// Compute binary cross-entropy

$\text{BCE} \leftarrow -\mathbf{Y} \cdot \log(\mathbf{P} + \epsilon) - (1 - \mathbf{Y}) \cdot \log(1 - \mathbf{P} + \epsilon)$;

// Compute probability of correct class

$\mathbf{P}_t \leftarrow \mathbf{Y} \cdot \mathbf{P} + (1 - \mathbf{Y}) \cdot (1 - \mathbf{P})$;

// Apply focal term to focus on hard examples

$\text{focal_term} \leftarrow (1 - \mathbf{P}_t)^\gamma$;

// Apply class balancing

$\alpha_t \leftarrow \mathbf{Y} \cdot \alpha + (1 - \mathbf{Y}) \cdot (1 - \alpha)$;

// Combine all terms

$\mathcal{L}_{Focal} \leftarrow \alpha_t \cdot \text{focal_term} \cdot \text{BCE}$;

// Average over all pixels and batch

$\mathcal{L}_{Focal} \leftarrow \frac{1}{B \cdot H \cdot W} \sum_{b,h,w} \mathcal{L}_{Focal}[b, :, h, w]$;

return \mathcal{L}_{Focal} ;

Part 3.3: Combined Loss Algorithm

Algorithm 10: Combined Loss Function

Data: Predictions $\hat{\mathbf{Y}}$, Targets \mathbf{Y} , Loss weights $\{w_{BCE}, w_{Dice}, w_{Focal}\}$

Result: Combined loss $\mathcal{L}_{total} \in \mathbb{R}$

Initialize:

$\mathcal{L}_{total} \leftarrow 0;$

Compute Individual Losses:

if $w_{BCE} > 0$ **then**

$\mathcal{L}_{BCE} \leftarrow \text{BCEWithLogitsLoss}(\hat{\mathbf{Y}}, \mathbf{Y});$

$\mathcal{L}_{total} \leftarrow \mathcal{L}_{total} + w_{BCE} \cdot \mathcal{L}_{BCE};$

end

if $w_{Dice} > 0$ **then**

$\mathcal{L}_{Dice} \leftarrow \text{DiceLoss}(\hat{\mathbf{Y}}, \mathbf{Y});$

$\mathcal{L}_{total} \leftarrow \mathcal{L}_{total} + w_{Dice} \cdot \mathcal{L}_{Dice};$

end

if $w_{Focal} > 0$ **then**

$\mathcal{L}_{Focal} \leftarrow \text{FocalLoss}(\hat{\mathbf{Y}}, \mathbf{Y});$

$\mathcal{L}_{total} \leftarrow \mathcal{L}_{total} + w_{Focal} \cdot \mathcal{L}_{Focal};$

end

return $\mathcal{L}_{total};$

Weight Selection Guidelines

- Balanced dataset: $w_{BCE} = 0.5, w_{Dice} = 0.5, w_{Focal} = 0$
- Imbalanced dataset: $w_{BCE} = 0.2, w_{Dice} = 0.3, w_{Focal} = 0.5$
- Fine boundaries: $w_{BCE} = 0.3, w_{Dice} = 0.7, w_{Focal} = 0$

Training Loop Algorithm

Algorithm 11: Complete Training Loop

Data: Model \mathcal{M} , Training data \mathcal{D}_{train} , Validation data \mathcal{D}_{val}

Result: Trained model parameters θ^*

Initialize:

$\theta \leftarrow \text{Xavier_Init}()$ // Initialize model parameters

Learning rate η , Epochs E , Batch size B optimizer $\leftarrow \text{Adam}(\theta, \eta)$;

scheduler $\leftarrow \text{ReduceLROnPlateau}(\text{optimizer}, \text{patience} = 5)$;

best_iou $\leftarrow 0$;

for $e = 1$ to E **do**

Training Phase:

$\mathcal{M}.\text{train}()$;

for $(\mathbf{X}, \mathbf{Y}) \in \mathcal{D}_{train}$ **do**

$\hat{\mathbf{Y}} \leftarrow \mathcal{M}(\mathbf{X})$;

$\mathcal{L} \leftarrow \text{CombinedLoss}(\hat{\mathbf{Y}}, \mathbf{Y})$;

 // Backward pass

 optimizer.zero_grad();

$\mathcal{L}.\text{backward}()$;

 // Gradient clipping (optional)

 clip_grad_norm(θ , max_norm = 1.0);

 optimizer.step();

end

Validation Phase:

$\mathcal{M}.\text{eval}()$;

 val_iou $\leftarrow \text{Evaluate}(\mathcal{M}, \mathcal{D}_{val})$;

 // Learning rate scheduling

 scheduler.step(val_loss);

if val_iou > best_iou **then**

 best_iou \leftarrow val_iou;

$\theta^* \leftarrow \theta$ // Save best model

end

end

return θ^* ;

IoU Calculation Algorithm

Algorithm 12: Intersection over Union Metric

Data: Predictions $\hat{\mathbf{Y}} \in \mathbb{R}^{B \times C \times H \times W}$, Targets $\mathbf{Y} \in \{0, 1\}^{B \times C \times H \times W}$, Threshold $\tau = 0.5$

Result: IoU score $\in [0, 1]$

Binary IoU Calculation:

// Convert logits to probabilities

$\mathbf{P} \leftarrow \text{Sigmoid}(\hat{\mathbf{Y}});$

// Apply threshold

$\mathbf{P}_{\text{binary}} \leftarrow (\mathbf{P} > \tau);$

// Calculate intersection and union

$\text{TP} \leftarrow \sum(\mathbf{P}_{\text{binary}} \wedge \mathbf{Y})$ // True Positives

$\text{FP} \leftarrow \sum(\mathbf{P}_{\text{binary}} \wedge \neg \mathbf{Y})$ // False Positives

$\text{FN} \leftarrow \sum(\neg \mathbf{P}_{\text{binary}} \wedge \mathbf{Y})$ // False Negatives

$\text{intersection} \leftarrow \text{TP};$

$\text{union} \leftarrow \text{TP} + \text{FP} + \text{FN};$

$\text{IoU} \leftarrow \frac{\text{intersection} + \epsilon}{\text{union} + \epsilon};$

Mean IoU for Multi-class:

$\text{mIoU} \leftarrow 0;$

for $c = 1$ **to** C **do**

$\text{IoU}_c \leftarrow \text{BinaryIoU}(\hat{\mathbf{Y}}[:, c, :, :], \mathbf{Y}[:, c, :, :]);$

$\text{mIoU} \leftarrow \text{mIoU} + \text{IoU}_c;$

end

$\text{mIoU} \leftarrow \text{mIoU} / C;$

return $\text{mIoU};$

Memory-Efficient Training with Gradient Accumulation

Algorithm 13: Memory-Efficient Training via Gradient Accumulation

Data: Model \mathcal{M} , Data loader \mathcal{D} , Effective batch size B_{eff} , Mini-batch size B_{mini} , Accumulation steps $N_{\text{acc}} = B_{\text{eff}}/B_{\text{mini}}$

Gradient Accumulation Training:

```
optimizer.zero_grad();
```

```
step_count  $\leftarrow$  0;
```

```
for  $(\mathbf{X}, \mathbf{Y}) \in \mathcal{D}$  do
```

```
    // Forward pass with mini-batch
```

```
     $\hat{\mathbf{Y}} \leftarrow \mathcal{M}(\mathbf{X});$ 
```

```
     $\mathcal{L} \leftarrow \text{Loss}(\hat{\mathbf{Y}}, \mathbf{Y});$ 
```

```
    // Scale loss by accumulation steps
```

```
     $\mathcal{L} \leftarrow \mathcal{L}/N_{\text{acc}};$ 
```

```
    // Backward pass (accumulate gradients)
```

```
     $\mathcal{L}.\text{backward}();$ 
```

```
    step_count  $\leftarrow$  step_count + 1;
```

```
    if step_count mod  $N_{\text{acc}} = 0$  then
```

```
        // Update weights after accumulation
```

```
        optimizer.step();
```

```
        optimizer.zero_grad();
```

```
    end
```

```
end
```

When to Use

- GPU memory limited but large batch size needed for stability
- Example: Effective batch = 32, but GPU fits only 8 \rightarrow accumulate 4 steps
- Trade-off: More computation time for same effective batch size

Ablation Study Algorithm

Algorithm 14: Systematic Ablation Study

Data: Base configuration \mathcal{C}_{base} , Components to ablate $\{c_1, c_2, \dots, c_n\}$

Result: Performance comparison table

Initialize Results:

results $\leftarrow \{\}$;

Baseline Model:

$\mathcal{M}_{base} \leftarrow \text{BuildModel}(\mathcal{C}_{base})$;

results["baseline"] $\leftarrow \text{TrainAndEvaluate}(\mathcal{M}_{base})$;

Ablation Experiments:

for each component c_i in $\{c_1, c_2, \dots, c_n\}$ **do**

$\mathcal{C}_{ablated} \leftarrow \mathcal{C}_{base}$;

 // Remove or modify component

switch c_i **do**

case "skip_connections" **do**

$\mathcal{C}_{ablated}.skip \leftarrow \text{False}$;

end

case "batch_norm" **do**

$\mathcal{C}_{ablated}.use_bn \leftarrow \text{False}$;

end

case "depth" **do**

$\mathcal{C}_{ablated}.layers \leftarrow \mathcal{C}_{base}.layers - 1$;

end

case "attention" **do**

$\mathcal{C}_{ablated}.skip_mode \leftarrow \text{"concat"}$;

end

end

$\mathcal{M}_{ablated} \leftarrow \text{BuildModel}(\mathcal{C}_{ablated})$;

 results[c_i] $\leftarrow \text{TrainAndEvaluate}(\mathcal{M}_{ablated})$;

end

return results;

Common Pitfalls and Solutions

Debugging Checklist

Use this when things don't work as expected!

Dimension Mismatches

Problem: Concatenation fails

- Check padding in convolutions
- Verify upsampling scale matches pooling
- Use `print(x.shape)` liberally

Poor Convergence

Problem: Loss plateaus early

- Check data normalization
- Verify loss function implementation
- Try gradient clipping
- Reduce learning rate

Memory Issues

Problem: CUDA out of memory

- Reduce batch size
- Use gradient accumulation
- Clear cache: `torch.cuda.empty_cache()`
- Use mixed precision training

Overfitting

Problem: Train IoU \uparrow Val IoU \downarrow

- Increase dropout
- Add more augmentation
- Use early stopping
- Reduce model capacity

Resources and References

Code Resources

- Starter code: `lab04_student.py`
- Dataset loader: `data_utils.py`
- Evaluation metrics: `metrics.py`

Key Papers to Reference

- Ronneberger et al. (2015): "U-Net: Convolutional Networks for Biomedical Image Segmentation"
- Oktay et al. (2018): "Attention U-Net: Learning Where to Look for the Pancreas"
- Zhou et al. (2018): "UNet++: A Nested U-Net Architecture"

Submission Requirements

- Completed notebook with all tasks
- Training logs and loss curves
- Best model checkpoint (.pth file)
- Brief report (2-3 pages) analyzing results
- **Due:** One week from today