


2. Consider the time series on Milk production data milk-production(1).csv it shows cow milk production per pound from 1962 to 1975.

- a. Try at least three different values for window size with simple moving average (SMA) for forecasting

```
> library(TTR)
> milkprod<-read.csv(file=" G:/Fall Semester 2017/ISL/Assignment-3/milk-production.csv",head=T,sep=",")
Error in file(file, "rt") : cannot open the connection
In addition: Warning message:
In file(file, "rt") :
  cannot open file ' G:/Fall Semester 2017/ISL/Assignment-3/milk-production.csv': Invalid argument
> milkprod<-read.csv("G:\\Fall Semester 2017\\ISL\\Assignment-3\\milk-production",head=T,sep=",")
Error: '\\F' is an unrecognized escape in character string starting ""G:\\F"
> milkprod<-read.csv(file="G:\\Fall Semester 2017\\ISL\\Assignment-3\\milk-production",head=T,sep=",")
Error: '\\F' is an unrecognized escape in character string starting ""G:\\F"
> milkprod<-read.csv(file=file="G:/Fall Semester 2017/ISL/Assignment-2/kc_weather_srt.csv",head=T,sep=",")
Error: unexpected '=' in "milkprod<-read.csv(file=file="
> milkprod<-read.csv(file="G:/Fall Semester 2017/ISL/Assignment-2/kc_weather_srt.csv",head=T,sep=",")
> milkprod<-read.csv(file="G:/Fall Semester 2017/ISL/Assignment-3/milk-production.csv",head=T,sep=",")
> library(TTR)
> milkprod<-read.csv(file=" G:/Fall Semester 2017/ISL/Assignment-3/milk-production.csv
+ ",head=T,sep=",")
Error in file(file, "rt") : cannot open the connection
In addition: Warning message:
In file(file, "rt") :
  cannot open file ' G:/Fall Semester 2017/ISL/Assignment-3/milk-production.csv
': Invalid argument
> milkprodTS<-ts(milkprod$Pounds_per_Cow,frequency = 12,start=c(1962,1))
> plot.ts(milkprodTS)
> sTS3 = SMA(milkprodTS,n=3)
```

```
> milkprod<-read.csv(file="G:/Fall Semester 2017/ISL/Assignment-2/kc_weather_srt.csv",head=T,sep=",")
> milkprod<-read.csv(file="G:/Fall Semester 2017/ISL/Assignment-3/milk-production.csv",head=T,sep=",")
> library(TTR)
> milkprod<-read.csv(file=" G:/Fall Semester 2017/ISL/Assignment-3/milk-production.csv
+ ",head=T,sep=",")
Error in file(file, "rt") : cannot open the connection
In addition: Warning message:
In file(file, "rt") :
  cannot open file ' G:/Fall Semester 2017/ISL/Assignment-3/milk-production.csv
': Invalid argument
> milkprodTS<-ts(milkprod$Pounds_per_Cow,frequency = 12,start=c(1962,1))
> plot.ts(milkprodTS)
> sTS3 = SMA(milkprodTS,n=3)
> sTS5 = SMA(milkprodTS,n=5)
> sTS8 = SMA(milkprodTS,n=8)
> lines(milkprodTS, col="black")
> lines(sTS3, col="darkgoldenrod1")
> lines(sTS5, col="blue")
> lines(sTS8,col="brown1")
```



b. Apply exponential moving average using HoltWinters for forecasting

```
> milkprod<-read.csv( file="G:/Fall Semester 2017/ISL/Assignment-3/milk-production.csv ",head=T,sep=",")
> milkprodTS<-ts(milkprod$Pounds_per_Cow,frequency = 12,start=c(1962,1))
> plot.ts(milkprodTS)
> sHW = HoltWinters(milkprodTS,beta=FALSE, gamma=FALSE)
> sHWl = HoltWinters(milkprodTS)
> sHWlines(sHW$fitted[,1], col= "green")
Error in sHWlines(sHW$fitted[, 1], col = "green") :
  could not find function "sHWlines"
> sHWlines(sHWl$fitted[,1], col= "red")
Error in sHWlines(sHWl$fitted[, 1], col = "red") :
  could not find function "sHWlines"
> sHW
Holt-Winters exponential smoothing without trend and without seasonal component.

Call:
HoltWinters(x = milkprodTS, beta = FALSE, gamma = FALSE)

Smoothing parameters:
  alpha: 0.9999339
  beta : FALSE
  gamma: FALSE


Coefficients:

-----
> sHWl
Holt-Winters exponential smoothing with trend and additive seasonal component.

Call:
HoltWinters(x = milkprodTS)

Smoothing parameters:
  alpha: 0.68933
  beta : 0
  gamma: 0.8362592

Coefficients:
      [,1]
a  885.775547
b   1.278118
s1 -16.743296
s2 -59.730034
s3  47.492731
s4  56.203890
s5 115.537545
s6  84.554817
s7  39.580306
s8  -4.702033
s9 -54.554684
s10 -51.582594
s11 -85.953466
s12 -42.907363
~ |
```



C. For the above, discuss how the forecasting differs in terms of MAD and MFE and why one approach or the other is better.

```

> milkprod<-read.csv(file="G:/Fall Semester 2017/ISL/Assignment-3/milk-production.csv ",head=T,sep=",")
> milkprodTS<-ts(milkprod$Pounds_per_Cow,frequency = 12,start=c(1962,1))
> plot.ts(milkprodTS)
> sTS3 = SMA(milkprodTS,n=3)
> error = milkprodTS - sTS3
> mfe3 = (sum(error,na.rm = TRUE)/length(error))
> mfe3
[1] 1.531746
> mad3 = (sum(abs(error),na.rm = TRUE)/length(error))
> mad3
[1] 29.69841
> sTS5 = SMA(milkprodTS,n=5)
> error1 = milkprodTS - sTS5
> mfe5 = (sum(error1,na.rm = TRUE)/length(error1))
> mfe5
[1] 2.355952
> mad5 = (sum(abs(error1),na.rm = TRUE)/length(error1))
> mad5
[1] 46.67976
> sTS8 = SMA(milkprodTS,n=8)
> error2 = milkprodTS - sTS8
> mfe8 = (sum(error2,na.rm = TRUE)/length(error2))
> mfe8
[1] 3.598958
> mad8 = (sum(abs(error2),na.rm = TRUE)/length(error2))
> mad8
[1] 55.39062

```

The Ideal value for MFE=0

Inference:

From the different N values we used, the better model would be N=3 as the average absolute error is 29.6 units where as others are more.