# 19CCE303 – DIGITAL COMMUNICATION ASSIGNMENT II

#### **PROBLEM:**

Fundamentals of Communication Systems, John G. Proakis, Masoud Salehi, Pearson Education, Second Edition, 2015

Chapter 10 – Digital Transmission through Bandlimited Channels

Computer Problem 10.5 Precoding for Duobinary Signals

Write a Python program that takes a binary data sequence  $\{d_k\}$ , pre-codes it for a duobinary pulse transmission system to produce the sequence  $\{p_k\}$ , and maps the pre-coded sequence into the transmitted amplitude levels  $\{a_k\}$ . Then, from the transmitted sequence  $\{a_k\}$ , and from the received noise-free sequences  $\{b_k\}$ , recover the original data sequence  $\{d_k\}$ . Verify the operation of your program using the data sequence  $\{1\ 0\ 0\ 1\ 0\ 1\ 1\ 1\ 0\ 1\ 0\}$ .

## **SOFTWARE REQUIRED:**

- Windows 10 Operating System
- Anaconda3 2021.11 (Python 3.9.7 64-bit)
- The Scientific Python Development Environment (Spyder) 5.1.5

### **PYTHON CODE:**

```
binary_data = [1,0,0,1,0,1,1,1,0,1,1,0]
print("\nBinary Data Sequence, {dk}: ", binary data)
# Precodes it for a duobinary pulse transmission system to produce the
sequence, {pk}: -
pn =[]; pn.append(\emptyset); m = 2
for i in range(len(binary data)):
    pn.append((binary_data[i]-pn[i])%m)
print("Precoded and Produced Sequence, {pk}: ", pn)
# Maps the precoded sequence into the transmitted amplitude levels, {ak}: -
an = []
for i in range(0,len(pn)):
    an.append(2*pn[i] - (m-1))
print("Transmitted Amplitude Levels, {ak}: ", an)
# Received noise-free sequences, {bk}: -
bn = []
for i in range(1,len(pn)):
    bn.append(an[i]+an[i-1])
```

# SANTOSH – [CB.EN.U4CCE20053]

```
print("Received Noise-Free Sequences, {bk}: ", bn)

# Recover the original data sequence: -
dn = []
for i in range(len(bn)):
    dn.append(int((((bn[i]/2)+(m-1))%m)))
print("Recovered Original Data Sequence: ", dn)
```

Python 3.9.7 (default, Sep 16 2021, 16:59:28) [MSC v.1916 64 bit (AMD64)] Type "copyright", "credits" or "license" for more information.

IPython 7.29.0 -- An enhanced Interactive Python.

Restarting kernel...

In [1]: 'E:/Plan B/Amrita Vishwa Vidyapeetham/Subject Materials/Semester V/
19CCE303 - Digital Communication/Assignments/Assignment II/
19CCE303\_Assignment\_II\_Code.py' = 'E:/Plan B/Amrita Vishwa Vidyapeetham/Subject
Materials/Semester V/19CCE303 - Digital Communication/Assignments/Assignment II'

Binary Data Sequence, {dk}: [1, 0, 0, 1, 0, 1, 1, 1, 0, 1, 1, 0]

Precoded and Produced Sequence, {pk}: [0, 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 1, 1]

Transmitted Amplitude Levels, {ak}: [-1, 1, 1, 1, -1, -1, 1, -1, 1, 1, -1, 1, 1]

Received Noise-Free Sequences, {bk}: [0, 2, 2, 0, -2, 0, 0, 0, 2, 0, 0, 2]

Recovered Original Data Sequence: [1, 0, 0, 1, 0, 1, 1, 1, 0, 1, 1, 0]

In [2]: