Implement Boosting ensemble method on a given detaset.

	Actual class	Tobloofile	Initial weight	abayed nothing
CGPA			APAD Y6	0.1249
>=9	Yes	yes		0.2501
< 9	No	10	1/6	0,250)
7=9	Yes	No	Y-6 whomphal	
<9	No wit	No	76	0.1249
>=9	Yes	Yes	04 16	01/249
>= 9	40	Yes		001249
desired to			6	1407

step 1: Assign without weight 1/6

Inderactive ness as noot node: step 2: a) weighted error Ecaph $\varepsilon_i = \sum_{i=1}^N H_i(d_i) \omega t(d_i)$

E CGPA = 2x 1 = 0.333 multiposition

b) compute weight of each weak classifier:

c) Calculate the normalizing factor

d) update the weight of all data instances into more times

with the weight of all data instances into more times

with a weight of all data instances into more times

with a weight of all data instances into more times

with a weight of all data instances into more times

with a weight of all data instances into more times

with a weight of all data instances into more times

with a weight of all data instances into more times

with a weight of all data instances into more times

and a weight of all data instances into more times

and a weight of all data instances into more times

and a weight of all data instances into more times

and a weight of all data instances into more times

and a weight of all data instances into more times

and a weight of all data instances into more times

and a weight of all data instances into more times

and a weight of all data instances into more times

and a weight of all data instances into more times

and a weight of all data instances in the more times

and a weight of all data instances in the more times

and a weight of all data instances in the more times

and a weight of all data instances in the more times

and a weight of all data instances in the more times

and a weight of all data instances in the more times

and a weight of a weight

For "income ocsv" dataget Best Accuracy Score: 0.86 (6r) 86% confusion matrix: