



Escribir:

Include "conf/alias/\*.conf"

Al final del archivo.

```

httpd.conf: Bloc de notas
Archivo Edición Formato Ver Ayuda
#
# Note: The following must must be present to support
#       starting without SSL on platforms with no /dev/random equivalent
#       but a statically compiled-in mod_ssl.
#
<IfModule ssl_module>
SSLRandomSeed startup builtin
SSLRandomSeed connect builtin
</IfModule>

# XAMPP: We disable operating system specific optimizations for a listening
# socket by the http protocol here. IE 64 bit make problems without this.

AcceptFilter http none
AcceptFilter https none
# AJP13 Proxy
<IfModule mod_proxy.c>
<IfModule mod_proxy_ajp.c>
Include "conf/extra/httpd-ajp.conf"
</IfModule>
</IfModule>
Include "conf/alias/*.conf"
  
```

Ir a xampp/apache/conf y crear carpeta alias. Dentro de esta carpeta se crean los archivos con los alias.

Estos archivos contendrán el siguiente texto:

```
<Directory "c:\users\foo\programming\dev">
#
# Possible values for the Options directive are "None", "All",
# or any combination of:
#   Indexes Includes FollowSymLinks SymLinksifOwnerMatch ExecCGI MultiViews
#
# Note that "MultiViews" must be named *explicitly* --- "Options All"
# doesn't give it to you.
#
# The Options directive is both complicated and important. Please see
# http://httpd.apache.org/docs/2.2/mod/core.html#options
# for more information.
#
Options Indexes FollowSymLinks Includes ExecCGI

#
# AllowOverride controls what directives may be placed in .htaccess files.
# It can be "All", "None", or any combination of the keywords:
#   Options FileInfo AuthConfig Limit
#
AllowOverride All

#
# Controls who can get stuff from this server.
#
Require all granted

</Directory>

Alias /ruta_url "ruta_local"
```

El texto en rojo se deberá cambiar a nuestra preferencia.

Ejemplo de alias:

Alias /lara "C:\xampp\htdocs\DWESSE\ejemplos\_clase\laravel\ejemplo2\public"

**IMPORTANTE:** Reiniciar apache después de toda la configuración.